INCH-POUND
A-A-59326/7A
May 1, 2003
SUPERSEDING
A-A-59326/7
September 25, 1998

COMMERCIAL ITEM DESCRIPTION SPECIFICATION SHEET

COUPLING HALF, FEMALE BY EXTERNAL PIPE THREAD, TYPE VII

The General Services Administration has authorized the use of this commercial item description specification sheet, for all federal agencies.

The complete requirements for procuring couplings described herein shall consist of this document and the latest issue in effect of A-A-59326A.




FIGURE 1. Coupling half.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent by letter to: US Army Tank-automotive and Armaments Command, ATTN: AMSTA-TR-D/210, 6501 E. 11 Mile Road, Warren, MI 48397-5000.

AMSC N/A FSC 4730

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:10Z
Check the source to verify that this is the current version before use.

1. SCOPE. This specification covers a female by external pipe thread type vii coupling half.

2. CLASSIFICATION. The size of the coupling halves is designated in table 1.

TABLE 1. Coupling half size.

Dash No	Cam-Lock Nom. Size	Thread NPT	Gasket Reqd
1	½	½-14	-1
2	¾	¾-14	-2
3	1	1-11 ½	-3
4	1 ¼	1 ¼-11 ½	-4
5	1 ½	1 ½-11 ½	-5
6	2	2-11 ½	-6
7	2 ½	2 ½-8	-7
8	3	3-8	-8
9	4	4-8	-9
Sizes are in inches			

3. SALIENT CHARACTERISTICS. The following characteristics differ from those listed in A-A-59326A.

3.1 Accessories. Gaskets and pull rings shall be included with the coupling half.

3.2 Hydrostatic test pressure. The ½ inch through 6-inch couplings shall withstand a hydrostatic test pressure of 300 pounds per square inch gage (psig) The coupling shall be supplied with pull rings and gasket indicated.

3.3 Threads. The coupling threads shall conform to National Tapered Pipe Thread per ANSI/ASME B1.20.1.

4 NOTES.

4.1 Part Identification Number (PIN). The following PIN procedure is for government purposes and does not constitutes a requirement for the contractor. This example describes a part numbering system for specification sheet A-A-59326/7A

AA59326A/7-4-SS-1; /7 indicates a Female by External Pipe Thread Coupling Half; -4 indicates a 1 ¼- inch nominal size; SS indicates stainless steel body; and -1 indicates a style 1 coupling.

Material: A - Aluminum
B - Copper Alloy (Brass or Bronze)
BA - Aluminum Bronze
SS - Stainless Steel

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:10Z
Check the source to verify that this is the current version before use.

Style 1 - Style 1 couplings do not require the incorporation of a positive locking mechanism to lock the cam arms in the closed position but the cam arms will stay in the closed position when the coupling halves are assembled.

Style 2 - Style 2 couplings will incorporate a positive locking mechanism to lock the cam arms in the closed position when the coupling halves are assembled. The locking mechanism will be manually released (the release doesn't have to stay in the released position) before the cam arms can be moved to the open position.

4.2 International standardization. Certain provisions of this specification (dimensions) are the subject of international standardization agreement (see A-A59326A).

MILITARY INTERESTS:

Custodians:
Army - AT
Navy - YD
Air Force – 99

Review Activities:
Army - AV, GL
Navy - MC, SH
Air Force - 71
DLA - CC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

Preparing Activity:
Army - AT

(Project 4730-2029-007)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:10Z
Check the source to verify that this is the current version before use.