NOTICE OF
CHANGE

DOD-STD-35-99A(MI)
NOTICE 2
18 SEPTEMBER 1992

MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

CABLE ASSEMBLIES

TO ALL HOLDERS OF DOD-STD-35-99A(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-99A(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
1	18 SEPTEMBER 1992	1	9 FEBRUARY 1979
2	18 SEPTEMBER 1992	2	9 FEBRUARY 1979
3	18 SEPTEMBER 1992	3	9 FEBRUARY 1979
4	18 SEPTEMBER 1992	4	9 FEBRUARY 1979
97	9 FEBRUARY 1979	(Reprinted without change)	
98	18 SEPTEMBER 1992	98	9 FEBRUARY 1979
99	18 SEPTEMBER 1992	99	9 FEBRUARY 1979
100	18 SEPTEMBER 1992	100	9 FEBRUARY 1979

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of DOD-STD-35-99A(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

Review activities:
Army-AT, AV, CR, ER
ME, MR, SC

User activity
Army - AR

Preparing activity:
Army - MI

(Project EGDS-A443)

AMSC N/A AREA EGDS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for cable assemblies.

1.2 Purpose. This military standard provides the necessary information to prepare a Specification Requirement Sheet (SRS) which will be used to generate an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash-numbered part, the following list contains additional subjects that are applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. It is recommended that MIL-STD-1353, Selection and Use of Electrical Connectors be reviewed prior to using this dash-numbered part book.

The title code for an MSE shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSE's for the MSE titles indicated. If a suitable title code is not contained in the Title Index. leave the title code spaces on the SRS blank, and attach a request for the assignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit codes listed in the Title Index entered on an SRS, specifies that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index, is compatible with the document(s) listed with that title under base document. The list of base documents may or may not be a complete listing. The information shown under coverage is intended for the user's reference; when more than one document is listed for an MSE title, this information will be found useful in determining which of the documents is most suitable for use as the base document.

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:01Z
Check the source to verify that this is the currentversion before use.

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

TABLE I. TITLE INDEX

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
CABLE ASSEMBLY, ELECTRICAL, POWER	077001	J-C-175	APPLIANCES
		J-C-1270	EXTENSION CORD
		MIL-C-3885	COMMUNICATIONS
		MIL-C-7974	EXTERNAL POWER
		MIL-C-15987	PORTABLE EQUIPT
		MIL-C-45820	SHOP AND FIELD
		MIL-C-45889	WARHEAD
		MIL-C-51385	INTERCONNECTION
		MIL-C-52286	POWER AND LIGHT
		MIL-C-55481	COMMUNICATION
		MIL-C-62122	INTERVEHICLE
		AN3430	115/200V 3PHASE
		MS2548	G5E
		MS21378	230/400 VAC AIR
		MS24208	115/200V 3PHASE
		MS25019	EXTERNAL 28VDC
		MS51334	25-40 AMP
		MS90328	115/200 VAC
		MS90347	28 VDC
		MS90384	GSE
CABLE ASSEMBLY, COAXIAL	077003	MIL-C-45224	MISSILE
		MIL-C-55427	RADIO FREQUENCY
		MIL-C-55583	SHIELDED, TWIST PAIR
CABLE ASSEMBLY ELECTRICAL SPECIAL PURPOSE	077004	GG-C-0080	MEDICAL

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:01Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
CABLE ASSEMBLY, ELECTRICAL SPECIAL PURPOSE	077004 (CONT)	MIL-C-14242	FUZE CONTROL
		MIL-C-14765	TEST EQUIPMENT
		MIL-C-21402	NON-MAGNETIC
		MIL-C-21479	COMPONENT TEST
		MIL-C-22442	EARPHONES
		MIL-C-25200	INTERCONNECTING
		MIL-C-45820	SHOP AND FIELD
		MIL-C-48521	INTERCONNECTION
		MIL-C-48526	INTERCONNECTION
		MIL-C-48539	INTERCONNECTION
		MIL-C-55486	TELEPHONE
		MIL-C-55583	COAXIAL
		MIL-C-60906	PROJECTILE
		MIL-C-60908	PROJECTILE
		MIL-C-60920	SWITCH
		MIL-C-60921	TEST
		MIL-C-82001	INTERVEHICULAR
		MIL-C-82493	INTERCONNECTION
		MIL-C-82576	TORPEDO TEST
		MIL-C-82514	TORPEDO CONTROL
		MIL-C-83506	MOLDED CONNECTOR

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATION

MILITARY

MIL-C-17	Cable, Radio Frequency, Flexible and Semirigid, General Specification For
MIL-C-7974	Cable Assemblies and Attachable Plugs, External Electrical Power, Aircraft
MIL-C-39012	Connector, Coaxial, Radio Frequency, General Specification For
MIL-C-55583	Cable Assembly, Special Purpose Electrical CX11230()IG and Cable Assembly Adapter DX10734()IG
MIL-C-60906	Cable Assembly, Special Purpose, Electrical, T4179A

STANDARDS

MILITARY

DOD-STD-35	Automated Engineering Document Preparation System
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-202	Test Methods for Electronic and Electrical Component Parts
MIL-STD-454	Standard General Requirements for Electronic Equipment
MIL-STD-810	Environmental Test Methods
MIL-STD-1285	Marking of Electric and Electronic Parts

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2181	THE TORQUE REQUIRED TO MATE AND UNMATE CONNECTORS SHALL BE NOT GREATER THAN 2181 OUNCE-INCH(S).
2182	THE TORQUE REQUIRED TO MATE AND UNMATE CONNECTORS SHALL BE NOT GREATER THAN 2182 POUND-INCH(S).
2184	THE TORQUE REQUIRED TO MATE AND UNMATE CONNECTORS SHALL BE NOT GREATER THAN 2184 NEWTON METER(S).
2162	MATING AND UNMATING FORCES. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2162.
2164	MATING AND UNMATING FORCES. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 2013 OF MIL-STD-1344.
2138	CONNECTORS SHALL BE GRADUALLY MATED AND UNMATED.
2152	CONNECTOR SHALL BE MATED AND UNMATED AT A RATE NOT GREATER THAN 2152 INCHES PER MINUTE.
2154	CONNECTOR SHALL BE MATED AND UNMATED AT A RATE NOT GREATER THAN 2154 MILLIMETERS PER MINUTE.
2156	PRIOR TO MEASUREMENTS CONNECTORS SHALL BE MATED AND UNMATED 2156 TIMES.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:01Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
MECHANICAL ABUSE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2682
NO EVIDENCE OF PHYSICAL DAMAGE.	2684
NO LOSS OF CONTINUITY.	2686
NO EVIDENCE OF DIELECTRIC BREAKDOWN.	2688
MINIMUM INSULATION RESISTANCE (MEGOHMS)	2689
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2662
PER (DOC DES)	2662
DROP HEIGHT (SELECT ONE)	
(FEET)	2666
(METERS)	2667

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:01Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2682	MECHANICAL ABUSE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2682.
2684	MECHANICAL ABUSE. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.
2686	THERE SHALL BE NO LOSS OF CONTINUITY AFTER THE TEST.
2688	THERE SHALL BE NO EVIDENCE OF ARCING, FLASHOVER OR INSULATION BREAKDOWN WHEN DIELECTRIC WITHSTANDING VOLTAGE IS APPLIED AFTER THE TEST.
2689	THE INSULATION RESISTANCE AFTER TEST SHALL BE NOT LESS THAN 2689 MEGOHM(S).
2662	MECHANICAL ABUSE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2662.
2664	MECHANICAL ABUSE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2664.
2666	THE DROP HEIGHT SHALL BE 2666 FEET.
2667	THE DROP HEIGHT SHALL BE 2667 METER(S).

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:01Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
MECHANICAL ABUSE (CONT)	
PER (DOC DES) (CONT)	
TEST LENGTH (SELECT ONE)	
(FEET)	2669
(METERS)	2670
DROP HEIGHT, COVERS INSTALLED (SELECT ONE)	
(FEET)	2672
(METERS)	2674
DROP HEIGHT, COVERS DANGLING (SELECT ONE)	
(FEET)	2676
(METERS)	2678
OZONE EXPOSURE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2722

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:01Z
Check the source to verify that this is the current version before use.