

FED. SUP CLASS
5945


INACTIVE FOR NEW DESIGN AFTER 5 JUN 87
NO SUPERSEDING STANDARD
(FOR NEW DESIGN USE MS27400)



12 PINS, .0625 ±.001 DIA
2 PINS, .040 ±.001 DIA (X1, X2)
GOLD PLATE PER MIL-G-45204, TYPE II, CLASS 1, UNDERPLATING, NICKEL 50 TO 150 MICROINCHES THICK.



CIRCUIT DIAGRAM
(SEE NOTE 4)



PIN LAYOUT

Ⓛ ENTIRE STANDARD REVISED

APPROVED 12 May 58 REVISED Ⓛ 5 JUN 87

P.A USAF - 85 Other Cust Navy - AS	International interest	TITLE RELAYS, ELECTROMAGNETIC, 10 AMPERES, 4 PDT, TYPE 1, SOCKET MOUNTED, HERMETICALLY SEALED	MILITARY STANDARD MS25327
Procurement Specification MIL-R-6106		SUPERSEDES:	PAGE 1 OF 5

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5945-0745-13

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

User activities: Army - Navy - Air Force -

Review activities: Army - EC Navy - Air Force - 11, 99

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:08Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm
.001	0.03	.290	7.37
.005	0.13	.344	8.74
.008	0.20	.375	9.52
.040	1.02	.435	11.05
.047	1.19	.580	14.73
.062	1.57	.725	18.42
.0625	1.588	.750	19.05
.072	1.83	.870	22.10
.093	2.36	1.500	38.10
.145	3.68	1.531	38.89
.147	3.73	1.821	46.02
.203	5.16	1.844	46.84
.210	5.33	2.187	55.55

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ±.010 (0.25 mm).
4. The use of diodes on ac relays is optional. Actual application must be shown on label.
5. Pins to be perpendicular to header surface within one degree.
6. Terminal numbers need not appear on relay headers provided there is affixed to the relay a suitable legible circuit diagram that positively and permanently identifies each terminal location specified herein.
7. In the event of a conflict between the text of this standard and the references cited herein, the text of this standard shall take precedence.
8. Referenced Government documents of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation form a part of this standard to the extent specified herein.

TABLE I. Dash numbers and characteristics.

Dash number MS25327-	Type	Coil	Terminal type	Max weight in pounds
01	1	dc	Plug in	.43
A1	1	ac	Plug in	.45

APPROVED 12 May 58 REVISED (L) ENTIRE STANDARD REVISED.

User activities: Army - Navy - Air Force -
Review activities: Army - EC Navy - Air Force - 11, 99

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:08Z
Check the source to verify that this is the current version before use.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Review activities: Army -
Navy - EC
Air Force - 11, 99

User activities: Army -
Navy -
Air Force -

DD FORM 672 1 MAY 73 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Procurement Specification: MIL-R-6106

P.A: USAF - 85
Other Cust: Navy - AS

International interest:

SUPERSEDES:

TITLE: RELAYS, ELECTROMAGNETIC, 10 AMPERES, 4 PDT, TYPE 1, SOCKET MOUNTED, HERMETICALLY SEALED.

MILITARY STANDARD

MS25327

PAGE 3 OF 5

FED. SUP CLASS 5945

TABLE II. Operating characteristics.

MS part no. MS25272-	Coil data											Time - (milliseconds maximum)					
	Coil	Nominal			Max		Max pick-up voltage			Drop-out voltage 2/	Hold voltage 2/	Operate 3/	Release 4/	Contact bounce			
		Volts 1/	Freq. Hz	Res Ω	Volts	Amperes	Normal 2/	High temp test	Cont current test					Main		Aux	
														NO	NC	NO	NC
D1	X1, X2	28	dc	N/A	29	0.350	18	19.5	22.5	1.5	7.0	20	20	2	2		
A1	X1, X2	115	400 5/	N/A	122	0.073	90	95	103	5.0	30	25	50	2	2		

1/ CAUTION: Use of any coil voltage less than nominal coil voltage will compromise the operation of the relay.
2/ Over the temperature range.
3/ With nominal coil voltage.
4/ From nominal coil voltage.
5/ MS25272-A1 may be used on 60 Hz if maximum ambient temperature is limited to 85°C (maximum coil current shall be 0.077 ampere).

APPROVED 12 May 58 REVISED (L) ENTIRE STANDARD REVISED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:08Z
Check the source to verify that this is the current version before use.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Review activities: Army -
Navy - EC
Air Force - 11, 99

User activities: Army -
Navy -
Air Force -

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Procurement Specification MIL-R-6106

P.A
USAF - 85
Other Cust
Navy - AS

International interest

SUPERSEDES:

TITLE
RELAYS, ELECTROMAGNETIC, 10 AMPERES, 4 PDT, TYPE I, SOCKET MOUNTED, HERMETICALLY SEALED

MILITARY STANDARD

MS25327

PAGE 4 OF 5

TABLE III. Rated contact load (Amperes per pole) (case grounded).

Type of load	Life operating cycles X 10^3	28 V dc				115 V ac, 1 phase				115/200 V ac, 3 phase 1/				See appropriate notes
		Main		Aux		Main		Aux		Main		Aux		
		NO	NC	NO	NC	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz	
Resistive	100	10	10			10	6			10	6			
Inductive	100													
Inductive	20	6	6			6	4			6	4			
Motor	100	4	4			4	3			4	3			
Lamp	100	2	2			2	1.5			2	1.5			
Transfer load														2/
Mechanical life reduced current	400	2.5	2.5			2.5	2			2.5	2			
Intmd current	Applicable per specification													

1/ Absence of value indicates relay is not rated for 3-phase applications.
2/ Transfer load indicates relay suitable for transfer between unsynchronized ac power supplies at rating indicated.

FED. SUP CLASS 5945

APPROVED 12 May 58 REVISED (L) ENTIRE STANDARD REVISED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:08Z
Check the source to verify that this is the current version before use.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Review activities: Army -
Navy - EC
Air Force - 11, 99

User activities: Army -
Navy -
Air Force -

DD FORM 1 MAY 53 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Procurement Specification MIL-R-6106

P.A USAF - 85
Other Cust Navy - AS

International interest

SUPERSEDES

TITLE RELAYS, ELECTROMAGNETIC, 10 AMPERE, 4 PDT, TYPE I, SOCKET MOUNTED, HERMETICALLY SEALED

MILITARY STANDARD

MS25327

PAGE 5 OF 5

FED. SUP CLASS 5945

Environmental characteristics

Temperature range	-70°C to +125°C
Max altitude rating	80,000 ft
Shock G-level	50 G
Duration	11 ms
Max duration contact opening	10 μs
Vibration - sinusoidal	
G-level	10 G
Frequency range	5 - 1500 Hz
Vibration - random	
Applicable specification	N/A
Power spectral density	N/A
RMS G min	N/A
Frequency range	N/A
Curve	N/A
High shock	N/A
Acceleration	15 G

Electrical characteristics

Insulation resistance, initial	100 megohms
After life or environmental tests	50 megohms

Dielectric strength (sea level)

	Initial	After life tests
Coil to case	1,000 V rms	1,000 V rms
Aux contacts		
All other points	1,500 V rms	1,125 V rms

Dielectric strength (Altitude)

	80,000 ft
Coil to case	500 V rms
Aux contacts	500 V rms
All other points	500 V rms

Max contact drop initial	0.150 volt
After life test	0.175 volt
Overload current	40 amperes dc, 60 amperes ac
Rupture current	50 amperes dc, 80 amperes ac
Duty rating	Continuous
RFI specification	MIL-STD-461

(Applicable to coil circuits of ac operated relays)

Quality conformance inspection

Performance of groups B and C inspections are not applicable

APPROVED 12 May 1958 REVISED (L) ENTIRE STANDARD REVISED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:08Z
Check the source to verify that this is the current version before use.