INCH-POUND


MS90558G
w/AMENDMENT 2
10 April 2024
SUPERSEDING
MS90558G
w/AMENDMENT 1
15 January 2016

MILITARY SPECIFICATION SHEET

# CONNECTOR, PLUG, ELECTRICAL, WALL MOUNTING, (WITH COUPLING RING), CLASS L, (EQUIPMENT)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-22992.





| Inches | mm |
|---|---|
| .005 | 0.127 |
| .010 | 0.254 |
| .011 | 0.279 |
| .031 | 0.787 |
| .062 | 1.57 |
| .312 | 7.92 |

FIGURE 1. Plug.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.





| Inches | mm |
|---|---|
| .312 | 7.92 |
| .187 | 4.75 |
| .010 | 0.254 |
| .001 | 0.025 |

FIGURE 1. Plug - Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.




| Inches | mm |
|---|---|
| .101 | 2.57 |
| .094 | 2.39 |
| .067 | 1.70 |
| .031 | 0.79 |
| .005 | 0.127 |

FIGURE 1. Plug - Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.

| Contact size | Z dia | V dia wire sealing range |
|---|---|---|
| 4 / 0 | .614 (15.60) / .624 (15.85) | .700 (17.78) / .790 (20.07) |
| 2 / 0 | .520 (13.21) / .530 (13.46) | .530 (13.46) / .655 (16.64) |
| 1 / 0-1 | .471 (11.96) / .481 (12.22) | .457 (11.61) / .585 (14.86) |
| 4 | .339 (8.61) / .349 (8.86) | .356 (9.04) / .430 (10.92) |
| 6 | .292 (7.42) / .302 (7.67) | .300 (7.62) / .360 (9.14) |

| Shell size | C ± .047 | | | F + .016 - .000 | J ± .016 | K ± .005 | W thread start ± .031 |
|---|---|---|---|---|---|---|---|
| | Phase | Neutral | Ground | | | | |
| 28 | .196 (4.98) | .078 (1.98) | .078 (1.98) | 2.639 (67.03) | 1.370 (34.80) | 1.557 (39.55) | 1.062 (26.97) |
| 32 | .196 (4.98) | .078 (1.98) | .078 (1.98) | 2.639 (67.03) | 1.370 (34.80) | 1.557 (39.55) | 1.062 (26.97) |
| 44 | .196 (4.98) | .078 (1.98) | .547 (13.89) | 2.998 (76.15) | 1.589 (40.36) | 1.776 (45.11) | 1.281 (32.54) |
| 48 | .196 (4.98) | .078 (1.98) | .547 (13.89) | 2.998 (76.15) | 1.589 (40.36) | 1.776 (45.11) | 1.281 (32.54) |
| 52 | .196 (4.98) | .078 (1.98) | .547 (13.89) | 2.998 (76.15) | 1.589 (40.36) | 1.776 (45.11) | 1.281 (32.54) |


| Shell size | R (BSC) | S + .021 - .020 | T ± .005 | AA dia + .006 - .005 | XX dia + .001 - .010 | YY dia + .010 - .001 |
|---|---|---|---|---|---|---|
| 28 | 1.844 (46.84) | 2.375 (60.33) | .177 (4.50) | 1.672 (42.47) | 1.522 (38.66) | 1.370 (34.80) |
| 32 | 2.062 (52.37) | 2.625 (66.68) | .209 (5.31) | 1.922 (48.82) | 1.772 (45.01) | 1.620 (41.15) |
| 44 | 2.812 (71.42) | 3.375 (85.73) | .281 (7.14) | 2.672 (67.87) | 2.522 (64.06) | 2.296 (58.32) |
| 48 | 3.000 (76.20) | 3.625 (92.08) | .281 (7.14) | 2.891 (73.43) | 2.725 (69.22) | 2.551 (64.80) |
| 52 | 3.156 (80.16) | 3.875 (98.43) | .281 (7.14) | 3.141 (79.78) | 2.975 (75.57) | 2.801 (71.15) |

FIGURE 1. Plug - Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.

| Shell size | A Thread class 2B | G dia + .006 - .010 | H + .001 - .010 | L ± .031 | M ± .047 | N + .011 - .020 | Q dia max |
|---|---|---|---|---|---|---|---|
| 28 | 2.000-.1428P-.2857L | 1.938 (49.23) | 1.812 (46.02) | .959 (24.36) | .328 (8.33) | 2.000 (50.80) | 2.312 (58.72) |
| 32 | 2.250-.1428P-.2857L | 2.188 (55.58) | 2.062 (52.37) | .959 (24.36) | .328 (8.33) | 2.250 (57.15) | 2.562 (65.07) |
| 44 | 3.000-.1428P-.2857L | 3.062 (77.77) | 2.812 (71.42) | 1.021 (25.93) | .390 (9.91) | 3.125 (79.38) | 3.531 (89.69) |
| 48 | 3.250-.1428P-.2857L | 3.312 (84.12) | 3.062 (77.77) | 1.021 (25.93) | .390 (9.91) | 3.375 (85.73) | 3.781 (96.04) |
| 52 | 3.500-.1428P.2857L | 3.562 (90.47) | 3.312 (84.12) | 1.021 (25.93) | .390 (9.91) | 3.625 (92.08) | 4.016 (102.01) |




ALTERNATE KEY POSITIONS

FIGURE 1. Plug - Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.

Non-grounding assemblies: finish N

| Shell size | Shell main key positions |
|---|---|
| | 2 wire |
| | 28 V dc |
| 28 | N (105°) |
| 32 | N (105°) |
| 44 | N (105°) |
| 48 | N (105°) |
| 52 | N (105°) |

Grounding assemblies: Finishes, conductive

| Shell size | Shell main key positions | | | | | | |
|---|---|---|---|---|---|---|---|
| | 60 Hz and 400 Hz (see note 1) | | | | | | |
| | 1 ∅ | | | 3 ∅ | | | 3 ∅ (see note 2) |
| | 2 wire | | 3 wire | 4 wire | | | 3 wire |
| | 120 V | 240V | 120/240 V | 120/208 V | 240/416 V | 277/480 V | 450/480 V |
| 28 | 4 (120°) | 5 (135°) | 4 (120°) | 4 (120°) | 5 (135°) | 6 (150°) | --------- |
| 32 | 4 (120°) | 5 (135°) | 4 (120°) | 4 (120°) | 5 (135°) | 6 (150°) | --------- |
| 44 | 4 (120°) | --------- | 4 (120°) | 4 (120°) | 5 (135°) | 6 (150°) | 1 (60°) |
| 48 | -------- | --------- | 4 (120°) | 4 (120°) | 5 (135°) | 6 (150°) | --------- |
| 52 | -------- | --------- | 4 (120°) | 4 (120°) | 5 (135°) | 6 (150°) | --------- |

NOTES:

1. Discrimination of 60 Hz and 400 Hz assemblies is accomplished by alternate positioning of inserts.

   See applicable insert drawing for keying.
2. For Navy ground support equipment use only. Arrangement 44-51, 44-52 and 44-56 are not applicable.
3. Shell main key positions 2 and 3 not used.
4. Dimensions are in inches. Metric equivalents are given for information only.
5. For protective cover, see MS90564.
6. F dimension applies only when the coupling nut is fully engaged.

FIGURE 1. Plug - Continued.


REQUIREMENTS:



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.

Dimensions and configurations: See figure 1.
Mates with receptacles shown on standard MS90557.
The Part or Identifying Number (PIN) shall include the size, finish and shell key alternate position.
Inserts and contacts are removable.
For final installation, contacts will be assembled in all insert holes.
Shell and nut finish: See MIL-DTL-22992.
N designates normal key position. For alternate key positions see figure 1.
For insert arrangements (including alternate insert rotations W, X, Y and Z, where applicable), see MS90565, MS14054, MS14055, and MS14057.
Covers specified in MS90564 shall be supplied with connector.
Pin contacts shall be in accordance with SAE- AS39029/48.

PIN example:




Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-DTL-22992, this document references the following:

MS14054
MS14055
MS14057
MS90557
MS90564
MS90565
SAE-AS39029/48



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA – CC

Preparing activity:
DLA – CC

Review activities:
Army – AR, AV, MI
Navy – AS, CG, MC, OS
Air Force – 19

(Project 5935-2024-125)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.