MIL-P-24364/3(SHIPS)
AMENDMENT 2
16 April 1984
SUPERSEDING
AMENDMENT 1
5 January 1973

MILITARY SPECIFICATION SHEET

PLASTIC SHEETS, LAMINATED, THERMOSETTING, ELECTRICAL INSULATING
SHEET, POLYESTER GLASS-MAT GRADE GPO N-3

This amendment forms a part of Military Specification Sheet MIL-P-24364/3(SHIPS), dated 11 July 1969, and is approved for use by the Naval Sea Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* Table I, title: Delete "Qualification test" and substitute "First article inspection".

Table I: Dissipation factor, values required for each thickness 1/8 inch, delete: "0.05" and substitute "0.10".

Table I: Flexural strength, values required for each thickness under 1/16 inch delete: "16,000" and substitute "18,000".

PAGE 3

Table II: Flexural strength, values required for each thickness range, under columns 6, 7 and 9 delete "16,000" and substitute "18,000", and under column 10 delete "14,000" and substitute "18,000".

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH
(Project 9330-NB10)

FSC 9330

Source: https://assist.dla.mil -- Downloaded: 20261O-19T21:32Z
Check the source to verify that this is the current version before use.