NATIONAL MILITARY ESTABLISHMENT SPECIFICATION

CARTRIDGE, SHOT, CALIBER .45, M15

This specification was approved by the Departments of the Army, the Navy, and the Air Force for use of procurement services of the respective Departments

1. CLASSIFICATION

1.1 Type and grade.—This specification covers one type and one grade of cartridge, shot, caliber .45, M15.

2. APPLICABLE SPECIFICATIONS, OTHER PUBLICATIONS, AND DRAWINGS

2.1 Specifications.—The following specifications and specifications listed on drawings in 2.3, of the issue in effect on the date of invitation for bids, form a part of this specification:

NATIONAL MILITARY ESTABLISHMENT SPECIFICATION

JAN–A–625—Ammunition, Small Arms, General Specification For.

U. S. ARMY SPECIFICATION

100–2—Standard Specification for Marking Shipment by Contractors.

(Copies of specifications should be obtained from the procuring agency or as directed by that agency. Both the title and identifying number or symbol should be stipulated when requesting copies.)

2.2 Other publications. — The following publications of the issue in effect on date of invitation for bids, form a part of this specification:

U. S. ARMY ORDNANCE DEPARTMENT PUBLICATION

ORD–SIP–S315—Visual Inspection Standards for Small Arms Ammunition

(Copies of the U. S. Army Ordnance Department publications may be obtained upon application to the Chief of Ordnance, Department of the Army, Washington 25, D. C. Both the title and identifying number or symbol should be stipulated when requesting copies.)

BUREAU OF SUPPLIES AND ACCOUNTS PUBLICATION

Navy Shipment Marking Handbook.[1]

(Copies of the Navy Shipment Marking Handbook may be obtained upon application to the Bureau of Supplies and Accounts, Navy Department, Washington 25, D. C., except that activities of the Armed Forces should make application to the Supply Officer in Command, Naval Supply Center, Norfolk 11, Va.)

2.3 Drawings.—The following drawings, with specifications shown thereon, of the issue in effect on date of invitation for bids, form a part of this specification:

U. S. ARMY ORDNANCE DEPARTMENT DRAWINGS

27–79–77—Cartridge, Shot, Cal. .45, M15, List of Drawings and Specifications and Inspection for Acceptance.

42–8–32 — Pistol, Automatic Cal. .45, M1911A1.

D–35497—Barrel.

D–7692095—Gage, Pressure, Cal. .45, Assembly and List of Drawings, and Lists of Parts.

46–6–41A—Rest, Recoil, Cal. .45.

D–45724—Gun, Accuracy, Cal. .45, Assembly and List of Drawings.

49–6–47A—Rest for Gage, Pressure, Cal. .45, Assembly.

D–7643674—Classification of Cartridge Case Defects, Small Arms Ammunition.

(Copies of U. S. Army Ordnance Department drawings may be obtained upon application to the Chief of Ordnance, Department of the Army, Washington 25, D. C. Both the title and identifying number or symbol should be stipulated when requesting copies.)

3. REQUIREMENTS

3.1 Material.—The material shall be in accordance with the applicable requirements of specification JAN–A–625.

3.1.1 *Powder.*—The propellant powder shall be any approved, clean burning, single base,

[1] Applicable only to Navy shipments.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:26Z
Check the source to verify that this is the current version before use.

smokeless powder normally used for the type of cartridge and load specified.

3.1.2 *Shot.*—The shot shall be "American Standard," and the number of pellets to the ounce and the pellet tolerance per ounce shall be as stated in the Technical Committee Manual of the Sporting Arms and Ammunition Manufacturers' Institute as amended, unless otherwise specified.

3.2 Assembly.—The assembled cartridge after crimping shall be snug and without voids among the internal components, other than the unavoidable interstices among the powder grains and shot pellets.

3.3 Identification.—Each cartridge lot shall be indentified by number and name of the contractor.

3.4 Physical requirements.

3.4.1 The cartridges shall be visually examined and gaged for the defect classification requirements specified in table I.

TABLE I.—*Defect classification for cartridge, shot, caliber .45, M15*

No.	Defect	Critical	Major	Minor	Major or Minor
	VISUAL				
	Cartridge:				
1	Discolored, dirty, oily, smeared (waterproofing)	---	---	X	---
2	Corroded	---	X	---	---
	Split between mouth and top of wad	---	---	X	---
	Split below top of wad	---	X	---	---
	Joint between case, neck and wad not covered by lacquer	---	X	---	---
	Tipped seating wads	---	X	---	---
	Flattened or deformed shot pellets	---	X	---	---
	Joint between case neck and wad covered by lacquer but wad not completely covered by lacquer	---	---	X	---
	Opening between wad and case wall	---	X	---	---
	Case:				
3	Round head	---	X	---	---
4	Dent [1]	---	---	---	X
5	Split case	---	X	---	---
6	Perforated case	X	---	---	---
7	Draw scratch [1]	---	---	---	X
8	Scratch	---	---	X	---
9	Beveled underside of head	---	X	---	---
10	Scaly metal [1]	---	---	---	X
11	No chamfer on head (rim) [1]	---	---	---	X
12	Wrinkle	---	---	X	---
13	Bulge	---	---	X	---
14	Defective head	---	---	X	---
15	Defective mouth	---	---	X	---
	Primer:				
19	No primer	X	---	---	---
20	Cocked primer	X	---	---	---
21	Inverted primer	X	---	---	---
22	Loose primer	---	X	---	---
23	Nicked or dented primer	---	---	X	---
24	No waterproofing (primer pocket joint)	---	---	X	---
	GAGING				
	Cartridge:				
25	Long over-all length	X	---	---	---
26	Short over-all length	---	X	---	---
27	Cartridge profile failure (requiring more than 10 lb. dead weight to insert in profile and alignment gage) [2]	---	X	---	---
28	Large extractor groove diameter	---	---	X	---
29	Small extractor groove diameter	---	---	X	---
30	Large diameter head	---	---	X	---
31	Small diameter head	---	---	X	---
32	Thick head	---	---	X	---
33	Thin head	---	X	---	---
	Primer:				
36	High primer	---	X	---	---
	Low primer	---	---	X	---

[1] These defects may be major or minor refer to publication ORD–SIP–S315.

[2] Each failing cartridge shall be inserted by the fingers, as far as possible, in a minimum dimensioned chamber of pistol, automatic, cal. .45, M1911A1, conforming with the requirements of drawing 42–8–32. If, upon releasing the slide, the cartridge fails to chamber completely, it shall be counted as a critical defective.

3.4.2 *Acceptable quality levels.*—The acceptable quality levels (percent defective) of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:26Z
Check the source to verify that this is the current version before use.

cartridges with respect to visual and dimensional defects shall not exceed the following:

Defects	*Percent*
Critical	0.00
Major	0.10
Minor	1.00

3.4.3 The cartridges shall be visually inspected and gaged by the contractor in accordance with the provisions of specification JAN–A–625.

3.4.4 *Pellet count.*—Each cartridge shall contain the number of standard shot pellets No. 7½ specified on the applicable drawing.

3.4.5 *Velocity.*—The minimum average velocity shall be 750 feet per second at 25.5 feet from the muzzle.

TABLE II.—*Defects and limits permitted in a sample of cartridge, shot, caliber .45, M15*

Defect [1]	Percent
Misfire	0.1
Primer leak:	
(A) Perforation in firing pin indent in primer cup	1.0
(B) Escape of gas through primer cup other than (A)	1.0
(C) Loose primer [2]	0.2
(D) Blown primer [3]	0
Case casualty:	
(A) Longitudinal split: [4]	
(a) mouth (i)	2.0
(b) upperbody (j)	1.5
(c) body (k) [5]	
(d) to head (l)	0
(e) through head (m)	0
(B) Circumferential rupture: [4]	
(a) partial (j, k)	0.4
(b) partial (l) [5]	
(c) complete (j, k, l)	0
Failure to extract	0
Failure to chamber	0

[1] The number of defects permitted is calculated as shown in specification JAN–A–625.

[2] Primer falls out of pocket upon opening weapon.

[3] Primer not in pocket after firing, and both head of cartridge case and pocket enlarged and distorted. (Determined visually.)

[4] For location indicated by small letters in parentheses see drawing D7643674.

[5] This allowance shall remain at one and shall not be proportionate to the number of cartridges in the lot.

3.4.6 *Waterproof.*—Each cartridge shall be waterproofed according to the applicable drawing. Firing tests for effectiveness of waterproofing shall be for information only.

3.4.7 *Pressure.*—The average pressure shall not exceed 17,000 pounds per square inch.

3.4.8 *Pattern.*—The cartridges shall develop an average pattern of 70 percent of the pellets in the load (as determined by the average pellet count (see table III) within a circle of 30-inch diameter at a distance of 25.5 feet from the muzzle of the weapon from which the cartridges are fired.

3.4.9 *Function and casualty.*—Cartridges shall be fired for function and casualty according to table III.

3.4.9.1 The total defects discovered in the velocity, pressure, pattern, function and casualty firing of any sample shall not exceed any of the percentages of the number fired shown in table II. In cases where a percentage results in fractional number of cartridges, the next higher whole number of cartridges shall govern.

3.4.10 *Workmanship.*—Workmanship shall conform to the requirements of specification JAN–A–625, and shall be of a quality meeting the requirements of applicable drawings.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1. Lot.—Normally and unless otherwise specified, the number of cartridges in a lot shall be the number produced in 1 day at the particular plant or unit concerned. However, where a day's production is relatively small, a lot may include the production of two or more consecutive days, but not more than 2,000,000 cartridges. The number of cartridges in a probational lot shall not exceed 500,000.

4.2 The contractor shall submit an ammunition lot for visual inspection and gaging by sublots. Sampling of such sublots and disposition with respect to visual inspection and gaging only shall be in accordance with the requirements of table I, specification JAN–A–625.

4.3 Sampling. — The acceptance samples shall be selected in accordance with the manner specified by specification JAN–A–625. The quantities for the various acceptance tests, other

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:26Z
Check the source to verify that this is the current version before use.

than visual inspection and gaging, shall be as specified in table III of this specification.

TABLE III.—*Acceptance test samples—first test*

(Size of lot, not over 2,000,000)

Test	Number of rounds
Pellet count	20
Velocity	20
Waterproof	20
Pressure	20
Pattern	20
Function and casualty	80
Total rounds	180

NOTE.—Retest for pellet count, velocity, waterproof, pressure, pattern, case casualty, and misfire shall consist of double the number listed in this table III, and shall be made in accordance with par. 4.3.

4.4 Inspection.—After the cartridges, either in sublots or lots, have been inspected visually and gaged by the contractor for the defects listed in table I, the inspection (visual and gaging) and firing tests for acceptance shall be made in accordance with the applicable provisions for acceptance of specification JAN–A–625, and, unless otherwise specified, shall be made at the place of manufacture.

4.5 Visual inspection and gaging.—Each cartridge of the acceptance sample shall be inspected visually for all the defects, and gaged for all the dimensions listed in table I of this specification.

4.6 Pellet count.—The retainer wad and the shot pellets shall be removed from each cartridge of the pellet count sample and the pellets counted.

4.7 Velocity.—All firings shall be made in pistol, automatic, caliber .45, M1911A1, shown on drawing 42–8–32, with a barrel having chamber and rifling conforming to Ordnance Department Drawing D35497. Each cartridge shall be inserted in the chamber, as far as possible, by the fingers, and the slide released.

4.8 Waterproof.—After both the cartridges and the water have been brought to room temperature, the cartridges shall be placed horizontally in the water under a 1-inch head over the rim, and so remain a continuous 24 hours. They shall then be handled and fired in accordance with specification JAN–A–625.

4.9 Pressure.—All firings shall be made in gage, pressure, caliber .45, shown on drawing D7692095.

4.10 Pattern.—Each cartridge shall be fired from gun, accuracy, caliber .45, shown on drawing D45724. For this firing the gun shall be held in rest, recoil, caliber .45, shown on drawing 49–6–41A. The pattern sheet of appropriate paper, not less than 40 inches square, shall be erected for each shot, 25.5 feet in front of the gun. For each paper target erected, sight the gun so that the sight picture or a prolongation of the bore's axis will cover the approximate center of the paper. The center of the pattern circle shall be located by estimating, as accurately as possible, the center of impact of the shot pellet perforations in each target fired upon. This estimated center shall be the center of a circle whose diameter is 30 inches which will encompass the greatest number of pellet perforations in the paper.

4.11 Function and casualty.—The cartridges shall be fired for function and casualty in pistol, automatic, caliber .45, M1911A1 and the method of chambering shall be the same as specified in 4.7.

(NOTE.—As the fired case is too long for ejection, the magazine should be withdrawn and the fired case allowed to drop.)

4.12 Headspace.—See specification JAN–A–625.

4.13 Defective weapons.—See specification JAN–A–625.

4.14 Retests.—See specification JAN–A–625.

5. PREPARATION FOR DELIVERY

5.1 Packing. — The cartridges shall be packed in accordance with the applicable drawings.

5.2 Marking shipments. — The packing boxes containing cartridges shall be marked for shipment in accordance with the requirements of specifications 100–2; for the Navy in accordance with the requirements of the Navy Shipment Marking Handbook.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:26Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Use.—This ammunition is used in the Department of the Air Force survival kits.

6.2 Ordering data.—Purchase instruments should specify the title, number, and date of this specification.

Notice.—This specification, together with specifications and drawings pertaining to it and bearing a "Notice" of similar restrictions, is intended for use only in connection with procurement by the United States Government; and shall not be reproduced either wholly or in part except when authorized in connection with Government procurement, nor be used for any other purpose execpt when specifically authorized by the Chief of Ordnance, Department of the Army.

Custodian:
Army—Ordnance Department.
Other interest:
Navy—O.
Air Force.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:26Z
Check the source to verify that this is the current version before use.