MIL-C-826C

29 December 1967
SUPERSEDING
MIL-C-826B
12 February 1965

MILITARY SPECIFICATION

CABBAGE, DEHYDRATED

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers dehydrated cabbage for use by the Armed Forces as an item of general issue.

1.2 Classification.- The product shall be of the following styles and forms, as specified (see 6.1):

Style A - Raw
Style B - Cooked

Form 1 - Diced
Form 2 - Shredded

2. APPLICABLE DOCUMENTS

* 2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

TT-C-495 - Coatings, Exterior, for Tinned Food Cans.
PPP-B-636 - Box, Fiberboard.
PPP-C-29 - Canned Subsistence Items, Packaging and Packing Of.
PPP-C-96 - Cans, Metal, 28 Gage and Lighter.

MILITARY

MIL-D-43266 - Desiccants and Desiccation, Method of; For Packaging Subsistence.
MIL-L-1497 - Labeling of Metal Cans for Subsistence Items.
MIL-L-35078 - Loads, Unit; Preparation of Nonperishable Subsistence In.

FSC 8915

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:32Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

Fed. Test Method Std. No. 101 - Preservation, Packaging and Packing Materials: Test Procedures.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal, shall apply:

U. S. Department of Health, Education and Welfare

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder.

(Application for copies should be addressed to the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.)

Association of Official Agricultural Chemists

Official Methods of Analysis.

(Application for copies should be addressed to the Association of Official Analytical Chemists, Box 540, Benjamin Franklin Station, Washington, D. C. 20044.)

U. S. Department of Agriculture

USDA-CMS - Visual Aid #1, Visual Aids for Inspection of Metal Containers.

(Application for copies should be addressed to the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:32Z
Check the source to verify that this is the current version before use.

National Research Council

Food Chemicals Codex.

(Application for copies should be addressed to the Office of Director, National Academy of Science, National Research Council, Washington, D. C. 20418.)

3. REQUIREMENTS

3.1 Preproduction sample approval.- When specified (see 6.1), a sample of the finished product shall be submitted to the contracting officer for approval before production is commenced.

3.2 Material.- The cabbage shall be clean, sound, and mature, and preferably of the green varieties of Danish, Domestic, Pointed, or Savoy type. Varieties such as the Copenhagen Market and the Glory of Enkhuizen will be acceptable. Cabbage of the red varieties shall not be used.

* 3.2.1 Sodium sulfite or sodium acid sulfite.- The sulfite(s) used shall be of a grade comparable to the Food Chemicals Codex.

3.3 Preparation.-

* 3.3.1 Trimming, core removal and washing.- The cabbage heads shall be properly trimmed to remove discolored, damaged or diseased portions. Core material shall be eliminated. Removal of core material may be effected either prior to or after dehydration. The cabbage shall be washed with potable cold water to remove soil and foreign materials.

3.3.2 Cutting.-

* 3.3.2.1 Form 1 - Diced cabbage.- The cabbage shall be processed through a cutter adjusted to 3/8 by 3/8 inch.

3.3.2.2 Form 2 - Shredded cabbage.- The cabbage shall be processed through a slicer adjusted to yield shreds 3/16 inch ± 1/16 inch by leaf thickness.

3.4 Processing.-

3.4.1 Style A.- Style A cabbage shall not be subjected to any heat treatment such as is necessary for blanching or cooking prior to dehydration.

3.4.2 Style B.- Style B cabbage shall be cooked until the midribs are translucent but not overcooked.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:32Z
Check the source to verify that this is the current version before use.

3.4.3 Sulfiting.- The cabbage shall receive a sulfite treatment, by such method as will insure uniform distribution throughout the product, and a residual sulfur dioxide content in the dehydrated product, within the limitations specified in 3.5.1. The wet cabbage, subsequent to the sulfite treatment, shall not be allowed to come into contact with iron or other metals which may cause discoloration.

3.4.4 Dehydration.- Dehydration conditions shall be such that the product is not scorched or otherwise damaged by heat and shall produce a product complying with 3.5.

3.5 Finished product.-

* 3.5.1 Dehydrated product.- The product shall be free from hay-like, scorched, musty or other objectionable odors. The sulfur dioxide content shall be 1500 ± 500 parts per million (ppm), as determined by the method specified in 4.5.2. The product shall be free from clumps and matted or rolled materials. Not more than 15 percent, by weight, of the product within a can shall pass through a U. S. Standard No. 8 sieve when tested, as specified in 4.5.3. The moisture content of the cabbage shall not exceed 5 percent.

3.5.1.1 Defect tolerances.- The dehydrated product shall contain not more than 2 percent by weight of defective pieces. A piece shall be considered defective if it is damaged by insect or pathological injury, decay, scorch, bruise, tray blackening, dirt, discoloration, or any other abnormalities.

3.5.2 Rehydrated product.- The rehydrated product shall have good flavor, texture and color, typical of raw or cooked cabbage, as applicable.

3.5.2.1 Style A.- Style A cabbage shall rehydrate to approximately its original texture and form, when one avoirdupois ounce of dehydrated product is added to 16 fluid ounces of cold water and allowed to soak for 45 minutes.

* 3.5.2.2 Style B.- Style B cabbage shall rehydrate to approximately its original cooked form when one avoirdupois ounce of the dehydrated product is added to 8 fluid ounces of boiling water (approximately 212°F.) and allowed to soak for 15 minutes. The product shall be tender, but not mushy.

* 3.6 All deliveries shall conform in every respect to the provisions of the Federal Food, Drug and Cosmetic Act and Regulations Promulgated Thereunder.

* 3.7 Workmanship.- The processing plant, grounds, equipment, packaging materials, personnel practices, and sanitary practices used in production of this item, shall be such as to minimize the possibility of contamination of the product through microbial growth, dust, pests, rodents, condensate, or other unsanitary-sources. The product shall be prepared and processed with minimum delay between the various stages of production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:32Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 Pre-acceptance inspection.- Product shall be rejected if produced in plants having unsanitary conditions which could result in a potential health hazard or contamination.

4.3 Sampling for inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105, except as otherwise indicated herein.

* 4.3.1 Inspection of components (examination and testing).- In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase documents.

* 4.3.1.1 Examination of desiccant.- Examination of desiccant shall be in accordance with the criteria (prior to incorporation in cans) in MIL-D-43266 except, that the examination for particle size shall not apply.

4.3.1.2 Testing of components.- Testing of components described in this specification and changes in the testing of components listed in subsidiary specifications shall be as shown in table I and 4.3.1.2.1. Test results for the characteristics shown shall apply to the lot average. A test failure shall indicate unacceptable cans and use of such shall be cause for rejection of the involved end item.

TABLE I - Testing of components

Component	Sample unit	Lot size expressed in	Inspection level	Characteristics	Results reported	Test ref and rqmt par
Cans and lids 1/	1 can with lid	Cans	S-1	Tin plate	Nearest .01 lb/ base box	4.5.5 5.1.1

1/ Tests for can coating and can label shall be performed on the same cans submitted for tin plate testing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:32Z
Check the source to verify that this is the current version before use.

* 4.3.1.2.1 Testing of desiccant.- Testing of desiccant shall be in accordance with MIL-D-43266 except that the sample for testing particle size and desiccant expansion shall be a composite derived from the number of bags necessary to yield 200 grams. The contents of the bags shall be composited just prior to testing.

4.3.2 Process examination.- Examination shall be performed during preparation and processing to determine conformance to the pertinent requirements of 3.3 and 3.4. Nonconformance to one or more requirements shall be cause for rejection of the involved cabbage.

* 4.3.3 Examination of end item.- Examinations shall be in accordance with tables III through IV and 4.3.3.1 through 4.3.3.5. Examination criteria shall be as shown in table II. Lot sizes shall be expressed in terms of cans. The AQLs shall be expressed in terms of percent defective for table III and defects per hundred units for table IV.

* TABLE II - Sampling plans and AQLs

Table	Inspection level	Sample unit	Lot size expressed in	AQLs Major	Minor	Total
III	S-3	1 filled can	Cans	---	2.5	---
IV	S-2	1 filled can	Cans	1.5	---	6.5

* TABLE III - Examination for net weight (dry solids basis) 1/ 2/

Category	Defect
Minor	
201	Less than 108 grams (401 by 411 can).
202	Less than 15-3/4 ounces (603 by 700 can).

1/ Subtract average moisture content (to nearest 0.1 percent) from unit net weight to obtain net weight.

2/ Report results to nearest gram for 401 by 411 can and nearest 1/8 ounce for 603 by 700 can. Lot shall be rejected if sample data indicate a lot average dry solid net weight less than specified weight.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:32Z
Check the source to verify that this is the current version before use.

TABLE IV - Examination of can contents 1/

Category		Defect
Major	Minor	
		Dehydrated product (see 3.5.1)
151		Not good typical aroma (i.e., presence of haylike, scorched, musty or other objectionable odor).
152		More than 2.3 grams per 113.4 grams of pieces damaged by insect or pathological injury, decay, scorch, bruise, tray blackening, dirt, discoloration or any other abnormality. 2/
	201	Presence of one or more clumps and matted or rolled material.
153		More than 15 percent of total can contents passes through a U. S. Standard No. 8 sieve (see 4.5.3.). 3/
		Rehydrated product (see 3.5.2) 2/
154		Color not typical of raw or cooked cabbage, as applicable.
155		Flavor not typical of raw or cooked cabbage, as applicable.
156		Texture not typical of raw cabbage (style A only).
157		Mushy (style B only).
158		Tough (style B only).
		Desiccant
159		Bag(s) missing.
160		Bag has tear, hole or open seal.
	202	Bag for form 2 compressed product not placed on top of product.

1/ Presence of any foreign material such as dirt, paint, wood, metal or other foreign material shall be cause for rejection of the lot.

2/ Make one determination per sample unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:32Z
Check the source to verify that this is the current version before use.

3/ When recording weighings in accordance with referenced procedure, report results to the nearest gram for 401 x 411 can and nearest 1/8 ounce for 603 x 700 can. Report calculated percentage of sieved material to the nearest percent.

* 4.3.3.1 Examination of cans for external condition and seam leakage.- Examination shall be in accordance with the applicable examination criteria in PPP-C-29 with the following exceptions. For external condition examination, the defects springer, flipper or swell shall not apply and USDA-CMS - Visual Aid #1 (illustrations of defects only) shall be used for classification of defects in lieu of guidance referenced in PPP-C-29.

4.3.3.2 Examination of can labeling.- Examination of cans for labeling shall be in accordance with the examination criteria contained in MIL-L-1497.

4.3.3.3 Examination of can coating.- When exterior coating of can is required to be in accordance with TT-C-495, examination criteria for can coating shall be in accordance with that specification.

* 4.3.3.4 Examination of the filled and closed shipping container.- Examination of the filled and closed shipping containers for levels A and B packing shall be in accordance with the quality assurance provisions contained in the appendix to PPP-B-636, with the following additions to the table for examination: Major - Marking missing, incorrect or illegible. Minor - Arrangement or number of cans not as specified. Examination of level C packing shall be in accordance with the above criteria except that only the defects pertaining to marking and arrangement shall apply.

* 4.3.3.5 Examination of palletized loads.- Palletized loads shall be examined in accordance with the criteria in MIL-L-35078.

4.3.4 Testing of end item.-

* 4.3.4.1 Oxygen content of cans.- The filled and sealed cans shall be tested for oxygen content in accordance with 4.5.4. The sample unit shall be one filled and sealed can, and the sample size shall be the number of sample units indicated by inspection level S-2. Lot size shall be expressed in terms of cans. The AQL, expressed as percent defective, shall be 2.5. A defect shall be scored if a sample unit has more than 2.0 percent (to nearest 0.1 percent) residual oxygen.

* 4.3.4.2 Moisture and sulphur dioxide.- The product shall be tested for moisture and sulphur dioxide content in accordance with 4.5. The sample for testing shall be a 1-pound composite of product extracted from the number of cans indicated by inspection level S-2. The composite shall be formed by the laboratory just prior to testing. Lot size shall be expressed in cans. Each result shall be reported to the same unit or decimal place specified for the pertinent requirement. Nonconformance to requirement for moisture or sulphur dioxide content shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:32Z
Check the source to verify that this is the current version before use.

4.4 Standby test samples.- The Government reserves the right to withdraw and withhold standby test samples of components or finished product or both (quantity of which shall be not more than twice that required by this specification) for inspection purposes. Samples not used will be returned to the supplier.

4.5 Tests.- Test procedures and controls which differ from those specified herein, may be used by the supplier if they provide a quality assurance equivalent to that specified. If the Government inspection activity determines that such procedures and controls do not provide, as a minimum, such quality assurance, the supplier will use the test procedures set forth herein. In case of dispute as to test results, the test methods specified herein will govern.

4.5.1 Moisture.- Moisture determination shall be made by the vacuum oven method as specified in 4.5.1.1 and 4.5.1.2.

NOTE: Samples for moisture determination shall be collected in clean, dry jars which shall be completely filled, sealed with airtight lids and held until analyzed.

* 4.5.1.1 Preparation of sample.- Prepare a clean dry Waring Blender or similar mill by grinding a sample and then discarding it. Grind approximately 100 grams of a well-mixed sample in the prepared Waring Blender or similar mill for one minute. Place the ground material on a U. S. Standard No. 20 sieve and analyze that portion which passes through for moisture.

4.5.1.2 Moisture determination.- Moisture determination procedure shall be as follows: Weigh two samples of approximately 2 grams each of the ground material into tared, dry, aluminum weighing dishes (approximately 2 to 2-1/2 inches in diameter and 3/4 inch in depth) with tight-fitting covers. Place the dishes with lids in a vacuum oven and dry for 16 hours at 60°C. under a pressure of not more than 100 mm. of mercury. During drying, admit to the oven a slow current of air (approximately 2 bubbles per second), dried by passing through concentrated sulfuric acid. Remove the dishes and allow them to cool in a desiccator before weighing. Calculate the percent of moisture in the original samples.

* 4.5.2 Sulfur dioxide determination.- The sulfur dioxide content shall be determined in accordance with the Official Methods of Analysis of the Association of Official Agricultural Chemists, chapter: Preservatives and Artificial Sweeteners; section: Sulfurous Acid; method: Total sulfurous acid.

* 4.5.3 Screening.- Screening test shall be performed as follows: Discard desiccant bag and weigh entire contents of can. Place approximately 1-1/2 ounces or 3 ounces of dehydrated material on an 8-inch or 12-inch diameter, respectively, U. S. Standard No. 8 sieve, tip back and forth through a 90-degree arc 25 times. Empty material remaining on sieve into an appropriate container and repeat this procedure until entire contents of can have been screened. Weigh total material passing through sieve and calculate percentage.

* 4.5.4 Oxygen content.- Oxygen content shall be determined in accordance with method 237 of Fed. Test Method Std. No. 101.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:32Z
Check the source to verify that this is the current version before use.

4.5.5 Tin coating weights.- Tin coating weights shall be determined by any method specified in PPP-C-96.

5. PREPARATION FOR DELIVERY

5.1 Packaging.- The product shall be packaged in accordance with 5.1.1 or 5.1.2, as specified (see 6.1).

* 5.1.1 Level A.- The product shall be filled into open-top style, round metal cans with soldered side seam and compound-lined, double-seamed ends. The cans shall be made throughout from not less than commercial 0.25-pound per base box electrolytic tin plate (see 4.5.5) and shall be coated outside with a coating conforming to type I or II, or when specified (see 6.1), type III, of TT-C-495. Net contents and can sizes shall be in accordance with table V as specified (see 6.1). Heating and compression, which does not adversely affect the dehydrated cabbage, may be used to effect packaging of the form 2 product. The cans shall be hermetically sealed. The product shall be gas-packed by first removing the air from the f- ed can and replacing it with nitrogen. If tip soldering is used to close the exhaust vents for nitrogen filling, a suitable noncorrosive flux shall be used. When the ends of the can are clinched prior to evacuation and gassing, the end flange or lid shall have been indented or dimpled to prevent seal-off trouble during the nitrogen flush. The oxygen content of the gases in the sealed container, not sooner than 3 days after filling, shall not exceed 2.0 percent when tested as specified in 4.5.4. Desiccant in accordance with MIL-D-43266 (except that it need not be placed in the center of the can in a horizontal position) and in sufficient quantity to reduce the moisture in the product to 1.5 percent, shall be included in each can. When the form 2 product is compressed during the filling proc the required amount of desiccant shall be put into one bag and placed on top of the product.

TABLE V - Can sizes, net weight per can, number and arrangement of cans in each shipping container

Can size	Net weight (ounces) (dry solids basis)	Number in case	Arrangement		
			Length	Width	Depth
401 by 411	4	24	4	3	2
603 by 700	16	6	3	2	1

5.1.2 Level C.- The product shall be packaged in accordance with 5.1.1 except that cans with or without a commercial exterior coating will be acceptable

5.2 Packing.- The cans of the product, in number and arrangement as shown in table V, shall be packed on end in snug-fitting shipping containers in accordance with 5.2.1, 5.2.2, or 5.2.3, as specified (see 6.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:32Z
Check the source to verify that this is the current version before use.

* 5.2.1 Level A.- The container shall be a snug-fitting fiberboard box, constructed, closed, and reinforced in accordance with style RSC, V2s of PPP-B-636.

* 5.2.2 Level B.- The container shall be a snug-fitting fiberboard box, constructed and closed in accordance with style RSC, type CF or SF, class domestic of PPP-B-636.

* 5.2.2.1 When specified (see 6.1 and 6.2), the container shall be a fiberboard box, constructed, closed, and reinforced in accordance with style RSC, W5c or W5s of PPP-B-636 except that round wire strapping shall not be used.

* 5.2.3 Level C.- The product shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rates for such supplies. The shipping container shall be in accordance with the rules or regulations applicable to the mode of transportation.

5.3 Unit loads.- The product, packed as specified (see 5.2), shall be arranged in unit loads in accordance with MIL-L-35078. The type and class of unit load shall be as specified (see 6.1).

5.4 Labeling and marking.-

5.4.1 Cans.- Cans shall be labeled in accordance with MIL-L-1497, and as follows:

CABBAGE, DEHYDRATED, RAW OR COOKED (as applicable)
(Preserved with sulphur dioxide)

_____ Ounces, net weight

DEHY. _____ Month and year of dehydration, in numerals (may be embossed on lid)

_____ Name and address of packer

_____ Location of processing plant

REMOVE AND DISCARD DESICCANT BAG

* 5.4.1.1 Directions for use.- The following directions for use, as applicable, shall be lithographed on the body or on one end of the can, or printed on the label:

For dehydrated raw cabbage:

401 x 411 can:

To prepare for salads and slaw:

Add 2 quarts of cool water to 4 ounces of cabbage, stir, cover

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:32Z
Check the source to verify that this is the current version before use.

and let stand at least 45 minutes. A 3-hour or overnight soak in refrigerator increases crispness and is recommended. Drain cabbage and combine with 1-1/2 cups of dressing. Yield: 16 1/3-cup servings.

To prepare for use as hot vegetable:

Add 1-1/2 quarts of cool water to 4 ounces of cabbage, stir, cover and let stand about 45 minutes. (Soaking may be omitted, if time is limited). Bring soaked cabbage to a boil, simmer 5 to 7 minutes, drain and season, or combine with other ingredients as instructed in recipe.

To substitute for fresh cabbage in recipes:

4 ounces are equivalent to 2-1/2 pounds of cabbage, as purchased, or 2 pounds of cabbage, edible portion.

6C3 x 700 can:

To prepare for salads and slaw:

Add 2 gallons of cool water to 1 pound of cabbage, stir, cover and let stand at least 45 minutes. A 3-hour or overnight soak in refrigerator increases crispness and is recommended. Drain cabbage and combine with 1-1/2 quarts of dressing. Yield: 66 1/3-cup servings.

To prepare for use as hot vegetable:

Add 1-1/2 gallons of cool water to 1 pound of cabbage, stir, cover and let stand about 45 minutes. (Soaking may be omitted, if time is limited). Bring soaked cabbage to a boil, simmer 5 to 7 minutes, drain and season, or combine with other ingredients as instructed in recipe.

To substitute for fresh cabbage in recipes:

1 pound is equivalent to 10 pounds of cabbage, as purchased or 8 pounds of cabbage, edible portion.

For dehydrated cooked cabbage:

401 x 411 can:

Add 1 quart of boiling water to 4 ounces of cabbage, stir, cover and let stand 15 to 20 minutes. Drain, season, stir and serve. Yield: 10 1/2-cup servings.

4 ounces of dehydrated cabbage are equivalent to 2-1/2 pounds of fresh cabbage, as purchased, or 2 pounds of fresh cabbage, edible portion.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:32Z
Check the source to verify that this is the current version before use.

603 by 700 can:

Add 1 gallon of boiling water to 1 pound of cabbage, stir, cover and let stand 15 to 20 minutes. Drain, season, stir and serve. Yield: 40 1/2 cup servings.

1 pound of dehydrated cabbage is equivalent to 10 pounds fresh cabbage, as purchased, or 8 pounds of fresh cabbage, edible portion.

5.4.2 Shipping containers.- Shipping containers shall be marked in accordance with MIL-STD-129.

* 5.4.3 Unit loads.- Unit loads shall be marked in accordance with MIL-L-35078 and MIL-STD-129.

6. NOTES

6.1 Ordering data.- Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Style and form of product required (see 1.2).
(c) Whether preproduction sample is to be furnished (see 3.1).
(d) Levels of packaging and packing required (see 5.1 and 5.2).
(e) When type III exterior can coating is required (see 5.1.1).
(f) Size of packaging required (see 5.1.1).
(g) When packing specified in 5.2.2.1 is required.
(h) Type and class of unit load required (see 5.3).

6.2 Packing specified in 5.2.2.1 is intended to provide the limited Military protection required for shipment of supplies to certain specified overseas destinations; transfer at sea; and for shipment and storage of Special Program Reserves.

* 6.3 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - SA
Air Force - 45

Review activities:

Army - MD
Navy - MC, SA
Air Force - 45

Preparing activity:

Army - GL

Project No. 8915-0289

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:32Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:32Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE. This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development
Laboratories
ATTN: DRDNA-ES (Mr. D. Luppino)
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:32Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:32Z
Check the source to verify that this is the current version before use.