MIL-B-833G
27 May 1988
SUPERSEDING
MIL-B-833F
24 November 1980

MILITARY SPECIFICATION

# BELT, TROUSERS, COTTON WEBBING, WITH CLIP

This specification is approved for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This document covers cotton webbing trouser belts with attached end clips.

* 1.2 Classification. Belts shall be of the following types and sizes as specified (see 6.2):

| | |
|---|---|
| Type I | - Black 174, 1-1/4 inch wide (with yellow brass end clip) (Navy, Marine Corps) |
| Type II | - Khaki 3709, 1-1/4 inch wide (with red brass end clip) (Marine Corps) |
| Type III | - Khaki 3709, 1-1/4 inch wide (with yellow brass end clip) (Navy) |
| Type IV | - Blue 1089, 1-1/4 inch wide (with nickel silver end clip) (Air Force) |
| Type V | - White, 1-1/4 inch wide (with yellow brass end clip) (Navy) |
| Type VI | - Black 174, 1-1/4 inch wide (with yellow brass with black enamel finish end clip) (Army) |
| Type VII | - Black 174, 1-1/4 inch wide (with nickel silver end clip) (Navy) |
| Type VIII | - White, 1-1/4 inch wide (with nickel silver end clip) (Navy) |

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 8440

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded at 2025-07-16T12:25
Check the source to verify that this is the current version before use.

| | |
|---|---|
| Type IX | - Blue 1089, 1-1/4 inch wide (yellow brass with black enamel finish end clip) (Air Force) |
| Type X | - Black 174, 1 inch wide (with nickel silver end clip) (Navy) |
| Type XI | - White, 1 inch wide (with nickel silver end clip) (Navy) |
| Type XII | - Black 174, 1 inch wide (with yellow brass end clip) (Navy) |
| Type XIII | - Khaki 3709, 1 inch wide (with yellow brass end clip) (Navy) |
| Type XIV | - White, 1 inch wide (with yellow brass end clip) (Navy) |
| Size | - 33 |
| Size | - 35 |
| Size | - 39 |
| Size | - 45 |
| Size | - 49 |

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

| | |
|---|---|
| PPP-B-636 | - Boxes, Shipping, Fiberboard |

MILITARY

| | |
|---|---|
| MIL-W-530 | - Webbing, Textile, Cotton, General Purpose, Natural or in Colors |
| MIL-B-1963 | - Buckles and Clips, End, Strap (For Belt, Trousers) |
| MIL-L-35078 | - Loads Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For |



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:33Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-731 - Quality of Wood Members for Containers and Pallets

(Copies of specifications, standards, and handbooks required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

2-4-45 - Belt, Trousers, Cotton Webbing, With Clip
2-1-545 - Belt, Trousers, Cotton Webbing, With Clip; Packing Arrangement for Rolls Of

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Copies should be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)



Source: https://assist.dla.mil -- Downloaded: 20260-16T11:33Z
Check the source to verify that this is the current version before use.

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

## 3. REQUIREMENTS

* 3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.4).

3.2 Materials (see 6.5).

3.2.1 Webbing, textile, cotton. The webbing shall conform to type IV of MIL-W-530. The width, class, and color of the webbing shall be as specified in table I for the types of belts indicated.

3.2.2 Clips, end. The end clips shall conform to type III of MIL-B-1963. The width, class, and subclass shall be as specified in table I for the types of belts indicated.

3.3 Construction. The construction shall be in accordance with Drawing 2-4-45 and as specified herein.

* 3.3.1 Setting of clips. The center of the webbing shall be aligned with the center of the end clip and the webbing shall be inserted to the full depth of the clips. The webbing shall lie flat within the confines of the end clip. When clinched, the prongs shall be fully embedded in the webbing and the edges of the webbing shall be equal distance from the edges of the end clips, ± 1/32 inch.

3.4 Marking. The size of the belt shall be legibly marked in the size characters and in the locations shown on Drawing 2-4-45. The color of the marking medium shall be in contrast to the color of the webbing.

3.5 Replacement of defective components. During the manufacturing process, components having material defects or damages that are classified as defects in 4.4.2 shall be removed from production and replaced with non-defective and properly matched components.

3.6 Workmanship. The finished belts shall conform to the quality of product established by this document and the occurrence of defects shall not exceed the applicable acceptable quality levels.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:33Z
Check the source to verify that this is the current version before use.

TABLE I. End clip requirements

| Belt type | Width of webbing (inches) | Webbing Class | Webbing Color | Size of end clip (inches) | End clip Class | End clip Subclass |
|---|---|---|---|---|---|---|
| I | 1-1/4 | 3 | Black 174 | 1-1/4 | 1 | A (yellow brass, mirror finish) |
| II | 1-1/4 | 3 | Khaki 3709 | 1-1/4 | 3 | - (red brass, mirror finish) |
| III | 1-1/4 | 3 | Khaki 3709 | 1-1/4 | 1 | A (yellow brass, mirror finish) |
| IV | 1-1/4 | 3 | Blue 1089 | 1-1/4 | 2 | - (nickel silver, satin finish) |
| V | 1-1/4 | 2 | White | 1-1/4 | 1 | A (yellow brass, mirror finish) |
| VI | 1-1/4 | 3 | Black 174 | 1-1/4 | 1 | B (yellow brass, black enamel finish) |
| VII | 1-1/4 | 3 | Black 174 | 1-1/4 | 2 | - (nickel silver, satin finish) |
| VIII | 1-1/4 | 2 | White | 1-1/4 | 2 | - (nickel silver, satin finish) |
| IX | 1-1/4 | 3 | Blue 1089 | 1-1/4 | 1 | B (yellow brass, black enamel finish) |
| X | 1 | 3 | Black 174 | 1 | 2 | - (nickel silver, satin finish) |
| XI | 1 | 2 | White | 1 | 2 | - (nickel silver, satin finish) |
| XII | 1 | 3 | Black 174 | 1 | 1 | A (yellow brass, mirror finish) |
| XIII | 1 | 3 | Khaki 3709 | 1 | 1 | A (yellow brass, mirror finish) |
| XIV | 1 | 2 | White | 1 | 1 | A (yellow brass, mirror finish) |





Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:33Z
Check the source to verify that this is the current version before use.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirement in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

* 4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

* 4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

* 4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.



Source: https://assist.dla.mil -- Downloaded: 202640-16T11:33Z
Check the source to verify that this is the current version before use.

* 4.4.2 End item visual examination. The end item shall be examined for the defects listed in table II. The lot size shall be expressed in units of belts. The sample unit shall be one belt. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0.

TABLE II. End item visual defects

| Examine | Defects |
|---|---|
| Webbing | Any hole, cut, tear, or smash<br>Not firmly and tightly woven, edge frayed or scalloped<br>Broken or missing end or pick<br>Spliced, (i.e., not one continuous piece)<br>Wrong color for type of belt specified<br>Width of webbing not as specified in table I for class being examined |
| Clip, end | Omitted or misplaced<br>Dents, nicks, abrasions or scratches on exposed surfaces<br>Broken or malformed, failing to serve intended purpose; protective finish omitted; corroded area; burr or sharp edge<br>Improperly clinched (i.e., prongs not fully embedded in webbing)<br>Not centered on webbing as specified (i.e., edges of webbing are not equal distance from edges of end clip, ± 1/32 inch)<br>End of webbing not set full depth in end clip<br>Webbing does not lie flat within confines of end clip<br>Black enamel finish is not adherent, e.g., it is blistered, peeling, flaking or cracked<br>Wrong color for type belt specified<br>Wrong finish for type belt specified<br>Size of end clip not as specified in table I for class being examined |
| Size marking | Omitted, illegible, incorrect, misplaced, or size characters not as specified |
| Cleanness | Spots or stains clearly noticeable |



Source: https://assist.dla.mil -- Downloaded: 202640-16T11:33Z
Check the source to verify that this is the currentversion before use.

4.4.3 End item dimensional examination. The end item shall be examined for the finished length specified on Drawing 2-4-45. Any length not within the specified tolerance shall be scored as a defect. The lot size shall be expressed in units of belts. The sample unit shall be one belt. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.4.4 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

| Examine | Defect |
|---|---|
| Marking (exterior and interior) | Omitted; incorrect; illegible; of improper size, location, sequence, or method of application |
| Materials | Any component missing, damaged, or not as specified |
| Workmanship | Inadequate application of components, such as incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling<br>Bulged or distorted container |
| Content | Number of rolls per shipping container is more or less than required<br>Number of belts per roll is more or less than required 1/<br>Size or type is not as indicated on container 1/ |

1/ For this defect, three rolls from each shipping container in the sample shall be examined.

* 4.4.5 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.



Source: https://assist.dla.mil -- Downloaded: 202610-16T11:33Z
Check the source to verify that this is the current version before use.

| Examine | Defect |
|---|---|
| Finished dimensions | Length, width, or height exceeds specified maximum requirement |
| Palletization | Pallet pattern not as specified<br>Interlocking of loads not as specified<br>Load not bonded as specified |
| Weight | Exceeds maximum load limits |
| Marking | Omitted; incorrect; illegible; of improper size, location, sequence, or method of application |

## 5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A. Five belts of one type and size only shall be evenly stacked with the clips at one end. The belts shall then be tightly rolled into a roll with the clips on the inside and secured with cotton tape, twine, or pressure-sensitive tape to form a unit pack.

* 5.1.2 Commercial. Belts shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

* 5.2.1 Level A packing. Belts of one type and size only, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Level A unit packs shall be packed as shown in Drawing 2-1-545. Inside dimensions of each shipping container shall be approximately 15-1/2 inches in length, 11-9/16 inches in width, and 7-1/8 inches in depth. Approximate dimensions are furnished as a guide only. Corrugated fiberboard filler pads shall be used to fill voids. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.4. Type I through type IX belts shall be packed 110 per shipping container and type X through type XIV belts shall be packed 130 per shipping container. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of unit load specified (see 6.2). When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.



Source: https://assist.dla.mil -- Downloaded: 202640-16T11:33Z
Check the source to verify that this is the currentversion before use.

5.2.2 Level B packing. Belts of one type and size only, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Level A unit packs shall be packed as shown in Drawing 2-1-545. Inside dimensions of each shipping container shall be approximately 15-1/2 inches in length, 11-9/16 inches in width, and 7-1/8 inches in depth. Approximate dimensions are furnished as a guide only. Corrugated fiberboard filler pads shall be used to fill voids. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.4. Type I through type IX belts shall be packed 110 per shipping container and type X through type XIV belts shall be packed 130 per shipping container.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.4.

* 5.2.3 Commercial packing. Belts, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

* 5.3 Palletization. When specified (see 6.2), belts, packed as specified in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 9 in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course.

5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The belts are used by Army, Navy, Marine Corps, and Air Force personnel.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Type and size required (see 1.2).
c. When a first article is required (see 3.1, 4.3, and 6.4).
d. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:33Z
Check the source to verify that this is the current version before use.

e. Type and class of unit load required (see 5.2.1).
f. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
g. When palletization is required (see 5.3).

6.3 Standard sample. For access to samples, address the contracting activity issuing the invitation for bids.

* 6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.2).

* 6.6 Subject term (key word) listing.

Accessories
Belt with clip
Trouser belts

6.7 Changes from previous issue. The margins of this document are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, as written, irrespective of the marginal notations and relationship to the last previous issue.



Source: https://assist.dla.mil -- Downloaded: 202640-16T11:33Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - NU
Air Force - 11

Review activities:

Army - MD
Navy - MC
Air Force - 99, 82
DLA - CT

User activities:

Navy - CG
Air Force - 45

Preparing activity:

Army - GL

Project No. 8440-0176



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:33Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| MIL-B-833G | Belt, Trousers, Cotton Webbing, With Clip |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR |
| | ☐ USER |
| b. ADDRESS *(Street, City, State, ZIP Code)* | ☐ MANUFACTURER |
| | ☐ OTHER *(Specify)*: _____ |

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:33Z
Check the source to verify that this is the current version before use.

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP 1 Apr 84