MIL-D-771D
4 August 1978
SUPERSEDING
MIL-D-771C
29 October 1971

MILITARY SPECIFICATION

DISTRIBUTORS, BITUMEN AND WATER, PACKAGING OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the requirements for methods, materials, and procedures for the preservation, packing, and marking of truck-mounted and trailer-mounted distributors (including kettles) for bitumen and water.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, and Seals.
TT-P-664	- Primer Coating, Synthetic, Rust-inhibiting, Lacquer-resisting.
UU-T-81	- Tags, Shipping and Stock.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-1055	- Barrier Material, Waterproofed, Flexible.

FSC PACK

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

PPP-C-843	- Cushioning Material, Cellulosic.
PPP-P-40	- Packaging and Packing of Hand Tools.
PPP-T-60	- Tape: Packaging, Waterproof.

MILITARY

MIL-P-116	- Preservation-Packaging, Methods of.
MIL-B-121	- Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-R-196	- Repair Parts for Internal Combustion Engines, Packaging of.
MIL-L-2105	- Lubricating Oil, Gear, Multipurpose.
MIL-B-3180	- Boilers and Related Equipment, Packaging of.
MIL-C-5501	- Cap and Plug, Protective, Dust and Moisture Seal.
MIL-E-10062	- Engines, Preparation for Shipment and Storage of.
MIL-L-21260	- Lubricating Oil, Internal Combustion Engine, Preservative, and Break-In.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-281	- Automobiles, Trucks, Truck-Tractors, Trailers and Trailer Dollies; Preservation and Packaging of.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Preproduction pack. When specified (see 6.2), the contractor shall furnish a preproduction pack within the time frame specified (see 6.2) to prove prior to starting production packaging, that the applied preservation, packing, and marking comply with the requirements of this specification. Examination shall be ass specified in Section 4 and shall be subject to

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

surveillance and approval by the Government (see 6.3). The preproduction pack may be accomplished utilizing either the preproduction distributor or a production distributor. If the preproduction model distributor is utilized, any preservation and packing shall be removed by the contractor at no expense to the Government when requested by the Government to facilitate comparison between the preproduction model distributor and production distributors.

3.2 Materials. Materials shall be as specified herein and in applicable specifications and standards. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification. Materials shall be free of defects (see 6.4).

3.3 Preservation. Preservation shall be Level A, Level B, or Commercial as specified (see 6.2).

3.3.1 Level A.

3.3.1.1 Disassembly and matchmarking.

3.3.1.1.1 Disassembly. Disassembly shall be the minimum necessary to safeguard parts vulnerable to damage, pilferage, and loss. The extent of further disassembly shall be confined to the removal of protruding parts that would otherwise increase cubage; however, disassembly shall be limited to those parts that can easily be removed and reinstalled without special tools or skilled personnel. Removed bolts, nuts, pins, screws, and washers shall be reinstalled in mating parts and secured to prevent their loss.

3.3.1.1.2 Matchmarking. Removed parts and mating parts on the distributor shall be matchmarked when necessary to facilitate reassembly. Removed parts shall be identified by cloth tags conforming to UU-T-81, Type A, and the marked tags shall be attached to mating parts. The printing thereon shall be in waterproof ink.

3.3.1.2 Preservatives. Preservatives specified herein shall conform to the applicable specification listed in and shall be applied in accordance with MIL-P-116, except preservative lubricating oil specified herein shall conform to MIL-L-21260, type and grade as specified.

3.3.1.2.1 Caution. Distributors used for potable water shall have no preservatives (other than Type P-14) applied to any surface that will contact the water. This requirement also applies to the repair parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

3.3.1.3 Unprotected surfaces.

3.3.1.3.1 Unfinished surfaces. Unpainted, unfinished metal surfaces of items such as tie rods, adjusting rods, springs, grease fittings, bolts, nuts, and similar parts, including those exposed by disassembly, except components contacting potable water (see 3.3.1.2.1), requiring the application of a contact preservative in accordance with MIL-P-116, shall be coated with Type P-1 preservative.

3.3.1.3.2 Machined surfaces. Exposed machined surfaces of parts, except components contacting potable water (see 3.3.1.2.1), shall be coated with Type P-6 or P-11 preservative and wrapped or covered with barrier material conforming to MIL-B-121, Type I, Grade A, Class 2, secured in place with tape conforming to PPP-T-60, Type IV.

3.3.1.4 Engines. All engines and engine accessories shall be preserved in accordance with the Level A requirements of MIL-E-10062, Type I, Method I.

3.3.1.5 Instrument panels. The glasses of instruments, meters and gages, if not protected by a cover, housing, or cab, shall be covered with barrier material conforming to MIL-B-121, Type I, Grade A, Class 2, over which a fitted piece of 1/4-inch plywood or hardboard shall be placed and secured with tape conforming to PPP-T-60, Type IV.

3.3.1.6 Gears.

3.3.1.6.1 Exposed gears. Exposed gears shall be coated with Type P-1 preservative.

3.3.1.6.2 Enclosed gears. Gears operating on lubricating oil (SAE 10, 30 or 50) shall have the housings filled to the operating level with preservative lubricating oil, Type I, grade as applicable, and the gear controls tagged to indicate: "The preservative oil contained in the gear housing is adequate for operation. Do not drain until the first required lubricant change." Gears operating on gear lubricant (SAE 80 or 90) shall have the housings filled to the operating level with lubricant conforming to MIL-L-2105, grade as applicable, and the gear controls tagged to indicate: "The lubricant contained in the gear housing is adequate for operation. Do not drain until the first required lubricant change." Gears not operating on lubricating oil (SAE 10, 30 or 50) or gear lubricant (SAE 80 or 90) shall have the housings filled to the operating level with the approved lubricant or operating oil, and the gear controls tagged to indicate: "The gear housing is filled with the approved lubricant. Do not drain." Tags specified herein shall conform to UU-T-81, Type A, and the printing thereon shall be in waterproof ink.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

3.3.1.7 Chains.

3.3.1.7.1 Exposed roller chains. Exposed roller chains shall be coated with enough Type P-3 or P-9 preservative to assure penetration of the preservative to the inner surfaces of the rollers, pins, and bushings. After the excess preservative has drained, the entire chains and the sprockets shall be coated with Type P-1 preservative.

3.3.1.7.2 Enclosed chains. Enclosed chains and chain housing shall be preserved, filled, and tagged as specified in 3.3.1.6.2 for enclosed gears.

3.3.1.8 Drive belts. Drive belts shall be removed or released from tension. Removed belts shall be preserved in accordance with MIL-P-116, Method IC-1. Unpainted pulley faces or grooves shall be coated with primer conforming to TT-P-664.

3.3.1.9 Pumps (centrifugal and rotary). The interior surfaces of the pumps, such as impellers, rotors, rotor shafts, pistons, piston rods, thrust pins, cylinders, cylinder walls, and gears, shall be coated with the applicable type preservative as follows: Preservative lubricating oil, Type I, Grade 30 for fuel and bitumen pumps; Type P-3 or P-9 preservative for nonpotable water pumps; Type P-14 preservative for potable water pumps. Openings into pump interiors (suction and discharge) shall be sealed or covered with plastic caps or plugs conforming to MIL-C-5501 or with tape conforming to PPP-T-60, Type IV.

3.3.1.10 Bitumen tanks. Interior surfaces of bitumen tanks (except corrosion-resistant treated tanks), tank gage mechanisms, screens and strainers, and the interior surfaces of overflow pipes and dome covers shall be coated with preservative lubricating oil, Type I, Grade 30. Unpainted exterior surfaces of the tanks requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with Type P-1 preservative. The drain valves shall be left open.

3.3.1.11 Water tanks. Interior surfaces of water tanks (except corrosion-resistant treated tanks), tank gage mechanisms, screens and strainers, and interior surfaces of overflow pipes and dome covers shall be coated with the applicable type of preservative as follows: Type P-3 or P-9 preservative for nonpotable water tanks, and Type P-14 preservative for potable water tanks. The drain valves shall be left open.

3.3.1.12 Spraybars, piping, valves, and fittings. Interior surfaces of bitumen spraybars, piping, valves, fittings, and nozzles for the spraybars shall be coated with preservative, lubricating oil, Type I, Grade 30. Interior surfaces of nonpotable water spraybars, piping, valves, fittings, and

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

nozzles for the spraybars shall be coated with Type P-3 or P-9 preservative. Exterior surfaces of the spraybars (both bitumen and water) requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with Type P-1 preservative. Ball or swivel joints of spraybars shall be coated with Type P-1 preservative. Spraybars removed from the distributors shall be wrapped with barrier material conforming to MIL-B-121, Type I, Grade A, Class 2, and the wrap shall be secured with tape conforming to PPP-T-60, Type IV.

3.3.1.13 Discharge hoses and hand spraybars. The flexible discharge hose shall be disconnected from the distributor and from the hand spraybar. The hose shall be coiled to the minimum safe diameter and the coil shall be secured with tape conforming to PPP-T-60, Type IV. Interior surfaces of the hand spraybars shall be coated with preservative as follows: Preservative lubricating oil, Type I, Grade 30 for bitumen spraybars; Type P-3 or P-9 preservative for nonpotable water spraybars. Unpainted exterior surfaces of the spraybars (both bitumen and water) requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with Type P-1 preservative. The spraybars shall be wrapped and secured as specified in 3.3.1.12.

3.3.1.14 Pump tachometers, gages, and thermometers. The dial glass of tachometers shall be protected with cushioning material conforming to PPP-C-843, Type II, Class A, and overwrapped with barrier material conforming to MIL-B-121, Type I, Grade A, Class 2, and the wrap shall be secured with tape conforming to PPP-T-60, Type IV. Gages and thermometers not removed from the distributors shall be protected with cushioning and overwrapped, and the wrap shall be secured as specified herein for tachometer dial glasses. Gages and thermometers removed from the distributors shall be wrapped with cushioning material specified herein and individually preserved in boxes conforming to PPP-B-636, W5c or W6c. Box closure shall be in accordance with the appendix to the box specification, Method V. Openings where gages have been removed shall be sealed with tape specified herein.

3.3.1.15 Bitumeters and fifth wheel tachometers. Bitumeter and fifth wheel tachometer assemblies removed from the distributors shall be detached from the wheels. The dial glass of the bitumeter dial shall be cushioned and secured as specified in 3.3.1.14. The assemblies shall be individually preserved in boxes conforming to PPP-B-636, W5c or W6c as applicable. Box closure shall be in accordance with the appendix to the box specification, Method V. Assemblies not removed from the distributors shall be secured in the carrying position on the distributors, and any unpainted metal surface requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with Type P-1 preservative. The dial glass shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

be cushioned, wrapped, and secured with tape as specified in 3.3.1.14, except when the bitumeter dial is located within the truck cab, no cushioning, wrapping or securing shall be required.

3.3.1.16 Heating systems. Interior surfaces of the burner fuel tanks (except corrosion-resistant treated tanks), fuel pumps, steel piping, and valves shall be coated with preservative lubricating oil, Type I, Grade 30. Excess preservative shall be drained from the system. The opening in the burner stack, if not equipped with a metal rain cap, shall be covered with barrier material conforming to PPP-B-1055, Class E-2 and secured with tape conforming to PPP-T-60, Type IV. If equipped with a rain cap, the cap shall be closed and secured with tape as specified herein.

3.3.1.17 Portable burners. Interior surfaces of the tank (except corrosion-resistant treated tanks), burner, and valves shall be coated with preservative lubricating oil, Type I, Grade 30. Unpainted exterior surfaces of the tank, burner, and hose clamps requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with Type P-1 preservative. The hose and carrying straps shall be detached. Any openings into the tank shall be sealed with tape conforming to PPP-T-60, Type IV. The straps shall be wrapped with barrier material conforming to PPP-B-1055, Class C-1, and the wrap shall be secured with tape conforming to PPP-T-60, Type IV. The hose shall be coiled to a minimum safe diameter and the coil secured with cotton cord or tape as specified herein.

3.3.1.18 Bitumen heaters (boiler type). The heater, components, and accessories shall be preserved in accordance with the Level A requirements of MIL-B-3180.

3.3.1.19 Hose, hose couplings, and hose fittings. Unpainted surfaces of couplings and fittings (except couplings and fittings that will contact potable water) requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with Type P-1 preservative. Hose couplings and fittings intended for use with potable water shall be coated with Type P-14 preservative. Each length of hose shall be coiled, the coil shall be secured amd wrapped with barrier material conforming to PPP-B-1055, Class C-1, and the wrap shall be secured with tape conforming to PPP-T-60, Type IV. Metal flexible hose, when furnished, shall not require wrapping but shall be coiled and secured with cotton cord or tape specified herein.

3.3.1.20 Metal measuring sticks. Unpainted metal measuring sticks requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with the applicable type of preservative as follows: Type P-1 preservative for bitumen and nonpotable water distributors; Type P-14 preservative for potable water distributors. Sticks coated

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

with Type P-14 preservative shall be wrapped with barrier-material conforming to MIL-B-121, Type I, Grade A, Class 2, and the wrap shall be secured with tape conforming to PPP-T-60, Type IV. The sticks shall be placed and secured in the carrying brackets on the distributor.

3.3.1.21 Repair parts. The preservative application criteria and applicable method(s) of preservation of MIL-P-116 shall be used to preserve the repair parts, except only Type P-14 preservative shall be applied to repair parts that will come in contact with potable water when placed in use on the distributor. When specified engine repair parts shall be preserved in accordance with MIL-R-196 (see 6.2).

3.3.1.22 Maintenance tools. Maintenance tools shall be preserved in accordance with the Level A requirements of PPP-P-40.

3.3.1.23 Distributor charts. Distributor charts required for each unit shall be preserved together in accordance with MIL-P-116, Method IC-1 or IC-3.

3.3.1.24 Technical publications or instructional material. Technical publications or instructional material for each distributor shall be preserved together in accordance with MIL-P-116, Method IC-1 or IC-3.

3.3.1.25 Truck chassis and trailers. The truck chassis, trailers, components, and accessories shall be preserved in accordance with the Level A (mobile) requirements of MIL-STD-281.

3.3.1.26 Consolidation. The components for each distributor, repair parts, maintenance tools, distributor charts, and technical publications or instructional material shall be consolidated in close-fitting boxes conforming to PPP-B-601, Overseas Type, style optional. Strapping shall not be required. The size of the boxes shall be determined by the available space for securing to the distributor and to accomplish the packing specified in 3.4.

3.3.2 Level B. Unless otherwise specified Level B preservation shall be as follows (see 6.2 and 6.7).

3.3.2.1 Disassembly. Disassembly shall be as specified in 3.3.1.1.1 for Level A.

3.3.2.2 Matchmarking. Matchmarking shall be as specified in 3.3.1.1.2 for Level A, except waterproofing of tags shall not be required.

3.3.2.3 Preservatives. Cleaning, drying, and application of preservatives shall be as specified in 3.3.1.2 and 3.3.1.2.1 for Level A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

3.3.2.4 Unprotected surfaces. Unprotected surfaces shall be preserved as specified in 3.3.1.3 for Level A.

3.3.2.5 Engines. All engines and engine accessories shall be preserved as specified in 3.3.1.4 for Level A.

3.3.2.6 Instrument panels. Instrument and gage glasses not protected by a cover, housing, or cab shall be protected as specified in 3.3.1.5 for Level A.

3.3.2.7 Exposed gears. Exposed gears shall be preserved as specified in 3.3.1.6.1 for Level A.

3.3.2.8 Enclosed gears and chains. The housings shall be filled to the operating level with the lubricant recommended for operation and the gears or chains actuated to assure coverage of all interior surfaces with the lubricant. A cloth tag conforming to UU-T-81 shall be attached to the controls indicating: "The housing is filled to the operating level with the required lubricant."

3.3.2.9 Exposed roller chains. Exposed roller chains shall be coated with enough Type P-3 or P-9 preservative to assure penetration of the preservative to the inner surfaces of the rollers, pins, and bushings.

3.3.2.10 Drive belts. Drive belts shall be released from tension.

3.3.2.11 Pumps. Pumps shall be preserved as specified in 3.3.1.9 for Level A.

3.3.2.12 Bitumen and water tanks. Preservation is not required, but the drain valves on bitumen water tanks shall be left open.

3.3.2.13 Gages and thermometers. Gages and thermometers removed from the distributors shall be preserved in accordance with MIL-P-116, Method III, using boxes conforming to PPP-B-636, Class Domestic, Variety SW, grade and style optional, as the containers. Openings where gages have been removed shall be sealed with tape specified herein.

3.3.2.14 Bitumeters and tachometers. The assemblies shall be secured in the carrying position on the distributors.

3.3.2.15 Heating systems and portable burners. Interior surfaces of the heating systems and portable burners shall be coated with preservative as specified in 3.3.1.16 and 3.3.1.17 for Level A. The opening in the burner

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

stack, if not equipped with a cap, shall be sealed as specified in 3.3.1.16; if equipped with a rain cap, the cap shall be closed and secured with tape as specified herein.

3.3.2.16 Bitumen heaters (boiler type). Boiler type bitumen heaters shall be preserved in accordance with the Level B requirements of MIL-B-3180.

3.3.2.17 Repair parts, maintenance tools, distributor charts, and technical publications or instructional material. Repair parts, maintenance tools, distributor charts, and technical publications or instructional material shall be preserved as specified in 3.3.1.21, 3.3.1.22, 3.3.1.23, and 3.3.1.24 for Level A.

3.3.2.18 Truck and trailer chassis. The truck and trailer chassis, components, and accessories shall be preserved in accordance with the Level B (mobile) requirements of MIL-STD-281.

3.3.2.19 Consolidation. Consolidation shall be as specified in 3.3.1.26 for Level A, except boxes shall be Domestic Type.

3.3.3 Commercial. Unless otherwise specified (see 6.2), each distributor, accessories, repair parts, maintenance tools, and technical publications shall be preserved in accordance with MIL-STD-1188.

3.4 Packing. Packing shall be Level A, Level B, or Commercial as specified (see 6.2).

3.4.1 Level A. Each complete distributor, preserved as specified in 3.3 shall be prepared for unboxed (mobile) shipment. Removed and consolidated components shall be secured on the distributor in any available space that will not increase cubage or interfere with lifting or towing. The components shall be secured in a manner to prevent movement, pilferage, or damage, by the use of zinc coated strapping conforming to QQ-S-781, Type I or IV, heavy duty, Finish B, size as applicable. On trailer-mounted distributors, the support legs (landing gears) shall be used for parking and storage only. For shipment, the trailer front shall be secured and supported by the use of wood cribbing or blocking as applicable, to prevent damage to the support legs.

3.4.2 Level B. Each complete distributor, preserved as specified in 3.3 shall be prepared for shipment as specified in 3.4.1 for Level A except strapping shall not be required to be Finish B.

3.4.3 Commercial. Unless otherwise specified (see 6.2), each complete distributor, preserved as specified in 3.3 shall be packed in accordance with MIL-STD-1188. Support legs of trailer-mounted distributors shall be used for

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

parking and storage only and shall not be used for support of the trailer during shipment.

3.5 Marking.

3.5.1 Military packaging. Marking shall be in accordance with MIL-STD-129.

3.5.2 Commercial packaging. Unless otherwise specified (see 6.2), marking shall be in accordance with MIL-STD-1188.

3.6 Depreservation guides. Two depreservation guides shall be prepared. One copy shall be placed in a waterproof envelope marked "Depreservation Guide", and the envelope secured to the distributor in a conspicuous location. The other copy shall be preserved with other instructional material and the pack marked to indicate: "A depreservation guide is inside." Unless otherwise specified, "DA Form 2258 - Depreservation Guide for Vehicles and Equipment" shall be used (see 6.2 and 6.5).

3.7 Workmanship. Workmanship shall be such as to provide maximum protection to the distributors by application of the requirements specified herein, to prevent corrosion, deterioration, and mechanical or physical damage during handling, shipment, and storage.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Material inspection. The contractor is responsible for insuring that supplies and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) Preproduction pack inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

4.3 Preproduction pack inspection.

4.3.1 Examination. The preproduction pack shall be examined for the defects specified in 4.4.4. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Inspection stages. Inspection stages shall be in four stages as follows:

(a) The first stage shall include inspection of procedures, methods, materials, containers, and unit marking prior to placing the components into consolidated containers.
(b) The second stage shall include inspection of closure and marking of consolidated containers.
(c) The third stage shall include inspection of materials and methods of securing consolidated containers and removed components to the distributor.
(d) The fourth stage shall include inspection of marking.

4.4.2 Unit of product. For the purpose of inspection a completed pack of any one level shall be considered a unit of product.

4.4.3 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.4 Examination. Samples selected in accordance with 4.4.3 shall be examined for the defects marked "X" for the applicable level in Table I. AQL shall be 2.5 percent defective.

Table I. Examination

Major	Defects	Level A	Level B
101.	Materials, methods, and containers not as specified. Each incorrect material, method, or container shall constitute one defect (3.2, 3.3, and 3.4).	X	X
102.	Disassembly not as specified (3.3.1.1.1, 3.3.2.1).	X	X
103.	Matchmarking not as specified (3.3.1.1.2, 3.3.2.2).	X	X
104.	Tags used for matchmarking not waterproofed (3.3.1.1.2).	X	-
105.	Petroleum base preservatives applied to surfaces that will contact potable water (3.3.1.2.1).	X	X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

Table I. Examination (continued)

Major	Defects	Level A	Level B
106.	Unfinished surfaces not coated with specified preservatives (3.3.1.3.1, 3.3.2.4).	X	X
107.	Machined surfaces not coated with preservative and wrapped and secured (3.3.1.3.2, 3.3.2.4).	X	X
108.	Engines and engine accessories not preserved in accordance with the referenced document (3.3.1.4, 3.3.2.5).	X	X
109.	Glasses of instruments, meters, and gages not protected (3.3.1.5, 3.3.2.6).	X	X
110.	Exposed gears not coated as specified (3.3.1.6.1, 3.3.2.7).	X	X
111.	Enclosed gears not preserved or the housings not filled with operational lubricant as applicable (3.3.1.6.2, 3.3.2.8).	X	X
112.	Gear housings not tagged as specified (3.3.1.6.2, 3.3.2.8).	X	X
113.	Tags on gear housings not waterproofed (3.3.1.6.2).	X	-
114.	Exposed roller chains not coated as specified (3.3.1.7.1, 3.3.2.9).	X	X
115.	Enclosed chain not preserved or the housing not filled with operational lubricant as applicable (3.3.1.7.2, 3.3.2.8).	X	X
116.	Drive belts not removed or released from tension (3.3.1.8).	X	-
117.	Drive belts not released from tension (3.3.2.10).	-	X
118.	Unpainted pulley faces or grooves not coated with primer (3.3.1.8).	X	-
119.	Interior surfaces of pumps not coated with the applicable type preservative (3.3.1.9, 3.3.2.11).	X	X
120.	Openings into pump interiors not covered or sealed with cap, plugs, or tape as specified (3.3.1.9, 3.3.2.11).	X	X
121.	Interior surfaces of bitumen tanks not coated with preservative when required (3.3.1.10).	X	-
122.	Unpainted exterior surfaces of bitumen tanks not coated with the specified preservative (3.3.1.10).	X	-
123.	Bitumen tanks not drained and the valves not left open (3.3.1.10, 3.3.2.12).	X	X
124.	Interior surfaces of water tank not coated with the applicable type preservative as specified (3.3.1.11).	X	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

Table I. Examination (continued)

Major	Defects	Level A	Level B
125.	Water tanks not drained and the valves not left open (3.3.1.11, 3.3.2.12).	X	X
126.	Interior surfaces of spraybars, piping, valves, fittings, and nozzles not coated with applicable type of preservative (3.3.1.12).	X	-
127.	Exterior surfaces of spraybars not coated with specified preservative (3.3.1.12).	X	-
128.	Spraybars removed from the distributors not wrapped with barrier materials (3.3.1.12).	X	-
129.	Flexible discharge hose not disconnected from the distributor and the hand spraybars (3.3.1.13).	X	-
130.	Flexible discharge hose not coiled and the coil not secured with tape (3.3.1.13).	X	-
131.	Interior surfaces of hand spraybars not coated with applicable type of preservative (3.3.1.13).	X	-
132.	Exterior surfaces of hand spraybars not coated with specified preservative (3.3.1,13).	X	-
133.	Hand spraybars not wrapped with barrier-material as specified (3.3.1.13).	X	-
134.	Dial glass of tachometers, gages, and thermometers not cushioned and protected as specified (3.3.1.14).	X	-
135.	Gages and thermometers removed from the distributors not preserved as specified (3.3.1.14, 3.3.2.13).	X	X
136.	Openings where gages have been removed not sealed with tape (3.3.1.14, 3.3.2.13).	X	X
137.	Bitumeter and tachometer assemblies, if removed, not preserved as specified (3.3.1.15).	X	-
138.	Bitumeter and tachometer assemblies, if not removed, not secured in the carrying position (3.3.1.15, 3.3.2.14).	X	X
139.	Interior surfaces of heater fuel systems and portable burners not coated with preservative as specified (3.3.1.16, 3.3.2.15).	X	X
140.	Opening into burner stack not sealed as specified (3.3.1.16, 3.3.2.15).	X	X
141.	Hose and carrying straps not removed from portable burners and preserved as specified (3.3.1.17).	X	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

Table I. Examination (continued)

Major	Defects	Level A	Level B
142.	Bitumen heaters (boiler type), components and accessories not preserved in accordance with the referenced document (3.3.1.18, 3.3.2.16).	X	X
143.	Hose, hose couplings, or fittings not coated with applicable type of preservative when required or secured and wrapped as specified (3.3.1.19).	X	-
144.	Metal measuring sticks not coated with applicable type preservative as specified (3.3.1.20).	X	-
145.	Metal measuring sticks coated with Type P-14 preservative not wrapped as specified (3.3.1.20).	X	-
146.	Metal measuring sticks not placed and secured on the distributor (3.3.1.20).	X	-
147.	Repair parts, maintenance tools, distributor charts, and technical publications or instructional material not preserved as specified (3.3.1.21, 3.3.1.22, 3.3.1.23, 3.3.1.24, 3.3.2.17).	X	X
148.	Truck and trailer chassis not preserved in accordance with the referenced document (3.3.1.25, 3.3.2.18).	X	X
149.	Consolidation not as specified (3.3.1.26, 3.3.2.19).	X	X
150.	Consolidation containers and components not secured to the mobile distributors in a manner to conserve cube, or secured so as to interfere with towing or lifting (3.4.1, 3.4.2).	X	X
151.	Strapping not as specified (3.4.1, 3.4.2).	X	X
152.	Marking missing, illegible, incomplete, or incorrect (3.5).	X	X
153.	Depreservation guide not prepared and attached as specified (3.6).	X	X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

5. PACKAGING

(This section not applicable to this specification.)

6. NOTES

6.1 Intended use. It is intended that this specification be used for reference in Section 5 of commodity and equipment specifications or for direct reference in contracts or as a guide for the preparation of packaging data sheets to be used in procurement.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) When a preproduction pack is required and the time frame required for submission of the preproduction pack (see 3.1).
(c) Degree of preservation and degree of packing required (see 3.3 and 3.4). Level B preservation (see 3.3.2 and 6.7), is intended to provide economical but limited protection and should be specified only when it has been determined the distributors will be held in covered storage.
(d) When Level B preservation shall be other than specified (see 3.3.2).
(e) When engine repair parts are to be preserved in accordance with MIL-R-196 (see 3.3.1.21).
(f) When commercial preservation, packing, and marking is other than specified (see 3.3.3, 3.4.3, and 3.5.3).
(g) When other than DA Form 2258 is to be used (see 3.6).

6.3 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to the approval of the contracting officer. Approval of the preproduction pack will not relieve the contractor of his obligation to preserve, pack, and mark the distributors in accordance with this specification.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.2).

6.5 Depreservation guides. The contracting officer should arrange to furnish the necessary copies of DA Form 2258, when requested by the contractor (see 3.6).

6.6 Environmental. Environmental pollution prevention measures are contained in the packaging material specification referenced herein. Refer to material specification or preparing activity for recommended disposability methods.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

6.7 Level B preservation. Level B preservation (see 3.3.2) has been developed for use by the Army and Air Force for the specific conditions specified in 6.2(c). For Navy procurements, details of Level B preservation, when required, will be developed at time of procurement when all conditions are known.

Custodians:
Army - ME
Navy - YD

Review activity:
Army - SM

Preparing activity:
Army - ME

Project 3895-0246

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-D-771D Distributors, Bitumen and Water, Packaging of

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Mobility Equipment Research
and Development Command
ATTN: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.