NOT MEASUREMENT SENSITIVE

MIL-D-771E
26 October 1990
SUPERSEDING
MIL-D-771D
4 August 1978

MILITARY SPECIFICATION

DISTRIBUTORS, BITUMEN AND WATER, PACKAGING OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for methods, materials, and procedures for the preservation, packing, and marking of truck-mounted and trailer-mounted distributors (including kettles) for bitumen and water.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

TT-P-664	- Primer Coating, Alkyd, Corrosion-Inhibiting, Lead and Chromate Free, VOC-Compliant.
UU-T-81	- Tags, Shipping and Stock.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-1055	- Barrier Material, Waterproofed, Flexible.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC PACK
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

PPP-C-843 - Cushioning Material, Cellulosic.
PPP-P-40 - Packaging and Packing of Hand Tools.
PPP-T-60 - Tape: Packaging, Waterproof.

MILITARY

MIL-P-116 - Preservation, Methods of.
MIL-B-121 - Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-S-196 - Support Items, Accessories and Kits, Mechanical: Packaging of.
MIL-L-2105 - Lubricating Oil, Gear, Multipurpose.
MIL-B-3180 - Boilers and Related Equipment, Packaging of.
MIL-C-5501 - Cap and Plug, Protective, Dust and Moisture Seal.
MIL-E-10062 - Engines: Preparation for Shipment and Storage of.
MIL-L-21260 - Lubricating Oil, Internal Combustion Engine, Preservative and Break-In.
MIL-V-62038 - Vehicle, Wheeled, Preparation for Shipment and Storage.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3953 - Strapping, Flat Steel and Seals.
D 4675 - Selection and Use of Flat Strapping Materials.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia PA 19103.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. Unless otherwise specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials. Materials shall be as specified herein and in applicable specifications and standards. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification. Materials shall be free of defects.

3.3 Preservation. Preservation shall be level A or C as specified (see 6.2).

3.3.1 Level A.

3.3.1.1 Disassembly and matchmarking.

3.3.1.1.1 Disassembly. Disassembly shall be the minimum necessary to safeguard parts vulnerable to damage, pilferage, and loss. The extent of further disassembly shall be confined to the removal of protruding parts that would otherwise increase cubage; however, disassembly shall be limited to those parts that can easily be removed and reinstalled without special tools or skilled personnel. Removed bolts, nuts, pins, screws, and washers shall be reinstalled in mating parts and secured to prevent their loss.

3.3.1.1.2 Matchmarking. Removed parts and mating parts on the distributor shall be matchmarked when necessary to facilitate reassembly. Removed parts shall be identified by cloth tags conforming to UU-T-81, type A and the marked tags shall be attached to mating parts. The printing thereon shall be in waterproof ink.

3.3.1.2 Preservatives. Preservatives specified herein shall conform to the applicable specification listed in and shall be applied in accordance with MIL-P-116, except preservative lubricating oil specified herein shall conform to MIL-L-21260, type and grade as specified.

3.3.1.2.1 Caution. Distributors used for potable water shall have no preservatives (other than type P-14) applied to any surface that will contact the water. This requirement also applies to the repair parts.

3.3.1.3 Unprotected surfaces.

3.3.1.3.1 Unfinished surfaces. Unpainted, unfinished metal surfaces of items such as tie rods, adjusting rods, springs, grease fittings, bolts, nuts, and similar parts, including those exposed by disassembly, except components contacting potable water (see 3.3.1.2.1), requiring the application of a contact preservative in accordance with MIL-P-116, shall be coated with type P-1 preservative.

3.3.1.3.2 Machined surfaces. Exposed machined surfaces of parts, except components contacting potable water (see 3.3.1.2.1), shall be coated with type P-6 or P-11 preservative and wrapped or covered with barrier material conforming to MIL-B-121, type I, grade A, class 2, secured in place with tape conforming to PPP-T-60, type IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

3.3.1.4 Engines. All engines and engine accessories shall be preserved in accordance with MIL-E-10062, level A, type I, method I.

3.3.1.5 Instrument panels. The glasses of instruments, meters, and gages, if not protected by a cover, housing, or cab, shall be covered with barrier material conforming to MIL-B-121, type I, grade A, class 2, over which a fitted piece of 1/4-inch plywood or hardboard shall be placed and secured with tape conforming to PPP-T-60, type IV.

3.3.1.6 Gears.

3.3.1.6.1 Exposed gears. Exposed gears shall be coated with type P-1 preservative.

3.3.1.6.2 Enclosed gears. Gears operating on lubricating oil (SAE 10, 30, or 50) shall have the housings filled to the operating level with preservative lubricating oil, type I, grade as applicable, and the gear controls tagged to indicate: "The preservative oil contained in the gear housing is adequate for operation. Do not drain until the first required lubricant change." Gears operating on gear lubricant (SAE 80 or 90) shall have the housings filled to the operating level with lubricant conforming to MIL-L-2105, grade as applicable, and the gear controls tagged to indicate: "The lubricant contained in the gear housing is adequate for operation. Do not drain until the first required lubricant change." Gears not operating on lubricating oil (SAE 10, 30, or 50) or gear lubricant (SAE 80 or 90) shall have the housings filled to the operating level with the approved lubricant or operating oil and the gear controls tagged to indicate: "The gear housing is filled with the approved lubricant. Do not drain." Tags specified herein shall conform to UU-T-81, type A and the printing thereon shall be in waterproof ink.

3.3.1.7 Chains.

3.3.1.7.1 Exposed roller chains. Exposed roller chains shall be coated with enough type P-3 or P-9 preservative to assure penetration of the preservative to the inner surfaces of the rollers, pins, and bushings. After the excess preservative has drained, the entire chain and the sprockets shall be coated with type P-1 preservative.

3.3.1.7.2 Enclosed chains. Enclosed chains and chain housing shall be preserved, filled, and tagged as specified in 3.3.1.6.2 for enclosed gears.

3.3.1.8 Drive belts. Drive belts shall be removed or released from tension. Removed belts shall be preserved in accordance with MIL-P-116, method IC-1. Unpainted pulley faces or grooves shall be coated with primer conforming to TT-P-664.

3.3.1.9 Pumps (centrifugal and rotary). The interior surfaces of the pumps, such as impellers, rotors, rotor shafts, pistons, piston rods, thrust pins, cylinders, cylinder walls, and gears, shall be coated with the applicable type preservative as follows: Preservative lubricating oil, type I, grade 30 for fuel and bitumen pumps; type P-3 or P-9 preservative for nonpotable water pumps; type P-14 preservative for potable water pumps. Openings into pump interiors (suction and discharge) shall be sealed or covered with plastic caps or plugs conforming to MIL-C-5501 or with tape conforming to PPP-T-60, type IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

3.3.1.10 Bitumen tanks. Interior surfaces of bitumen tanks (except corrosion-resistant treated tanks), tank gage mechanisms, screens and strainers, and the interior surfaces of overflow pipes, and dome covers shall be coated with preservative lubricating oil, type I, grade 30. Unpainted exterior surfaces of the tanks requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with type P-1 preservative. The drain valves shall be left open.

3.3.1.11 Water tanks. Interior surfaces of water tanks (except corrosion-resistant treated tanks), tank gage mechanisms, screens and strainers, and interior surfaces of overflow pipes, and dome covers shall be coated with the applicable type of preservative as follows: Type P-3 or P-9 preservative for nonpotable water tanks, and type P-14 preservative for potable water tanks. The drain valves shall be left open.

3.3.1.12 Spraybars, piping, valves, and fittings. Interior surfaces of bitumen spraybars, piping, valves, fittings, and nozzles for the spraybars shall be coated with preservative, lubricating oil, type I, grade 30. Interior surfaces of nonpotable water spraybars, piping, valves, fittings, and nozzles for the spraybars shall be coated with type P-3 or P-9 preservative. Exterior surfaces of the spraybars (both bitumen and water) requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with type P-1 preservative. Ball or swivel joints of spraybars shall be coated with type P-1 preservative. Spraybars removed from the distributors shall be wrapped with barrier material conforming to MIL-B-121, type I, grade A, class 2, and the wrap shall be secured with tape conforming to PPP-T-60, type IV.

3.3.1.13 Discharge hoses and hand spraybars. The flexible discharge hose shall be disconnected from the distributor and from the hand spraybar. The hose shall be coiled to the minimum safe diameter and the coil shall be secured with tape conforming to PPP-T-60, type IV. Interior surfaces of the hand spraybars shall be coated with preservative as follows: Preservative lubricating oil, type I, grade 30 for bitumen spraybars; type P-3 or P-9 preservative for nonpotable water spraybars. Unpainted exterior surfaces of the spraybars (both bitumen and water) requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with type P-1 preservative. The spraybars shall be wrapped and secured as specified in 3.3.1.12.

3.3.1.14 Pump tachometers, gages, and thermometers. The dial glass of tachometers shall be protected with cushioning material conforming to PPP-C-843, type II, class A and overwrapped with barrier material conforming to MIL-B-121, type I, grade A, class 2. The wrap shall be secured with tape conforming to PPP-T-60, type IV. Gages and thermometers not removed from the distributors shall be protected with cushioning and be overwrapped. The wrap shall be secured as specified herein for tachometer dial glasses. Gages and thermometers removed from the distributors shall be wrapped with cushioning material specified herein and individually preserved in boxes conforming to PPP-B-636, W5c or W6c. Box closure shall be in accordance with the appendix to the box specification, method V. Openings where gages have been removed shall be sealed with the tape specified herein.

3.3.1.15 Bitumeters and fifth wheel tachometers. Bitumeter and fifth wheel tachometer assemblies removed from the distributors shall be detached from the wheels. The dial glass of the bitumeter dial shall be cushioned and secured as

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

specified in 3.3.1.14. The assemblies shall be individually preserved in boxes conforming to PPP-B-636, W5c or W6c as applicable. Box closure shall be in accordance with the appendix to the box specification, method V. Assemblies not removed from the distributors shall be secured in the carrying position on the distributors and any unpainted metal surfaces requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with type P-1 preservative. The dial glass shall be cushioned, wrapped, and secured with tape as specified in 3.3.1.14, except when the bitumeter dial is located within the truck cab, no cushioning, wrapping, or securing shall be required.

3.3.1.16 Heating systems. Interior surfaces of the burner fuel tanks (except corrosion-resistant treated tanks), fuel pumps, steel piping, and valves shall be coated with preservative lubricating oil, type I, grade 30. Excess preservative shall be drained from the system. The opening in the burner stack, if not equipped with a metal rain cap, shall be covered with barrier material conforming to PPP-B-1055, class E-2 and secured with tape conforming to PPP-T-60, type IV. If equipped with a rain cap, the cap shall be closed and secured with tape as specified herein.

3.3.1.17 Portable burners. Interior surfaces of the tank (except corrosion-resistant treated tanks), burner, and valves shall be coated with preservative lubricating oil, type I, grade 30. Unpainted exterior surfaces of the tank, burner, and hose clamps requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with type P-1 preservative. The hose and carrying straps shall be detached. Any openings into the tank shall be sealed with tape conforming to PPP-T-60, type IV. The straps shall be wrapped with barrier material conforming to PPP-B-1055, class C-1, and the wrap shall be secured with tape conforming to PPP-T-60, type IV. The hose shall be coiled to a minimum safe diameter and the coil secured with cotton cord or tape as specified herein.

3.3.1.18 Bitumen heaters (boiler type). The heater, components, and accessories shall be preserved in accordance with MIL-B-3180, level A.

3.3.1.19 Hose, hose couplings, and hose fittings. Unpainted surfaces of couplings and fittings (except couplings and fittings that will contact potable water) requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with type P-1 preservative. hose couplings and fittings intended for use with potable water shall be coated with type P-14 preservative. Each length of hose shall be coiled, the coil shall be secured and wrapped with barrier material conforming to PPP-B-1055, class C-1, and the wrap shall be secured with tape conforming to PPP-T-60, type IV. Metal flexible hose, when furnished, shall not require wrapping but shall be coiled and secured with cotton cord or tape specified herein.

3.3.1.20 Metal measuring sticks. Unpainted metal measuring sticks requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with the applicable type of preservative as follows: Type P-1 preservative for bitumen and nonpotable water distributors; type P-14 preservative for potable water distributors. Sticks coated with type P-14 preservative shall be wrapped with barrier material conforming to MIL-B-121, type I, grade A, class 2. The wrap shall be secured with tape conforming to PPP-T-60, type IV. The sticks shall be placed and secured in the carrying brackets on the distributor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

3.3.1.21 Repair parts. The preservative application criteria and applicable method(s) of preservation of MIL-P-116 shall be used to preserve the repair parts, except only type P-14 preservative shall be applied to repair parts that will come in contact with potable water when placed in use on the distributor. When specified engine repair parts shall be preserved in accordance with MIL-S-196 (see 6.2).

3.3.1.22 Maintenance tools. Maintenance tools shall be preserved in accordance with PPP-P-40, level A.

3.3.1.23 Distributor charts. Distributor charts required for each unit shall be preserved together in accordance with MIL-P-116, method IC-1 or IC-3.

3.3.1.24 Technical publications or instructional material. Technical publications or instructional material for each distributor shall be preserved together in accordance with MIL-P-116, method IC-1 or IC-3.

3.3.1.25 Truck chassis and trailers. The truck chassis, trailers, components, and accessories shall be preserved in accordance with MIL-V-62038, level A (mobile).

3.3.1.26 Consolidation. The components for each distributor, repair parts, maintenance tools, distributor charts, and technical publications or instructional material shall be consolidated in close-fitting boxes conforming to PPP-B-601, overseas type, style optional. Strapping shall not be required. The size of the boxes shall be determined by the available space for securing to the distributor and to accomplish the packing specified in 3.4.

3.3.2 Level C. The distributor and all of its components shall be preserved in accordance with the contractor's standard practice in a manner to prevent deterioration and damage during shipment from the contractor to the initial destination. Any components requiring lubricant shall be lubricated for operation as required in the operator's service manual.

3.4 Packing. Packing shall be level A, B, or C as specified (see 6.2).

3.4.1 Level A. Each complete distributor, preserved as specified in 3.3, shall be prepared for unboxed (mobile shipment. Removed and consolidated components shall be secured on the distributor in any available space that will not increase cubage or interfere with lifting or towing. The components shall be secured in a manner to prevent movement, pilferage, or damage, by the use of zinc coated strapping conforming ASTM D 3953, type ! or 2, heavy duty, size as applicable. On trailer-mounted distributors, the support legs (landing gears) shall be used for parking and storage only. For shipment, the trailer front shall be secured and supported by the use of wood cribbing or blocking as applicable, to prevent damage to the support legs.

3.4.2 Level B. Each complete distributor, preserved as specified in 3.3 shall be prepared for shipment as specified in 3.4.1 for level A except strapping shall not be required to be zinc-coated.

3.4.3 Level C. Each complete distributor, preserved as specified in 3.3, shall be packed to assure carrier acceptance and safe delivery to destination at lowest ratings in compliance with applicable carrier rules and regulations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

3.5 Marking. In addition to any special marking specified in the contract or purchase order (see 6.2), marking shall be in accordance with MIL-STD-129.

3.6 Depreservation guides. Two depreservation guides shall be prepared. One copy shall be placed in a waterproof envelope marked "Depreservation Guide" and the envelope secured to the distributor in a conspicuous location. The other copy shall be preserved with other instructional material and the pack marked to indicate: "A depreservation guide is inside." Unless otherwise specified, DA Form 2258 - Depreservation Guide for Vehicles and Equipment" shall be used (see 6.2 and 6.4).

3.7 Workmanship. Workmanship shall be such as to provide maximum protection to the distributors by application of the requirements specified herein, to prevent corrosion, deterioration, and mechanical or physical damage during handling, shipment, and storage.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the government. The government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of section 3. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the government to acceptance of defective material.

4.1.2 Material inspection. The contractor is responsible for insuring that supplies and materials are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article pack inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article pack inspection.

4.3.1 Examination. The first article pack shall be examined for the defects specified in 4.4.4. Presence of one or more defects shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection stages. Inspection shall be in four stages as follows:

a. The first stage shall include inspection of procedures, methods, materials, containers, and unit marking prior to placing the components into consolidated containers.
b. The second stage shall include inspection of closure and marking of consolidated containers.
c. The third stage shall include inspection of materials and methods of securing consolidated containers and removed components to the distributor.
d. The fourth stage shall include inspection of marking.

4.4.2 Unit of product. For the purpose of inspection a completed pack of any one level shall be considered a unit of product.

4.4.3 Sampling. Sampling for examination shall be in accordance with MIL-STD-105. Samples shall be determined by using MIL-STD-105, tables I and IIa.

4.4.4 Examination. Samples selected in accordance with 4.4.3 shall be examined for the defects marked "X" for the applicable level in table I. Presence of one or more defects shall be cause for rejection.

TABLE I. Classification of defects.

No.	Defect	Level		
		A	B	C
101.	Disassembly not as specified (see 3.3.1.1.1).	X	-	-
102.	Matchmarking not as specified (see 3.3.1.1.2).	X	-	-
103.	Tags used for matchmarking not waterproofed (see 3.3.1.1.2)	X	-	-
104.	Petroleum base preservatives applied to surfaces that will contact potable water (see 3.3.1.2.1).	X	-	-
105.	Unfinished surfaces not coated with specified preservatives (see 3.3.1.3.1).	X	-	-
106.	Machined surfaces not coated with preservative and wrapped and secured (see 3.3.1.3.20).	X	-	-
107.	Engines and engine accessories not preserved in accordance with the referenced document (see 3.3.1.4).	X	-	-
108.	Glasses of instruments, meters, and gages not protected (see 3.3.1.5).	X	-	-
109.	Exposed gears not coated as specified (see 3.3.1.6.1).	X	-	-
110.	Enclosed gears not preserved or the housings not filled with operational lubricant as specified (see 3.3.1.6.2).	X	-	-
111.	Gear housings not tagged as specified (see 3.3.1.6.2).	X	-	-
112.	Tags on gear housings not waterproofed (see 3.3.1.6.2).	X	-	-
113.	Exposed roller chains not coated as specified (see 3.3.1.7.1).	X	-	-
114.	Enclosed chain not preserved or the housing not filled with operational lubricant as applicable (see 3.3.1.7.2).	X	-	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects. (Continued)

No.	Defect	Level A	Level B	Level C
115.	Drive belts not removed or released from tension (see 3.3.1.8).	X	-	-
116.	Unpainted pulley faces or grooves not coated with primer (see 3.3.1.8).	X	-	-
117.	Interior surfaces of pumps not coated with the applicable type preservative (see 3.3.1.9).	X	-	-
118.	Openings into pump interiors not covered or sealed with cap, plugs, or tape as specified (see 3.3.1.9).	X	-	-
119.	Interior surfaces of bitumen tanks not coated with preservative when required (see 3.3.1.10).	X	-	-
120.	Unpainted exterior surfaces of bitumen tanks not coated with the specified preservative (see 3.3.1.10).	X	-	-
121.	Bitumen tanks not drained and the valves not left open (see 3.3.1.10).	X	-	-
122.	Interior surfaces of water tank not coated with the applicable type preservative as specified (see 3.3.1.11).	X	-	-
123.	Water tanks not drained and the valves not left open (see 3.3.1.11).	X	-	-
124.	Interior surfaces of spraybars, piping, valves, fittings and nozzles not coated with applicable type of preservative (see 3.3.1.12).	X	-	-
125.	Exterior surfaces of spraybars not coated with specified preservative (see 3.3.1.12).	X	-	-
126.	Spraybars removed from the distributors not wrapped with barrier materials (see 3.3.1.12).	X	-	-
127.	Flexible discharge hose not disconnected from the distributor and the hand spraybars (see 3.3.1.13).	X	-	-
128.	Flexible discharge hose not coiled and the coil not secured with tape (see 3.3.1.13).	X	-	-
129.	Interior surfaces of hand spraybars not coated with applicable type of preservative (see 3.3.1.13).	X	-	-
130.	Exterior surfaces of hand spraybars not coated with specified preservative (see 3.3.1.13).	X	-	-
131.	Hand spraybars not wrapped with barrier material as specified (see 3.3.1.13).	X	-	-
132.	Dial glass of tachometers, gages, and thermometers not cushioned and protected as specified (see 3.3.1.14).	X	-	-
133.	Gages and thermometers removed from the distributors not preserved as specified (see 3.3.1.14).	X	-	-
134.	Openings where gages have been removed not sealed with tape (see 3.3.1.14).	X	-	-
135.	Bitumeter and tachometer assemblies, if removed, not preserved as specified (see 3.3.1.15).	X	-	-
136.	Bitumeter and tachometer assemblies, if not removed, not not secured in the carrying position (see 3.3.1.15).	X	-	-
137.	Interior surfaces of heater fuel systems and portable burners not coated with preservative as specified (see 3.3.1.16).	X	-	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects. (Continued)

No.	Defect	Level A	Level B	Level C
138.	Opening into burner stack not sealed as specified (see 3.3.1.16).	X	-	-
139.	Hose and carrying straps not removed from portable burners and preserved as specified (see 3.3.1.17).	X	-	-
140.	Bitumen heaters (boiler type), components and accessories not preserved in accordance with the referenced document (see 3.3.1.18).	X	-	-
141.	Hose, hose couplings, or fittings not coated with applicable type of preservative when required or secured and wrapped as specified (see 3.3.1.19).	X	-	-
142.	Metal measuring sticks not coated with applicable type preservative as specified (see 3.3.1.20).	X	-	-
143.	Metal measuring sticks coated with type P-14 preservative not wrapped as specified (see 3.3.1.20).	X	-	-
144.	Metal measuring sticks not placed and secured on the distributor (see 3.3.1.20).	X	-	-
145.	Repair parts, maintenance tools, distributor charts, and technical publications or instructional material not preserved as specified (see 3.3.1.21, 3.3.1.22, 3.3.1.23, and 3.3.1.24).	X	-	-
146.	Truck and trailer chassis not preserved in accordance with the referenced document (see 3.3.1.25).	X	-	-
147.	Components requiring lubricant not lubricated as specified by operator's manual for level C (see 3.3.2).	-	-	X
148.	Consolidation not as specified (see 3.3.1.26).	X	-	-
149.	Consolidation containers and components not secured to the mobile distributors in a manner to conserve cube or secured so as to interfere with towing or lifting (see 3.4.1).	X	X	-
150.	Strapping not as specified (see 3.4.1).	X	X	-
151.	Marking missing, illegible, incomplete, or incorrect (see 3.5).	X	X	X
152.	Depreservation guide not prepared and attached as specified (see 3.6).	X	X	X
153.	Workmanship not as specified (see 3.7).	X	X	X

5. PACKAGING

(This section is not applicable to this specification.)

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

6.1 Intended use. It is intended that this specification be used for reference in section 5 of commodity and equipment specifications or for direct reference in contracts or purchase orders, or in the preparation of packaging data sheets to be used for acquisition.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of the specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article pack is required and time frame required for submission of the first article pack (see 3.1).
d. Level of preservation and packing required (see 3.3 and 3.4).
e. When engine repair parts are to be preserved in accordance with MIL-S-196 (see 3.3.1.21).
f. Any special marking (see 3.5).
g. When other than DA Form 2258 is to be used (see 3.6).

6.3 First article pack. The first article pack may be accomplished utilizing either the first preproduction model or a production model. If the preproduction model is utilized, any preservation and packing shall be removed by the contractor at no expense to the Government, when requested by the Government, to facilitate comparison between the preproduction model and the production model. Any changes or deviations of production packs from the approved first article pack will be subject to the approval of the contracting officer. Approval of the first article pack will not relieve the contractor of his obligation to preserve, pack, and mark the pumps and accessories in accordance with this specification.

6.4 Depreservation guides. The contracting officer should arrange to furnish the necessary copies of DA Form 2258, when requested by the contractor (see 3.6).

6.5 Environmental. Environmental pollution prevention measures are contained in the packaging material specification referenced herein. Refer to material specification or preparing activity for recommended disposability methods.

6.6 Subject term (key word) listing.

Marking
Packing
Preservation

6.7 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - ME
Navy - YD

Review activity:
Army - SM

Preparing activity:
Army - ME

Project 3895-0309

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-D-771E	901026

3. DOCUMENT TITLE

Distributors, Bitumen and Water, Packaging Of

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)
	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial (703) 664-5717
	(2) AUTOVON 354-5717
c. ADDRESS (Include Zip Code) US Army Belvoir RDE Center ATTN: STRBE-TSE Ft. Belvoir, VA 22060-5606	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-76111:272
Check the source to verify that this is the current version before use.