MILITARY SPECIFICATION

PILE DRIVING RIG, SKID MOUNTED; STEEL, W/MOONBEAM ASSEMBLY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a skid-mounted, steel, pile driving rig.

2* APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards , and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, and Seals.
TT-V-121	- Varnish, Spar, Water-Resisting.
UU-T-81	- Tags, Shipping and Stock.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by

AMSC N/A FSC 3895

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.

PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-P-40	- Packaging and Packing of Hand Tools.

MILITARY

MIL-P-116	- Preservation, Methods of.
MIL-P-514	- Plates, Identification, Instruction and Marking, Blank.
MIL-T-704	- Treatment and Painting of Materiel.
MIL-G-10924	- Grease, Automotive and Artillery.
MIL-C-46168	- Coating, Aliphatic Polyurethane, Chemical Agent Resistant.

STANDARDS

MILITARY

MIL-STD-129	Marking for Shipment and Storage.
MIL-STD-130	Identification Marking of US Military Property.
MIL-STD-163	Steel Mill Products, Preparation for Shipment and Storage.
MIL-STD-889	Dissimilar Metals.
MIL-STD-ll86	Cushioning, Anchoring, Bracing, Blocking and Waterproofing; With Appropriate Test Methods.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR 1926 - Pile Driving Equipment Requirements.

(Application for copies should be addressed to: Superintendent of Documents, US Government Printing Office, Washington, DC 20402.)

DRAWINGS

ME

TA13208E0400	- Pile Driving Rig: Skid Mounted; Steel, 65 Ft. Lg. Lead w/Moonbeam Assembly.

Source: https://assist.dla.mil -- Downloaded: 202610-16T11:24Z
Check the source to verify that this is the current version before use.

NAVAL FACILITIES ENGINEERING COMMAND

303927 to 303929, inclusive	- Pile Driver, Skid Rig, 75 Ft. Leads w/Barge Mounting Accessories, Steam Drive.
889694	- Pile Driver, Skid Mounted, 75 Ft. Leads.
889695	- Pile Driver, Barge Mounted.

(Copies Of specifications, standards, handbooks, drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the non-Government documents which is current on the date of the solicitation.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section IX, Welding Qualifications.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

AMERICAN WELDING SOCIETY, INC. (AWS)

D1.1 - Structural Welding Code - Steel.

{Application for copies should be addressed to the American Welding Society, Inc. , 550 LeJeune Road, P.O. Box 351040, Miami, FL 33126.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

J492 - Rivets and Riveting.

(Application for copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.)

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specifications sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Description. The skid-mounted, pile driving rig shall consist essentially of a boom, a moonbeam, a head block, a skid frame, and unless otherwise specified (see 6.2), a lead 65 feet long. When specified (see 6.2), the length of lead shall be 55 feet or 75 feet. The pile driving rig shall be as shown on Top Assembly TA13208E0400 when 55-foot or 65-foot leads are specified. The pile driving rig shall be as shown on Drawing 303927, 303928, 303929, 889694, and 889695 when the 75-foot lead is specified.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article. Unless otherwise specified (see 6.2), a sample shall be subjected to first article inspection (see 4.3 and 6.3). Any changes or deviations of pile driving rigs from the approved first article during production will be subject to the approval of the contracting officer. Approval of the first article will not relieve the contractor of his obligation to furnish pile driving rigs conforming to this specification.

3.3 Material. Material shall be as shown on applicable drawings and as specified herein.

3.3.1 Material deterioration prevention and control. The pile driving rig shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operating and storage environments to which the pile driving rig may be exposed.

3.3.2 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

3.3.3 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with component and subcomponent, and shall make information available upon request to the contracting officer or designated representative.

3.3.4 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the pile driving rig may be newly fabricated from recovered materials to the maximum extent practicable, provided the pile driving rig produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the pile driving rig.

Source: https://assist.dla.mil -- Downloaded: 202610-16T11:24Z
Check the source to verify that this is the current version before use.

3.4 Lead. The lead shall be as shown on the drawings, except that when a 55-foot lead is specified (see 3.1) the intermediate 10-foot section shown on TA13208E0400 shall be omitted.

3.5 Platform. The planks for the decking shall be smooth on two edges (S2E).

3.6 Hoisting rope. Unless otherwise specified (see 6.2), the pile driving rig shall be furnished with one 250-foot length of 3/4-inch, and one 300-foot length of 5/8-inch wire rope as shown in the drawings.

3.7 Bolts and nuts. Bolts shall be semi-finished of the type, size, and thread series indicated on the drawings. Thread fit shall be class 2 (free).

3.8 Delivery lubrication service. When delivered, all components shall be lubricated. Grease lubrication shall be with greases conforming to MIL-G-10924. Each lubricated component shall be tagged in a conspicuous place to indicate the temperature range and grade of grease used.

3.9 Identification marking. The rig shall be identified in accordance with MIL-STD-130. The marking shall be applied on plates conforming to MIL-P-514, type I, style 1, composition C, of type I, grade A, class 1 material. Plates shall be attached by screws, bolts, or rivets in a conspicuous protected location.

3.10 Treatment and painting . The portions of the rig and its components and parts normally painted, both internall and externally, shall be cleaned, treated, and painted in accordance with MIL-T-704, Type F or G, as applicable. Unless otherwise specified (see 6.2), top coat color shall be camouflage green 383 conforming to MIL-C-46168.

3.11 Workmanship. The pile driving rig shall be free from defects such as incomplete welds, rust, cracks, and other defects that could impair the operation or serviceability of the pile driving rig.

3.11.1 Metal fabrication. Metal used in fabrication shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause injury to the material. Corners shall be square and true. Flame-cutting, using tips suitable for the thickness of the steel, may be employed instead of shearing and sawing. All bends shall be made with controlled means to insure uniformity of size and shape. Precaution shall be taken to avoid over-heating. Heated steel shall be allowed to cool slowly. External surfaces shall be free of burrs, sharp edges and corners, except when sharp edges or corners are required or where they are not detrimental to safety.

3.11.2 Bolted connections. Boltholes shall be accurately formed or drilled and shall have the burrs removed. Washers or lockwashers shall be provided and all bolts, nuts, and screws shall be tight. Adjoining surfaces shall be flat, and in full contact with each other. Bolted fasteners shall be torqued to the torque requirement of the fastener.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.

3.11.3 Riveted connections. Rivet holes shall be accurately formed or drilled and shall have the burrs removed. Rivets shall completely fill the holes. Rivet heads shall be full, concentric with the rivet holes, and in full contact with the surface of the member and shall be in accordance with SAE J492.

3.11.4 Welders and welding.

3.11.4.1 Welders. Before assigning any welder or welding operator to manual welding work covered by this specification, the contractor shall obtain certification that the welder or welding operator has passed qualification tests as prescribed by either of the following listed codes for the type of welding operation to be performed, and that such qualification is effective as defined by the particular code:

AWS D1.1, Structural Welding Code - Steel.
ASME Boiler and Pressure Vessel Code, Section IX, Welding Qualifications.

Certification shall be made available for review by the contracting officer or designated representative. The Government reserves the right to require recertification of any welder or welding operator.

3.11.4.2 Welding. The surfaces of parts to be welded shall be free from scale, paint, grease, and other foreign matter. When multiple layers of weld metal are required, each layer shall be thoroughly cleaned before depositing another layer. All welded parts and assemblies shall be free from cracks and other imperfections that may reduce the effectiveness of the part or assembly. All weldments shall be free from slag, flux, weld spatter and other impurities. Work shall be positioned for flat welding whenever practicable. No undercuts or overlays will be permitted on any weldment. Butt-type joints having members of equal thickness shall be alined within 10 percent of the thickness of the members involved. Where different steels are welded to each other, filler metal having strength of the lower strength steel shall be used. When the same steels, having similar properties are used, the deposited filler metal shall develop the full design strength of the particular weld joint or weldment.

3.11.4.3 Mechanical properties. Mechanical properties of all welds shall be such that welds will transmit stress without failure or permanent deformation when subjected to any test specified herein.

3.11.5 Machine work. Tolerances and gages for metal fits shall conform to the limitations specified in the applicable drawings.

3.12 Safety. The construction of the pile driving rig shall meet OSHA 29 CFR 1926 requirements for pile driving equipment.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.

herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. The contractor is responsible for insuring that components and materials are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The first article pile driving rig shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first article pile driving rig shall be tested as specified in 4.5.2. Failure of this test shall be cause for rejection.

4.4 Quality conformance inspection. The pile driving rig shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.5 Inspection procedure.

4.5.1 Examination. The pile driving rig shall be examined for the following defects:

101. Dimensions not as specified.
102. Fasteners not as specified.
103. Assembly not complete or incorrect.
1040 Parts or components missing or not as specified. Each part or component missing or not as specified shall constitute one defect.
105. Parts or components do not function.
106. Material not as specified.

Source: https://assist.dla.mil -- Downloaded: 202610-16T11:24Z
Check the source to verify that this is the current version before use.

107. Materials not resistant to corrosion and deterioration, or treated to be resistant to corrosion and deterioration for the applicable storage and operating environments.
108. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other.
109. Contractor does not have documentation available for identification of material, material finishes, or treatment.
110. used, rebuilt or remanufactured components, pieces, or parts incorporated in the pile driving rig.
111. Technical publications missing or not as specified.- -
112. Lubrication not as specified.
113. Treatment and painting not as specified.
114. Paint color not as specified.
115. Workmanship not as specified.
116. Metal fabrication not as specified.
117. Bolted connections not as specified.
118. Riveted connection not as specified.
119. Welders certification not made available for review.
120. Welding not as specified.
121. Mechanical properties not as specified
122. Safety requirements not as specified
123. Accessories, identification, or other marking missing.

4.5.2 Test. The components for a pile driving rig shall be assembled and erected, simulating the required procedure of setting up for actual pile driving operations. During and after erection of the pile driving rig, the rig shall be checked for ease of assembly, alinement, and fit. Interference of mating members, incorrect fit at joints, or misalinement shall constitute failure of this test.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection.

4.6.1.1 Unit of product. For the purpose of inspection, a complely packed rig prepared for shipment shall be considered a unit of product.

4.6.1.2 Examination. Each packed rig shall be examined for the following defects. Any defects shall be corrected to comply with the requirements of Section 5 before shipment is made.

124. Materials not as specified. Each incorrect material shall constitute one defect.
125. Containers not as specified. Each incorrect container shall constitute one defect.
126. Matchmaking not as specified for level A.
127. Cloth matchmaking tags not marked with waterproof ink for level A.
128. Unprotected metal surfaces not coated with preservative as specified for level A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.

129. Wire rope not preserved for level A and packed for level A or B in accordance with the referenced document.
130. Maintenance tools not preserved in accordance with the referenced document for level A.
131. Technical publications not preserved as specified for level A.
132. Consolidation not as specified for level A.
133. Packing not as specified for level A or B.
134. Strapping not as specified for level A or B.
135. Contents of boxes not blocked, braced, or anchored to as specified for level A or B.
136. Marking missing, illegible, incorrect, or incomplete.

5. PACKAGING

5.1 Preservation. The degree of preservation shall be level A or C, as specified (see 6.2)

5.1.1 Level A.

5.1.1.1 Basic rig. Components of the pile driving rig shall be preserved as miscellaneous small parts, structural members, and sections. The small parts, structural members, and sections shall be matchmarked if necessary to facilitate assembly. Small parts shall have matchmaking information on cloth shipping tags conforming to UU-T-81, type A, or on metal tags, and the tags attached to mating parts. The cloth tags shall be marked with waterproof ink. Large parts shall be matchmarked with lusterless white enamel, overcoated with varnish conforming to TT-V-121.

5.1.1.2 Components.

5.1.1.2.1 Unprotected metal surfaces. Unprotected metal surfaces of the pile driving rig components requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with type P-1 preservative. The preservative shall conform to the applicable specification listed in and shall be applied in accordance with MIL-P-116.

5.1.1.2.2 Wire rope. Wire rope shall be preserved in accordance with MIL-STD-163.

5.1.1.2.3 Repair parts. The preservative application criteria and applicable methods of preservation of MIL-P-116 shall be used to preserve repair pares.

5.1.1.2.4 Maintenance tools. Maintenance tools shall be preserved in accordance with PPP-P-40, level A.

5.1.1.2.5 Technical publications. Technical publications shall be preserved in accordance with MIL-P-116, method IC-1 or IC-3.

5.1.1.2.6 Consolidation. Repair parts, maintenance tools, technical publications, and small miscellaneous parts requiring segregation or protection

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.

from mechanical damage shall be consolidated together in close-fitting boxes conforming to PPP-B-636, W6c, W5c, or V3, as applicable to the weight of the items. Closure of the boxes shall be in accordance with method V of the box specification appendix.

5.1.2 Level C. Unpainted metal surfaces shall be coated with grease to protect against rust. Technical publications shall be preserved as specifed in 5.1.1.2.5. Small components (repair parts, tools, publications) snail be consolidated in sturdy boxes to prevent loss and damage.

5.2 Packing. The degree of packing shall be level A, level B, or C, as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Structural members and sections. Component structural members and fabricated sections shall be bundled in secured lifts. The bundles shall be secured with not less than two flat steel straps conforming to QQ-S-781, class 1, type I or IV, finish B, size 1–1/4 inch wide by 0.031 or 0.035 thick.

5.2.1.2 Lumber. Planks and timbers shall be bundled in secured lifts. The bundles shall be secured as specified in 5.2.1.1.

5.2.1.3 Wire rope. The wire rope shall be packed in accordance with MIL-STD-163.

5.2.1.4 Miscellaneous small parts, repair parts, tools, and publications. Consolidated and loose miscellaneous small parts, repair parts, tools, and publications shall be packed together in one or more close-fitting boxes conforming to PPP-B-601, overseas type, style A or I. The contents shall be blocked, braced, and anchored in accordance with MIL-STD-1186. The boxes shall be closed and strapped in accordance with the appendix to the box specification Strapping shall conform to QQ-S-781, class 1, type I or IV, finish B, size as applicable-

5.2.2 Level B. The components of the pile driving rig shall be packed as specified in 5.2.1, except boxes shall be Domestic Type, and strapping shall be either finish A or B.

5.2.3 Level C. Structural members, fabricated sections, and timber/planks shall be bundled or shipped loose. Small components not already consolidated shall be boxed to prevent loss.

5.3 Marking. Marking shall be in accordance with MIL-STD-129.

6. NOTES .

6.1 Intended use. The skid-mounted, pile driving rig covered by this specification is intended for use in driving piles both vertical and batter when used with a hoist mounted on the skid platform.

Source: https://assist.dla.mil -- Downloaded: 202610-16T11:24Z
Check the source to verify that this is the current version before use.

6.2 ordering data. Procurement documents should specify the following:

a. Title, number , and date of this specification.
b. When length of lead will be 55 feet or 75 feet long (see 3.1).
c. Time frame required for submission of first article model (see 3.2), or when a first article is not required.
d. When hoisting rope is not required (see 3.6).
e. Color required when other than specified (see 3.10).
f. Level of preservation and packing required (see 5.1 and 5.2).

6.3 First article. When a first article inspection is required, the items should be a preproduction model. The first article should consist of one or more units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, tests, and approval of the first article test results and disposition of the first article.

6.4 Subject term (key word) listing.

Moonbeam assembly
Pile driving
Pile driving rig - mobile
Piles
Skid mounted rig

6.5 Change from previous issue. Asterisks (or vertical lines) are not used in this version to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - ME
Navy - YD
Air Force - 99

Preparing activity:
Army - ME

Review activities:
Army - AT
Navy - MC
Air Force - 84
DLA - CS

Project 3895-0286

Source: https://assist.dla.mil -- Downloaded: 202640-16T11:24Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretations, is too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO PO
NECE
IF MA
IN T
UNITED

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Belvoir RDE Center
ATTN: STRBE-TSE
Ft. Belvoir, VA 22060-5606

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-747D	Pile Driving Rig, Skid Mounted; Steel, w/Moonbeam Assembly

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.