MIL-P-749E

9 JUNE 1959

SUPERSEDING
MIL-P-00749D(Ord)
31 MARCH 1959

MILITARY SPECIFICATION

PRIMERS, PERCUSSION, FOR SMALL ARMS AMMUNITION

This specification has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

1. SCOPE

1.1. This specification covers percussion primers used for igniting the propellant charge in small arms ammunition (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification.

SPECIFICATIONS

MILITARY

MIL-A-625 — Ammunition, Small Arms, General Specification for.

STANDARDS

MILITARY

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-109 — Inspection Terms and Definitions.

MIL-STD-129 — Marking for Shipment and Storage.

DRAWINGS

ORDNANCE CORPS

B-8594698 — Primer (Styphnate) for 7.62mm.

B-8594094 — Primer (Styphnate) for 7.62mm and Cal. .30.

B-7645332 — Primer (Styphnate) for Caliber .30.

B-6200959 — Primer (Styphnate) for Caliber .30 Carbine.

B-7645336 — Primer (Styphnate) for Caliber .45.

B-7645339 — Primer (Styphnate) for Caliber .50.

B-6137544 — Cartridge, Ball, Caliber .30, M2.

FSC 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.

B–6200954 — Cartridge, Ball, Carbine, Caliber .30, M1.

C–7553702 — Cartridge, NATO, Ball, 7.62mm, M59.

C–8595543 — Cartridge, NATO, Ball, 7.62mm, M80.

B–6000503 — Cartridge, Ball, Caliber .45, M1911.

B–6000503A — Cartridge, Ball, Caliber .45, M1911, Steel Case.

C–7553097 — Cartridge, Ball, Caliber .50, M33.

C–8594735 — Cartridge, Spotter-Tracer, Caliber .50, M48A1.

B–6000045 — Case, Cartridge, Caliber .30.

B–6000045A — Case, Cartridge, Caliber .30 (Steel).

C–7553738 — Case, Cartridge, 7.62mm.

B–6200957 — Case, Cartridge, Carbine, Caliber .30.

B–6200957A — Case, Cartridge, Carbine, Caliber .30 (Steel).

B–60000501 — Case, Cartridge, Caliber .45.

B–60000501A — Case, Cartridge, Caliber .45 (Steel).

C–5502646 — Case, Cartridge, Caliber .50.

C–5502646A — Case, Cartridge, Caliber .50 (Steel).

C–8594736 — Case, Spotter-Tracer, Caliber .50, M48A1.

D–7553274 — Packing and Marking for Primer (for Caliber .50) in Cartons, in Cans, M20, in Box M22.

D–7553230 — Packing and Marking for Primers (for Caliber .30, .45, and 7.62mm Cartridges) in Cans, M21, in Box M23.

D–7553225 — Packing and Marking for Primers (for Caliber .30, .45, and 7.62mm Cartridges) in Cans, M20, in Box M22.

GL–8658516 — Index to Lists of Inspection Gages and Parts gaged on Primers, Percussion, Small Arms Ammunition (Test Equipment Included).

PUBLICATIONS

Ordnance Corps

ORD–M608–PM Vol. III — Manual of Test Methods for Small Arms Ammunition.

ORD–SIP–S314 — Visual Inspection Standards for Small Arms Ammunition Primer Defects.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

2.2 Other documents. The following documents form a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply:

Uniform Classification Committee

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.

Uniform Freight Classification, Ratings, Rules and Regulations.

(Copies may be purchased from the Uniform Classification Committee, 202 Chicago Union Station, Chicago 6, Ill.)

AMERICAN TRUCKING ASSOCIATION, INC.

National Motor Freight Classification, Uniform Ratings, Rules and Regulations.

(Copies may be purchased from the National Classification Board, 1424 Sixteenth street, N. W., Washington 6, D. C.)

INTERSTATE COMMERCE COMMISSION –49 CFR 71-78

Interstate Commerce Commission Rules and Regulations for the Transportation of Explosives and Other Dangerous Articles.

(The Interstate Commerce Commission regulations are now a part of the Code of Federal Regulations available from the Superintendent of Documents, Government Printing Office, Washington 25, D. C. Orders for the above publication should cite "49 CFR 71–78".)

3. REQUIREMENTS

3.1 General. Materials, parts, and assemblies shall comply with the requirements specified on the applicable drawings, referenced specifications, and the following:

3.2 Preproduction sample. Unless otherwise directed by the contracting officer, a preproduction sample shall be required.

3.3 Sensitivity. The sum of the average critical height $\overline{(H)}$ plus 5 standard deviations (5S) shall not exceed the limit specified for each type of primer. The difference between the average critical height (H) and 2 standard deviations (2S) shall be not less than the limit specified as follows for each type of primer:

Primer	Height Inches H + 5S	H — 2S
Drawing Number B–8594698	15	2½
Drawing Number B–8594094	15	2½
Drawing Number B–7645332	15	2½
Drawing Number B–6200959	18	2½
Drawing Number B–7645336	16	2½
Drawing Number B–7645339	15	2½

3.4 Action time. The action time (see 6.2) of the cartridge assembled with primer produced under Drawing B–7645336, B–6200959, B–8594698, B–8594094, B–7645332, or B–7645339, shall not exceed 0.0035 second at ambient temperatures, at minus 65 degrees to minus 70 degrees Fahrenheit (F.) and at plus 165 to plus 170 degrees (F.).

3.5 Function and casualty. The primer shall not misfire.

3.6 Workmanship. Workmanship requirements shall be as specified in Specification MIL–A–625.

3.7 Cleaning. The cleaning method used shall not be injurious to the primer components, nor shall the components be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions. The quality assurance provisions in this section and other documents referenced in this specification are applicable to inspection performed by or for the Government. Reference shall be made to Standard MIL–STD–109 to define the inspection terms used. Inspection shall be in accordance with Specification MIL–A–625, except as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.

4.1.1 *Contractor inspection.* Unless otherwise specified herein, the supplier is responsible for the performance of all inspection requirements prior to submission for Government inspection and acceptance. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order.

4.1.2 *Contractor quality assurance system.* The contractor shall provide and maintain an adequate assurance system, acceptable to the Government, covering the supplies under the contract. A current written description of the system shall be submitted to the contracting officer prior to initiation of production. The written description will be considered acceptable when, as a minimum, it provides the quality assurance required by this specification and other applicable documents referenced in this specification. The contractor shall notify the Government of and obtain approval for any change to the written procedure that might affect the degree of assurance required by this specification or other applicable documents referenced herein.

4.1.3 *Government verification.* All quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of (a) surveillance of the operations to determine that practices, methods, and procedures of the written inspection plan are being properly applied, and (b) Government product inspection to measure quality of product offered for acceptance. Deviations from the prescribed or agreed upon procedures or instances of poor practices which might have a detrimental effect upon the quality of the product will be immediately called to the attention of the contractor. Failure of the contractor to promptly correct deficiencies discovered will be cause for suspension of acceptance until correction has been made or until conformance of product to prescribed criteria has been demonstrated. To avoid interference with operations, the contractor shall designate a responsible official or officials to whom the Government inspector will report such instances.

4.2 Preproduction inspection.

4.2.1 *Preproduction sample.* Prior to the start of regular production, the contractor shall submit a preproduction sample to a Government approved facility for evaluation. The sample shall consist of 2000 primers from the contractor's initial production, manufactured in the same manner, using the same materials, equipment, processes and procedures as will be used in regular production. The contracting officer will furnish instructions for shipment of the sample to a designated facility for examination and tests. Any production under the contract prior to approval of the preproduction sample shall be at the risk of the contractor. After the start of production, additional preproduction samples shall be submitted for approval immediately subsequent to each major change in material or manufacturing process as determined by the contracting officer.

4.2.2 *Inspection.* The preproduction sample shall be examined and tested for all requirements of the drawings and specifications including all those characteristcs listed in 4.3.3 and 4.3.4. All testing shall be conducted in accordance with 4.4. The Government reserves the right to require additional preproduction samples until such time as an acceptable sample is submitted.

4.3 Inspection provisions. Alternate inspection procedures and inspection equipment may be used by the contractor when such procedures and equipment provide, as a minimum, quality assurance required in the contractual documents. The inspection proce-

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.

dures or equipment specified in this specification and referenced documents will prevail in case of dispute. However, in all ballistic testing, the use of the equipment specified and the methods of test prescribed in this specification and other documents referenced herein shall be mandatory.

4.3.1 *Material.* Reports of objective tests performed on the material by the contractor shall be required to insure compliance with the chemical and physical requirements. Reports shall include positive identification of the material and part, the applicable requirements, the specific test performed and the results obtained. Numerical results of each specimen or sample inspected shall be included except that where numerical results are impossible an adjective description shall be used. Initial test reports shall accompany the preproduction sample. Prior to inspection, the inspector shall determine from the information stated on the test reports whether the material submitted complies with requirements. Components made from material which does not comply shall be rejected.

4.3.2 *Lot.*

4.3.2.1 *Submittal of product.* The contractor shall submit the product in accordance with Standard MIL-STD-105.

4.3.2.2 *Size of lot.* A lot shall consist of one type of primers manufactured at one facility from like materials and under like conditions. Unless otherwise specified, the primers in a lot shall not exceed the production of one shift at the particular facility concerned.

4.3.2.3 *Lot identification.* Each lot of primers shall be identified as to type, caliber and number as well as with a lot number. No lot number shall be assigned to more than one lot containing the same type of primer.

4.3.3 *Examination.* Examination shall be performed as indicated below:

4.3.3.1 *Critical defects.* Each primer in the lot shall be visually examined for critical defects. All primers containing such defects shall be rejected.

4.3.3.2 *Sampling.* Samples for examination shall be selected in accordance with inspection level II of Standard MIL-STD-105. Each primer of the sample shall be visually examined and gaged for all major and minor defects listed in table I. If the number of defective primers is equal to or greater than the applicable rejection number, the lot shall be rejected subject to reinspection in accordance with Specification MIL-A-625.

4.3.3.3 *Acceptable quality levels.* The acceptable quality levels with respect to visual and dimensional defects shall be as follows:

Defects	*Percent*
Major Visual	0.035
Minor Visual	1.5
Minor Dimensional	1.5

4.3.3.4 *Classification of defects.* The visual and dimensional defects shall be classified as specified in table I.

TABLE I

No.	Defect	Critical	Major	Minor	Major or Minor
	Primer				
1	No anvil	X			
2	Double anvil	X			
3	No charge	X			
4	No foil-where applicable		X		
5	Double or multiple foil-where applicable		X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.

No.	Defect	Critical	Major	Minor	Major or Minor
6	Slipped foil-where applicable				X
7	Inverted or sidewise inserted anvil	X			
8	Crushed or mutilated				X
9	Loose composition				X
10	Deep seated anvil		X		
11	Cocked anvil				X
12	Low anvil		X		X
13	Excessive lacquer			X	
14	Loose anvil		X		
15	Stained or corroded metallic components(s)				X
16	Foreign matter		X		
17	High anvil				X
	Cup				
18	Bell-shaped		X		
19	Bad bevel			X	
20	Brass shavings				X
21	Cracked				X
22	Crooked or eared				X
23	Dents				X
24	Flat on crowned cup				X
25	Crowned on flat cup				X
26	High crown		X		
27	Laminated metal				X
28	Ringed				X
29	Scratches				X
30	Nicked				X
31	V or U				X
32	Low cup			X	
	Anvil				
33	Burred			X	
34	Chipped				X
35	Filled		X		
36	Partial	X			
37	No vent holes	X			
38	Laminated metal		X		
39	Ringed			X	
40	Unsymetrical vent holes			X	
	Foil				
41	Partial-where applicable			X	
42	Stained-where applicable	X			
	Pellet				
43	Heavy		X		
44	Light	X			
	Gaging				
	Primer				
45	Diameter			X	
46	Excess tolerance between long and short axis diameter			X	
47	Height			X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.

[1] Refer to Publication ORD–SIP–S314 for definite classification of defects 1 through 44.

4.3.4 *Tests.* The tests listed in table II shall be conducted in accordance with the methods and procedures specified in 4.4.

4.3.4.1 *Test samples.* The quantities for the various tests shall be as specified in table II. Only primers having met the visual and dimensional requirements shall be used in the ballistic tests, and shall have been selected in such a manner that the sample is representative of the entire lot. The primers selected shall be thoroughly mixed before being divided into samples for the various tests.

TABLE II

Test		Quantity of primers	Requirement paragraph
Sensitivity: [1]			3.3
Primer drawing	*Case drawing*		
B7645332; B8594094	B6000045 or B6000045A	600	
B7645339	C5502646 or C5502646A	600	
B7645336	B6000501 or B6000501A	600	
B6200959	B6200957 or B6200957A	600	
B8594698; B8594094	C7553738	600	
Action time: [2]			3.4
Primer drawing	*Cartridge drawing*		
B7645332; B8594094	B6137544	50	
B8594698; B8594094	C7553702 or C8595543	50	
B7645339	C8594735 or C7553097	50	
B7645336	B6000503 or B6000503A	50	
B6200959	B6200954	50	
Function and casualty: [3]			3.5
Primer drawing	*Cartridge drawing*		
B7645332; B8594094	B6137544	304	
B7645339	C7553097	200	
B7645336	B6000503A	286	
B6200959	B6200954	180	
B8594698; B8594094	C7553702 or C8595543	300	
B7645339	C8594735	200	

[1] Failure of the primers to comply with applicable requirements shall be cause for rejection of the lot. Retest may be conducted with double the quantity used in the initial test. Failure of the primers in the retest sample to comply with the applicable requirements shall be cause for rejection of the lot.

[2] Failure of any cartridge to comply with the applicable requirements shall be cause for rejection of the primer lot. Retest may be conducted with double the test sample provided that no more than one cartridge fails to comply with the requirement in the initial test and the action time of the failing cartridge does not exceed .020 seconds. If any additional cartridges fail to meet the requirement upon retest, the primer lot shall be rejected.

[3] Failure of any primer to comply with the applicable requirement shall be cause for rejection of the lot without retest.

4.3.4.2 *Retests.* Retests, when permissible, will be conducted at the request of the contractor. Retest for sensitivity shall be made by testing 100 primers at each height. All retests for sensitivity shall be conducted in accordance with Publication ORD–M608–

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.

PM, Vol. III, regardless of the method used in the original test.

4.3.5 *Packing and marking examination.* Examination shall be performed as indicated below:

4.3.5.1 *Critical defects.* One hundred-percent examination shall be performed for all critical defects. All items containing such defects shall be removed from the lot.

4.3.5.2 *Major and minor defects.* Examination for major and minor defects shall be performed in accordance with inspection level I of Standard MIL–STD–105 using an AQL of 0.65% for major defects and an AQL of 2.5% for minor defects for each phase of examination listed in table III. If the number of defective items is equal to or greater than the applicable rejection number, the lot shall be rejected. Screening and resubmission of such lots shall be in accordance with procedures specified in Specification MIL–A–625 for ammunition.

4.3.5.3 *Classification of defects.* Packing and marking defects shall be classified as specified in table III.

TABLE III

No.	Defect	Critical	Major	Minor
	Carton, before sealing			
1	Partition(s) in tray filler missing	X		
2	Improper quantity of primers		X	
3	Improper positioning of primers			X
	Carton, after sealing			
4	Label missing or insecurely applied		X	
5	Carton torn or ripped		X	
6	Marking missing, incorrect or illegible			X
	Can, before sealing			
7	Contents incorrect			X
8	Filler, separator or removal tape missing or improper			X
	Can, after sealing			
9	Punctured can		X	
10	Severe dents or buckles			X
11	Tear strip tongue missing or defective		X	
12	Key missing or defective			X
13	Marking missing, incorrect or illegible			X
	Box			
14	"Handle Carefully" marking missing, incorrect or illegible	X		
15	Other marking missing, incorrect or illegible			X
16	Reinforcement or wingnut missing			X
17	Rust preventive oil missing			X
18	Nail point protruding on inside of box	X		
19	Separator missing			X

4.3.6 *Inspection equipment.* The examination and tests shall be made using equipment listed on the applicable inspection equipment list referenced on GL–8658516, except as

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.

provided in 4.3. The Government will determine by means of its monitoring program, that the contractor has available and correctly utilizes, gaging, measuring, and test equipment of required accuracy and precision and that the instruments are of proper type and range to make measurements of the required accuracy. The contractor shall have available a set of master gages, standards and other appropriate instruments for regularly scheduled calibration of his inspection equipment. Records of such regularly scheduled calibration shall be maintained by the contractor and be made available to the Government for review. The calibration of gages, standards and instruments will be periodically checked by authorized Government personnel.

4.4 Test methods and procedures.

4.4.1 *Sensitivity test.* The primers shall be inserted into the primer pocket of the cartridge case so that the surface of the primer cup, when measured from the center of the primer, is within 0.005 ± 0.002 inch below flush of the cartridge case head. A suitable steel die approved by the contracting officer may be used in lieu of the cartridge case. The test shall be performed in accordance with the complete run-down method described in Publication ORD–M608–PM, Vol. III.

4.4.1.1 *Two-height method.* At the discretion of the contracting officer, the two-height method of testing for sensitivity may be used in lieu of the complete run-down test when sensitivity results for five consecutive lots have been found to comply with the requirements of 3.3 and computed skewness values have been found to be not greater than .787 nor less than —.787 (see 6.3). However, one out of every 10 lots submitted shall be tested by the complete run-down method. Failure in any test to meet sensitivity or skewness requirements shall be considered sufficient cause to revert to use of the run-down method on a lot by lot basis. The two-height test shall be conducted in accordance with the two-height method described in Publication ORD–M608–PM, Vol. III. Fifty primers shall be tested at each height.

4.4.1.2 *Primers.* Primers to be used in spotter-tracer cartridge cases will be tested for sensitivity in the caliber .50 cartridge case, Drawing C5502646. When caliber .50 cartridge cases, Drawing C5502646, are not available for primer sensitivity tests, spotter-tracer cartridge cases, Drawing C8594736, shall be used.

4.4.2 *Action time.* The primers shall be inserted and crimped in cartridge cases. The primed cases shall be assembled into cartridges and fired for action time. The cartridges shall be conditioned and handled in the same manner as that prescribed in Publication ORD–M608–PM, Vol. III for the velocity test. Qualification of the test barrel shall be as prescribed in Publication ORD–M608–PM, Vol. III for the velocity test. Five warming (fouling) shots shall be fired, prior to firing the test, to assure that the equipment in functioning properly. Continuous air cooling should be used on the barrel. If air cooling is not available, the barrel should be allowed to cool to ambient temperature after every 20 cartridges are fired. The action time of each shot shall be recorded.

4.4.2.1 *Lot temperature test.* The ammunition for the low temperature test shall be placed in a controlled temperature box in such a manner that all cartridges are subjected to a uniform temperature, cooled to a temperature of minus 40 to minus 45 degrees F. and held thereat for a minimum of 4 hours immediately before firing. The controlled temperature box shall be of sufficient capacity to permit cooling of the ammunition to the desired temperature, and to allow free circulation of air. The ammunition shall be fired immediately upon removal from the cold box in the specified weapon which shall be at ambient temperature. If the weapon is not convenient to the controlled tempera-

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.

ture box, the ammunition shall be placed in an insulated chest which has been cooled to a temperature of minus 40 to minus 45 degrees F., transported to the weapon and fired immediately upon removal.

4.4.2.2 *High temperature test.* The ammunition for this test shall be stored, conditioned and fired in the same manner as that specified for the low-temperature test, except that the temperature at which the ammunition is conditioned shall be plus 125 to plus 130 degrees F.

4.4.3 *Reduced testing for action time.* At the discretion of the contracting officer, testing for action time may be reduced if five consecutives lots, all using the same primer mix and production process, have met the requirements of 3.5. The reduced plan shall consist of testing one out of every five lots submitted. The lots tested under the reduced plan shall be selected randomly. Testing shall be resumed on a lot by lot basis when the primer mix or production process changes or when the requirements specified are not met.

4.4.4 *Function and casualty.* The primer shall be inserted and crimped in cartridge cases. The primed cases shall be assembled into cartridges and fired for function and casualty. The weapons used shall be at room temperature, but not less than 60 degrees F., at the beginning of tests. The test shall be conducted in accordance with Publication ORD-M608-PM, Vol. III and the following, as applicable:

Weapon	*No. of cartridges*	*Intervals between magazines, clips, bursts, or cartridges*
Rifle, 7.62 mm. M14	100 rapid fire	30 seconds, max.
Gun, Mach, 7.62mm, T65 or M60	100 in burst in each of two weapons ..	None.
Gun, Mach, Cal. .30, M37 or Gun, Mach, Cal. .30, M1919A4	200 in bursts of 100	Complete cooling.
Rifle, U. S. Cal. .30, M1	104 in clips, rapid fire	30 seconds, max.
Carbine, Cal. .30, M2	180 in magazines ...	Cool after each 60 cartridges.
Pistol, Automatic, Cal. .45, M1911A1	196 in clips, rapid fire	Cool after each 49 cartridges.
Gun, Sub-Mach, Cal. 45, M3	90 in magazines	30 seconds, max.
Rifle, Spotting, Cal. .50, M8	100 rapid fire in each of 2 rifles	Cool 30 seconds after each 50 cartridges.
Gun, Mach, Cal. .50, M3, ACFT, Basic	200 in burst of 100 .	Complete cooling.

Primers to be used in spotter-tracer cartridges will be tested for function and casualty in the caliber .50 cartridge, Drawing C7553097. When components for the caliber .50 cartridge, Drawing C7553097 are not available, spotter-tracer cartridge, Drawing C8594736, shall be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.

4.4.4.1 *Reduced testing.* At the discretion of the contracting officer, function and casualty firing may be reduced if five consecutive testing one out of every five lots submitted. lots, all using the same primer mix and production process, have met the requirement of 3.5. The reduced plan shall consist of Testing of every lot shall be resumed when the requirements of 3.5 is not complied with or when the primer mix or production process changes.

5. PREPARATION FOR DELIVERY

5.1 Packing.

5.1.1 *Level A.* The primers shall be packed in accordance with Drawing D7553230, D7553225, or D7553274, as applicable.

5.1.2 *Level C.* Unless otherwise specified by the procuring activity, the primers shall be packed in standard commercial containers so as to insure acceptance by common or other carrier for safe transportation, in accordance with ICC regulations listed in 2.2, at the lowest rate, to the point of delivery. The primers shall be packed and spaced in such a manner that barrier of some material is present between the crown of one primer and the base of another primer in order to resist mass detonation and shield the primers from contact with stray electrical current, flame and shock.

5.2 Marking shipments. Packing boxes containing the primers shall be marked in accordance with the applicable drawings cited in 5.1 and Standard MIL–STD–129 for contract number, primer type, number of priming composition, primer lot number, and date of manufacture.

5.3 Data cards. Data card information shall be as specified in Specification MIL–G–2550.

6. NOTES

6.1 Ordering data. Procurement documents should specify the title, number, and date of this specification.

6.2 Action time is the total elapsed time from the application of energy to the primer until the emergence of the bullet from the barrel and passage through the terminal pickup.

6.3 The method for computation of the skewness value is shown on figure 1.

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodians:
Army—Ordnance Corps
Navy—Bureau of Ordnance
Air Force

Preparing activity:
Army–Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.

H = Ht.	Pi = fraction misfiring	k_i = variance factor	k_iP_i = Variance factor times fraction misfiring	s_i = Skewness factor	S_iP_i
		1		1	
		3		7	
		5		19	
		7		37	
		9		61	
		11		91	
		13		127	
		15		169	
		17		217	
		19		271	
		21		331	
		23		397	
		25		469	
		27		547	
ΣP_i =		Σk_iP_i =		ΣS_iP_i =	
*H100% + .5 =		$-(\Sigma P_i)^2$ =		$\mu 3$ =	
H =		$\sigma 2$ =		$\alpha 3$ =	
*H100% = 1st ht.		σ =			
at which 100% misfire					

$\mu 3 = \Sigma S_iP_i - 3\,\Sigma k_i Pi\ Pi + 2\,(\Sigma Pi)^3$
$\alpha 3 = \mu 3/0^3$ = skewness value

FIGURE 1. *Calculation sheet for primer sensitivity and skewness*

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:24Z
Check the source to verify that this is the current version before use.