MIl-T-780E
30 April 1975
SUPERSEDING
MIL-T-780D
3 April 1969

# MILITARY SPECIFICATION

## TAMPER, PISTON-HAMMER TYPE, PNEUMATIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 This specification covers a pneumatically driven, manually controlled, piston-hammer type tamper.

## 2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

| | |
|---|---|
| WW-C-633 | - Couplings, Hose: (Half), Pneumatic, Universal Type. |
| PPP-B-601 | - Boxes, Wood, Cleated-Plywood. |
| PPP-B-636 | - Boxes, Shipping, Fiberboard. |
| PPP-P-40 | - Packaging and Packing of Hand Tools. |
| PPP-T-60 | - Tape: Packaging, Waterproof. |

Military

| | |
|---|---|
| MIL-P-116 | - Preservation-Packaging, Methods of. |
| MIL-B-121 | - Barrier Material, Greaseproofed, Waterproofed, 'Flexible. |
| MIL-P-514 | - Plates, Identification, Instruction and Marking, Blank. |
| MIL-T-704 | - Treatment and Painting of Material. |
| MIL-C-5501 | - Caps and Plugs, Protective, Dust and Moisture Seal, General Specification for. |

FSC 3895

Source: https://assist.dla.mil -- Downloaded: 202610-16T11:28Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

| | |
|---|---|
| MIL-STD-105 | - Sampling Procedures and Tables for Inspection by Attributes. |
| MIL-STD-129 | - Marking for Shipment and Storage. |
| MIL-STD-130 | - Identification Marking of Miliatary Property. |
| MIL-STD-1474 | - Noise Limits for Army Material. |
| MS35647 | - Padlocks, Key Operated. |
| MS35793 | - Handle, Bail-Chest, Surface Mounting, Plain Holes. |
| MS35829 | - Hinge, Continuous (Piano), .075 Thickness, .187 and .250 Pin Dia. |

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer. )

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

COMPRESSED AIR AND GAS INSTITUTE

Compressed Air and Gas Handbook.

(Application for copies should be addressed to the Compressed Air and Gas Institute, 122 East 42nd Street, New York, NY 10017.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606. )

AMERICAN NATIONAL STANDARDS INSTITUTE, INC. (ANSI)

S5.1 - Measurement of Sound from Pneumatic Equipment, Specification for.

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-16 11:28Z
Check the source to verify that this is the current version before use.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations , Inc., ATTN: Tariff Order Section, 1616 P Street, NW, Washington, DC 20036. )

3. REQUIREMENTS

3.1 Description. The tamper shall consist of a front head, back head, cylindrical body, throttle valve, trigger lever, piston, and tamping pad.

3.1.1 Characteristics. The tamper shall be between 45 and 54 inches long, and shall weigh between 31 and 48 pounds when equipped with the tamping pad. The full force of the blow shall be exerted through the tamping pad when the tamper is operated in all positions from the vertical to 90 degrees from the vertical. The tamper shall operate as specified herein on compressed air at pressure ranging from 70 to 100 pounds per square inch gage (psig). The total air consumption of the tamper shall be not more than 46 cubic feet per minute (cfm) maximum with 90 psig at the tamper. The tamper shall deliver a minimum of 625 blows per minute at no load, and a 26-foot-pound minimum force of blow with 90 psig air pressure at the tamper. The tamper shall operate for 75 hours without evidence of mechanical failure, breakage, scoring, or wear of more than 0.001 inch to the piston or cylinder.

3.1.2 Interchangeability.. All parts having the same manufacturer's part number shall be interchangeable with each other with respect to installation and performance.

3.2 First article (preproduction model . The supplier shall furnish one Or more tampers as specified (see 6.2) for examination and testing within the time frame specified (see 6.2) to prove prior to starting production, that his production methods and choice of design detail will produce tampers the comply with the requirements of this specification. Marination and tests shall be as specified in Section 4; and, unless otherwise specified herein, all examinations and tests shall be conducted by the supplier subject to surveillance and approval by the Government (see 6.3). When specified (see 6.2), the Government will conduct any or all of the preproduction examination and tests, as specified (see 6.2).

3*3 Initial production. When specified (see 6.2), the supplier shall furnish to 'the Government, me or more tampers for inspection as specified in 4.4.



Source: https://assist.dla.mil -- Downloaded: 202610-16T11:28Z
Check the source to verify that this is the current version before use.

3.4 Material. Material shall be as specified herein. Material not specified be selected by the supplier and shall be subject to all provisions of this specification.

3.5 sound level. The sound level of the tamper shall be in accordance with MIL-STD-1474, 88 dB(A) for steady-state noise when tested in accordance with 4.6.2.5.1. The sound level shall comply with the exterior noise requirements of MIL-STD-1474 when tested in accordance with 4.6.2.5.2 (aural nondetectability and impulse noise do not apply). The precautions of MIL-STD-1474 (see 6.4) shall be provided if the sound level exceeds 85 dB(A) when tested in accordance with 4.6.2.5 l 3. Hearing protectors shall not be supplied with the tamper.

3.6 Tampering pad. The pad shall be of malleable iron or cast steel, with a circular base having a diameter of not less than 5 inches nor more than 6 inches. The pad shall be attached to the piston rod by means of a locking screw or nut. A maintenance tool shall be furnished for removing pad locking screw or nut l

3.7 Body. The body shall be made of alloy steel or malleable iron.

3.8 Throttle valve. The throttle valve shall be of the self-closing, lever-operated type.

3.9 Latch. A latch shall be furnished to lock the valve lever.

3.10 Piston rod. The piston rod shall be made from one piece of barstock or machined forged steel.

3.13 Seal. A seal for wiping the piston rod shall be furnished to keep out dirt and grit ,

3.22 Air inlet. connection. The air inlet connection thread shall be 1/2 inch internal American National pipe thread.

3.13 Air strainer. The air strainer or screen with a mesh of 24 per inch shall be replaceable and shall not be damaged when the supply hose is connected or disconnected from the air inlet connection.

3.14 Coupling half. Unless otherwise specified, a coupling half conforming to WW-C-633, Type III, Size 1/2 inch male, shall be furnished.

3.15 Oil reservoir l An oil reservoir shall be furnished. The oil reservoir shall be built into the back head or cylinder. The oil reservoir shall have a capacity for not less than 30 minutes of continuous operation while operating at 90 psig at the tamper.



Source: https://assist.dla.mil -- Downloaded: 2026l0-16T11:28Z
Check the source to verify that this is the current version before use.

3.16 Lubrication. All surfaces requiring lubrication shall be lubricated by the internal oil reservoir.

3.17 Identification marking. The tamper shall be identified in accordance with MIL-STD-130. The required marking shall be applied directly to the housing surface by metal stamp or forging.

3.18 Treatment end painting The portions of the tamper and its components and parts normally painted shall be cleaned, treated, and painted in accordance with MIL-T-704, Type A, color as specified.

3.19 Chest. When specified (see 6.2), a chest made of steal not less than 0.071 inch in thickness shall be famished and shall be of a size to hold the maintenance tools, tamper, and repair parts specified herein. The chest lid shall be secured to one edge of a side by a continuous hinge extending the full length of the chest edge. The hinge shall conform to MS35829-7C . The lid shall be held in the closed position by not less than two hook-type tension latches with strikers bolted or riveted to the chest and to the lid. A hasp shall be provided to secure the lid to the chest and accomodate a lock conforming to MS35647. Two lifing handles conforming to MS35793 shall be provided, one located at each end of the chest. The lid shall remain in the fully open position by the weight of the lid or by holding devices.

3.20 Workmanship. The tamper shall be free of defects such as galvanic action resulting from contact of dissimilar metals, rust, cracks, , and other defects that could impair its operation or serviceability. All parts, components, and assemblies of the tamper including castings, forgings, molded parts, stampings, bearings, seals, and machined surfaces shall be clean and free from sand, dirt, fins, pits, sprues, scale, and other harmful or extraneous materials. All edges shall be rounded or beveled.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. l Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:28Z
Check the source to verify that this is the current version before use.

4.2 classification of "inspections. Inspections shall be classified as follows :

(a) Preproduction inspection of the tamper (see 4.3).
(b) Initail production inspection (see 4.4).
(c Quality conformance inspection (see 4.5).
d Inspection comparison (see 4.7).
e Inspection of preparation for delivery (see 4.8).

4.3 Preproductio inspection.

4.3.1 Examination. The tamper shall be examined as specified in 4.6.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The tamper shall be tested as specified in 4.6.2 through 4.6.2.5. Failure of any test shall be cause for rejection.

4.4 Initial production inspection. When specified (see 3.3), one or more initial production tampers will be selected at random by the Government from the tampers being produced by production tooling and will be examined as specified in 4.6.1 and tested as specified in 4.6.2 through 4.6.2.5 to determine conformance to the requirements of this specification. The inspection will be performed by the Government at a site selected by the Government. Acceptance of an initial production tamper shall not exclude the remaining tampers from the quality conformance inspection and acceptance provisions specified in Section 4. In addition to any test specified as part of the initial production test, the Government reserves the right to conduct any or all other tests contained in this specification as part of the initial production test, and failure of such additional tests shall have the same effect as failure of those tests specified as initial production tests.

4.4.1 Inspection failure . Failure of an initial production tamper to meet any requirements specified during and as a result of the examination and tests specified in 4.4 shall be cause for rejection of the initial production tamper(s) and shall be cause for refusal by the Government to continue acceptance of production tampers until evidence has been provided by the supplier that corrective action has been taken to eliminate the deficiencies. Correction of such deficiencies shall be accomplished by the supplier at no cost to the Government on tampers previously accepted and produced under the contract. Any deficiencies found as a result of the initial production inspection will be considered prima facie evidence that all tampers accepted prior to the completion of initial production inspection are similarly deficient unless evidence to the contrary is furnished by the supplier and such evidence is acceptable to the contracting officer.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:28Z
Check the source to verify that this is the current version before use.

4.5 Quality conformance inspection.

4.5.1 Examination. Each tamper shall be examined as specified in 4.6.1. Presence of one or more defects shall be cause for rejection.

4.5.2 Tests. Each tamper shall be tested as specified 4.6.2.6. Failure of the tests shall be cause for rejection.

4.6 Inspection procedure.

4.6.1 Examination. The tamper shall be examined for the following defects:

101. Dimensions and weight not as specified.
102. Parts or Components missing.
103. Material not as specified.
104. Pad maintenance tool not furnished.
105. Throttle valve not as specified.
106. Coupling half not as specified.
107. Strainer mesh not as specified.
108. Identification markings absent or incorrect l
109. Treatment and painting not as specified.
110. Workmanship not aS specified.

4.6.2 Tests. Prior to being tested, the tamper shall be disassembled. The piston and cylinder diameters shall be recorded, and the piston and cylinder shall be indicated. The tamper shall be reassembled, and the oil reservoir shall be filled with oil furnished by the supplier. The oil shall be compatible with the military lubricants (see 6.5) listed herein.

4.6.2.1 Operation. Operate the tamper at 10-degree angular increments for not less than 5 minutes in each position from the vertical to 90 degrees from the vertical, tampering fill for not less than 75 hours, consisting of 25 hours each at pressures of 70, 90, and 100 psig. At 5-hour intervals during the test, examine the exhaust for presence of oil in the exhausted air. At the completion of 75 hours of operation take the following action:

a Examine the strainer for damage or defective mounting.
b Examine all external parts of the tamper. Remove the tamping pad using the maintenance tool.
d Disassemble the tamper and examine the for for damage, wearing, or scoring l

Evidence of mechanical failure, permanent defamation, or damaged or scored parts; inability of the tamper to operate in any of the positions from horizontal to vertical; evidence of the tamping pad coming loose during operation;



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:28Z
Check the source to verify that this is the current version before use.

evidence of damage to the strainer or defective mounting of the strainer; inability to remove the tamping pad; evidence of excessive wear of the piston diameter or cylinder diameter (see 3.1.1 and 4.6.2); or absence of oil vapor in the exhaust air shall constitute failure of this test.

4.5.2.2 Force of blow. Attach a steel ball with a Brinell hardness of not less than 200 and a (0.499- to 0.500(inch spherical diameter to the end of the tamper piston rod. With the tamper operating at 90 psig air pressure, make 20 impressions with the steel ball in a l/4-inch-thick strip of 1020 steel which has a Brinell hardness between 163 and 179. Measure in millimeters the mean diameter of the impressions. convert to foot-pounds using Table I. A force of blow less than 26 foot-pounds shall constitute failure of this test.

Table I. Force of Blow Conversion Table

| Impression Diameter mm | Force of Blow - Ft-Lb | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| | 0.00 | 0.01 | 0.02 | 0.03 | 0.04 | 0.05 | 0.06 | 0.07 | 0.08 | 0.09 |
| 6.0 | 23.9 | 24.07 | 24.24 | 24.41 | 24.58 | 24.75 | 24.92 | 25.09 | 25.26 | 25.43 |
| 6.1 | 25.6 | 25.77 | 25.94 | 26.11 | 26.28 | 26.45 | 26.62 | 26.79 | 26.96 | 27.13 |
| 6.2 | 27.3 | 27.49 | 27.69 | 27.88 | 28.08 | 28.27 | 28.47 | 28.66 | 28.86 | 29.05 |
| 6.3 | 29.25 | 29.46 | 29.67 | 29.88 | 30.09 | 30.30 | 30.51 | 30.72 | 30.93 | 31.14 |
| 6.4 | 31.35 | 31.59 | 31.85 | 32.09 | 32.34 | 2.58 | 32.83 | 33.07 | 33.32 | 33.56 |

4.6.2.3 Air-consumption test. Measure the toted air consumption (cfm of free air) at 90 psig with the throttle valve fully open. A water displacement meter or airflow meter shall be used in accordance with procedures outlined in the Compressed Air and Gas Handbook to determine air consumption. Air consumption exceeding 46 cfm shall constitute failure of this test.

4.6.2.4 Piston speed test. Determine the piston speed when operating without butt (blow per minute at no load). Less than that specified in 3.1.1 shall constitute failure of this test.

4.6.2.5 Sound level measurement.

I 4.6.2.5.1 Operator's station. Measure the sound level at the operator's station, the location above the tamper on its major axis, in accordance with ANSI 35.1-1971 while operating at 6 bar gage. Nonconformance to 3.5 shall constitute failure of this test.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:28Z
Check the source to verify that this is the current version before use.

4.6.2.5.2 Exterior position. Measure the exterior sound level in accordance with ANSI S5.1-1971 at 7 meters. Nonconformance to 3.5 shall constitute failure of this test.

4.6.2.5.3 Hazard precaution test. Measure the sound level at all the 1 meter locations of ANSI S5.1-l971 while operating at 6 bar and tamping a soil fill. Failure to provide the necessary precautions of 3.5 shall constitute failure of this test.

4.6.2.6 Individual operation. Operate each tamper for 10 minutes at 100 psig. Operational difficulties or breakage, or permanent deformation of any part shall constitute failure of this test.

4.7 Inspection comparison. The Government may select tampers at any time during the contract production period and subject these tampers to the examination specified in 4.6.l and the tests specified in 4.6.2 through 4.6.2.5 to determine conformance to the requirements of this specification. The inspection will be performed by the Government, at a site selected by the Government, on tampers selected at random from those which have been accepted by the Government and will not include the previously inspected preproduction model and initial production tampers. In addition to any test specified as part of the inspection comparison, the Government reserves the right to conduct any and all other tests contained in this specification as part of the inspection comparison and failure of such additional tests shall have the same effect as failure of those tests specified as inspection comparison.

4.7.1 Inspection failure. Failure of an inspection comparison tamper to meet any requirement specified herein during and as a result of the examination and tests specified in 4.7 shall be cause for rejection of the inspection comparison tamper(s) and shall cause for refusal by the Government to continue acceptance of production tampers until evidence has been provided by the supplier that corrective action has been taken to eliminate the deficiencies. Correction of such deficiencies shall be accomplished by the supplier at no cost to the Government on tampers previously accepted and produced under the contract. Any deficiencies found as a result of the inspection comparison will be considered prima facie evidence that all tampers accepted prior to the completion of inspection comparison are similarly deficient unless evidence to the contrary is furnished by the supplier and such evidence is acceptable to the contracting officer.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:28Z
Check the source to verify that this is the current version before use.

4.8 Inspection of preparation for delivery.

4.8.1 Quality conformance inspection of pack.

4.8.1.1 Inspection stages. Inspection shall be in two stages as follow:

(a) The first stage shall include inspection of materials, methods, and packages inside the shipping container.
(b) The second stage shall include inspection of materials and marking after closing and strapping the shipping container.

4.8.1.2 unit of product. For the purpose of inspection, a unit of product for the first stage of inspection shall be a complete pack with the container not closed. For the second stage of inspection, a unit of product shall be a completed pack prepared for shipment.

4.8.1.3 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.8.1.4 Examination. Samples selected in accordance with 4.8.1.3 shall be examined for the following defects. AQL shall be 2.5 percent defective.

| | | |
|---|---|---|
| 111. | Materials, methods and containers not as specified. Each incorrect material, method, or container shall constitute one defect. | |
| 112. | Unprotected exterior surfaces not coated with preservative and wrapped or covered as required for Level A. | |
| 113. | Interior surfaces of the cylinder assembly not coated with oil and the air inlets and outlets closed as specified for Level A. | |
| 114. | Hose not coiled and secured as specified for Level A. | |
| 115. | Maintenance tools not preserved in accordance with the referenced document for Level A. | |
| 116. | Consolidated packaging not as specified for Level. A. | |
| 117. | Packing not as specified for Level A or B. | |
| 118. | Strapping not as specified for Level A. | |
| 119. | Marking missing, illegible, incorrect, or incomplete. | |

5. PREPARATION FOR DELIVERY

5.1 Preservation and packing. Preservation and packaging shall be Level A or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly. Disassembly of the tamper shall be in accordance with the recommendations of the supplier.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:28Z
Check the source to verify that this is the current version before use.

5.1.1.2 Preservatives. Preservatives specified herein shall conform to the applicable specifications listed in and shall be applied in accordance with MIL-P-116.

5.1.1.3 Unprotected surfaces. Unprotected exterior metal surfaces requiring the application of a contact preservative in accordance with MIL-P-116 shall be preserved as follows.

5.1.1.3.1 Machined surfaces. Exposed exterior machined metal surfaces shall be mated with Type P-6 preservative. The coated surfaces shall 'be covered or wrapped with barrier material conforming to MIL-B-121, Type I, Grade A, Class 2, and secured in place with tape conforming to PPP-T-60, Type IV.

5.1.1.3.2 Unfinished surfaces. Exposed exterior unfinished metal surfaces shall be coated with Type P-1 preservative. No wrap shall be required*

5*1.1*4 Cylinder assembly. Interior surfaces of the cylinder assembly shall be coated with oil conforming to Type P-10 preservative, Type I, Grade 30. The oil shall 'be applied through the lubricating system or by feeding the oil into the air inlet while actuating the piston, until the preservative appears at the exhaust port. Air inlets and outlets shall be closed with plastic caps or plugs, as applicable, conforming to MIL-C-5501.

5.1.1.5 Hose. When a leader hose is furnished, the hose shall be coiled and the coil secured with a minimum of three equally spaced ties of cotton tape or twine.

5,3..1,6 Repair parts. The preservative application criteria and applicable methods of preservation of MIL-P-116 shall be used to preserve repair parts.

5.1.1.7 Maintenance tools. Maintenance tools shall be preserved in accordance with PPP-P-40, Level A.

5.1.1.8 Technical publications. Technical publications shall be preserved in accordance with MIL-P-116, Method IC-1.

5.1.1.9 Consolidated packagi ng. When a chest is furnished (see 3.19), components comprising a complete tamper shall be consolidated together in the chest, and the chest lid closed and secured. When a chest is not furnished the components shall be consolidated together in a close-fitting box conforming to PPP-B-636, W5c or V3c, style optional, as applicable to



Source: https://assist.dla.mil -- Downloaded: 202640-16T11:28Z
Check the source to verify that this is the current version before use.

the weight of the' components. The components shall be blocked, braced, and cushioned within the box in a manner to prevent free movement and damage to the contents or to the box. Boxes shall be waterproof closed in accordance with the appendix to the box specification.

5.1.2 Level C. Each complete tamper shall be preserved and packaged to afford protection against deterioration and damage from the supplier to the initial destination. The supplier's standard commercial practice is acceptable when it fulfills these requirements.

5.2 Packing. Packing shall be Level A, B, Or C as specified (see 6.2).

5.2.1 Level A. The tampers shall be packed in a close-fitting box conforming to PP-B-601, Overseas Type,Grade B. When the tampers are furnished in chests, and more than one tamper is to be packed in the same box, the chests shall be blocked in the box in a manner to prevent movement and to prevent the chests from contacting each other. Box closure and strapping shall be in accordance with the appendix to the box specification.

5.2.2 Level B. The tampers shall be packed as specified in 5.2.1 except boxes shall be Domestic Type.

5.2.3 Level C. The tampers shall be packed to assure carrier acceptance and safe delivery to destination at lowest rates in containers complying with Unifom Freight Classification rules or National Motor Freight Classification rules.

5.3 Marking. In addition to any special marking required by the contract or order, packages and shipping containers shall be marked in accordance with MIL-STD-129 .

6. NOTES

6.1 Intended use. The tamper covered by this specification is intended to be used for compacting or tamping earth when refilling all types of excavations.

6.2 Ordering data. procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) The frame required for submission of the preproduction model and number of tampers required (see 3.2).



Source: https://assist.dla.mil -- Downloaded: 202610-16T11:28Z
Check the source to verify that this is the current version before use.

(c) When the Government will conduct any or all of the preproduction model. acumination and tests. When the Government will conduct some but not all of the preproduction examination and tests, the contracting officer should specify which examination and tests will be conducted by the Government and which examination and tests shall be conducted by the supplier (see 3.2).
(d) When initial production inspection is required and number of tampers to be furnished (see 3.3).
(e) When a coupling half is not to be furnished (see 3.14).
(f) Color specified (see 3.18).
(g) when a chest is required (see 3.19).
(h) Level of preservation and packaging and level of packing required (see 5.1 and 5.2).

6.3 Preproduction model. Any changes or deviations of production tampers from the approved preproduction model during production will be subject to the approval of the contracting officer. Approval of the preproduction model will not relieve the supplier of his obligation to furnish tampers conforming to this specification.

6.4 Noise hazard. When the noise level of the tamper exceeds 85 dB(A), the appropriate discussion of the noise hazard per MIL-STD-1474 (Manual Paragraph) shall include the requirement for hearing protection, the noise level of the item, the distance from the item at which 85 dB(A) will always be met, and what operational situation or system configuration will reduce the level to 85 dB(A).

6.5 Lubricants. The contracting officer should furnish a list of military lubricants applicable to the tamper covered by this specification as contained in the Federal Supply Catalog, Department of Defense Section, Identification List C91100-IL, for FSC Group 91.

6.6 Data requirements. The contracting officer should include requirements for such data as technical publications, instructional materials, illustrated parts list, and supplier's maintenance and operation manual to be furnished with each tamper.

6.7 Provisioning. The contracting officer should include provisioning requirements for repair parts and maintenance tools as necessary (including any special tools) and instructions on shipment of tampers. A suggested paragraph is as follows:

"Shipment of tampers shall include repair parts, maintenance tools, operational instructions, and accessories, unless exceptions are provided elsewhere in the contract. "



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:28Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE: MIL-T-780E TAMPER, PISTON-HAMMER TYPE, PNEUMATIC

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-16T11:28Z
Check the source to verify that this is the current version before use.