MILITARY SPECIFICATION

CONTAINER, AMMUNITION, METAL, FOR PROPELLING CHARGES AND CARTRIDGES

This amendment forms a part of Military Specification MIL-C-63461 (AR), dated 20 July 1981, and is approved for use by the U.S. Army Armament Munitions and Chemical Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Delete: "AND CARTRIDGES".

1.1 Scope. Delete "and for packing cartridges".

PAGE 3

3.3.1 Tensile strength (if applicable). Add the following new subparagraphs:

"3.3.1.1 Tensile strength of body material. The tensile strength of the body material shall not be less than 47,000 pounds per square inch (psi) nor greater than 53,000 psi when tested as specified in 4.5.1".

3.4 Painted surface. Delete in its entirety and substitute:

"3.4 Painted surface. The painted surfaces of the container shall comply with the requirements of TT-C-490. However, the film thickness and salt spray requirements of TT-C-490 shall not apply to the interior surfaces and the welded spots and sharp corners of the exterior surface of the container."

* 3.5 Cover assembly. Delete in its entirety and substitute:

"3.5 Cover assembly. Upon assembly of the cover assembly to the body assembly (body weldment), the cover assembly shall freely engage and rotate within the body assembly. As the cover assembly is rotated with the "Y" handle in the open position, the "Y" handle shaft ends shall freely engage into the respective bayonet slots of the rim. When the "Y" handle is rotated toward the closed position, the "Y" handle shall push the spring clip out of the way and snap into place (closed position) and

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:55Z
Check the source to verify that this is the current version before use.

the spring clip shall return to its original position locking the "Y" handle. When the "Y" handle is returned to the open position, it shall push the spring clip out of the way permitting a 180° rotation of the "Y" handle to the open position with the spring clip returning to its normal position. Rotation of the cover assembly will permit disengagement from the body assembly."

PAGE 4

* Add new paragraph as follows:

"3.8 Air pressure test.

3.8.1 Air pressure of unpainted cover assembly. The unpainted cover assembly shall withstand an internal air pressure of three pounds per square inch (psi) minimum (min.), for five (5) seconds under water, without apparent leakage occurring when tested as specified in 4.5.8.1.

3.8.2 Air pressure of unpainted body assembly. The unpainted body assembly shall withstand an internal air pressure of three psi min., for five (5) seconds under water, without apparent leakage occurring when tested as specified in 4.5.8.1.

3.8.3 Air pressure of painted container assembly.

3.8.3.1 Pressure drop method. The sealed container shall withstand the internal air pressure specified in the applicable container assembly drawing for one of the test times specified without apparent leakage occurring when tested as specified in 4.5.8.2.1.

3.8.3.2 Gage Method. The sealed container shall withstand an internal air pressure of three psi min., for the time specified in the applicable container assembly drawing, without apparent leakage occurring when tested as specified in 4.5.8.2.2

3.8.3.3 Water immersion method. The sealed container shall withstand an internal air pressure of three psi min., for five seconds min. under water, without apparent leakage occurring when tested as specified in 4.5.8.2.3.

PAGE 10

* 4.4.2.3 Support, shaft. Defects:

Delete: "105. Horizontal location of large hole and slot ...
.40% 3.2 Gage
107. Vertical location of small hole ...
.40% 3.2 Gage
108. Horizontal location of small hole ...
.40% 3.2 Gage"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:55Z
Check the source to verify that this is the current version before use.

PAGE 12

* 4.4.2.5 Handle. Classification of Defects:

Delete: "103. Vertical location of small hole ... .40% 3.2 Gage
104. Horizontal location of small hole ... .40% 3.2 Gage
201. Distance from center of shaft hexhole to outer edge of tabs .40% 3.2 Gage"

PAGE 15

* 4.4.2.8 Retainer, Major Defects:

Delete: "103. Wall thickness .40% 3.2 Gage
104. Inside depth .40% 3.2 Gage"

PAGE 25

* 4.4.2.18 Plug, stacking, Major Defects.

Delete: "101. Plug (smaller) diameter .40% 3.2 Gage
102. Knob (larger) diameter .40% 3.2 Gage
104. Length of knob .40% 3.2 Gage"

Add: 101. Length of indexing projection .40% 3.2 Gage
102. Width of indexing projection .40% 3.2 Gage
104. Width of plug .40% 3.2 Gage
105. Location of indexing plug .40% 3.2 Gage"

PAGE 28

4.4.3.1 Tensile strength. Delete in its entirety and substitute the following:

"4.4.3.1 Tensile strength (see 3.3.1), Major Defect. Six (6) bodies shall be randomly selected for this test. From each body, three (3) specimens shall be selected at random for determination of body material tensile strength. Also, from each body, four (4) specimens approximately equally spaced along the axis shall be taken at right angles to the weld and the tensile strength of their welds shall be determined. Each of these values shall be compared with the lowest determined value of the body material tensile strength for compliance with the requirement of 3.3.1. If one or more specimens (longitudinal body weld or body material) fail to comply with 3.3.1 or 3.3.1.1, that sample body shall be classed defective. If two or more sample bodies are classed defective, the lot shall be rejected."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:55Z
Check the source to verify that this is the current version before use.

* 4.4.3.8.1 Air pressure of unpainted cover assembly: Delete: "(see applicable container assembly dwg. (see 2.1))" and substitute: "see 3.8.1".

PAGE 29

* 4.4.3.8.2 Air pressure of unpainted body assembly: Delete: "(see applicable container assembly drawing (see 2.1))" and substitute: "see 3.8.2".

* 4.4.3.8.3 Air pressure of painted container assembly: Delete: "(see applicable container assembly drawing (see 2.1)) and substitute: "see 3.8.3".

* 4.5.5 Deflection load of spring, first sentence, change: "dwg 9331695" to "dwg 9331694".

* 4.5.8 Air pressure test: Delete in its entirety and substitute:

"4.5.8 Air pressure test.

4.5.8.1 Air pressure of unpainted cover assembly and unpainted body assembly (water immersion method). Subject the cover assembly and container body to the specified internal air pressure for the test time specified. For the cover assembly, apply the pressure when the cover assembly is assembled to a master body assembly (or its equivalent) equipped with a gasket.

For the body assembly, apply the pressure when the body assembly is assembled to a master cover (or equivalent) and gasket. The master cover and the master body assembly shall be provided with satisfactory means for applying and maintaining the pressure during the test and for showing evidence of leakage. Observation shall be made for the presence of bubbles. No bubbles (other than surface bubbles) shall be permitted. A cover assembly or body assembly which does not meet the requirements, shall be classed defective.

4.5.8.2 Air pressure of painted container assembly.

4.5.8.2.1 Pressure drop method. Apply the internal air pressure, specified on the applicable container assembly, to the container. Observation shall be made for a pressure drop exceeding the requirement for the corresponding test time (as specified on the applicable drawing). A container which exceeds the requirement shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:55Z
Check the source to verify that this is the current version before use.

4.5.8.2.2 Gage method. The gage used to test for this requirement shall have a calibrated scale of 0.1 psi per division. Spacing between graduations shall allow for visual resolution capability or .025 psi. With this gage, no indication of leakage shall be allowed (no visual movement of gage needle). A container which does not meet the requirement shall be classed defective.

4.5.8.2.3 Water immersion method. The container shall be immersed in water and pressurized to the specified air pressure for the required time. Observation shall be made for the presence of bubbles. No bubbles (other than surface bubbles) shall be permitted. A container which does not meet the requirement shall be classed defective.

* The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment."

Custodian:
ARMY-AR

Preparing activity:
ARMY-AR

(Project 8140-A568)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:55Z
Check the source to verify that this is the current version before use.