INCH-POUND
MIL-DTL-70759A(AR)
12 September 2004
SUPERSEDING
MIL-C-70759 (AR)
27 August 2001

DETAIL SPECIFICATION

CONTAINER, AMMUNITION: HAND-HELD PYROTECHNIC SIGNAL SERIES, PA142

This specification is approved for use by the US Army ARDEC and is available for use by all Departments and Agencies of the Department of Defense.

Comments, suggestions, or questions on this document should be addressed to (Commander ARDEC, ATTN: AMSRD-AAR-AIS-SS, Picatinny, NJ 07806-5000) or emailed to (ardec-stdzn@pica.army.mil). Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil.

AMSC N/A FSC:8140

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 Scope. This specification covers the requirements and quality assurance provisions for the manufacture of one type of Container, Ammunition: Hand-Held Pyrotechnics Signal Series, PA142, plastic container used for packing pyrotechnic hand held signals.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-STD-1168 – Ammunition Lot Numbering and Ammunition Data Card
MIL-STD-1916 – DOD Preferred Method for Acceptance of Product

(Copies of this document are available online http://assist.daps.dla.mil/quicksearch/ or http://assist.daps.dla.mil or from the Standardization Documents Order Desk, 700 Robbins Avenue, Bldg 4D, Philadelphia, PA 19111-5094).

2.2.2 Other Government documents, drawings, and publications. The following other Government documents drawings and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract .

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

DRAWINGS (see 6.3)

US ARMY ARMAMENT RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER (ARDEC) DRAWINGS

12900000	Container, Signal, PA142
12900002	Cover, Container
12900003	Body, Container
12900007	O-ring

(Copies of these drawings are available online from Drawing-Request@pica.army.mil or from US Army ARDEC, ATTN: AMSRD-AAR-AIC-T, Picatinny, NJ 07806-5000.

CODE OF FEDERAL REGULATIONS

Title 49, Transportation, Parts 100-199

(Copies of this document are available online at www.acess.gpo.gov/nara/cfr or from the Superintendent of Documents, U.S. Printing Office, North Capitol & "H" Streets N.W., Washington, D.C. 20402. Orders should specify 49 CFR 100-199, latest revision).

2.3 Non-Government publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

ASME-B1.8	Stub Acme Screw thread

(Copies of these documents are available from www.asme.org or ASME Information Central Orders/Inquiries, P.O. Box 2300, Fairfield, NJ 07007-2300).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM) INTERNATIONAL

ASTM-E794	Standard Test method for Melting and Crystallization Temperatures by Thermal Analysis

(Copies of this document are available from www.astm.org or ASTM International 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article inspection. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.2.

3.2 Material. Materials shall be in accordance with drawing 12900000, Container, Signal, PA142 and standards, ASME-B.18 Stub ACME Screw thread.

3.2.1 Regrind material. No reground material shall be used in molding the container bodies and covers.

3.3 Components and assembly. -The components and assemblies shall comply with the all the requirements as specified on the drawings.

3.3.1 Container, Signal, PA142. – The container shall be fabricated as specified on drawing 12900000.

3.3.2 Cover, Container. – The cover, container shall be checked dimensionally as specified on drawing 12900002.

3.3.3 Body, cover. – The body, cover shall be checked dimensionally as specified on drawing 12900003

3.3.4 O-Ring. – The O-ring shall be fabricated and tested as specified on drawing 12900007.

3.4 Material physical properties. The material used in the manufacture of the containers cover (dwg. 12900003) and body (dwg. 12900003) shall conform to the physical properties listed in applicable drawings.

3.4.1 Glass content. The glass content shall be 15% +/- 1%.

3.4.2 Dimensional control of molded plastic parts. A dimensional check of the cavity shall be performed after continuous production of 8 hours.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

3.5 Three foot drop test. The container shall be capable of passing the air pressure (leak test) of paragraph 3.7 below after being subjected to a three foot drop.

3.6 Seven foot drop test. The container shall not open and/or spill its contents.

3.7 Air pressure test (leak test). The container (dwg. 12900000) shall withstand a pressure differential of 3.0 psi (6.4 inches of Hg), and shall show no evidence of air or water leakage.

3.8 Cover removal torque. The removal torque shall be between the range of 15 to 45 in-lb when locking nubs are fully engaged.

3.9 Workmanship. All parts shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of cracks, burrs, surface defects, flash, air bubbles, holes, blisters, sharp corners, warpage, amides, dirt, twists or any similar characteristics that may impair proper functioning. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents.

3.10 Ammunition Lot Numbering. Ammunition lot numbers shall be assigned in accordance with MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

TABLE I. Requirement/verification cross reference matrix

Method of Verification N/A – Not applicable (N/A) 1 – Analysis 2 – Demonstration 3 – Examination 4 – Test		Classes of Verification A – First Article B – Conformance							
Section 3 Requirement		Verification Method					Verification		Section 4 Class Method
		N/A	1	2	3	4	A	B	
First Article Test	3.1				X	X	X	X	4.2
Materials/Regrind Material	3.2, 3.2.1				X		X	X	4.4.1, 4.5.1.1
Components and Assembly	3.3				X		X	X	4.3.2.6
Container, Signal PA142	3.3.1				X		X	X	4.3.2.6
Cover, Container	3.3.2				X		X	X	4.3.2.4
Body, Container	3.3.3				X		X	X	4.3.2.3
O-ring	3.3.4				X		X	X	4.3.2.5
Material Physical Properties	3.4				X	X	X		4.4.1, 4.5.1.1
Glass Content	3.4.1				X	X	X		4.4.1, 4.5.1.1.1
Dimensional Control of Molded Plastic Part	3.4.2				X		X	X	4.5.2
Three Foot Drop Test	3.5					X	X	X	4.4.2
Seven Foot Drop Test	3.6					X	X	X	4.4.3
Air Pressure Test (Leak Test)	3.7					X	X	X	4.4.4
Cover Removal Torque	3.8					X	X	X	4.4.5
Workmanship	3.9				X		X	X	4.4.6
Ammunition Lot Numbering	3.10				X		X	X	4.4.7

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2).

b. Conformance inspection (see 4.3).

4.1.1 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in paragraph 4.4.1 and 4.5.2.

4.2 First article. When specified in the contract, sample shall be subject to first article inspection in accordance with Table II.

4.2.1 Quantity. Inspection shall be performed in accordance with Table II.

4.2.2 Rejection. If any item of the sample fails to comply with the applicable requirements, the first article sample shall be rejected.

4.3 Conformance inspection.

4.3.1 Lot formation. Lot formation shall be in accordance with the lot formation requirement of MIL-STD-1916, paragraph 4.2.

4.3.2 Classification of characteristics.

4.3.2.1. Sampling requirements. Inspection sampling requirements for Critical, Major and Minor characteristics are defined in MIL-STD-1916, Table I and Table II. Critical characteristics shall be addressed in accordance with MIL-STD-1916, Major characteristics shall be Level IV and Minor characteristics shall be II except where indicated.

4.3.2.2. Conformance inspection. Conformance inspection shall be performed in accordance with paragraph 4.3.2.3 through 4.3.2.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

TABLE II. First article inspection

PARAGRAPH	TITLE Container & Components	SHEET 1 OF 2		DRAWING NUMBER SEE BELOW NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Body (dwg. 12900003) Examination for defects Glass content	 30 10	 3.3 3.4.1	 4.3.2.3, Note 1, Cavity 4.5.1.1.1, 4.4.1, Cavity
	Cover (dwg. 12900002) Examination for defects Glass content	 30 10	 3.3 3.4.1	 4.3.2.4, Note 1, Cavity 4.5.1.1.1, 4.4.1, Cavity
	O-ring (dwg. 12900007) Examination for defects	 30	 3.3	 4.4.2.5
	Container assembly) (dwg. 12900000) Examination for defects	 30	 3.3	 4.4.2.6
NOTES: 1. See 4.5.2 for qualification and production control of molded parts.				

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

TABLE II. First article inspection -Continued

PARAGRAPH	TITLE Container & Components	SHEET 2 OF 2		DRAWING NUMBER SEE BELOW
				NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Sequential tests			
	Cover removal torque	30	3.8	4.4.5
	Air pressure test (leak test)	30	3.7	4.4.4, Note 4
	Three foot drop (Note 1)		3.5	4.4.2
	Cold	10		
	Ambient	10		
	Hot	10		
	Air pressure test (Leak test)	30	3.7	4.4.4, Note 3
	Seven foot drop			
	Ambient	10	3.6	4.4.3, Note 2

NOTES: 1. Each container shall be dropped in each of the four orientations as specified in 4.4.2 after temperature conditioning and leak test. The containers shall be evenly distributed for temperature conditioning. 2. Use same ten containers previously dropped at ambient three foot drop. Each container shall be dropped as specified in 4.4.3. 3. Only containers subjected to 3 foot drop test shall be subjected to air pressure test. 4. Use same 30 containers previously tested for cover removal torque.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1		DRAWING NUMBER
4.3.2.3	Body			12900003
				NEXT HIGHER ASSEMBLY 12900000
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA (sample size)	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Outside diameter at each side of o-ring groove	Level IV		Gage, Note 1
102	Shoulder chamfer missing or damaged	Level IV		Visual, Note 1
103	Thread pitch diameter, min.	Level IV		Gage, Note 1
104	Thread major diameter, min.	Level IV		Gage, Note 1
105	Diameter o-ring groove	Level IV		Gage, Note1
106	Width o-ring groove	Level IV		Gage, Note 1
107	Thickness at base	Level IV		Gage, Note 1
108	Inside diameter, min.	Level IV		Gage, Note 1
109	Height of locking recesses, min.	Level IV		Gage, Note 1
110	Length from mouth to locking recesses, min.	Level IV		Gage, Note 1
Minor				
201	Outside diameter	Level II		Gage, Note 1
202	Overall length	Level II		Gage, Note 1
203	Poor workmanship	Level II		Visual, Note 1

NOTES: 1. See 4.5.2 for qualification and production control of molded parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1		DRAWING NUMBER
4.3.2.4	Cover			12900002
				NEXT HIGHER ASSEMBLY 12900000
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Inside diameter, max.	Level IV	3.3	Gage, Note 1
102	Thread pitch diameter, max.	Level IV	3.3	Gage, Note 1
103	Thread minor diameter, max.	Level IV	3.3	Gage, Note 1
104	Height of locking nubs, min	Level IV	3.3	Gage, Note 1
105	Inside depth	Level IV	3.3	Gage, Note 1
Minor				
201	Knurl incomplete or damaged	Level II	3.3	Visual, Note 1
202	Outside diameter, min.	Level II	3.3	Gage, Note 1
203	Poor workmanship	Level II	3.9	Visual, Note 1

NOTES: 1. See 4.5.2 for qualification and production control of molded parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1		DRAWING NUMBER
4.3.2.5	O-Ring			12900007
				NEXT HIGHER ASSEMBLY 12900000
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Inside diameter	Level IV	3.3	Gage
102	Cross-sectional diameter	Level IV	3.3	Gage
Minor				
201	Poor workmanship	Level II	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH 4.3.2.6	TITLE Container Assembly	SHEET 1 OF 1		DRAWING NUMBER 12900000 NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Cover does not thread properly to container body	30	3.3	Visual/Manual, Note 5
102	Parts missing, damaged or incorrectly assembled	30	3.3	Visual, Note 5
103	Sequential tests –			
	Cover removal torque	30	3.8	4.4.5, Note 5
	Air pressure test (leak test)	30	3.7	4.4.4, note 4
	Three foot drop – ambient	10	3.5	4.4.2, Note 1
	- cold	10	3.5	4.4.2, Note 1
	- hot	10	3.5	4.4.2, Note 1
	Air pressure test (leak test)	30	3.7	4.4.4, Note 3
	Seven foot drop - ambient	10	3.6	4.4.3, Note 2
Minor				
201	Poor workmanship	Level II	3.9	Visual, Note 5

NOTES: 1. Each container shall be dropped in each of the four orientations as specified in 4.4.2 after temperature conditioning and leak test. Samples for three foot drop test shall be taken from the above quantity and equally distributed for temperature conditioning. 2. Containers from ambient three foot drop shall be used for ambient seven foot drop. 3. Only containers subjected to 3 foot drop test shall be subjected to air pressure test. 4. Use same containers previously tested for cover removal torque. 5. See 4.5.2 for qualification and production control of molded parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

4.4 Methods of inspection.

4.4.1 Material physical properties. The physical properties of the material samples shall be determined in accordance with Table III.

Table III – Test methods for determining physical properties

Physical property	Test methods
Glass content	ASTM-E794

4.4.2 Three foot drop test. The container shall be conditioned (Hot 160 +/- 5˚F, ambient 70 +/- 5˚F and cold -65 +/- 5˚F) for 24 hours. During the conditioning, individual containers shall be filled with internal cushioning at both ends and inert dunnage representing a signal and dropped, after conditioning, from a height of three feet onto a three inch thick steel plate. Each container shall be dropped in each of the following four orientations: bottom down, side, side 90˚ to previous drop, 45˚ bottom down. The container will be dropped within three (3) minutes of removal from chamber. Observations shall be made for compliance with applicable requirements (Non-destructive test).

4.4.3 Seven foot drop test. The individual containers shall be conditioned and dropped in the orientations specified in paragraph 4.4.2. The drop orientations shall be equally distributed between the containers. The individual containers shall be filled with internal cushioning at both ends and inert dunnage representing a signal and dropped after conditioning, from a height of seven feet onto a three-inch thick steel plate. The container will be dropped within three (3) minutes of removal from chamber. Observations shall be made for compliance with applicable requirements (Non-destructive test).

4.4.4 Air pressure (Leak test). The container shall be immersed in de-aerated water contained in a vacuum chamber. A vacuum differential of at least 3 PSI (6.4 inches of Hg) shall be drawn and held for 30 seconds while observing for air bubbles. A steady stream or recurring stream of air bubbles shall constitute a failure. Dry off outside walls of the container. Check for moisture inside the container (leak in). Use fluorescent dye in water, after test check for moisture/water under black light. (Non-destructive test).

4.4.5 Cover removal torque. The container assembly shall be held in an appropriate fixture so as to prevent rotational movement of the body. A torque shall be applied to the cover until cover movement is observed. The torque at the point of movement shall be observed for compliance with the applicable requirement (Non-destructive test).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

4.4.6 Workmanship. Visually verify that parts and assemblies meet requirements of paragraph 3.9.

4.4.7 Ammunition Lot Numbering. Visually verify that an ammunition lot number has been assigned to each lot as described in MIL-STD-1168.

4.5 Testing. Testing is described in the first article and quality conformance inspection tables.

4.5.1.1 Material properties. There shall be adequate controls to insure that the materials comply with the applicable requirements. If any sample fails to meet the requirements of the lot shall be rejected.

4.5.1.1.1 Glass content. Ten (10) cover and body per cavity per production lot shall be selected at random and tested as specified in 4.4.1. Any sample failing with the applicable requirement stated in 3.4.1 shall be cause for that lot to be rejected. (First Article Only).

4.5.2 Dimensional control of molded plastic parts. To qualify a new or reworked cavity for use in production, a sample of three (3) parts (as molded) from each cavity shall be fully inspected dimensionally after a curing time of 48 hours. This is done in place of normal sampling associated with the classification of defects. As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed in 4.3.2.3 and 4.3.2.4 as applicable after continuous production of 8 hours. Of the three (3) samples, one (1) sample shall be the last part produced. If any defective parts are found when inspection is performed for the control of the cavity, the cavity producing the defective part shall be removed from production. All cavities removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in contract or order (see 6.2). When actual packaging of materiel is to be performed by DOD personnel, these personnel or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point’s packaging activity within the Military Department of Defense Agency, or within the Military Department’s System Command. Packaging data retrieval is available from the managing Military Department or Defense Agency’s automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use on the Container, Ammunition: Hand-Held Pyrotechnic Signal Series.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and, if required, the specific issue of
individual documents referenced (see 2.2.1).

c. Requirements for submission of first article sample.

d. Requirement for submission of inspection equipment designs.

e. Applicable stock number.

f. Packaging requirements, if other than specified in Section 5.

g. Serialization requirements, if applicable.

h. Certificate of conformance for each lot or shipment of product.

6.3 Drawings. Drawings listed in section 2 of this specification under the heading U.S. Army Armament, Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as U.S. Army Armament, Research and Development Command (ARRADCOM), Frankford, Rock Island, or Picatinny drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.4 Submission of inspection equipment designs for approval. Submit equipment designs as required to Commander, ARDEC, ATTN: AMSRD-AAR-QEM-B, Picatinny, NJ 07806-5000. Request letter of submittal should state contractor, contract number, specification number, item nomenclature and classification of defects or test paragraph, inspection equipment, inspection method and the frequency of inspection should be submitted for approval to ARDEC, ATTN: AMSRD-AAR-QEM-B, Picatinny, NJ 07806-5000.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

6.5 Submission of alternative conformance provisions. All contractor proposed alternative conformance provisions will be submitted to the Government for evaluation/approval as directed by the contracting activity. Submit equipment designs as required to Commander, ARDEC, ATTN: AMSRD-AAR-QEM-B, Picatinny, NJ 07806-5000.

6.6 Automated acceptance inspection equipment. Equipment for which no, or minimal, human involvement is required in the acceptance determination. This would include equipment employing probes/sensors/transducers that are automatically manipulated to perform measuring and detection functions. If readout is provided, the equipment will be categorized as automated even if operator interpretation is needed in the accept/reject decision.

6.7 Ammunition lot numbers. Ammunition lot numbers requires ammunition data cards in accordance with MIL-STD-1168.

6.8 Definitions of defects.

6.8.1 Critical. A critical defect is a defect that judgment and experience indicate would result in hazardous or unsafe conditions for individuals using, maintaining, or depending upon the product, or a defect that judgment and experience indicate must be to assure performance of the tactical function of a major end item such as a tank, land vehicle, missile, aircraft, artillery, or other major weapon system.

6.8.2 Major. A major defect is a defect, other than critical, that is likely to result in failure, or to reduce materially the usability of the unit of product for its intended purpose.

6.8.3 Minor. A minor defect is a defect that is not likely to reduce materially the usability of the unit of product for its intended purpose, or is a departure from established standards having little bearing on the effective use or operation of the unit.

6.9 Subject term (key word) listing.

Container Assembly
Cover Assembly
Plastic Container
Process Control

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

6.10 Base Specification The original document MIL-C-70759 dated 27 August 2001 was not published. The specification was issued as an Engineering Change Proposal in Technical Data Packages.

6.11 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army-AR

Preparing activity
Army-AR

(Project 8140-0223)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.