MILITARY SPECIFICATION SHEET

OSCILLATORS, CRYSTAL, TYPE 3 (TEMPERATURE COMPENSATED (TCXO)), 3.2 MHz, SOLDER SEAL, SQUARE WAVE, CMOS

This amendment forms a part of MIL-O-55310/22A, dated 7 August 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Heading, delete "CLASS" and substitute "TYPE."

PAGE 2

Performance, calibration tolerance, delete and substitute "Initial accuracy at reference temperature: ±1 ppm."

PAGE 3

Frequency temperature stability including hysteresis and trim effect, delete and substitute "Initial frequency-temperature accuracy including hysteresis and trim effect: ±3 ppm maximum from -55°C to +85°C and trim range of ±3 ppm."

Frequency-voltage stability, delete "Frequency-voltage stability" and substitute "Frequency-voltage tolerance."

Above frequency-voltage tolerance add "Frequency-temperature slope at reference temperature: ±1 x 10^{-7}/°C maximum between the limits of 21°C ±3°C."

Frequency-load stability, delete "Frequency-load stability" and substitute "Frequency-load tolerance."

PAGE 4

Phase noise, vibration, add "(Group C inspection only)."

Symmetry, delete "Symmetry" and substitute "Duty cycle."

PAGE 5

Frequency aging, last paragraph, last sentence, delete "The least square fit variance of the data from the variance shall not exceed 10% of the total aging change allowed during the test period." and substitute "The square root of the least square fit variance of the data from the function shall not exceed 5 percent of the total change allowed during the test period."

Above vibration (nonoperating), add "Frequency-environment tolerance: ±0.5 ppm."

Vibration (nonoperating), delete "Vibration (nonoperating)" and substitute "Vibration, sinusoidal (nonoperating)."

Vibration (operating), delete "Vibration (operating)" and substitute "Vibration, sinusoidal (operating)."

PAGE 7

Altitude (operating), delete "Altitude" and substitute "Ambient pressure."

Quality assurance provisions, delete quality assurance provisions section in its entirety and substitute "Quality assurance provisions in accordance with MIL-O-55310."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:00Z
Check the source to verify that this is the current version before use.

Following quality assurance provisions add "Screening: In accordance with MIL-O-55310 for class B. Post burn-in electrical test shall consist of the inspections in table II.

TABLE II. Screening electrical tests (post burn-in).

Electrical test	Condition
Output voltage	@ 21°C ±3°C
Input current	@ 21°C ±3°C
Startup time	@ 21°C ±3°C
Initial frequency-temperature accuracy including hysteresis and trim effect	condition 1

PAGE 8

Delete page 8 in its entirety.

PAGE 9

Delete page 9 in its entirety.

PAGE 10

Military part number example, delete "Screening B (see table IV)" and substitute "Product assurance level B".

Military part number example, operating temperature range, delete "B" and substitute "D".

Custodians:
Army - ER
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, MI, SM
Air Force - 99
DLA - ES

User activities:
Navy - AS, CG, MC
Air Force - 19

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5955-0643-17)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:00Z
Check the source to verify that this is the current version before use.