MIL-P-63073A(AR)
AMENDMENT 2
18 May 1983
SUPERSEDING
AMENDMENT 1
18 November 1981

MILITARY SPECIFICATION

PRIMER ELECTRIC, M120
PARTS FOR

This Amendment forms a part of Military Specification MIL-P-63073A(AR), dated 10 January 1980, and is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 14

4.4.2.6: Add the following Major Defect:

"112 Flash hole variation, max (a)" AQL "0.40%", Requirement Paragraph "3.2", Inspection Method "Gage".

NOTES: Add Note "(a) Two holes, minimum shall be checked in each row".

PAGE 18

* 4.4.2.9: Examination or Test Block, Critical Category:

Delete: "None defined".
Delete: Major defect 103 and Major defect 104.
Add: Critical defects 1 and 2:

"1 Pitch diameter of large internal threads, max." AQL or 100% block "100%", Requirement Paragraph "3.2", Inspection Method "Gage".
"2 Minor diameter of large internal threads, max." AQL or 100% block "100%", Requirement Paragraph '3.2", Inspection Method "Gage".

FSC 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:09Z
Check the source to verify that this is the current version before use.

4.4.2.11: Add the following Major Defect:

"112 Flash hole variation, max (a)" AQL "0.40%", Requirement Paragraph "3.2", Inspection Method "Gage".

NOTES: Add Note "(a) Two holes, minimum shall be checked in each row."

* Delete: Major defect 101 and Major defect 102.

* Add: Critical defects 4 and 5:

"4 Pitch diameter of external thread, min." AQL or 100% block "100%", Requirement Paragraph "3.2", Inspection Method "Gage".

"5 Major diameter of external thread, min." AQL or 100% block "100%", Requirement Paragraph "3.2", Inspection Method "Gage".

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A398)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:09Z
Check the source to verify that this is the current version before use.