MIL-W-63377 (AR)
AMENDMENT 1
18 May 1990

MILITARY SPECIFICATION

WARHEAD, ILLUMINATING, M257 W/M442 FUZE (2.75 INCH ROCKET ILLUMINATING FLARE)

This amendment forms a part of Military Specification MIL-W-63377 (AR), dated 29 April 1987, and is approved for use within the U.S. Army Armament, Munitions, and Chemical Command, and is available for use within all Departments and Agencies of the Department of Defense.

PAGE 3

3.4.1, Delete in its entirety and substitute:

"3.4.1, Function Time. The time between rocket motor ignition and flare candle ignition shall be 13.5 ± 2.0 seconds with Mk40 motor and 13.5 ± 2.5 seconds with Mk 66 motor."

Page 5

3.14, Delete "20 pounds is applied to the sear." and substitute, "less than 20 pounds is applied to the pull wire."

3.17, Delete "50 pounds minimum and 75 pounds maximum" and substitute, "40 pounds minimum and 65 pounds maximum".

3.18, Delete "16 g's plus or minus .5 g's" and substitute, "12 to 14 g's".

3.19, Delete "twenty-two (22) g's plus or minus .5 g's" and substitute, "20 to 22 g's".

PAGE 34

4.4.2.16, Delete Major 102 in its entirety.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:45Z
Check the source to verify that this is the current version before use.

PAGE 47

4.5.3.1, Delete "4.3.4" and substitute "4.4.4".

PAGE 51

4.4.2.33, Delete Major 102 in its entirety.

PAGE 53

4.4.2.35, Delete Major 108 in its entirety.

PAGE 61

4.5.7, Delete "20 pounds on the sear." and substitute "less than 20 pounds on the pull wire.".

Delete "10 pounds on the sear." and substitute "less than 10 pounds on the pull wire."

Delete "sear movement or gas generator function." and substitiute "pull wire extraction or gas generator function."

PAGE 62

4.5.10, Delete "16 g's plus or minus .50 g's" and substitute "12 to 14 g's".

Delete, in last sentence, "classed defective." and substitute "classed defective and removed from the lot."

4.5.11, Delete "22 g's plus or minus .50 g's" and substitute "20 to 22 g's".

Delete, in last sentence, "classed defective." and substitute "classed defective and removed from the lot."

4.5.12, Delete, in last sentence, "classed defective." and substitute "classed defective and removed from the lot."

4.5.13, Delete "A rocket motor shall be assembled" and substitute "A rocket motor may be assembled".

PAGE 63

4.5.13, paragraph a, Delete the following:

"This time shall be 13.0 $\pm$ 2.0 seconds or 13.5 $\pm$ 2.0 seconds depending on the type of motor used. (see 3.4.1)."

and substitute the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

"This time shall be 13.5 ± 2.0 seconds or 13.5 ± 2.5 seconds depending on the type of motor used. (see 3.4.1)."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340-A776)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.