Igniter, Mark 247 Mod 0

This amendment forms a part of Military
Specification MIL-I-23062 dated 30 October 1961

Page 4

3.3.1, line 3 - Delete "-75°F and 170°F and substitute "-10°F and 130°F".

line 4 - Delete "-75°F and 170°F and substitute "-10°F and 130°F".

Page 5

* 3.3.9 Delete in its entirety and substitute:

"3.3.9 Pressure Output

3.3.9.1 Maximum Pressure. The maximum pressure output of the igniter when the igniter has been conditioned to a temperature of 70 ± 5 F and fired into a closed bomb chamber of 30 cubic centimeters free volume shall meet the requirements of Table 1.

3.3.9.2 Pressure (30 to 60 milliseconds). The pressure output of the igniter during the period 30 through 60 milliseconds after application of the firing current when the igniter is tested in accordance with 3.3.9.1 shall meet the requirements of Table I."

* 3.3.10 Delete in its entirety and substitute:

"3.3.10 Firing Time

3.3.10.1 Time-to-Pressure Rise. When the igniter is fired under conditions described in 3.3.9, the elapsed time form application of a direct current of 5 amperes until a rise in pressure is first noted shall meet the requirements of Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:23Z
Check the source to verify that this is the current version before use.

3.3.10.2 Time-to-Maximum Pressure. When the igniter is fired under conditions described in 3.3.9, the time from application of a direct current of 5 amperes to the time maximum pressure occurs shall meet the requirements of Table I."

* Add new Table I: "Table I
Functional Requirements

Performance Parameter*	Type of Spec Limit	Spec Limits	
		Minimum	Maximum
Time-to-Pressure Rise, ms	Single	--	15
Maximum Pressure, psig	Double	1600	2400
Time-to-Maximum Pressure, ms	Single	30	--
Pressure (30 - 60 ms), psig	Single	1600	--

*See 6.4 for definition of performance parameters.

3.3.11, line 1 - Delete "-75°F" and substitute "-10°F".

3.3.12, line 2 - Delete "170°F" and substitute "130°F".

3.4, lines 4 and 5 Delete "-65°F to 160°F" and substitute "0°F to 120°F".

Page 6

* In the title - Delete "Table I" and substitute "Table II".

Page 8

* 4.2, last sentence - Delete "Table I" and substitute "Table II".

Page 9

4.3.8, line 2 - Delete "-75°F" and substitute "-10°F".

4.3.9, line 2 - Delete "170°F" and substitute "130°F".

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:23Z
Check the source to verify that this is the current version before use.

* 4.5.2.2.1.4 Delete in its entirety and substitute:

"4.5.2.2.1.4 Pressure Output - Firing Time. Each igniter shall be subjected to the test specified in 4.3.7 and shall function and produce a pressure-time program with performance parameters that meet the requirements of Table I. Acceptability criteria as shown in MIL-STD-414 for an Acceptable Quality Level (AQL) of 1.5 percent shall apply."

Pages 13 through 15

* Delete in their entirety and substitute as follows:

"6. NOTES

6.1 Intended use. The igniter covered by this specification is intended for use as an igniter for the Mark 2 and Mark 3 solid propellant gas generators.

6.2 Ordering data. Procurement documents should specify the following:

6.2.1 Procurement requirements.

(a) Title, number, and date of this specification
(b) Preproduction sample
(c) Lot size
(d) Total quantity of order
(e) That the safety precaution requirements of the Contractor's Safety Manual for Ammunition, Explosives and Related Dangerous Material, DOD 4145.26M, are applicable.

NOTE: When this specification is used as part of of the description of work to be accomplished by a Government activity, the safety precaution requirements of Ammunition Ashore, OP 5, should be made applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:23Z
Check the source to verify that this is the current version before use.

6.2.2 Contract data requirements. Items of deliverable data required by this specification are cited in the following paragraphs herein:

Paragraph	Data Requirement (Short Title)	Applicable DID
4.4		*
6.3		*

DIDs (Data Item Descriptions/DD Forms 1664) for the above data requirements are/will be (*) documented in the applicable ADL (Authorized Data List).

Such data will be delivered as identified on completed (numbered) DIDs when specified on DD Forms 1423 (Contract Data Requirements Lists) and incorporated into applicable contracts

6.2.3 Inspection level. The inspection levels and normal or tightened inspection at the start of the contract shall be determined by the procuring activity.

6.3 Process improvement. Corrective action taken to reduce rejection of component parts during processing shall be included as part of the test report when component parts rejection rate becomes excessive.

6.4 Definitions.

6.4.1 Time-to-pressure rise. Elapsed time from application of firing current until a rise in pressure is first noted on the firing record (expressed in milliseconds).

6.4.2 Maximum pressure. The maximum pressure noted on the firing record when the igniter is tested in accordance with 4.3.4 (expressed in psig).

6.4.3 Time-to-maximum pressure. The elapsed time from application of firing current to the time the maximum pressure is noted on the firing record when the igniter is tested in accordance with 4.3.7 (expressed in milliseconds).

6.4.4 Pressure, 30 to 60 milliseconds. The highest pressure noted on the firing record during the time period 30 through 60 milliseconds after the application of firing current when the igniter is tested in accordance with 4.3.7 (expressed in psig).

Source: https://assist.dla.mil -- Downloaded: 20260-19T15:23Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was doen as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment."

Preparing Activity:

Navy - OS

Project No. 1336-N273

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:23Z
Check the source to verify that this is the current version before use.