INCH-POUND

MIL-C-70998 (AR)
AMENDMENT 2
29 July 1996
SUPERSEDING
AMENDMENT 1
24 September 1993

MILITARY SPECIFICATION

CONTAINER, SHIPPING AND STORAGE, CARTRIDGE, 25MM, PA125
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-C-70998 (AR), dated 18 February 1992, and is approved for use by the US Army Armament, Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.4.1, add the following to end of paragraph:

"The filler pad shall be centrally located to and adhere to cover assembly. The filler pad shall not interfere with operation of gasket 3.5, 3.8. Adhesive material shall not come in contact with gasket material."

* 3.4.1, delete from paragraph:

"The filler pad shall be centrally located to and adhere to cover assembly. The filler pad shall not interfere with operation of gasket 3.5, 3.8. Adhesive material shall not come in contact with gasket material."

PAGE 4

Add new paragraph 3.4.4 as follows:

"3.4.4 Body assembly. Filler pad shall be centrally located to and adhere to body assembly. The filler pad shall not be folded or creased so as to take up more volume at the container bottom than intended for use."

* Delete paragraph 3.4.4 in its entirety.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:18Z
Check the source to verify that this is the current version before use.

PAGE 11

Add new major characteristic 107 to paragraph 4.4.2.2 as follows:

"107.	Filler pad missing, creased, incomplete adhesion, or adhesive visible"	Level II	3.4.4	Visual

* 4.4.2.2, delete major characteristic 107 in its entirety.

PAGE 12

4.4.2.3, characteristic 104:

Delete: "Missing, inverted, loose, misaligned or defective gasket"

Substitute: "Gasket: Missing, inverted, loose, misaligned, exterior spotted from adhesive or defective. Filler pad: Missing, loose, misaligned, adhesive visible or defective."

* 4.4.2.3, characteristic 104:

Delete: "Gasket, Missing, inverted, loose, misaligned, exterior spotted from adhesive or defective. Filler pad: Missing, loose, misaligned, adhesive visible or defective."

Substitute: "Missing, inverted, loose, misaligned or defective gasket."

PAGE 13

4.4.2.4, note 2/: Delete "ferrule" and substitute "handle".

PAGE 16

4.6.2c: Delete in its entirety and substitute the following:

"c. Remove all cover assemblies. Inspect the gasket for fit, security, adhesive, cuts and splits. Filler pad shall not interfere with removal and/or replacement of gasket."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:18Z
Check the source to verify that this is the current version before use.

PAGE 20

6.7: Delete "car" and substitute "care".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 8140-6164)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:18Z
Check the source to verify that this is the current version before use.