MILITARY SPECIFICATION

CHARGE, PROPELLING, M200 FOR 105MM HOWITZER, M204
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-C-48360 (AR) dated 3 July 1980, and is approved for use by the US Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of Department of Defense.

PAGE 1

Title: Delete "M204" and substitute "M119", and wherever it appears in this specification.

PAGE 3

3.4.3 Delete "47,000 PSI" and substitute "46,500 PSI".

3.4.4 Delete in its entirety and substitute new paragraph 3.4.4:

"3.4.4 Muzzle velocity and velocity standard deviation. The muzzle velocity at 70°F temperature shall not be less than 1995 feet per second nor greater than 2045 feet per second and the standard deviation of the lot shall not be greater than 8 feet per second."

PAGE 10

4.4.2.4 Add Critical 1. and Major 105 as follows:

Category	Examination or Test	Req. Para.	Para. Ref.
Critical 1.	Proving Ground		
	Pressure exceeds PIMP at 145°F	3.4.1	4.5.3
Major 105	Proving Ground		
	Muzzle velocity and muzzle velocity standard deviation	3.4.4	4.5.3

AMSC N/A FSC 1315

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:23Z
Check the source to verify that this is the current version before use.

PAGE 15

4.4.3.3.2 Delete paragraph in its entirety and substitute:

Muzzle velocity and muzzle velocity standard deviation. determination of acceptance will be in accordance with MIL-STD-414, Section B, Table B3, AQL of 0.65%. All muzzle velocity and muzzle velocity standard deviation samples will be ballistic tested at 70°F. Fifteen (15) charges will be fired for muzzle velocity and muzzle velocity standard deviation. If the sample is determined unacceptable the lot will be rejected. In addition, if the velocity standard deviation of the sample multiplied by the factor 0.76 exceeds the applicable lot requirement, the lot shall be rejected. Fifteen (15) calibration charges will be fired alternately with the test samples and the muzzle velocity and pressure of all the test charges will be corrected to standard conditions.

PAGE 17

4.5.3.2 Delete "The rounds shall be fired in a M205 cannon which has a tube wear of no greater than 0.015 in. (0.381 MM) when measured 25.25 in. (641.3 MM) from the rear of the tube" and substitute "The rounds shall be fired in a L20A1 tube which has a tube wear of no less than 50% of life remaining".

PAGE 18

6.7 Delete "47,000 PSI" and substitute "46,500 PSI".

Delete "2170 to 2220 FPS" and substitute "1995 to 2045 FPS".

Custodian:
ARMY-AR

Preparing Activity:
ARMY-AR

(Project 1315-A764)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:23Z
Check the source to verify that this is the current version before use.