
MILITARY SPECIFICATION SHEET

CABLES, ELECTRICAL, (FLEXIBLE, FLAT, UNSHIELDED), (ROUND CONDUCTOR), (WIRE SIZE 26, 7/34 or 28, 7/36 STRANDING)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the cables described herein shall consist of this specification and the latest issue of MIL-C-49055.





OPTIONAL CONFIGURATION

INCHES	MM
.003	.08
.007	.18
.015	.38
.025	.64
.035	.89
.050	1.27

NOTES:
1. Dimensions are in inches.
(B) 2. All undimensional pictorial representations are for reference purposes only.
3. Cable marking shall be placed along reference edge of cable.
4. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.

FIGURE 1. Round conductor flat cable.

(B) denotes changes.

FSC 6145

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:45Z
Check the source to verify that this is the current version before use.

(B) TABLE I. Dash numbers and characteristics.

Dash number	Number of conductors "N"	Cable width "A"	Weight (lbs/1,000 ft) Nom 1/	Weight (lbs/1,000 ft) Max	AWG	Dia "C" inches ±.003	Dia "D"	Stranding	End conductor to end conductor "B"
01	9	0.450 ±0.010	10.3	11.7	28	.035	0.015	7/36	0.400 ±0.010
02	10	0.500 ±0.010	11.4	13.0	"	"	"	"	0.450 ±0.010
03	14	0.700 ±0.010	16.0	18.2	"	"	"	"	0.650 ±0.010
04	15	0.750 ±0.010	17.1	19.5	"	"	"	"	0.700 ±0.010
05	16	0.800 ±0.015	18.3	20.9	"	"	"	"	0.750 ±0.011
06	20	1.000 ±0.015	22.9	26.1	"	"	"	"	0.950 ±0.011
07	24	1.200 ±0.015	27.4	31.2	"	"	"	"	1.150 ±0.011
08	25	1.250 ±0.015	28.5	32.5	"	"	"	"	1.200 ±0.011
09	26	1.300 ±0.015	29.7	33.9	"	"	"	"	1.250 ±0.011
10	34	1.700 ±0.020	38.9	44.3	"	"	"	"	1.650 ±0.015
11	37	1.850 ±0.020	42.2	48.1	"	"	"	"	1.800 ±0.015
12	40	2.000 ±0.020	45.7	52.1	"	"	"	"	1.950 ±0.015
13	50	2.500 ±0.020	57.2	65.2	"	"	"	"	2.450 ±0.015
14	60	3.000 ±0.020	68.6	78.2	"	"	"	"	2.950 ±0.015
15	64	3.200 ±0.020	73.2	83.4	"	"	"	"	3.150 ±0.015
16	9	0.450 ±.010	14.4	16.4	26	.039	.019	7/34	0.400 ±0.010
17	10	0.500 ±.010	16.0	18.2	"	"	"	"	0.450 ±0.010
18	14	0.700 ±.010	22.4	25.5	"	"	"	"	0.650 ±0.010
19	15	0.750 ±.010	24.0	27.3	"	"	"	"	0.700 ±0.010
20	16	0.800 ±.015	25.6	29.2	"	"	"	"	0.750 ±0.011
21	20	1.000 ±.015	32.0	36.5	"	"	"	"	0.950 ±0.011
22	24	1.200 ±.015	38.4	43.8	"	"	"	"	1.150 ±0.011
23	25	1.250 ±.015	40.0	45.6	"	"	"	"	1.200 ±0.011
24	26	1.300 ±.015	41.6	47.4	"	"	"	"	1.250 ±0.011
25	34	1.700 ±.020	54.4	62.0	"	"	"	"	1.650 ±0.015
26	37	1.850 ±.020	59.2	67.5	"	"	"	"	1.800 ±0.015
27	40	2.000 ±.020	64.0	73.0	"	"	"	"	1.950 ±0.015
28	50	2.500 ±.020	80.0	91.2	"	"	"	"	2.450 ±0.015
29	60	3.000 ±.020	96.0	109.4	"	"	"	"	2.950 ±0.015
30	64	3.200 ±.020	102.4	116.7	"	"	"	"	3.150 ±0.015

1/ Nominal values are for information only, not requirements.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and table I.

Insulation material: In accordance with MIL-C-49055.

Voltage rating: 300 volts rms at sea level.

Conductor coating: Tin.

(B) Conductor stranding: Size 26, 7/34 or 28, 7/36 stranding.

Weight: See table I.

Insulation flaws: 2,500 volts rms.

Dielectric withstanding voltage: 2,000 volts rms.

Insulation resistance: 500 megohms-1,000 feet (minimum).

(B) Conductor resistance: 69.0 ohms maximum/1,000 feet at 23°C.

Thermal shock: -55° ±5°C; +105° ±5°C, shrinkage 0.0625-inch maximum either end.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:45Z
Check the source to verify that this is the current version before use.

(B) Flexing endurance: -20° ±5°C; +105° ±5°C, 50 cycles.

Moisture resistance:

Insulation resistance: 50 megohms-1,000 feet (minimum).

Low pressure (elevated temperature): +105°C (maximum conductor temperature).

Color: Optional.

Part number: M49055/1-(dash number from table I followed by material designator from MIL-C-49055).

Custodians:
Army - CR
Navy - AS
Air Force - 85

Review activities:
Army - AV, MI, AR
Navy - EC, OS, SH
Air Force - 11, 17, 99
DLA - IS, ES
NSA -
NAS -
NASA - MSFC

User activities:
Army - ME, AT
Navy - MC

Agent:
DLA - ES

Preparing activity:
Army - CR

(Project 6145-0827-1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:45Z
Check the source to verify that this is the current version before use.