INCH-POUND
MIL-PRF-3098/42J
9 December 2004
SUPERSEDING
MIL-PRF-3098/42H
27 August 1997

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR64/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-3098.

Pertinent characteristics: 2.4 MHz to 20 MHz; fundamental; noncontrolled; antiresonance.



Inches	mm	Inches	mm
.001	0.03	.192	4.88
.002	0.05	.402	10.21
.008	0.20	.435	11.05
.017	0.43	.500	12.70
.150	3.81	.530	13.46
.183	4.65		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Crystal unit - CR64/U.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:29Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 2.4 MHz to 20 MHz, inclusive.

Frequency tolerance:

Operating temperature range: ±50 parts per million (ppm).

Antiresesonace, load capacitance: 30.0 pF ±0.5 pF.

Equivalent resistance: See table I.

Operating temperature range (noncontrolled): -55°C to +105°C, inclusive.

Mode of oscillation: Fundamental.

Rated drive level: 1.0 mW, maximum.

Capacitance, shunt: 2.4 MHz to 4.0 MHz - 1.7 pF min. to 7.0 pF max.
4.0 MHz to 6.0 MHz - 2.7 pF min. to 7.0 pF max.
6.0 MHz to 20.0 MHz - 3.7 pF min. to 7.0 pF max.

Shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Vibration: Method 204 of MIL-STD-202, test condition A.

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Thermal shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Aging:

Frequency change permitted: ±5 ppm.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:29Z
Check the source to verify that this is the current version before use.

TABLE I. Equivalent resistance.

Frequency range, inclusive	Maximum resistance
MHz	Ohms
2.40 to 2.60	300
2.61+ to 2.89	250
2.90+ to 3.75	180
3.75+ to 4.75	120
4.75+ to 6.00	75
6.00+ to 7.00	50
7.00+ to 10.00	30
10.00+ to 20.00	25

* Reference documents. In addition to MIL-PRF-3098, this document references the following:

MIL-STD-202

* The margins of this specification sheet are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR, MI, SM
Navy - AS, CG, MC, OS, SH
Air Force – 19, 99

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5955-0777)

* NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:29Z
Check the source to verify that this is the current version before use.