INCH-POUND
MIL-PRF-3098/45K
w/AMENDMENT 1
22 January 2020
SUPERSEDING
MIL-PRF-3098/45K
13 April 2010

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR67/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-3098.

Pertinent characteristics: 17 MHz to 62 MHz; third mechanical overtone; noncontrolled; series resonance.




FIGURE 1. Crystal unit - CR67/U.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:30Z
Check the source to verify that this is the current version before use.

Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.183	---	4.65
B	---	.435	---	11.05
C	---	.402	---	10.21
D	---	.530	---	13.46
E	.500	---	12.70	---
F	.016	.019	0.41	0.48
G	---	.150	---	3.81
H	.184	.200	4.67	5.08

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Crystal unit - CR67/U - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:30Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions, marking, and configuration: See figure 1.

Frequency range: 17 MHz to 62 MHz, inclusive.

Capacitance, shunt: 7 pF, maximum.

Mode of oscillation: Third mechanical overtone.

Rated drive level: 1.0 mW, maximum.

Resonance: Series.

Calibration values:

Resistance: 40 ohms.

Resistor voltage drop: 0.28 volt.

Operating temperature range (noncontrolled): -55°C to +105°C, inclusive.

Frequency tolerance: ±25 parts per million (ppm).

Equivalent resistance: 40 ohms, maximum.

Shock:

Frequency change permitted: ± 5 ppm.

Equivalent resistance change permitted: ±10 percent.

Vibration: MIL-STD-202-204, test condition A.

Frequency change permitted: ± 5 ppm.

Equivalent resistance change permitted: ±10 percent.

Thermal shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Aging:

Frequency change permitted: ±5 ppm.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:30Z
Check the source to verify that this is the current version before use.

Part or Identifying Number (PIN): CR67/U (followed by specified frequency), see 1.2 of MIL-PRF-3098.

Referenced documents. In addition to MIL-PRF-3098, this document references the following:

MIL-STD-202-204

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy - EC
Air force - 85
DLA - CC

Review activities:
Army - AR, MI, SM
Navy - AS, CG, MC, OS, SH
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5955-2020-009)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:30Z
Check the source to verify that this is the current version before use.