FED. SUP CLASS
9510




TABLE I. DASH NUMBERS.

DASH NO	A	HEAT TREATMENT	FORMING PROCESS (SEE REQT 3)	ADDITIONAL REQT (SEE REQT 4)	DASH NO	A	HEAT TREATMENT	FORMING PROCESS (SEE REQT 3)	ADDITIONAL REQT (SEE REQT 4)
001	.375	ANNEALED	H	po or sb	049	.625	ANNEALED	H	
003	.375	HARDENED AND TEMPERED	H		051	.675	ANNEALED	H	
005	.375	NORMALIZED	H		053	.688	HARDENED AND TEMPERED	H	
007	.375	NORMALIZED AND TEMPERED	H		055	.688	NORMALIZED AND TEMPERED	H	
009	.375	ANNEALED	H		057	.688	NORMALIZED	H	
011	.437	ANNEALED	H		059	.750	ANNEALED	H	po or sb
013	.437	HARDENED AND TEMPERED	H		061	.750	NORMALIZED	C	
015	.437	NORMALIZED	H		063	.750	NORMALIZED AND TEMPERED	C	
017	.437	ANNEALED	H	rt	065	.750	HARDENED AND TEMPERED	H	
019	.437	AS FORGED	H		067	.750	ANNEALED	H	
021	.500	ANNEALED	H	po or sb	069	.813	HARDENED AND TEMPERED	H	po or sb
023	.500	NORMALIZED AND TEMPERED	H		071	.813	NORMALIZED	H	
025	.500	HARDENED AND TEMPERED	H		073	.875	ANNEALED	H	po or sb
027	.500	NORMALIZED	H	sb	075	.875	NORMALIZED	H	
029	.500	NORMALIZED	C		077	.875	HARDENED AND TEMPERED	H	
031	.500	ANNEALED	H		079	.875	AS FORGED	H	
033	.563	ANNEALED	H	po or sb	081	.875	ANNEALED	H	
035	.563	HARDENED AND TEMPERED	H		083	.938	NORMALIZED	H	
037	.563	NORMALIZED	H	sb	085	.938	ANNEALED	H	
039	.563	NORMALIZED AND TEMPERED	H		087	1.000	ANNEALED	H	po
041	.563	ANNEALED	H		089	1.000	ANNEALED	H	
043	.625	ANNEALED	H	po or sb	091	1.000	NORMALIZED AND TEMPERED	H	
045	.625	NORMALIZED	H		093	1.000	NORMALIZED	C	
047	.625	HARDENED AND TEMPERED	H		095	1.000	HARDENED AND TEMPERED	H	

APPROVED 9 October 1984 REVISED

USER ACTIVITIES:
NAVY - MC, OS

REVIEWER ACTIVITIES:
AIR FORCE - 84
DLA - IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
AS		BAR, METAL, ROUND, ALLOY STEEL 4130 CHROME - MOLYBDENUM (AIRCRAFT QUALITY)	MS14294
Other Cust MR 99			
PROCUREMENT SPECIFICATION: MIL-S-6758	SUPERSEDES:		PAGE 1 OF 3

DD FORM 1 MAY 73 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 9510-0420

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:39Z
Check the source to verify that this is the current version before use.

TABLE I. DASH NUMBERS. - CONTINUED

DASH NO	A	HEAT TREATMENT	FORMING PROCESS (SEE REQT 3)	ADDITIONAL REQT (SEE REQT 4)
097	1.000	AS FORGED	H	
099	1.063	NORMALIZED AND TEMPERED	H	
101	1.063	ANNEALED	H	
103	1.188	NORMALIZED AND TEMPERED	H	
105	1.125	ANNEALED	H	
107	1.125	ANNEALED	H	po or sb
109	1.125	HARDENED AND TEMPERED	H	
111	1.125	NORMALIZED	H	
113	1.125	NORMALIZED AND TEMPERED	H	
115	1.250	ANNEALED	H	
117	1.250	ANNEALED	H	po or sb
119	1.250	NORMALIZED	C	
121	1.250	NORMALIZED AND TEMPERED	H	
123	1.250	HARDENED AND TEMPERED	H	
125	1.313	NORMALIZED AND TEMPERED	H	
127	1.313	ANNEALED	H	
129	1.375	ANNEALED	H	
131	1.375	ANNEALED	H	po or sb
133	1.375	NORMALIZED AND TEMPERED	H	
135	1.375	HARDENED AND TEMPERED	H	
137	1.375	NORMALIZED	H	
139	1.438	NORMALIZED	H	
141	1.500	ANNEALED	H	po or sb
143	1.500	ANNEALED	H	
145	1.500	NORMALIZED AND TEMPERED	H	
147	1.500	NORMALIZED	H	
151	1.500	NORMALIZED	H	rt
153	1.500	HARDENED AND TEMPERED	H	
155	1.563	ANNEALED	H	
157	1.625	ANNEALED	H	
159	1.750	ANNEALED	H	po or sb
161	1.750	NORMALIZED AND TEMPERED	H	po
163	1.750	ANNEALED	H	
165	1.750	NORMALIZED	H	
167	1.875	ANNEALED	H	
169	1.875	NORMALIZED AND TEMPERED	H	po or sb
171	1.875	NORMALIZED	H	
173	2.000	ANNEALED	H	
175	2.000	ANNEALED	H	po or sb
177	2.000	NORMALIZED	C	
179	2.000	NORMALIZED	H	po or sb
181	2.250	NORMALIZED	H	po or sb
183	2.500	ANNEALED	H	po or sb
185	2.500	ANNEALED	H	
187	2.500	NORMALIZED	H	
189	2.500	NORMALIZED	H	rt
191	2.500	NORMALIZED	H	po or sb
193	2.750	NORMALIZED	H	po
195	3.000	ANNEALED	H	po or sb
197	3.000	NORMALIZED	C	
199	3.000	NORMALIZED	H	po
201	3.000	NORMALIZED	H	sb
203	3.250	NORMALIZED	H	
205	3.500	ANNEALED	H	
207	3.500	NORMALIZED	H	po or sb
209	4.000	ANNEALED	H	
211	4.000	ANNEALED	H	po or sb
213	4.000	NORMALIZED	H	po or sb
215	4.500	NORMALIZED	H	
217	5.000	ANNEALED	C	st
219	5.000	NORMALIZED	H	
221	5.500	NORMALIZED	C	
223	5.500	NORMALIZED	H	
225	6.000	ANNEALED	H	
227	6.000	NORMALIZED	H	
229	6.000	ANNEALED	C	st
231	7.000	ANNEALED	H	st
233	8.000	ANNEALED	H	
235	8.000	NORMALIZED	H	
237	8.000	ANNEALED	H	rt

APPROVED 9 October 1984 REVISED

USER ACTIVITIES:
NAVY-MC,OS

REVIEWER ACTIVITIES:
AIR FORCE-84
DLA-IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:39Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
9510

REQUIREMENTS:

1. MATERIAL. ALLOY STEEL 4130 (UNS G41300), AS SPECIFIED IN PROCUREMENT DOCUMENT.


2. LENGTH. STANDARD LENGTH OF ROUND BAR IS 10 FEET MINIMUM, 12 FEET MAXIMUM.

3. FORMING PROCESS. COLD DRAWN - CODE "C"
HOT ROLLED - CODE "H"

4. ADDITIONAL REQUIREMENTS. PICKLED OVERALL - CODE "po"
SANDBLASTED OVERALL - CODE "sb"
SMOOTH TURNED OVERALL - CODE "st"
ROUGH TURNED OVERALL - CODE "rt"

5. PART NUMBER. THE PART NUMBER CONSISTS OF THE BASIC MS NUMBER, PLUS A FORMING PROCESS CODE, PLUS A DASH NUMBER FROM TABLE I.

EXAMPLE: MS14294H001



6. MARKING. IRON AND STEEL PRODUCTS SHALL BE MARKED IN ACCORDANCE WITH FED-STD-183 WITH THE EXCEPTION THAT A PART NUMBER FROM THIS MILITARY STANDARD SHALL BE INCLUDED AS PART OF THE IDENTIFICATION MARKING.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.

2. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS, OR REQUEST FOR PROPOSAL, EXCEPT THE REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.

3. FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

APPROVED 9 October 1984 REVISED

USER ACTIVITIES:
NAVY - MC, OS

REVIEWER ACTIVITIES:
AIR FORCE - 84
DLA - IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
AS (Other Cust MR 99)		BAR, METAL, ROUND, ALLOY STEEL 4130 CHROME-MOLYBDENUM (AIRCRAFT QUALITY)	MS14294
PROCUREMENT SPECIFICATION: MIL-S-6758	SUPERSEDES:		PAGE 3 OF 3

DD FORM 1 MAY 73 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 9510-0420

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:39Z
Check the source to verify that this is the current version before use.