INCH-POUND

MIL-C-71165 (AR)
AMENDMENT 1
23 October 1996

MILITARY SPECIFICATION

CONTAINER, AMMUNITION, LIGHTWEIGHT METAL FOR TOW 2A GUIDED MISSILE, SURFACE ATTACK: BGM - 71E - 5B WEAPON SYSTEM

This amendment forms a part of Military Specification MIL-C-71165 (AR) , dated 15 June 1993 and is approved for use by the U.S. Army Armament Research, Development and Engineering Center (ARDEC), and is available for use by all Departments and Agencies of the Department of Defense.

Page 4

3.6.1 Delete paragraph in its entirety and substitute with the following new paragraph:

"3.6.1 Air pressure of unpainted cover assembly The unpainted cover assembly shall withstand an internal air pressure of three psi for five (5) seconds minimum. Bubbles, other than surface bubble shall cause rejection."

3.6.2 Delete paragraph in its entirety and substitute with the following new paragraph:

"3.6.2 Air pressure of unpainted body assembly The unpainted body assembly shall withstand an internal air pressure of three psi for five (5) seconds minimum. Bubbles, other than surface bubble shall cause rejection."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:25Z
Check the source to verify that this is the current version before use.

PAGE 7

TABLE I - First article inspection

Assemblies and components, change paragraph as follows:

"EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH
Container assemblies, painted (Dwg. 12953476 as applicable)		
Examination for defects	5	3.2
Air pressure	10	3.6
Painted surface 1/	3	3.4"

Page 11

4.4.2.1 Spring Clip, Hairpin, delete Major 102 "Radius of bend" and Major 103 "Length from end to lower edge of bend" in their entireties and change paragraph as follows:

"Major				
101	Diameter of coil	Level III	3.2	Gage
104	Diameter of spring wire	Level VI	3.2	Gage"

PAGE 12

4.4.2.2 Support, Shaft, change paragraph as follows:

"Major				
106	Material thickness	Level VI	3.8	Gage"

Delete Major 104 "True position of holes located on side (used for assembly of spring and clamp)" in its entirety

PAGE 13

4.4.2.3 Handle, Square, change paragraph as follows:

"Major				
105	Material thickness	Level V	3.8	Visual"

Delete Major 103 "Width of spring slot" and Major 104 "Length of spring slot (DIM B)" in their entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:25Z
Check the source to verify that this is the current version before use.

PAGE 17

4.4.2.7 cover, change paragraph as follows:

"Major
106 Material thickness Level VI 3.2 Visual"

PAGE 20

4.4.2.10 cover Assembly, Prior to painting, change as follows:

Delete Major 102 "Component missing or inadequately assembled" In its entirety.

PAGE 21

4.4.2.11 cover Assembly, Painted, add Major 102 as follows:

"Major
102 Component missing or inadequately assembled Level III 3.2 Visual"

PAGE 24

4.4.2.14 body, delete Major 102 "Inside diameter, min. 1/" and change paragraph as follows:

"Major
104 Material thickness Level VI 3.2 Gage"

Add Note 1/ as follows: Major 103 can be checked on body weldment Dwg. 12944493

Page 26

4.4.2.16 body Assembly (Weldment), change paragraph as follows:

"Major
104 Inside diameter of body after painting, min. Level VI 3.2 Gage"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:25Z
Check the source to verify that this is the current version before use.

Page 28

Delete paragraph 4.4.3.2 in its entirety and replace with the following:

"4.4.3.2 Weld strength of rim to body (see Dwg. 12944480),Major defect. During the first half of a production shift and during the last half of a production shift, a body assembly shall be randomly selected for this test. If any body assembly fails to meet the requirement when tested in accordance with 4.5.2, the quantity of body assemblies which were welded during this shift between this weld strength test and the earlier weld strength test and (if applicable) shall be rejected."

Page 29

Delete paragraph 4.5.2 in its entirety and replace with the following:

"4.5.2 Weld strength of rim to body. The strength of the weld shall be determined through a longitudinal force test per Dwg. 12944493.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 8140 - 0170)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:25Z
Check the source to verify that this is the current version before use.