INCH-POUND

MIL-C-48683A (AR)
AMENDMENT 1
30 March 1990

MILITARY SPECIFICATION

CARTRIDGE, 40mm, M918 TP; PROJECTILE ASSEMBLY

This Amendment forms a part of Military Specification MIL-C-48683A (AR), dated 26 October 1987, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Add to 3.4:

" For 1,000 meter test, sound and smoke or sound and flash are also acceptable."

PAGE 5

4.3.1 Change:

From:	" Body Assembly	9399402	50"
To:	" Body Assembly (prior to painting)	9399402	25
	Body Assembly (after Painting)	9399402	25"

PAGE 8

Add to Projectile Assembly (Dwg. 9399374) under functioning:

" Petalling (missing petals), 200 5/, 1-2 6/, 3.4 4.5.6, 4.5.6.2, 4.5.6.3
Petalling (blown case), 200 5/ 0-1, 3.4, 4.5.6, 4.5.6.2, 4.5.6.3" .

Add Note 5/:

" 5/ Projectiles fired in 135 to 200 feet and rapid fire tests shall be recovered and inspected for missing petals and blown bases."

Add Note 6/:

" 6/ One defect consists of one or more missing petals per projectile."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

Table I Change,

From: " Body Assembly (Dwg. 9399402)

Examination for defects	50	3.2	4.4.2.12, 4.4.2.13
Salt Spray	4	3.2	4.5.2.2
Push test of rotating band	50	3.2	4.5.9"

To: " Body Assembly (prior to painting) (Dwg. 9399402)

Examination for defects	25	3.2	4.4.2.12
Body Assembly (after painting) (Dwg. 9399402)	25	3.2	4.5.2.13
Salt Spray	4	3.2	4.5.2.2
Push test of rotating band	50	3.2	4.5.9"

Add to Note 1:

" For 1,000 meter test, sound and smoke or sound and flash are also acceptable."

PAGE 13

Add Major 110

" 110. Missing or improperly placed groove, .40, 3.2 Visual" .

PAGE 15

Add new paragraph 4.4.2.6.1 as included Page 15a.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
4.4.2.6.1	Spring, Anti-Creep (alternate)				9399408
					NEXT HIGHER ASSEMBLY
					9399390
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined				
MAJOR					
101.	Load Test	125	Acc-1 Rej-2		4.5.3
102.	Length		.40		Gage
103.	Outer diameter		.40		Gage
MINOR					
201.	Poor workmanship		.65		Visual

NOTES:

AMSMC Form 1570a, 1 Apr 85 Replaces DRDAR-QA Form 160a, 1 Jun 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

PAGE 17

4.4.2.8, Change from " 201" to " 201"
202 202
202 203
201 204

PAGE 20

4.4.2.11, Major 104 and Major 106, Delete in their entirety.

4.4.2.11, Minor 205, Delete in its entirety.

4.4.2.11, Delete Major 107 in its entirety.

4.4.2.11, Major 108, Delete " Total"

4.4.2.11, Change From: " Thickness of groove (6) in base"
To: " Thickness below groove (6) in base"

PAGE 21

Add to 4.4.2.12:

" 105. Runout of indicated point of taper with outside large diameter .40, 3.2, Gage/9399396

106. Location, large diameter on taper, .40, 3.2, Gage/9399396".

PAGE 22

Add Major 104:

"104. Missing or improperly placed markings, .40, 3.2, Visual".

PAGE 23

Add to 4.4.2.14:

"108. Petalling (missing petals), 50 5/, 1-2 6/, 3-4, 4.5.6, 4.5.6.2
109. Petalling (blown base), 50 5/, 1-0, 3.4, 4.5.6, 4.5.6.2"

Add Note 5/

"5/ Projectiles fired in 135 to 200 feet and rapid fire tests shall be recovered and inspected for missing petals and blown bases.".

Add Note 6/

" 6/ One defect consists of one or more missing petals per projectile."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

4.4.2.14,
Major 106, delete " Rapid fire test, 150 to 656.2 feet (200 meters) 50 0-1 4. 3.4 4.5.6, 4.5.6.3"

Critical 6, change,
From: " 244"
To: " 194"

Critical 6, Delete " 4.5.6.3"

Major 107, Change,

From: " 244"
To: " 194"

Major 107, Delete " 4.5.6.3" .

PAGE 24

4.4.2.14:

Note 2/ Delete " and rapid fire tests."

Add:

" 202. Marking missing, improper or illegible, .65 3.2 Visual" .

Add to note 4: " For 1,000 meter test, sound and smoke to, sound and flash are also acceptable."

In note 5, delete: " and rapid fire test"

PAGE 31

4.4.2.2, Delete in its entirety.

PAGE 32

4.5.3 Delete: " Dwg 9399390" and substitute " Dwg. 9399395" .

4.5.6, change

From: " MK 19 MOD III Grenade Machine Gun"
TO: " weapon"

4.5.6.1, Delete " linked" from paragraph. (3 times)

Add to end of paragraph: " All tests performed shall be observed from the gun position."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

4.5.6.1, Delete " linked" from paragraph.

Change
From: " Machine gun"
To: " weapon"

4.5.6.2, Delete " linked" from paragraph.

Change
From: " Machine gun"
To: " weapon"

4.5.6.3, Change

From: " Machine gun"
To: " MK 19 MOD III Grenade Machine Gun"

Add to end of paragraph: " This test shall be performed at an approved government installation."

Custodian
(Army-PA)

Preparing activity:
Army-PA

(Project 1310-A435)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.