INCH-POUND

MIL-DTL-55302/158C
9 March 2005
SUPERSEDING
MIL-C-55302/158B
1 June 1993

DETAIL SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLE SOCKET CONTACTS, 64 OR 96 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.100 INCH SPACING)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-55302.





FIGURE 1. Connector, receptacle, .100 (2.54 mm) spacing.


AMSC N/A

FSC 5935


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.



DETAIL "A"




DETAIL "B"




DETAIL "C" OPTIONAL DESIGNS FOR PRINTED CIRCUIT TAILS

FIGURE 1. Connector, receptacle, .100 (2.54 mm) spacing – Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.



VIEW FROM TERMINATION END CONNECTOR MARKING



RECOMMENDED MOUNTING PATTERN 64 CONTACTS



RECOMMENDED MOUNTING PATTERN 96 CONTACTS

FIGURE 1. Connector, receptacle, .100 (2.54 mm) spacing – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

Dash number M55302/158-	Number of contacts	Type of termination
01	96	Printed circuit tails 1/
02	64	Printed circuit tails 2/ 1/


1/ Solder contact suitable for .062 or .093 thick printed wiring boards.
2/ These connectors have middle row (row B) of contacts excluded.

Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
.002	.05	.020	.51	.047	1.19	.110	2.79	.400	10.16
.004	.10	.022	.56	.054	1.37	.122	3.10	.418	10.62
.005	.13	.024	.61	.063	1.60	.200	5.08	.735	18.67
.006	.15	.025	.64	.066	1.68	.209	5.31	3.100	78.74
.008	.20	.031	.79	.083	2.11	.236	6.00	3.342	84.89
.010	.25	.035	.89	.100	2.54	.260	6.60	3.500	88.90
.015	.38	.040	1.02	.102	2.59	.335	8.51	3.701	94.01
.017	.43	.041	1.04	.104	2.64				


NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ± .005 (.13 mm).
4. These connectors mate with connectors specified in MIL-C-55302/157.
5. Clearance must be provided around the top of the mounting hole for 2.5 mm hex nut.
6. Slots, openings, indentations etc. that fall within the envelope dimensions and which do not affect form, fit or function are acceptable providing they do not prevent intermateability and are not used for polarizing purposes in military applications.

FIGURE 1. Connector, receptacle, .100 (2.54 mm) spacing – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.



TEST PIN A




TEST PIN B

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ± .008 (0.20 mm) on decimals and 2° on angles.

FIGURE 2. Test pins.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.



Inches	mm
.020	0.51
.040	1.02

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.

FIGURE 3. Contact plating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Design and construction:

Dimensions and configuration: See figure 1, 2, and 3.

Material and finish:

Contact plating: The plating in the contact area shall be gold in accordance with ASTM B488, type II, code C or D, class 1 over nickel plating in accordance with SAE-AMS-QQ-N-290, 30 to 150 microinches. The contact mating area is defined on figure 3.

Nonfunctional area: Any portion of the contact other than the contact mating area or termination area can be plated in accordance with MIL-DTL-55302.

Contact identification: See figure 1.

Body design: The insulator body of each receptacle may be two-piece construction secured by mechanical means.

Contact separation force: Separation force shall be .5 ounce minimum, using the following test pins:

1. Insert and withdraw test pin A (see figure 2).
2. Insert test pin B (see figure 2) fully and withdraw test pin B .071 inch and then measure separation force.

Mating and unmating: The maximum mating force, in pounds, shall not exceed a value equal to 0.25 times the number of contacts, and the withdrawal force, in pounds, shall be a minimum of 0.025 times the number of contacts and shall not exceed the measured insertion force, when the housing is loaded with contacts and mated with connector in accordance with MIL-C-55302/157.

Contact rating: 3.0 amperes maximum per contact.

Contact resistance: No individual contact pair shall have a resistance exceeding .020 ohm.

Contact retention: 3 pounds minimum per contact.

Dielectric withstanding voltage:

Sea level: 1,000 volts rms, 50 or 60 hertz.

High altitude: 300 volts rms, 50 or 60 hertz.

Part or Identifying Number (PIN): M55302/158- (dash number from figure 1).

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-DTL-55302, this document references the following:

MIL-DTL-55302/157
ASTM B488
SAE-AMS-QQ-N-290
MIL-DTL-55302/131

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-4503-000)

Review activities:
Army – AR, AT, AV, CR4, MI
Navy – AS, MC, OS, SH
Air Force – 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:53Z
Check the source to verify that this is the current version before use.