INCH-POUND
MIL-D-52987A(ME)
17 May 1989
SUPERSEDING
MIL-D-52987(ME)
30 December 1980

MILITARY SPECIFICATION

# DISTRIBUTOR, WATER, SELF-PROPELLED; MINIMUM 2500 GALLON, SECTIONALIZED, AND NON-SECTIONALIZED

This specification is approved for use within the USA Belvoir Research, Development and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification covers a commercial water distributor of the articulated, tractor-tanker type equipped with a diesel engine, a power-shift transmission, and off-the-road earthmover tires on 2-axles. The distributor will self-load, transport, and evenly distribute a minimum of 2500 gallons of water.

1.2 Classification. The distributor should be of the following types, as specified (see 6.2):

Type I - Non-sectionalized (air transportable and airdroppable).
Type II - Sectionalized (air transportable, airdroppable, and helicopter transportable).

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (See 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA, Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3825
DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

| | |
|---|---|
| A-A-1108 | - Extinguisher, Fire, Vaporizing Liquid. |
| VV-F-800 | - Fuel Oil, Diesel. |

MILITARY

| | |
|---|---|
| MIL-V-173 | - Varnish, Moisture- and Fungus-Resistant (for Treatment of Communications, Electronic, and Associated Equipment). |
| MIL-P-514 | - Plates, Identification, Instruction, and Marking, Blank. |
| MIL-T-704 | - Treatment and Painting of Materiel. |
| MIL-D-771 | - Distributors, Bitumen and Water, Packaging of. |
| MIL-C-1283 | - Can, Gasoline, Military, 5-Gallon. |
| MIL-L-2104 | - Lubricating Oil, Internal Combustion Engine Tactical Service. |
| MIL-L-2105 | - Lubricating Oil, Gear, Multipurpose. |
| MIL-M-7866 | - Molybdenum Disulfide, Technical, Lubrication Grade. |
| MIL-G-10924 | - Grease, Automotive and Artillery. |
| MIL-P-14105 | - Paint, Heat Resisting (for steel surface). |
| MIL-G-23827 | - Grease, Aircraft and Instrument, Gear and Actuator Screw. |
| MIL-A-46153 | - Antifreeze, Ethylene Glycol, Inhibited, Heavy Duty, Single Package. |
| MIL-L-46167 | - Lubricating Oil, Internal Combustion Engine, Arctic. |
| MIL-C-46168 | - Coating, Aliphatic Polyurethane, Chemical Agent Resistant. |
| MIL-B-46176 | - Brake Fluid, Silicone, Automotive, All Weather, Operational and Preservative. |
| MIL-T-83133 | - Turbine Fuel, Aviation Kerosene Type, Grade JP-8. |

STANDARDS

MILITARY

| | |
|---|---|
| MIL-STD-129 | - Marking for Shipment and Storage. |
| MIL-STD-130 | - Identification Marking of U.S. Military Property. |
| MIL-STD-209 | - Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment. |
| MIL-STD-669 | - Loading Environment and Related Requirements for Platform Rigged Airdrop Material. |
| MIL-STD-810 | - Environmental Test Methods and Engineering Guidelines. |
| MIL-STD-814 | - Requirements for Tiedown, Suspension and Extraction Provisions on Military Army Materiel for Airdrop. |
| ML-STD-889 | - Dissimilar Metals. |
| MIL-STD-1410 | - Methods for Selection of Industrial Engines for End Item Application. |
| MIL-STD-1474 | - Noise Limits for Army Materiel. |
| MIL-STD-1791 | - Designing for Internal Aerial Delivery in Fixed Wing Aircraft. |
| MS51113 | - Switch, Vehicular Lights, 24 Volt, DC, (Waterproof). |
| MS51330 | - Stop Light-Taillight, Vehicular, 24-Volt, Blackout Tail, Blackout Stop. |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

| | |
|---|---|
| MS52125 | - Composite Light Tail, Stop, Turn and Marker. |
| MS52131 | - Connector, Plug, Electrical Intervehicle Power Cable. |
| M53052 | - Bracket Assembly, Liquid Container, Five Gallon. |

HANDBOOK

MILITARY

AIR FORCE SYSTEM COMMAND

Design Handbook DH1-11 - Air Transportability.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those in effect on the date of the solicitation.

DRAWINGS

TACOM

| | |
|---|---|
| 12258941 | - Connector, Receptacle 54 Pin. |
| 12258955 | - Vehicle Test Card. |
| 12360910 | - Headlight: Blackout, 24 Volt (Waterproof). |

(Copies of drawings required by contractors in connection with specific acquisition functions should be obtained from the USA Tank-Automotive Command, ATTN: AMSTA-MD, Warren, MI 48397-5000.)

MILTTARY TRAFFIC MANAGEMENT COMMAND (MTMC/TEA)

Pamphlet 70-1 - Transportability for Better Strategic Mobility.

(Application for copies should be addressed to the Military Traffic Management Command, Transportation Engineering Agency (MTMC/TEA), ATTN: MIT-TR, P.O. Box 6276, Newport News, VA 23606-0276).

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

| | |
|---|---|
| A 120 | - Black and Hot-Dipped Zinc-Coated (Galvanized) Welded and Seamless Steel Pipe for Ordinary Uses, Specification For. |
| D 2239 | - Polyethylene (PE) Plastic Pipe (SD R-PR), Specification For. |
| D 2737 | - Polyethylene (PE) Plastic Tubing, Specification For. |
| D 2751 | - Acrylonitrile - Butadiene - Styrene (ABS) Sewer Pipe and Fittings, Specification For. |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Society of Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

AMERICAN WELDING SOCIETY (AWS)

| | |
|---|---|
| AWS D14.3 | - Welding Earthmoving and Construction Equipment. |

(Application for copies should be addressed to the American Welding Society, 550 N.W. LeJune Road, P.O. Box 351040, Miami, FL 33135.)

NATIONAL FIRE PREVENTIION ASSOCIATION (NFPA)

| | |
|---|---|
| NFPA No. 1961 | - Fire Hose. |
| NFRA No. 1963 | - Screw Threads and Gaskets for Fire Hose Connections. |

(Application for copies should be addressed to the National Fire Protection Association International, 60 Battery March Street, Boston, MA 02110.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION (NMFTA)

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, ATTN: Traffic Order Section, 2200 Mill Road, Alexandria, VA 22314.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

| | |
|---|---|
| J53 | - Minimum Performance Criteria for Emergency Steering of Wheeled Earthmoving Construction Machines. |
| J185 | - Access Systems for Off-Road Machines. |
| J231 | - Minimum Performance Criteria for Falling Object Protective Structure (FOPS) . |
| J386 | - Operator Restraint Systems for Off-Road Work Machines. |
| J514 | - Hydraulic Tube Fittings. |
| J551 | - Performance Levels and Methods of Measurements of Electromagnetic Radiation from Vehicles and Devices. |
| J678 | - Speedometers and Tachometers - Automotive. |
| J925 | - Minimum Access Dimensions for Construction and Industrial Machinery. |
| J994 | - Alarm - Back Up - Electric - Performance. |
| J1040 | - Performance Criteria for Rollover Protective Structures (ROPS) for Construction, Earth Moving, Forestry, and Mining Machines. |
| J1152 | - Braking Performance - Rubber-Tired Construction Machines. |
| J1349 | - Engine Power Test Code - Spark Ignition and Diesel. |

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

UNIFORM CLASSIFICATION COMMITTEE (UCC)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, (except for related associated detail specifications, specification sheets or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The water distributor shall be the latest model of the standard product of the contractor and shall have demonstrated industry acceptability by having been manufactured, marketed, and sold in significant numbers to the commercial public for the same or similar application, interfacing with the same or similar components, except as specified herein, for at least 1 year prior to invitation for bids or request for proposal. Product improvements incorporated in the commercial production units in this 1 year period are acceptable. In the case of a recently introduced item, the contractor shall submit sufficient valid industrial operational/test data including all test reports for the item and its components, such as engine, transmission and, hydraulic system, field user reports, including any failures or problem areas, and corrective action taken to demonstrate acceptability of the item. When specified requirements are not stated herein, all items listed as standard equipment in the contractor's published specification brochures and catalogs, or normally furnished to commercial customers as standard equipment, shall be furnished. The distributor shall be equipped with any optional equipment necessary to comply with requirements specified herein. optional equipment is defined as equipment not standard with the distributor but which has been furnished to the commercial customer, such as special features or allied equipment. The distributor shall be equipped with all components necessary to enable the distributor to function reliably and efficiently in sustained operation. The distributor shall conform to all Federal laws and regulations governing safety and pollution, which are in effect on the date of invitation for bids or request for proposal.

3.2 Description. The water distributor shall be a commercial model consisting of a tractor front section and a tanker rear section. The distributor shall be rubber-tired, diesel engine driven two axle with the front axle oscillating, articulated frame steering, two single driving front wheels and two single nondriving rear wheels and shall be equipped with a power shift transmission. The distributor shall be equipped with a front and rear towing device. The distributor shall consist of the following:



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

a. Tractor section (see 3.10).
b. Hydraulic system (see 3.15).
c. Tank body and equipment section (see 3.11).
d. Pump and plumbing (see 3.12 and 3.13).
e. Distributor system (see 3.14).

Component and vehicle ratings shall be not greater than each manufacturer's published rating. Components and equipment ratings shall not be raised to meet the requirements of this specification.

3.2.1 Type I. The type I distributor with rollover protecting structure/falling object protective structure (ROPS/FOPS) removed shall be capable of being loaded and rigged on an air delivery platform in accordance with MIL-STD-669, air transported and air delivered by parachutes.

3.2.2 Type II. The type II distributor with ROPS/FOPS removed shall meet the requirements specified for type I (see 3.2.1) and shall also be capable of being sectionalized into 2 sections for external air transport by helicopter. Sectionalization material may be removed for airdrops.

3.3 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.4) in accordance with 4.3.

3.4 Production equipment. All distributors of the same type furnished under this specification shall be physically and mechanically identical to the first article distributor approved by the Government, except that product improvements incorporated in the contractor's standard commercial product lines are permitted at no cost to the Government subject to tire following:

a. Physical and performance characteristics have not been degraded.
b. New components involving Government selected repair parts are directly interchangeable with the superseded component or part.
c. The Government is notified of all changes to any item on the recommended parts list where fit and function is effected a minimum of 45 days prior to the production date of change. When the changes and alterations have been incorporated in the production unit, the Government shall be furnished, by serial number, the dates production becomes effective.
d. Appropriate changes are made to the Government validating operation, maintenance, and parts manuals before delivery.
e. The contractor shall provide repair parts for the distribution over the service life of the distribution.

3.5 Material. Material not specified herein shall be selected by the contractor and shall be subject to all provisions of this specification.

3.5.1 Material deterioration prevention and control. The distributor shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various form of corrosion and deterioration that may be encountered in any of the applicable operating and storage environments to which the distributors may be exposed.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

3.5.2 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

3.5.3 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with component and subcomponent, and shall make information available upon request to the contracting officer or designated representative.

3.5.4 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the distributor may be newly fabricated from recovered materials to the maximum extent practicable, provided the distributor produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the distributor.

3.6 Safety. All available standard or optional accessories shall be included to provide protection for maintenance and operating personnel from rotating or reciprocating parts and from all parts subject to high operational temperatures and so located as to be a hazard. Exhaust discharges shall be directed so as to not endanger personnel. All platforms and steps shall have anti-skid surfaces. Contractor's standard grab irons shall be provided. A decal shall be furnished and shall be located in the area of the articulation point, warn g of limited personnel clearance during frame articulation and placement of safety pin or bar for the distributor operating and transport modes. Asbestos materials shall not be used in this vehicle.

3.6.1 Noise limits. The noise produced by the distributor shall conform to MIL-STD-1474 requirements, with the exception of MIL-STD-1474 5.2, 5.3, and 5.4, when tested in accordance with 4.5.2.2. The provisions of MIL-STD-1474, 4.3 and 4.4 shall be provided if and only if MIL-STD-1474 5.1.1.2 procedures have been pursued and documented to the satisfaction of the procuring activity and written permission to exceed the 85 dB(A) limit is obtained from the procuring activity. Hazard signs shall conform to MIL-STD-1474 4.3, except the sign shall state "HEARING PROTECTION REQUIRED WITHIN (specify) FEET". The sign shall be readable at the distance indicated on the sign.

3.6.2 Rollover protective structure (ROPS) and falling subjects protective structure (FOPS). The distributor shall be equipped with a removable bolted down ROPS/FOPS canopy. The canopy shall be replaceable without cutting or welding. Removal of the ROPS/FOPS canopy shall be limited to the exterior canopy and shall not involve removal of the operators platform or undercarriage support structure. All gauges and operator's controls shall remain intact. The ROPS/FOPS shall conform to SAE J1040 and SAE J231 respectively. A seat belt conforming to SAE J386 shall be properly installed for use by the operator. Quick disconnect fittings (electric, etc.) shall be provided as applicable to facilitate canopy removal. A slinging eye(s) shall be provided to facilitate removal of ROPS/FOPS.

3.7 Physical characteristics.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

3.7.1 Weight limits. For airdrop, the distributor, without the removable ROPS/FOPS, without auxiliary hose assembly, without sectionalization kit, but with all other attachments, accessories, coolant, lubricating and hydraulic systems filled to capacity and with not less than 25 percent nor more than 75 percent fuel, shall weigh no more than 30,600 pounds. The type II distributor when sectionalized into 2 sections shall weigh not more than 16,000 pounds per section.

3.7.2 Dimensions. The overall width of the distributor shall not exceed 104 inches except that the width may be increased to not more than 105 inches to accommodate special airborne/airmobile provisions. The operational lengths of the types I and II distributors shall not exceed 392 and 423 inches respectively. In order to conform to a height limit of 100 inches when rigged for airdrop, the reducible height of the distributor should be riot more than 91 inches. No major component removal, except MPS/FOPS canopy, shall be required to obtain the reduced height. If the height exceeds 91 inches (provided the rigged load can meet the tipoff curve given in MIL-STD-814, figure 9) the contractor must demonstrate prior to step I proposal opening date that the distributor can be rigged so as to conform to the 100 inch limit and MIL-STD-814 tipoff curve, and withstand the forces encountered in the simulated airdrop impact test (see 4.5.2.15) without damage or permanent deformation.

3.8 Sectionalizaton. The type II distributor, less ROPS/FOPS shall be capable of being sectionalized into two sections for helicopter transport. The weight of either section shall not exceed 16,000 pounds. The powered section shall be driveable and steerable under its own power for a distance of 50 feet over relatively flat unimproved areas. The reassembly and disassembly times, with tools furnished with the distributor and with the tools available to the operator under field conditions and without assistance of other powered equipment, shall not exceed 4 hours each. Cutting and welding are not permitted. Components and accessories used in sectionalization and reassembly shall be stored on the distributor or in a demountable container attached to the vehicle but shall not interfere with the operation of the equipment.

3.9 Performance. The distributor shall withstand the usage encountered in military operations such as self-loading, hauling and evenly distributing water. The distributor shall withstand crossing roadless rough terrain, including gullies causing the tractor tanker to oscillate in both directions, fording streams, and negotiating steep longitudinal and sidehill slopes, without damage. The distributor shall be capable of having its normal construction tasks performed by one operator including filling of the tank. The distributor shall be capable of driving at maximum travel speed in transport, being towed by another vehicle, and limited towing of other equipment.

3.9.1 Travel speed. The distributor shall be capable of a forward travel speed of not less than 20 mph, loaded, on level pavement.

3.9.2 Braking. The distributor's braking performance shall be in accordance with SAE J1152. In event of power assist failure, the distributor shall be capable of being stopped with a brake force not to exceed 70 pounds.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

3.9.3 Stability. The distributor shall negotiate 35 percent side slopes empty, 20 percent side slopes loaded, and descend 40 percent longitudinal slopes without any wheel losing contact with the ground. All parts requiring lubrication shall be lubricated when the distributor is operated under these conditions.

3.9.4 Fording. The distributor shall start and operate during and after fording operations in fresh water to a depth of 20 inches including wave action without damage and without leakage of water into any reservoir including reservoirs containing lubricants.

3.9.5 Environmental conditions.

3.9.5.1 Tractor section. Without the use of any external means, the engine shall start within five minutes and shall operate under full-load conditions within fifteen minutes after engine start in any ambient temperature from -25 to +120 °F. Cold start aids must be integral with the distributor and no aids may be used which rely upon external support such as an electrical power source. Hand-held aerosol cans or unmetered starting fluid devices are not permitted. The distributor shall be capable of operating in hot, humid tropical environments; in dry, dusty environments and in moderate to cold climate to -25 °F. If the distributor is equipped with air brakes, an air dryer or alcohol evaporator system shall be furnished.

3.9.5.2 Tanker section. The water tanker section shall be capable of distributing water in temperatures from plus 35 to 120 °F.

3.10 Tractor section.

3.10.1 Engine horsepower. The diesel engine shall meet the requirements of MIL-STD-1410 for application in class II end item. The engine shall be equipped with a muffler. The exhaust stack shall be equipped with a rain cap or shall be fabricated and mounted to prevent the entry of rain or snow.

3.10.1.1 Engine horsepower. The applied net horsepower of the engine at the flywheel when measured in accordance with SAE J1349 shall be not less than 150 horsepower using fuel conforming to MIL-T-83133, grade JP-8.

3.10.2 Engine cooling system. A cooling system meeting the requirements of 3.9.5.1 shall be provided. On or near the radiator cap, a burn or scalding hazard warning shall be permanently attached.

3.10.3 Fuel tank. The fuel tank shall have sufficient capacity for 10 hours of continuous normal operation. The tank shall be equipped with a means for draining water and sediment from the bottom of the tank.

3.10.4 Air system. An engine driven compressed air system shall be furnished to provide air for the brake system (when equipped with air brake system) and for water distributor nozzle actuation. The system shall include an air compressor, an alcohol evaporation or air dryer, and air reservoir with safety valve, and the lines and fittings. A service outlet with hose and fittings necessary for tire inflate shall be provided with the air system. An on-board electric or hydraulically powered air compressor is an acceptable alternative (when unit is not equipped with air brake system) to provide for water distributor nozzle actuation and tire inflation requirements.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

3.10.5 Oil sampling valve. Oil sampling valves shall be provided on the engine, transmission and hydraulic system. The valves shall be manually operated and shall automatically close when released. It shall be made of material resistant to corrosion such that it will not contaminate the sample. The discharge port of the valve shall be covered with a capture chain cap conforming to SAE J514. The valve shall be located in such a way as to insure that the personnel will not be exposed to danger when taking oil sampler with the engine running. The location of the oil tap shall be such that when samples are taken, it shall be a true representation of oil that is flowing while the engine is running. Sampling valves shall be labeled engine, transmission or hydraulic; whichever is appropriate to indicate the type of oil sampled.

3.10.6 Tachometer drive. A heavy-duty key type tachometer drive shall be provided and shall have a 5/32-inch female connection in accordance with SAE J678. The output drive shall be covered with a threaded captive chained cap for protection when not in use.

3.10.7 Drive train. A drive train consisting of a torque converted, full powershift transmission, front drive axle with differential and planetary final drives, and all necessary connecting components shall be furnished. The transmission shall provide not less than four forward speeds and one reverse speed. A locking or limited-slip differential shall be furnished in the drive axle.

3.10.8 Wheels and tires. Commercial standard demountable wheels or rims shall be provided. Traction type tubeless tires shall be furnished and shall have a tread pattern suitable for distributor operation. The contractor's standard tire size, thread depth and ply rating shall be furnished. The contractor's standard fenders shall be furnished to restrict mud throwing and splash from the tires. Tires furnished to the Government shall be not more than 12 months old from date of cure of the rubber to date of acceptance by the Government.

3.10.9 Steering and braking.

3.10.9.1 Steering system. The distributor shall have an articulated frame type steering system. The steering system shall provide full control of the distributor under all normal operating conditions and shall provide emergency steering conforming to SAE J53 that will give the operator steering control in the event of engine failure.

3.10.9.2 Braking system. The distributor shall be equipped with power assisted brakes on all four wheels. A parking system and an emergency braking system shall be provided. The braking system shall comply with SAE J1152. When nonpetroleum based brake fluid is used in a hydraulic braking system, it shall use silicone type brake fluid in accordance with MIL-B-46176. Asbestos material shall not be used in the brake linings or shoes for this vehicle.

3.10.10 Operator’s compartment.

3.10.10.1 Seat. The seat shall be located to provide the operator with convenient access to operating controls, and visibility of the work zone and all instruments and gauges mounted in the operator's compartment when seated with seat belt fastened and properly adjusted.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

3.10.10.2 Instruments and indicators. The following instruments and indicators shall be provided:

a. Engine oil pressure gage.
b. Engine coolant temperature gauge.
c. Torque converted oil temperature gage.
d. Ammeter or voltmeter.
e. Engine hourmeter or service meter.
f. Air pressure gage (when equipped with air system).
g. Low air pressure warning buzzer (when equipped with air system).
h. Fuel level indicator (dipstick or gage).
i. Hydraulic oil level indicator (dipstick, sight tube, or gage).
j. Air cleaner restriction indicator.
k. Low water level warning indicator.

Manufacturer's standard monitor package with supplemental gages as required, is acceptable in lieu of individual gages specified above.

Additional instruments and indicators standard with the contractor's commercial practice, which contribute to the safety and reliability of operation, shall be furnished. The instruments, indicators and their sending units shall be weatherproof.

3.10.10.3 Controls. All controls for the distributor shall be located in the operator's compartment and shall be within reach of the operator in his normal operating position.

3.10.4 Fire extinguisher. A fire extinguisher shall be provided and mounted in the operator compartment so that it shall be accessible from the ground. The bracket shall be Coast Guard approved and shall secure a 5 pound Halon fire extinguisher as described by A-A-1108.

3.11 Water tanker section. The rear water tanker section of the distributor shall be as specified herein. The tanker section shall provide the volume and structure necessary for the capacity of at least 2500-gallons of water plus 3 percent expansion space. The payload weight shall be based on water at 8.3 pounds per gallon and 62.3 pounds per cubic foot. The tanker section shall include a coupler and gooseneck, water tank, running gear, guarded water lever sight gage, hydraulically driven pump, plumbing, and nozzles.

3.11.1 Tank. The tank shall be fabricated from steel of at least 1/4-inch plate and shall have the front and rear heads welded into the tank skin employing either lap joint or ring stiffener design. The tank shall include structurally reinforcing longitudinal and transverse baffle members to strengthen the tank and restrict water surge. The interior of the tank shall be treated to resist the corrosive effects of air and water. Drains shall be provided at the lowest portions of the tank and all plumbing components so that all water can be drained by gravity to prevent damage during freezing ambient temperatures.

3.11.2 Manhole. The tank shall be equipped with a round or oval manhole opening not less than 30-inches in major diameter. A light weight, liquid-tight, easy opening, quick-latching manhole cover shall be supplied. Hinged covers shall be hinged at the forward edge.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

3.11.3 Vents. Vents shall be provided to allow for expansion of the water in the tank and discharging the tank at maximum rate with the manhole and fill cover sealed.

3.11.4 Catwalk and ladder. A catwalk not less than 24-inches wide shall be provided over the top of the tank. The catwalk shall be centrally located at the manhole. The catwalk shall withstand a minimum loading of 300-pounds on each square foot and shall be of the open serrated grating type. A non-skid access ladder shall provided for access to the catwalk. Both catwalk and ladder shall be in accordance with SAE J185. All operator access areas shall be equipped with non-skid decking surfaces and handholds that permit use of arctic mittens as shown in SAE J925.

3.11.5 Rear running gear. The rear running gear on the rear section of the distributor shall include a non-driving axle or twin spindles having the same interchangeable tire and wheel assemblies as the tractor. The equipment rear timing gear shall be equipped with rear fenders to restrict mud throwing and splash from the tire. The fenders shall support a minimum weight of 300 pounds over any 1 square foot area.

3.12 Pump. A hydraulically driven, minimum 4-inch centrifugal pump shall be installed either in the tank or at the rear of the tank. The pump shall be of the self-loading type. The pump self-loading system shall include plumbing and valving with an isolating auxiliary water section in the main tank of at least 100 gallons to assure at least two primings of the water pump. Pump impeller materials shall be corrosion resistant. The pump, shall be capable of lifting water from 10-feet below ground level through the 30-feet of suction hose to self-load water to the top of the tank. The pump and tank shall be equipped with a low water level warning indicator. Waterproof instruction cards, in accordance with 3.21, shall be furnished to provide the operator with the water distribution rate on the ground in gallon-per-100-foot length pattern, correlated to the following variables:

a. First and second transmission geared speeds at governed engine rpm.
b. Water pump speeds of 100 percent and 50 percent of engine governed rpm.
c. Per nozzle at maximum opening size, using 1, 2, 3, and 4 nozzles.

3.13 Plumbing. The distributor plumbing shall conform to the following:

a. Provide a mesh screen strainer in the pump inlet line which is removable and accessible for cleaning to prevent damage to the pump.
b. Provide an outlet valve with remote operator control; locate valves within the perimeter of the distributor and include break-away-joints between the valve and the nozzles.
c. Provide plumbing to the water distribution system using metal water pipe covered by ASTM A 120 and plastic water pipe covered by ASTM D 2239, D 2737, or D 2751.
d. Provide bath gravity and pump pressure feed from the tank to the water distribution system; in addition, also furnish a capped outlet fitting for future user installation of a multi-nozzle, transverse rear spraybar.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

e. Provide two lengths of suction hose, for self loading, each length 15-feet long; provide male and female couplings of the cam-lock type on the hose and the tank; provide a strainer and foot valve for the hose; provide hose tubes for securely stowing the hose on the tank; provide each open end of the hose stowage tube with a latching metal protective cap to prevent entry of dirt and water; provide cap with hinges or captive chains to prevent loss of caps. Hoses shall be not more than 12 months old from date of cure of the rubber to date of acceptance by the Government.

3.14 Water distribution system. The water distribution system shall be by pressurized nozzles. The distribution system shall route water from the pump outlet to a rear mounted transverse pipe feeding four adjustable, non-ferrous fan spray nozzles. Each nozzle shall be independently compressed air remote controlled from the tractor operator's compartment having air pressure open and spring close features. Each nozzle shall be horizontally adjustable 180 degrees using common hand tools and provide coverage from a 15-foot swath to not less than a 30-foot swath. The width of nozzle spray shall be manually adjustable at the nozzle. The maximum operation of all four nozzles shall provide a width coverage of not less than a 65-foot swath.

3.3.5 Hydraulic system. The distributor shall be equipped with a hydraulic system which shall provide sufficient force for operating all attachments and related components.

3.16 Electrical system. The distributor shall be equipped with a 24-volt (6 TL battery) electrical system. The electrical circuitry, including all components and connections, except as specified below, shall be protected from the effects of fungus growth and moisture by an overall treatment with a varnish conforming to MIL-V-173, composition I with 1-percent copper 8-quinolinolate (by weight) or 7-percent salicylanilide based on the nonvolatile content of varnish:

a. Components or circuit elements that are inherently fungus and moisture resistant or which are hermetically sealed need not be treated.
b. Components or circuit elements whose functions will be adversely affected by the varnish coating shall not be treated.

When used, the varnish shall be applied by spray, brush, or a combination of both, to give a minimum, dry-film thickness of 1-mil to component or element surfaces. These surfaces shall be previously cleaned and prepared so that they are free from all foreign matter that would interfere with the adherence or function of the varnish.

3.16.1 Alternator. The rated output of the alternator shall be not less than 35 amps.

3.16.2 Lighting. The following lights with associated circuits, circuit breakers, or other protective devices and switches shall be provided:

a. Two headlights.
b. Two front working light.
c. Combination stop and taillights.
d. Turn signals and emergency flashers.
e. Instrument panel lighting.
f. Rear floodlights(s).



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

All lights with the exception of the instrument panel lighting shall be guarded or mounted in a protected location. If the lights are mounted on the ROPS, alternate provisions shall be made for mounting the lights when ROPS are removed. The brake lights shall override the emergency flashers.

3.16.2.1 Blackout lighting. One blackout headlight conforming to Drawing 12360910 shall be mounted as close to the extreme left of the vehicle as practical and positioned to provide illumination with minimum obstruction. Two blackout stoplight-taillights conforming to MS51330 shall be mounted adjacent to the taillights specified in 3.16.2 and shall be mounted in recesses or provided with guards. The blackout light shall be controlled by an interior switch conforming to MS51113 which is readily accessible to the operator in his seated position. All other exterior lights, backup alarm and the horn, if electric, will be made inoperable automatically when the blackout lights are switched on. All instrument panel lights (exclusive of warning indicator lights) and gages which are illuminated in the blackout mode shall not emit energy outside of the 380 to 700 nanometer wavelength range. A separate wiring harness may be provided for the blackout lights. In lieu of separate service and blackout taillight assemblies, composite light assemblies, conforming to MS52125 may be provided. All warning indicator and enunciator lights shall be light emitting diodes (LED).

3.16.3 Electromagnetic radiation. The distributor shall be suppressed to limit electromagnetic radiation to limits of SAE J551.

3.16.4 Horn. An operator controlled horn shall be furnished.

3.16.5 Backup alarm. A backup alarm conforming to SAE J994, type C shall be furnished.

3.16.6 Slaving components. The distributor shall be equipped with a 24 volt slave receptacle conforming to MS52131. The slave receptacle shall permit charging of the batteries and slave starting of the engine from an external power source and shall also provide a power source for charging and slaving other equipment. The slave receptacle shall be installed on the exterior of the distributor near the battery enclosure and shall be accessible to personnel standing on the ground.

3.16.7 Diagnostic connector assembly (DCA). Unless otherwise specified (see 6.2) the distributor shall incorporate an easily accessible DCA in the operators compartment for interface with the Government's simplified Test Equipment/Internal Combustion Engine-Reprogrammable (STE/ICE-R) in accordance with STE-ICE-R Design Guide for Vehicle Diagnostic Connector Assemblies Report No. CR-82-588-003. The diagnostic connector shall be in accordance with Drawing 12258941. As a minimum, DCA shall be capable of monitoring the functions defined in table 2-2 of Report No. CR-82-588-003. When specified (see 6.2), additional test parameters to be monitored in either the DCA or transducer kit (TK) mode shall be as specified in the contract. Test points identified to monitor functions in the TK mode shall be accessible without the removal of major assemblies and installed attachments. Fittings/adapters required for the interface with the STE/ICE-R test set when monitoring in the TK mode shall be permanently installed on the distributor. Adapters in the STE/ICE-R test set shall readily mate with test point connections on the distributor. A separate wiring harness shall be provided for the DCA and shall include all wiring and necessary hardware to perform required capabilities. A fuel



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

shut-off method shall be provided for conducting compression unbalance checks. The contractor shall also provide STE/ICE-R vehicle test cards in the format identified in Drawing 12258955 addressing both DCA and TK measurements and shall incorporate the test cards into the distributor technical manuals when manuals are provided (see 6. 11).

3.17 Antivandalism protection. The distributor shall be equipped with locks to secure the following:

a. Fuel tank filler cap.
b. Hydraulic oil tank filler cap.
c. Engine oil filler cap and dipstick.
d. Transmission oil filler cap and dipstick.
e. Radiator filler cap.
f. Toolbox.
g. Battery box.

When any of the above items are secured by lockable cab doors or lockable engine side panels, individual locks are not required. Keys for ignition, cab doors, cover panels, filler caps and tool battery boxes shall be interchangeable to the maximum extent possible. Two sets of keys shall be furnished with each distributor and each set shall be identical for every distributor.

3.18 Attachments. The removable attachments shall not be included in determining the airborne and airmobile weights of the distributor in 3.7.1 and 3.8.

3.18.1 Auxiliary discharge hose and reel. A removable auxiliary hose and reel assembly shall be furnished. The assembly shall be a hose reel with swivel, valve, and at least 70-feet of 1-1/2 inch inside diameter, elastomer lined, NFPA No. 1961 and 1963 fire hose assembly. A crank shall be provided for hand rewind of the winding mechanism. A ratchet device shall be provided to prevent tension or looseness on the hose. Four-way roller guides shall be provided to prevent damage to the hose when used other than straight out. The hose and reel assembly shall be mounted between the rear wheels. The free end of the hose shall be fitted with a delivery nozzle. The nozzle shall be equipped with a 1-1/2-inch diameter rigid spout. The nozzle shall be of the shutoff type or shall have a shutoff valve at the nozzle inlet. A metallic dust cap shall be furnished for the nozzle spout. Hoses shall be not more than 12 months old from date of cure of the rubber to date of acceptance by the Government.

3.19 Transportability. The distributor shall be capable of being transported by military or commercial trailers, trains, marine vessels, aircraft and shall be capable of withstanding the impact forces encountered in shipment, air drop, and low altitude parachute extraction system (IAPES) without damage or permanent deformation. The distributor shall be equipped with tiedown or slinging provisions.

3.19.1 Tiedown provisions. The tiedown provisions shall conform to MIL-STD-209, class 2 or 3, type IV equipment, and to MIL-STD-1791 for equipment restraint criteria. The tiedown provisions shall satisfactorily complete the pull testing as specified without weld failure, permanent deformation, cracking, loosening, or breaking of the provision or its connecting structural components.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

3.19.2 Slinging provisions. The slinging provisions shall conform to MIL-STD-209, class 1 or 3, type IV. The provisions shall enable the complete distributor to be lifted in the normal operating position. The provisions shall be located so that not less than one inch clearance is maintained between slings and all exterior parts and shall be fastened to members which will stand stresses in the amount and direction of pull specified for the provisions without weld failure, permanent deformation, cracking, loosening, or breaking of the provision or its connecting structural components. Slinging provisions may also be used as tiedown provisions when such provisions meet the requirement specified in 3.19.1. All slinging/tiedown provisions shall be labeled "LIFT", "LIFT DOWN" or "LIFT TIEDOWN", as appropriate, in 1-inch (2.54 cm) high letters.

3.19.3 Air transportability. The distributors shall meet the requirements of MIL-STD-1791 and AFSC Design Handbook DH1-11 for air transport. The distributor shall be capable of being loaded and transported in the C-130, C-141, C-5A aircraft and lifted by helicopters.

3.19.4 Rail transportability. The distributor shall be rail transportable in CONUS and NATO countries without restrictions. The distributor shall have a dimensional profile within the Gabarit International de Chargement (GIC) in accordance with MTMC/TEA pamphlet 70-1, outline diagram when loaded on a 50-inch (127 cm) high rail car. The distributor shall be capable of withstanding shock loads resulting from rail impact testing in accordance with 4.5.2.14.4 without failure, damage, or permanent deformation.

3.3.9.5 Highway transportability. The distributor, when loaded on a semitrailer/tractor, shall be within the highway permit limits of all states.

3.19.6 Parachute suspension provisions. Four integral suspension provisions conforming to MIL-STD-814 shall be furnished on the distributor. The parachute suspension provisions shall withstand the stresses in the amount and direction of pull specified without weld failure or permanent deformation of the distributor or provisions. The parachute suspension provisions shall be labeled "ATTACH DROP PARACHUTE HERE" in inch letters.

3.19.7 Extraction parachute provision. Extraction provisions shall be provided on the distributor for attachment of the parachute extraction system. Except as specified herein, the extraction provision shall conform to MIL-STD-814 and shall withstand stresses in the amount and direction of pull specified without weld failure or permanent deformation of the distributor or the provision. In lieu of the limit load specified in MIL-STD-814, the limit load of the provision shall be 56,580 pounds. The design ultimate strength of welded sections shall be four times the limit load. The extraction provision shall be labeled "ATTACH EXTRACTION PARACHUTE HERE".

3.19.8 Airdrop. The distributor shall meet the requirements of MIL-STD-660 for air drop.

3.20 Identification plates and marking. Each distributor shall be furnished with an identification plate showing the contractor's model number, NSN, USA registration number, vehicle identification number, weight, date of manufacture and date of delivery. The identification plate shall be permanently affixed to the distributor in a readily accessible and conspicuous location. Plates shall conform to MIL-P-514 or



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

contractor's standard plates subject to the approval of the contracting officer. All attachments or removed or disassembled for shipment shall be matchmarked for proper reassembly. The distributor and each attachment shall be identified in accordance with the contractor's standard method.

3.20.1 Vehicle weight classification sign kit. The contractor shall apply the vehicle weight classification numbers to each vehicle, using a vehicle weight classification number kit furnished by the Government (see 3.29). The kit shall be located on the front of the vehicle in a location approved by the contracting officer. The contracting officer shall assign the classification numbers to be displayed on the vehicle. Instructions for changing the numbers, based on the vehicle configuration, shall be provided.

3.20.2 Case. The contractor shall furnish the fasteners and shall install the Government-furnished case (see 3.29) in the operator's compartment.

3.21 Instruction plates. The distributor shall be equipped with instruction plates including warnings and cautious suitably located and permanently affixed, describing any special or important procedures to be followed in operating and servicing the distributor. Plates shall conform to MIL-P-514 or contractor's standard plates subject to the approval of the contracting officer. Instructions for water distribution rate (see 3.12) and for disassembly of the type II distributor into two sections and reassembly shall be provided on cards, approximately 8-1/2-inches by 11-inches, which shall be encased in laminated plastic. One set of these cards shall be furnished with each distributor.

3.22 Shipping data plates. Shipping data plates for each distributor shall be furnished and shall show the silhouette of the distributor (and each section of type II distributor, only), indicating the location and capacity of tiedown provisions, slinging provisions, extraction provisions, suspension provisions, the center of balance and shipping weight. Plates shall conform to MIL-P-514 or contractor's standard plates subject to the approval of the contracting officer. The plates shall be attached to the left side of the distributor and shall show the locations as viewed from the left side. The plates on the sections, (type II distributors only) shall be located in conspicuous protected locations. All plates shall be permanently attached.

3.23 Identification Marking. The distributor shall be identified in accordance with MIL-STD-130 on an identification plate conform to MIL-P-514, composition C, of type I, grade A, class 1 material. The plate shall be furnished and mounted by the contractor. A shipping data plate shall be furnished and shall conform to MIL-P-514, type II, composition C, of type I, grade A, class 2 material and, in addition, shall indicate the silhouette of the distributor in transport position indicating the center of gravity and location and capacity of the slinging and the tiedown provisions. Each plate shall be attached by screws, bolts, or rivets in a conspicuous protected location.

3.24 Treatment and painting. The portions of the distributor normally painted, internally and external, shall be cleaned, treated, and painted in accordance with MIL-T-704, type F or G, as applicable. Unless otherwise specified (see 6.2), top coat color shall be camouflage green 383 conforming to MIL-C-46168. When specified (see 6.2), the distributor shall be overcoated in accordance with the Government furnished camouflage patterns with MIL-C-46168 top coat of the colors specified in the camouflage patterns except



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

the first article may be camouflage green 383. Heat resistant paint conforming to MIL-P-14105 shall be used for areas exceeding 400 °F.

3.24.1 Camouflage pattern data. When specified (see 6.2), the contractor shall provide camouflage pattern data.

3.25 Lubrication. A lubrication means shall be provided for all moving parts requiring lubrication. Each distributor shall be serviced and run-in with military lubricants conforming to MIL-L-2104, MIL-L-2105, MIL-L-46167, MIL-M-7866, MIL-G-10924, and MIL-G-23827, as applicable. Silicone fluid for hydraulic brakes shall be in accordance with MIL-B-46176.

3.26 Decontamination apparatus, portable (DAP), M13. The distributor DAP mounting bracket (MS53052-1) shall be installed in a manner which shall not interfere with the normal operation of the equipment. The DAP has the approximate dimensions of a standard issue five gallon can conforming to MIL-C-1283 with a weight of 54 pounds. An upright installation is preferred. Horizontal mounting shall be used only with the approval of the contracting officer. The DAP device has a flash point of 165 °F and shall be installed away from exhaust or heat sources.

3.27 Special tools. Unless otherwise specified (see 6.2), any nonstandard or special tools required for equipment operation and operator maintenance distributor shall be furnished with the distributor.

3.28 Toolbox. A lockable weather protected storage compartments or toolbox of sufficient size to hold all tools and equipment required for operation and operator maintenance shall be provided.

3.29 Government-furnished property. When specified (see 6.2), the following property in the quantity indicated will be furnished by the Government (see 6.5).

| Item No. | Description | Quantity |
|---|---|---|
| 1. | Camouflage paint pattern. | As required. |
| 2. | Cases complete with maintenance form. Case NSN 7520-00-559-9618. | As required. |
| 3. | Vehicle Weight Classification Sign Kit. NSN 9905-00-565-6267. | As required. |
| 4. | Report CR 82-588-003 STE/ICE Design Guide for Vehicle Diagnostic Connector. | As required. |

3.30 Workmanship. The distributor shall be free form defects such as poor welds, rust, cracks, and other defects that could impair its operation or serviceability.

3.30.1 Castings and forgings. All castings and forgings shall be clean of harmful extraneous material such as sand, dirt, sprues, scale, and flux. Rework material shall meet typical mechanical properties of new casted or forged material and not affect fit or function.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

3.30.2 Metal fabrication. Metal used in fabrication shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause injury to the material. All bends shall be made with controlled means to insure uniformity of size and shape. Precaution shall be taken to avoid overheating. External surfaces shall be free of burrs, sharp edges, and comers, except when sharp edges or corners are required or where they are not detrimental to safety.

3.20.3 Welding and welders. Welding procedures and welder qualification shall be in accordance with AWS D14.3.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. The contractor is responsible for insuring that components and materials are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article inspection. The first article (see 6.2), furnished by the contractor shall be examined (see 4.5.1) and demonstrated (see 4.5.2), to determine compliance with the requirements of this specification. Prior to the examination and demonstration of the distributor, the following shall be performed:

a. Service the distributor with the lubricants specified.
b. Break in the distributor as prescribed by the contractor.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

4.3.1 First article examination. Prior to the first article demonstration, the distributor shall be examined for the defects marked "X" in column 1 of table I. Presence of one or more defects shall be cause for rejection. Prior to the first article demonstration the distributor shall be examined and compared with this specification, with the contractor's published brochures and with commercial manuals. Any discrepancy between the specification, brochures, manuals and the first article models shall be cause for rejection.

4.3.2 First article demonstration. Upon successful completion of the examination specified in 4.3.1, the first article distributor shall be subjected to the demonstrations marked "X" in column 1 of table II. Failure of any demonstration or any demonstration reports shall be cause for rejection. All tests as specified in 4.3, where applicable, shall be run on MIL-T-83133, grade JP-8. All tests as specified in 4.4, where applicable, shall be run on either VV-F-800, grade DF2 or MIL-T-83133, grade JP-8.

4.3.3 Test Report. The contractor shall prepare and submit the first article test report to the contracting officer for approval within the time frame specified (see 6.2). This report shall include a detailed description of all examinations and tests performed, deficiencies encountered, and actions taken to correct the deficiencies.

4.4 Quality conformance inspection.

4.4.1 Production examination. Each distributor shall be examined for the defects marked "X" in column 2 of table I. Presence of one or more defects shall be cause for rejection.

4.4.2 Production demonstration. Each distributor shall be demonstrated as specified in column 2 of table II. Failure of any demonstration shall be cause for rejection.

4.5 Inspection schedule.

4.5.1 Examination. Each distributor shall be examined in accordance with table I. The presence of one or more defects shall be cause for rejection. AQL shall be 1.0 percent defective.

TABLE I. Examination schedule.

| First Article | Production | Defect | Requirement Paragraph |
|---|---|---|---|
| 1 | 2 | 3 | 4 |
| X | X | 101. Distributor type not as specified. | 1.2 |
| X | X | 102. Distributor description not as specified. | 3.2 |
| X | X | 103. Towing devices not as specified. | 3.2 |
| X | - | 104. Material not as specified. | 3.5 |
| X | - | 105. Materials not resistant to corrosion and deterioration, or treated to be resistant to corrosion and deterioration of the applicable storage and operating environments. | 3.5.1 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

TABLE I. Examination schedule. Cont'd

| First Article | Production | Defect | Requirement Paragraph |
|---|---|---|---|
| 1 | 2 | 3 | 4 |
| X | - | 106. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other. | 3.5.2 |
| X | - | 107. Contractor does not have documentations available for identification of materials, material finishes, or treatment. | 3.5.3 |
| X | | | |
| X | - | 108. Used, rebuilt or remanufactured components, pieces, or parts incorporated in the distributor. | 3.5.4 |
| X | X | 109. Safety characteristics not as specified. | 3.6 |
| X | X | 110. Noise limit or warning plate not as specified. | 3.6.1 |
| X | - | 111. Dimensions not as specified. | 3.7.2 |
| X | X | 112. Sectionalization and components not as specified. | 3.8 |
| X | X | 113. Tractor section not as specified. | 3.10 thru 3.10.10.4 |
| X | X | 114. Water tanker section not as specified. | 3.11 |
| X | X | 115. Tank, man hole, and vents not as specified. | 3.11.1 thru 3.11.3 |
| X | X | 116. Catwalk and ladder not as specified. | 3.11.4 |
| X | X | 117. Running gear not as specified. | 3.11.5 |
| X | X | 118. Pump not as specified. | 3.12 |
| X | X | 119. Plumping and components not as specified. | 3.13 |
| X | X | 120. Water distribution system not as specified. | 3.14 |
| X | X | 121. Hydraulic system not as specified. | 3.15 |
| X | X | 122. Electrical System not as specified. | 3.16 thru 3.16.7 |
| X | X | 123. Antivandalism protection not as specified. | 3.17 |
| X | X | 124. Attachments not as specified. | 3.18 |
| X | X | 125. Transportability not as specified. | 3.19 thru 3.19.8 |
| X | X | 126. Identification plates not as specified. | 3.20 |
| X | X | 127. Vehicle weight classification numbers not applied as specified. | 3.20.1 |
| X | X | 128. Case not installed as specified. | 3.20.2 |
| X | X | 129. Instruction plates not as specified. | 3.21 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

TABLE I. Examination schedule. Cont'd

| First Article | Production | Defect | Requirement Paragraph |
|---|---|---|---|
| 1 | 2 | 3 | 4 |
| X | X | 130. Shipping data plates not as specified. | 3.22 |
| X | X | 131. Treatment and painting not as specified. | 3.23 |
| X | X | 132. Camouflage pattern data not provided as specified. | 3.23.1 |
| X | X | 133. Stenciling instructions not furnished. | 3.24 |
| X | X | 134. Lubrication not as specified. | 3.25 |
| X | X | 135. DAP mounting bracket not as specified or not installed as specified. | 3.26 |
| X | X | 136. Special tools not furnished. | 3.27 |
| X | X | 137. Toolbox not furnished. | 3.28 |
| X | X | 138. Workmanship not as specified. | 3.30 thru 3.30.3 |
| X | X | 139. Parts or components missing. | Sec. 3 |
| X | X | 140. Assembly incomplete or incorrect. | Sec. 3 |
| X | X | 141. Cracked or broken parts or assemblies. | Sec. 3 |
| X | X | 142. Permanent deformation of any part or assembly. | Sec. 3 |
| X | X | 143. Leaks in coolant, fuel, oil lines, or cylinders. | Sec. 3 |

4.5.2 Tests. Tests shall be conducted in accordance with table II. Prior conducting any operational tests, all STE/ICE-R diagnostic tests specified in 3.16.7 shall be measured and recorded.

TABLE II. Demonstration schedule.

| First Article | | Production | Test | Test Paragraph | Requirement Paragraph |
|---|---|---|---|---|---|
| 1 | | 2 | 3 | 4 | 5 |
| Type I | Type II | | | | |
| X | X | X | Production run-in | 4.5.2.1 | Section 3 |
| X | X | - | Noise level | 4.5.2.2 | 3.6.1 |
| - | X | - | Sectionalization | 4.5.2.3 | 3.2, 3.8 |
| X | X | - | ROPS/FOPS | 4.5.2.4 | 3.6.2 |
| X | X | - | Weight | 4.5.2.5 | 3.7.1 |
| X | X | - | Performance | 4.5.2.6 | 3.2, 3.9, 3.12 thru 3.15 |
| X | X | - | Travel | 4.5.2.7 | 3.9.1 |
| X | X | - | Braking | 4.5.2.8 | 3.9.2 |
| X | X | - | Stability | 4.5.2.9 | 3.9.3 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

TABLE II. Demonstration schedule. Cont'd

| First Article | | Production | Test | Test Paragraph | Requirement Paragraph |
|---|---|---|---|---|---|
| 1 | | 2 | 3 | 4 | 5 |
| Type I | Type II | | | | |
| X | X | - | Fording | 4.5.2.10 | 3.9.4 |
| X | X | - | Electromagnetic radiation | 4.5.2.11 | 3.16.3 |
| - | | | | | |
| X | X | - | DCA | 4.5.2.12 | 3.16.7 |
| X | X | - | STE/ICE-R | 4.5.2.13 | 3.16.7 |
| X | X | - | Transportability | 4.5.2.14 | 3.19 thru 3.19.8 |
| X | X | - | Water pumping System | 4.5.2.6 | 3.12 thru 3.15 |

4.5.2.1 Production run-in. Start and operate each distributor as follows:

Operate the distributor in all gears forward and reverse at maximum speeds commensurate with conditions for one-half hour. Stop and restart the engine not less than five times. Operate all pump and valve controls for five minute periods. Operate the distributor through not less than 10 full right and 10 full left turns at the maximum speed commensurate with safe operation. Make not less than five abrupt panic stops from a speed not less than 20 mph using the service brake. Release and reapply the parking brake not less than five times. Turn on all lights for the duration of the run-in. Evidence of any deficiency, need for adjustment or maintenance, malfunction of any control, or evidence of leakage of fuel, lubricants, or hydraulic fluid shall be cause for rejection of the distributor by the Government until corrected to the Government 's satisfaction. The Government may require additional run-in after deficiencies are corrected. Any defeat found during production run-in shall be prima facie evidence that distributors previously accepted are similarly defective unless evidence satisfactory to the contracting officer, is furnished by the contractor that they are not similarly defective.

4.5.2.2 Noise level test. Noise levels shall be measured in accordance with MIL-STD-1474 requirements and reported in the format indicated by MIL-STD-1474, figure 7. As a minimum, noise levels shall be measured when equipment is operating under full load. The noise level at the typical operating position shall be provided as, dB(A) level. Failure to comply with MIL-STD-1474 provisions and 3.6.1 shall constitute failure of this test.

4.5.2.3 Sectionalization. The type II distributor, less ROPS/FOPS, shall be demonstrated for compliance to sectionalization requirements of 3.8. Nonconformance to 3.8 shall constitute failure of this test. The demonstrations shall consist of the following:



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

a. Sectionalization. This demonstration shall be conducted on a relatively flat unimproved area of sufficient size for disassembly, maneuvering, and reassembly of the distributor. Using hand tools furnished with the distributor (no power tools allowed), separate the distributor into two sections. Drive the powered section trader its own power for a distance of 50 feet from the remaining section and steer the powered section at least 45 degrees to the longitudinal axis of the remaining section. Drive and steer the powered section to join with the remaining section and reassembly the two sections into a composite unit using the above hand tools only. Record the time required for the maneuvering and reassembly operation. No chains, cables, hoists, blocking, or other vehicles shall be used to assist in the disassembly, maneuvering, and reassembly operations. Nonconformance to 3.8 shall constitute failure of this demonstration. The sectionalization demonstration will be compared to the disassembly and assembly instruction specified in 3.21. In addition, those assemblies or components unique to the type II vehicle, or required as a result of the sectionization feature, shall be evaluated and verified as a part of this test, to include disassembly, examination, and reassembly. Maintenance function, procedures, or tools peculiar to the type II equipment, as well as publications associated with the specific features of sectionization, shall also be evaluated and verified. All errors in publications or procedures shall be corrected by the contractor and submitted to the Government for approval prior to acceptance of the preproduction model of the distributor. During this demonstration, the water distribution functions and maintenance tasks shall be performed following procedures in the technical publications using common tools plus any special tools identified by the contractor.

4.5.2.4 ROPS/FOPS. The ROPS and FOPS shall be tested in accordance with SAE J1040 and SAE J231. The removal and replacement of the ROPS/FOPS canopy shall be demonstrated following the procedures in the contractor's manual. Permanent deformation or damage to any part of the ROPS/FOPS canopy or its mounts, or inability to meet the requirements of 3.6.2 and 3.19 shall constitute failure of this demonstration.

4.5.2.5 Weight. The weights of the distributor and the distributor sections (type II only) shall be measured with a scale calibrated within 6 months of the demonstration. Inability to meet the minimum and maximum weight limits of 3.7.1 shall constitute failure of this demonstration.

4.5.2.6 Performance. The distributor shall be demonstrated as follows for a minimum total of 40 hours to prove conformance to 3.2, 3.9, and 3.12 through 3.15.

a. Travel - Drive the distributor at maximum speed over a smooth paved surface and over gravel and crushed stone haul roads and unimproved trails. Negotiate the distributor over off-road terrain. Demonstrate the distributor's ability to ford creeks and to cross V-ditches, typical of those along highways. Negotiate mud at least 12-inches deep while steering to both right and left (duck-walk). Immobilize the distributor in the muddy area and demonstrate its ability to withstand being retrieved by towing out or pushing out, both forward and rearward; continue towing the distributor with the engine shut down to a simulated, suitable repair area.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

b. Self-loading - Demonstrate the self-loading ability of the distributor for 10-tank fillings from a water source, 10-feet below the center of the pump inlet.
c. Water distributing - Demonstrate the fan nozzle capability from all nozzles, distributing a total of 10-tank fulls at maximum flow. Then, demonstrate the individual capability at each nozzle to distribute water, 1/2-tank full at minimum spray pattern and the remaining 1/2-tank full at maximum spray pattern. Manually rotate each nozzle 180° using common hand tools.
d. Water pump demonstration - Perform a demonstration of the water pump operational capability for a minimum of 2 hours pumping water at the capacity rated by the manufacturer. Correct all data to standard sea level atmospheric conditions of 29.92-inches of mercury and to the specific weight of water (62.3-pounds per cubic foot) at a temperature of 68 °F and compare with manufacturer's rating.

Nonconformance to 3.9, 3.12 through 3.15 or any malfunction or breakage of mechanical, hydraulic, or compressed air components, evidence of leakage, inability of the pump to operate up to rated capacity or as specified shall constitute failure of this demonstration.

4.5.2.7 Travel speed. The travel speed of the distributor shall be measured to prove conformance to 3.9.1. Nonconformance to 3.9.1 shall constitute failure of this test.

4.5.2.8 Braking system. The brakes shall be tested to prove conformance to 3.9.2. Nonconformance to 3.9.2 shall constitute failure of this test.

4.5.2.9 Stability. The stability of the distributor shall be measured to prove conformance to 3.9.3. Nonconformance to 3.9.3 shall constitute failure of this test.

4.5.2.10 Fording. The fording ability of the distributor shall be measured to prove conformance to 3.9.4. Nonconformance to 3.9.4 shall constitute failure of this test.

4.5.2.11 Electromagnetic radiation. The distributor shall be measured to prove conformance for requirements in 3.16.3. Nonconformance to 3.16.3 shall constitute failure of this test.

4.5.2.12 DCA capability. The distributor manufacturer shall conduct the appropriate test procedure to verify that the DCA harness is properly wired and free of errors that could damage the distributor wiring and components or the STE/ICE-R vehicle test meter (VTM). All DCAs must be tested with a DCA wiring tester or equivalent and be free of defects. Nonconformance shall constitute failure of the DCA. Operational testing of the DCA and its capability shall be performed during the performance testing. Nonconformance to 3.16.7 shall constitute failure of this test.

4.5.2.13 STE/ICE-R interface. Test the DCA for all measurement specified in 3.16.7 using STE/ICE-R. After completion of all first article testing, the test shall be repeated and the results compared to the first test performed as specified in 4.5.2. Nonconformance to 3.16.7 or failure of any component or



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

wiring in the DCA harness, which result in inability to obtain the measurements previously recorded with the STE/ICE-R (see 4.5.2) shall constitute failure of this test.

4.5.2.14 Transportability tests. The distributor shall be tested for transportability as follows:

4.5.2.14.1 Tiedown provisions test. The tiedown provisions shall be tested in accordance with MIL-STD-209 to prove conformance to 3.19.1. Inability to meet the requirements of 3.19.1 shall constitute failure of this demonstration.

4.5.2.14.2 Slinging provisions test. The slinging provisions shall be tested in accordance with MIL-STD-209 to prove conformance to 3.19.2. Inability to meet the requirements of 3.19.2 shall constitute failure of this demonstration.

4.5.2.14.3 Air transport test. The distributor shall be tested in with MIL-STD-1791 to prove conformance to 3.19.3. Inability to meet the requirements of 3.19.3 shall constitute failure of this demonstration.

4.5.2.14.4 Rail impact test. The first article distributor shall be tested in accordance with MIL-STD-810 to prove conformance to 3.19.4. Inability to meet the requirements of 3.19.4 shall constitute failure of this demonstration.

4.5.2.14.5 Highway transport test. Inability to meet the requirements of 3.19.5 shall constitute failure of this demonstration.

4.5.2.14.6 Parachute suspension provision tests. The first article distributor shall be tested in accordance with MIL-STD-814 to prove conformance to 3.19.6. Inability to meet the requirements of 3.19.6 shall constitute failure of this demonstration.

4.5.2.14.7 Extraction parachute provision test. The first article distributor shall be tested in accordance with MIL-STD-814 to prove conformance to 3.19.7. Inability to meet the requirements of 3.19.7 shall constitute failure of this demonstration.

4.5.2.14.8 Airdrop tests. The first article distributor shall be tested in accordance with MIL-STD-669 to prove conformance to 3.19.8. This demonstration will be conducted by the Government at a Government facility, however, acceptance of the first article models will be dependent on the successful completion of this demonstration. The demonstration shall consist of the following:

a. Rig the machine in accordance with MIL-STD-669 and confirm that the rigged weight and dimensions conform to the requirements of the AFSC Design Handbook DH1-11.
b. Drop test the machine in accordance with MIL-STD-669.
c. After the first drop, the machine shall be de-rigged, examined, started, and driven forward and backward a few feet, and all controls shall be actuated.
d. The machine shall then be sectionalized and reassembled in accordance with the contractor's instructions to ascertain that no damage was done to the sectionalization features by the test drop. (This step is omitted for the type I machine).



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

e. Re-rig and drop test the machine a second time in accordance with MIL-STD-669.
f. After de-rigging, the distributor shall be demonstrated for 8 hours performing tasks in 4.5.2.6.

Failure to meet the weight and dimensional requirements of Design Handbook DH1-11, and the requirements of 3.19.8 weld failure, leakage, permanent deformation of any structural member or components, inability to reassemble the components removed for airdrop, inability to disassemble and reassemble the type II distributor, or inability of the distributor to perform its intended functions shall constitute failure of this demonstration.

4.5.2.14.9 Failure criteria. Failure to meet the requirements of 3.19 and 4.6.1.2 tests shall constitute failure of this test.

4.6 Inspection of packaging. The preservation packing and marking shall be examined for compliance with the quality assurance provisions of MIL-D-771 and any additional requirements specified in section 5, herein.

5. PACKAGING

5.1 Preservation. Preservation shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. Each complete distributor, components and attachments, shall be preserved in accordance with the level A requirement of MIL-D-771.

5.1.2 Level B. Each complete distributor, components and attachments, shall be preserved in accordance with the level B requirements of MIL-D-771.

5.1.3 Level C. Each complete distributor and all items issued with the distributor shall be preserved in the following manner: Items with critical surfaces required for fit or function shall be provided protection by the use of preservative coating, volatile corrosion inhibitors, or desiccated packs. Items requiring protection from physical damage to surfaces, or which are fragile by nature, shall be protected by wrapping, pack compartmentalization, or cartonizing of the individual item. The cooling system shall be filled with a fresh solution of 50 percent water and 50 percent antifreeze, conforming to MIL-A-46153, and a tag attached indicating the temperature to which the cooling system can be subjected to before freezing. The crankcase shall contain the required amount of lubricating oil. A guide shall be furnished indicating the preservation and packing materials to be removed, in detail, and any other servicing required prior to placing the distributor in operation.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A. Each complete distributor, preserved as specified in 5.1, shall be packed in accordance with the level A requirements of MIL-D-771.

5.2.2 Level B. Each complete distributor, preserved as specified in 5.1, shall be packed in accordance with the level B requirements of MIL-D-771.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. Each complete distributor, preserved as specified in 5.1, shall be packed to assure carrier acceptance and safe delivery to destination at lowest ratings in compliance with Uniform Freight Classification Rules or National Motor Freight Classification Rules.

5.3 Marking. In addition to any special marking specified in the contract or purchase order (see 6.2), marking shall be in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The water distributor covered by this specification is intended for world-wide, earthmoving and construction projects by the Armed forces in engineer troop support use in soil stabilization, soil compacting, dust alleviation, and limited fire fighting.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of the specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1).
c. Type of water distributor required (see 1.2).
d. Number and type of first article distributors, time frame required for submission, and whether the Government will conduct any or all of the examinations and tests. When the Government will conduct some but not all of the first article examinations and tests, the contracting officer should specify which examinations and tests will be conducted by the Government and which examinations and tests shall be conducted by the contractor (see 3.2).
e. When a DCA is not required (see 3.16.7).
f. When additional test parameters are required (see 3.16.7).
g. Color required when other than as specified (see 3.23).
h. When overcoating with camouflage patterns is required (see 3.23).
i. When the contractor shall provide camouflage pattern data (see 3.23.1).
j. When special tools shall not be furnished (see 3.27).
k. When GFP is required to be furnished (see 3.30).
l. Time frame for submitting first article test report (see 4.3.3).
m. Level of preservation and packing required (see 5.1 and 5.2).
n. Special marking required (see 5.3).
o. Timeframe for completing and submitting the vehicle classification (see 6.7).
p. When items on the basic issue items list are not required (see 6.8).
q. Time frame for completing and submitting a TIP (see 6.9).
r. When transportability report required (see 6.11).

6.3 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DIDs) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DIDs are tailored to reflect the requirements of the specific acquisition to



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

ensure correct contractual application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

| Reference Paragraph | DID Number | DID Title |
|---|---|---|
| a. 3.23.1 | DI-MISC-80192 | Color photograph prints |
| b. 3.23.1 | DI-MISC-80176 | Camouflage line art data |

The above DIDs were those cleared as of the date of the specification. The current issue of DoD 5010.12-L, Acquisition Management System and Data Requirements Control List (AMSDL), must be researched to ensure the only current, cleared DIDs are cited on the DD Form 1423.

6.4 First article. When a first article inspection is required, the item(s) should be a production model. The first article should consist of one or more units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of the first article test results and disposition of the first articles. Invitation for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.5. Government-furnished property. The contracting officer should arrange to furnish the property specified in 3.29.

6.6 Lubricants. MIL-STD-838 prescribes the policy for using specification-type products wherever possible and provides specific requirements for potential use of non-standard proprietary products. MIL-STD-838 is implemented by MIL-HDBK-113. The contracting officer should note that unless otherwise authorized by the US Army Belvoir Research, Development, and Engineering Center (ATTN: STRBE-VF), Fort Belvoir, VA 22026-5606, lubricants, fluids, and greases for ground equipment systems must be restricted to those listed under MIL-HDBK-113, chapter 2.

6.7 Vehicle classification. The contracting officer should arrange to furnish a vehicle classification specification sheet to the contractor and request the return of reviewed sheet to the Government. The information thus obtained should be utilized to determine the weight classification numbers for the distributor. The contracting officer should then request the contractor to apply the numbers to the distributor. The use of a Government-furnished sign kit conforming to MIL-S-40626 should be utilized where applicable (see 3.20.1).

6.9 Basic issue items. The contracting officer should arrange to furnish the Basic Issue Item List.

6.9 Technical information package (TIP). When required (see 6.2), the contractor shall complete and submit a TIP within the timeframe specified depicting the distributor and its components exactly as it will be furnished, subject to 3.19.3. Notation shall be made of all components which have not been in field use



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

for a minimum of 1 year and shall include identification of the component or part previously used. The TIP shall be submitted with all bids and proposals. Copies of the TIP are available from the Belvoir Research, Development and Engineering Center, ATTN: STRBE-FMT, Fort Belvoir, VA 22060-5606.

6.10 Technical manuals. The requirement for technical manuals should be considered when this specification is applied on a contract. If technical manuals are required, military specifications and standards that have been cleared and listed in DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL) must be listed on a separate Contract Data Requirements List (DD Form 1423), which is included as an exhibit to the contract. The technical manuals must be acquired under separate contract line item in the contract.

6.10.1 Technical manual approval. The contracting officer should arrange for the technical manuals to be submitted to TACOM (AMSTA-MD) for review and approval.

6.11 Transportability report. When specified (see 6.2), the contracting officer should arrange for the contractor to furnish a transportability report in accordance with AR 70-47 and S.O.P 70-38 for the distributor 95 days prior to delivery of the first article distributor.

6.12 DCA test development. The contracting officer shall arrange for the contractor to grant the Government access to 7-10 distributors for test and development of algorithm constants/limits for the following dynamic STE/ICE-R tests:

a. Engine power.
b. Compression unbalance.
c. Starter current first peak.
d. Internal battery resistance.
e. Starter circuit resistance.
f. Battery resistance change.

The distributors, support personnel and indoor facilities must be available for three consecutive 5 work weeks. The distributors selected for test should be in like new condition, in production configuration, with vehicle engines having break-in road mileage of not less than 200 miles.

6.12.1 DCA design approval. The contracting officer should arrange for the DCA design to be submitted to TACOM (AMSTA-MD) for review and approval.

6.13 Subject term (key word) listing.

2500 gallon
Air droppable
Air transportable
Articulated steering
Distributor
Helicopter transportable
Nonsectionatized
Sectionatized
Self propelled
Water



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

6.14 Changes from previous issue. Asterisks (or vertical lines) are riot used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - ME

Preparing activity:
Army - ME

User activity:
Army - AT

Project 3825-A184



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.