INCH-POUND

MIL-F-48863C (AR)
AMENDMENT 2
17 APRIL 1989
SUPERSEDING
AMENDMENT 1
17 September 1987

MILITARY SPECIFICATION

FUZE, GUIDED MISSILE, M934E6 PARTS
ASSEMBLY, LOADING AND PACKING FOR

This Amendment forms a part of Military Specification MIL-F-48863C (AR), dated 01 July 1985, and is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 13

3.3.2: Add the following:

"3.3.2.1 Process control documents. Where adhesives, sealants or lubricants are permitted or required by the drawings, a process control document is required in accordance with MIL-A-48078."

3.3.3, line 4: After ". . . in the contract" add ", and shall include an analysis of Critical Defect material handling (see 3.5)."

PAGE 15

Add the following:

"3.5 Critical defect material handling. An analysis of Critical Defect material handling shall be made in accordance with MIL-A-48078. This analysis shall be provided to the Government prior to First Article Submission."

PAGE 18

* 4.3.2.1.1/b: Delete "(SD)" after "Static Detonator Safety". Under req/method paragraph column: Delete "3.2.9.3"

* 4.3.2.1.1/b: Delete "SD - Initiate detonator by self destruct mode".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

PAGE 31

4.4.2.8, Major 101: Delete ".25%" and substitute "--".

PAGE 34

4.4.2.11, Minor 204: Delete "UNF-28" and substitute "UNF-2B".

PAGE 35

4.4.2.12: Add new major category:

"Category Major	Exam or Test	AQL or 100%	Req. Para.	Para Ref/ Insp. Meth.
102	Adhesive on shoulder-stop pins missing or improperly applied following cure."	.40%	3.3.1.3	Visual

PAGE 36

4.4.2.13: Add new major category

"Category Major	Exam or Test	AQL or 100%	Req. Para.	Para Ref/ Insp. Meth.
106	Sealant on 22 g lock screw missing or improperly applied"	100%	3.3.1.3	Visual

PAGE 39

4.4.2.16, Minor 203: In column labeled Paragraph Reference/ Inspection Method delete "Gage" and substitute "Visual".

* 4.4.2.16, Minor 205: In column labeled examination or test add "1/".

* Notes: Add "1/ "Cracks are permitted in part number 9297032 after potting provided they do not alter the physical integrity and profile of the potted module and epoxy has not exuded beyond the surface of 9297032. The cracks may be of any configuration in any location on the module."

PAGE 41

4.4.2.18, Major 105: Delete "Slope, diameter, and true position of window recess to outside diameter" and substitute "Slope and virtual condition of the window recess".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

PAGE 47

4.4.2.24; Major III: delete "Actuator" and substitute "Lever"

PAGE 49

4.4.2.26, Major 101: Delete "B-B" and substitute "A-A".

4.4.2.26, Major 104: Delete "A-A" and substitute "B-B".

PAGE 50

4.4.2.26, Minor 201: Delete "from centerline large" and substitute "centerline to the large".

4.4.2.26, Minor 205: Delete "breaks in to " and substitute "breaks into."

4.4.2.26, Minor 206: Delete "size and true position" and substitute "maximum and minimum virtual condition".

PAGE 51

4.4.2.26, Minor 208: Delete "size and true position" and substitute "maximum virtual condition".

4.4.2.26, Minor 209: Delete "size and true position: and substitute "maximum and minimum virtual condition".

PAGE 54

4.4.2.27, Major 116: Delete "Large radius and true position shown in section P-P" and substitute "Maximum and minimum virtual condition inspected with respect to Datums C-D and E-F of the large radius shown in section P-P".

4.4.2.27, Major 117: Delete "angled large threaded hole, Datum H," and substitute "Datum H".

4.4.2.27, Minor 203: Delete "Depth of second deepest recess" and substitute Depth of third deepest recess".

PAGE 57

4.4.2.30, Major 101: Delete "Dimension and location" and substitute "Maximum and minimum virtual condition".

PAGE 61

4.4.2.34, Major 101: Delete "Lens height" and substitute "Distance from tab to end opposite the lens".

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:42Z
Check the source to verify that this is the currentversion before use.

PAGE 62

4.4.2.35, Major 101: Delete "Lens height" and substitute "Distance from tab to end opposite the lens".

PAGE 65

4.4.2.38, Major 106: Under column labeled Paragraph Reference/Inspection Method delete "3.2.13.8".

4.4.2.38, Major 106: Under column labeled Reference Paragraph add "3.2.13.8".

PAGE 73

4.5.20.1, line 3: Delete "Move" and substitute "With the rotor locked in the armed position, move".

PAGE 75

6.3, line 4: Delete ",Dover, NJ 07801." and substitute "(D), Picatinny Arsenal, NJ, 07806-5000.".

*The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian
Army-AR

Peparing activity:
Army-AR

(Project 1336-A585)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.