MILITARY SPECIFICATION

HANDLING TOOL, ATOMIC WEAPON CASE SECTION: H-4141 AND H-4192

1. SCOPE

1.1 Scope. This specification covers requirements, quality assurance provisions and the preparation for delivery criteria for two types of handling equipment used with the Honest John warhead section.

1.2 Classification. This specification covers Handling Tool, Case Section, Atomic Weapon of the following H4141 and H4192.

Type I - Handling Tool, Case Section, Atomic Weapon: H4141.
Type II - Handling Tool, Atomic Weapon Case Section: H4192.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-T-5021 - Tests; Aircraft Welding Operators Certification.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168 - Lot Numbering of Ammunition.

DRAWINGS

ORDNANCE CORPS

8826399 - Handling Tool Case Section, Atomic Weapon: H-4141
8848565 - Handling Tool, Atomic Weapon Case Case Section: H-4192

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

EL-8856520 - Equipment List.
8858718 - Carton, Packing for Handling Tool, Case Section, Atomic Weapon: H4141.
8858719 - Box, Packing for Handling Tool, Case Section, Atomic Weapon: H4141.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The handling tool assembly shall comply with all requirements specified on the drawing (dwg 8826399 and 8848565, with all requirements specified herein, and with the requiements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Serialization. A six letter serial code shall be assigned to the item. Serial codes required on these items shall be obtained by means of a letter addressed to: Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTENTION: SARPA-QA-T-M. The letter of request shall include:

a. Exact nomenclature of the item as specified on the applicable drawing.
b. Name of the contractor.
c. Contract number or procurement request order number.
d. Number of serial codes required (unused code numbers. shall be returned).

3.4 Static load. The handling tool assembly shall be capable of supporting a 1,000 pound load without evidence of permanent distortion, cracked welds or structural weakness when tested as specified in 4.3.1.

3.5 Welding. Welds shall be reasonably smooth and free of craters. They shall exibit characteristics of fusion, penetration and soundness of weld deposit representative of good welding practice. They shall be free of irregularities which indicate lack of good practice on the part of the operator. All welding fluxes, scale, weld spatter, guide, and basic solutions shall be removed prior to application of any finish coat.

3.5.1 Welding operators. All fusion welding shall be performed by operators who are currently certified as Class "B" welders in accordance with MIL-T-5021.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

3.6 Workmanship.

3.6.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.6.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.6.3 Burrs. Parts shall be free from burrs.

3.6.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.6.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection.

4.2.1 Lot formation.

4.2.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.2.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

4.2.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table I and Table II), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44=47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table II
MInor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.2.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.2.2.1.1 Handling tool, case section, atomic weapon, H4141 (see dwg. 8826399) and handling tool, atomic weapon case section H4192 (see dwg 8848565).

Categories	Characteristics	Method of Inspection
Critical:		
1.	Crack in weld	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

2. Improper welding (see 3.5).....Visual

Major:

101. Incorrect radius.....Gage
102. Location of latch slot.....Gage
103. Depth of latch slot.....Gage
104. Inability of latch to hold its position.....Visual
105. Incorrect torque on nut.....Manual
106. Objective evidence relating to material missing or improper (see 3.1).....Visual
107. Serialization improper or missing (see 3.3).....Visual

Minor:

201. Marking missing, incorrect or unidentifiable.....Visual
202. Protective finish damaged to the extent of exposing base metal.....Visual
203. Evidence of poor workmanship (see 3.6).....Visual

4.2.2.1.2 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major:		
101.	Preservation, packing, and packaging not in accordance with applicable drawings	Visual
102.	Marking not in accordance with applicable drawings	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

4.2.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

	Test	Test classification
a.	Static load	Major

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.2.3.1 Static load. Each handling tool in the lot shall be tested in accordance with 4.3.1. If any item fails to comply with 3.4, the item shall be rejected and removed from the lot.

4.2.4 Acceptance inspection equipment.

4.2.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (See EL-8856520). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.2.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.3 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.3.1 Static load. A 1,000 pound static weight having a surface which mates with the curvature of the handling tool assembly shall be secured to the fixture and raised vertically to an elevation of 4 feet. After 1 minute at this height, the load shall be lowered and disengaged from the lift fixture assembly.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The handling tool shall be packaged in accordance with dwg 8858718 using the specified moisture barrier.

5.1.2 Level C. The handling tool shall be packaged in accordance with dwg 8858718 except that the moisture barrier may be omitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.

5.2 Packing.

5.2.1 Level A and C. The handling tool shall be packed in accordance with dwg 8858719.

5.3 Marking. Marking shall be as specified in accordance with dwg 8858718 and 8868719.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.

b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.2.4.1). Data specified in 4.2.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.2.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-N-I.

6.4 Supersession data. This specification supersedes the requirements of Purchase description PA-PD-1992 Amendment 1 dated 22 January 1964.

Custodian.
Army - PA

Preparing activity:
Army - PA

Project No. NUOR-A016

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:29Z
Check the source to verify that this is the current version before use.