MILITARY SPECIFICATION

REGULATOR: 11733468

This specification is approved for use by all Department and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of electronic assembly known as Regulator, 11733468 (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-F-13926	Fire Control Material, General Specification Governing the Manufacture and Inspection of
MIL-F-14232	Parts, Equipment and Tools for Army Materiel; Packaging and Packing of
MIL-I-45607	Inspection Equipment, Acquisition Maintenance and Disposition of

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	Quality Assurance Terms and Definitions
MIL-STD-202	Test Methods for Electronic and Electrical Component Parts

DRAWINGS

U.S. Army, Frankford Arsenal

D11733468	Regulator

PACKAGING DATA SHEET

PS11733468	Regulator

(Copies of specifications, standards, drawings, and packaging data sheets required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Fabrication .- This Regulator shall be manufactured in accordance with Drawing D11733468 and all drawings pertaining thereto, and shall conform to the requirements of 3.3 through 3.3.2 inclusive.

3.2 Materials.- Materials shall be in accordance with drawings, material specifications and general specifications forming a part of this specification.

3.2.1 Nonflammable materials.- External parts and coatings of the regulator shall be of nonflammable material.

3.2.2 Fungus resistant material.- Regulator external parts shall be inherently nonnutrient of fungus.

3.2.3 Inclosure.- The regulator shall be inclosed in a metallic case which shall be insulated from one input terminal and one output terminal and one battery contact.

3.2.4 External surfaces.- Surfaces shall exhibit no evidence of peeling, flaking, chipping, cracking, crazing, or other impairment of the coating subsequent to meeting the requirements specified herein.

3.3 Construction.- The regulator shall be manufactured in accordance with Drawing D11733458. Where specific manufacturing processes are not specified, good commercial methods consistent with the present state of the art shall be employed.

3.3.1 Internal wiring.- Internal dress of wires shall assure that no electrical short circuits occur under mechanical shock and vibration.

3.3.2 Internal components.- Components in the regulator shall be rigidly secured to prevent permanent change in their relative position. Mounting methods shall not depend on solder alone for mechanical strength. Potting compound alone may be used to prevent movement of internal components, providing the compound does not flow at the specified maximum operating temperature (see 3.5.2).

3.4 General specification.- The contractor shall be responsible for adherence to and compliance with the following requirements of Specification MIL-F-13926:

(a) Order of precedence.
(b) Dimension-s and tolerances.
(c) Inorganic protective surface finishes.
(d) Part identification and marking.
(e) Workmanship.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

3.5 Regulator performance: Environmental .- The regulator shall show no evidence of damage after exposure to 3.5.1 and 3.5.3 through 3.5.5. The regulator shall then be exposed. to 3.5.2. Specified ambient temperature extremes shall be within ± 5°F.

3.5.1 Temperature cycling and thermal shock.- The regulator shall withstand in uninterrupted sequence the following ambient temperature excursions:

(a) A gradual decrease from 75 ± 15°F to -80°F, maintained for at least one hour.
(b) A gradual increase to -25°F, maintained for at least one hour.
(c) Immediate exposure to 75 ± 15°F, maintained for at lest one hour.
(d) A gradual increase from 75 ± 15°F to 160°F, maintained for at least one hour.
(e) A decrease to 125°F, maintained for at least one hour.
(f) Immediate exposure to 75 ± 15°F.

3.5.2 Operating temperature.- Unless otherwise specified, the regulator shall meet the requirements of 3.6 and 3.7, after at least a two hour exposure, at the ambient temperatures of -40°F and +125°F.

3.5.3 Hermetic sealing.- When thermally stabilized at an ambient temperature not in excess of 100°F, the regulator shall exhibit no evidence of compound or air leakage when immersed (for no less than two minutes, and no more than three minutes) in a bath of water maintained at a minimum ambient temperature of 180°F.

3.5.4 Shock.- The regulator shall show no evidence of damage when subjected to 6 shock pulses parallel to, and 6 shock pulses perpendicular to its longitudinal axis, at an ambient temperature of 75 ± 15°F. Each shock impact shall have the following characteristics.

(a) A half-sine wave pulse of at least 75 gravity units (G's) at its peak.
(b) A pulse duration of 6 ± 2 milliseconds between the 10% values of its peak amplitude.
(c) The energy under each shock curve shall-not be less than 0.25 G second.
(d) The after oscillations shall not exceed 15% of the nominal half-sine wave peak amplitude.

3.5.5 Vibration.- The regulator shall show no evidence of damage when vibrated for 10 minutes in each of its 3 mutually perpendicular axes (total of 30 minutes) at an ambient temperature of 75 ± 15°F. The vibration shall be a simple harmonic motion having a 0.03 inch amplitude (0.06 inch total excursion). The frequency shall vary uniformly over a range of 10 to 55 cycles per second (cps) and return to 10 cps in one minute.

Source: https://assist.dla.mil -- Downloaded: 20261010-22T19:26Z
Check the source to verify that this is the current version before use.

3.6 Performance electrical.

3.6.1 Polarization of input terminal.-The regulator input terminal shall be polarized positive with respect to the regulator metallic case, which shall be negative and considered as electrical circuit ground.

3.6.2 Polarization of output terminal.- The regulator output terminal shall deliver an electrical potential of positive polarity with respect to the regulator metallic case, which shall be negative and considered as electrical circuit ground.

3.6.3 Polarization of battery terminal.- The regulator battery terminal shall be polarized positive with respect to the regulator metallic case, which shall be negative and considered as electrical circuit ground.

3.6.4 Input potential.- The regulator shall be energized by a direct current (de) electrical potential of from 18.0 to 30.0 volts.

3.6.5 Reverse polarity.- The regulator shall not be damaged by the application of electrical potentials of 3.6.4 in reverse polarity.

3.7 Performance - operational.- The regulator shall exhibit no spasmodic or intermittent operation when meeting the following requirements:

3.7.1 Electrical shock.- The regulator under full load (see 3.7.3) shall meet the following requirements after being subjected to one hour of intermittent operation consisting of a continuously repetitive 30 second ON and 30 second OFF cycle at an ambient temperature of 75 ± 15°F only.

3.7.2 Input voltage surge.- The regulator shall show no evidence of damage, and shall exhibit no increase in output voltage for any time period, when the regulator input is subjected to at least a 100 millisecond voltage spike having a minimum amplitude of 80.0 dc volts.

3.7.3 Output current.- The regulator shall deliver, under full load, at least 45.0 dc milliamperes when meeting the requirement 3.7.5.

3.7.4 Output voltage.- The regulator shall deliver a dc voltage of 2.65 ± .3 volts at all operating temperatures described in 3.5.2. Above outputs shall be with an input. voltage over the range specified in 3.6.4.

3.7.5 Emergency power source.- The regulator shall supply a voltage at the output connector equal to. the voltage of two BA-42 batteries. This voltage shall be connected to tthe battery contact positive with respect to case ground, with no voltage applied to the input. When an input is supplied over the range specified in 3.6.4 the output shall be that specified in 3.7.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

3.6 Performance electrical.

3.6.1 Polarization of input terminal.-The regulator input terminal shall be polarized positive with respect to the regulator metallic case, which shall be negative and considered as electrical circuit ground.

3.6.2 Polarization of output terminal.- The regulator output terminal shall deliver an electrical potential of positive polarity with respect to the regulator metallic case, which shall be negative and considered as electrical circuit ground.

3.6.3 Polarization of battery terminal.- The regulator battery terminal shall be polarized positive with respect to the regulator metallic case, which shall be negative and considered as electrical circuit ground.

3.6.4 Input potential.- The regulator shall be energized by a direct current (de) electrical potential of from 18.0 to 30.0 volts.

3.6.5 Reverse polarity.- The regulator shall not be damaged by the application of electrical potentials of 3.6.4 in reverse polarity.

3.7 Performance - operational.- The regulator shall exhibit no spasmodic or intermittent operation when meeting the following requirements:

3.7.1 Electrical shock.- The regulator under full load (see 3.7.3) shall meet the following requirements after being subjected to one hour of intermittent operation consisting of a continuously repetitive 30 second ON and 30 second OFF cycle at an ambient temperature of 75 ± 15°F only.

3.7.2 Input voltage surge.- The regulator shall show no evidence of damage, and shall exhibit no increase in output voltage for any time period, when the regulator input is subjected to at least a 100 millisecond voltage spike having a minimum amplitude of 80.0 dc volts.

3.7.3 Output current.- The regulator shall deliver, under full load, at least 45.0 dc milliamperes when meeting the requirement 3.7.5.

3.7.4 Output voltage.- The regulator shall deliver a dc voltage of 2.65 ± .3 volts at all operating temperatures described in 3.5.2. Above outputs shall be with an input. voltage over the range specified in 3.6.4.

3.7.5 Emergency power source.- The regulator shall supply a voltage at the output connector equal to. the voltage of two BA-42 batteries. This voltage shall be connected to tthe battery contact positive with respect to case ground, with no voltage applied to the input. When an input is supplied over the range specified in 3.6.4 the output shall be that specified in 3.7.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

3.7.6 Rise time. - The regulator shall meet the output voltage requirement of 3,7.5 within 3.0 milliseconds of applying an input voltage of from 18.0 to 30.0 dc volts.

3.8 Reliability.- The minimum operating life of the Regulator shall be 1000 hours of continuous operation, and shall meet all requirements of this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government.The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General provisions.- The component and subassembly inspection requirements of MIL-F-13926 form a part of the quality assurance provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 First article (initial production) approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of 10 regulators manufactured in the same manner using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.2.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.2.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection.

4.3 Inspection provisions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

4.3.1 Submission of product.- Unless otherwise specified by the contracting officer, inspection lot size, lot formation and presentation of lots shall be in accordance with "Submission of Product" provisions of MIL-STD-105.

4.3.2 Examination and test.- Examination and tests related to Section 3 herein shall be performed on a single defect (individual characteristics) basis in accordance with MIL-STD-105 and the sampling plans specified in Tables I, II and III herein. Examinations and tests for packaging, packing and marking shall be in accordance with MIL-P-14232 and Section 5 herein. The tabulated classification of defects in Tables I, II and III shall constitute the minimum inspection to be performed by the supplier after first article approval and prior to Government acceptance or rejection by item or lot.

TABLE I - CLASSIFICATION OF DEFECTS- 100% INSPECTION

No.	CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
101.	Polarization of input terminal	3.6.1	4.6.3.1
102.	Polarization of output terminal	3.6.2	4.6.3.2
103.	Polarization of battery terminal	3.6.3	4.6.3.3
104.	Input potential	3.6.4	4.6.3.4
105.	Reverse polarity	3.6.5	4.6.3.5
106.	Electrical shock	3.7.1	4.6.4.1
107.	Input voltage surge	3.7.2	4.6.4.2
108.	Output current	3.7.3	4.6.4.3
109.	Output voltage	3.7.4	4.6.4.4
110.	Emergency Power Source	3.7.5	4.6.4.5
111.	Rise time	3.7.6	4.6.4.5

NOTE: The tests in Table I shall be conducted at a temperature between +70°F and +80°F.

4.3.3 Acceptance and rejection.- Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in MIL-STD-105.

4.4 Special sampling.

4.4.1 General.- Three assemblies shall be selected at random as a special sampling from each 50 produced. The sample shall meet the requirements and tests in Table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

TABLE II

NO.	CHARACTERISTIC C	Requirement	TEST PROCEDURE
301.	Fabrication	3.1 and 3.3	4.6.1.1
302.	Materials	3.2	4.6.1.2
303.	Non-flammable materials	3.2.1	4.6.1.2.1
304.	Inclosure	3.2.3	4.6.1.2.3
305.	External surfaces	3.2.4	4.6.1.2.4
306.	Construction	3.3	4.6.1.3
307.	Internal wiring	3.3.1	4.6.1.3.1
308.	Internal components	3.3.2	4.6.1.3.2
309.	General specifications	3.4	Visual - MIL-F-13926

NOTE: The tests in Table II shall be conducted at a temperature between +70°F and +80°F.

4.4.2 Environmental.- Three assemblies shall be selected at random as samples from each 50 produced, or from each month's production, whichever occurs first. Each sample shall meet the requirements and tests in Table III and shall then meet the requirements and tests in Table I.

TABLE III

NO.	CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
303.	Temperature cycling and Thermal Shock	3.5.1	4.6.2.1
304.	Operating Temperature	3.5.2	4.6.2.2
305.	Hermetic Sealing	3.5.3	4.6.2.3
306.	Shock	3.5.4	4.6.2.4
307.	Vibration	3.5.5	4.6.2.5

4.4.3 Failure of sample.- Should any one item of a special sampling fail to meet the specified test requirements, acceptance of the represented inspection lot shall be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted items have been approved (see 4.3.3).

4.5 Inspection equipment.- Except as otherwise provided for by the contract, the contractor shall supply and maintain inspection equipment in accordance with the applicable requirements of MIL-I-45607.

4.5.1 Government furnished inspection equipment.- Where the contract provides for Government furnished test equipment, supply and maintenance of test equipment shall be in accordance with applicable requirements specified in MIL-I-45607.

4.5.2 Contractor furnished inspection equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

4.5.2.1 Government design- All inspection equipment specified by drawing number in specifications or SQAP forming a part of the contract shall be supplied by the contractor in accordance with technical data included in the technical data package list.

4.5.2.2 Contractor design.- The contractor shall design and supply inspection equipment compatible with the “Test Methods and Procedures" specified in 4.6 of this specification and with the component inspection of MIL-F-13926. Since tolerance of test equipment is normally considered to be within 10% of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions and tolerances used in the design of test equipment shall be so selected and controlled as to insure that the test equipment will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit, and permit positive rejection when non-conforming. Construction shall be such as to facilitate routine calibration of test equipment.

4.6 Test methods and procedures.

4.6.1 Fabrication, materials and construction.

4.6.1.1 Fabrication.- The regulator shall be visually examined to Drawing D11733468 to determine compliance with the requirements of 3.1 and 3.3 through 3.3.2 prior to final acceptance.

4.6.1.2 Materials.- The component parts and coatings of the regulator assembly shall be visually examined to determine compliance with the requirements on Drawing D11733468 and 3.2 herein. Certification of material compliance shall be submitted prior to final inspection of the regulator.

4.6.1.2.1 -Non-flammable materials.- The external parts and coatings of the regulator shall be subjected to flame resistance tests specified in the respective material specifications in Drawing D11733468 to determine compliance with 3.2.1 prior to final acceptance. A Certificate of Material compliance shall be submitted prior to final inspection of the regulator.

4.6.1.2.2 Fungus resistance material.- This test shall be conducted in accordance with the fungus resistance test specified in MIL-F-13926 to meet the requirement specified in 3.2.2. This test shall only be performed on the first article test samples and shall be conducted on only two of the ten first article samples.

4.6.1.2.3 Inclosure.- The external metal case of the regulator shall be visually inspected for compliance with 3.2.3. Insulation resistance shall be performed as specified in MIL-STD-202 between each terminal and case ground.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

4.6.1.2.4 External surfaces.- The external surfaces of the regulator shall be visually inspected for completeness of the specified coating and show no evidence of surface damage or deterioration to determine compliance with 3.2.4.

4.6.1.3 Construction.- The converter shall be subjected to a visual, tactile, and dimensional inspection for conformance to the applicable drawings and requirements of this specification.

4.6.1.3.1 Internal wiring.- The internal wiring shall be inspected for compliance with 3.3.1 during shock and vibration tests in 4.6.2.4 and 4.6.2.5 respectively.

4.6.1.3.2 Internal components.- Prior to final inspection of regulators, internal components shall be visually inspected for conformance with applicable soldering requirements of MIL-F-13926 and for rigidity and mounting security as specified in 3.3.2.

4.6.2 Environmental tests.

4.6.2.1 Temperature cycling and thermal shock.- The environmental test equipment utilized in this test shall be in accordance with the "Test Facilities" requirements of MIL-F-13926 and the conditions of 3.5.1. Subsequent to this test the regulator shall be subjected to the tests specified in 4.6.3 and 4.6.4.

4.6.2.2 Operating temperature.- The environmental test equipment utilized in this test shall be in accordance with "Test Facilities" requirements of MIL-F-13926. The regulator shall be subjected to the temperature and time periods specified in 3.5.2. While at each extreme temperature the regulator shall be tested in accordance with 4.6.3 and 4.6.4.

4.6.2.3 Hermetic sealing.- The regulator, when at a temperature not to exceed 100°F, shall be immersed for 2 or 3 minutes in a bath of water, or any other suitable liquid of similar viscosity, and maintained at a temperature of at least 180°F. During this test the regulator shall show no evidence of leakage in compliance with 3.5.3. Subsequent to the immergence, and within 5 minutes of exposure the regulator shall be tested in accordance with 4.6.3 and 4.6.4.

4.6.2.4 Shock.- This test shall be conducted in accordance with Method 202 of MIL-STD-202. While under shock impact. the regulator shall be energized to determine compliance with 3.3.1. Subsequent to exposure to shock, the regulator shall be subjected to a visual examination and shall show no evidence of physical damage. The regulator shall then be subjected to the tests specified in 4.6.3 and 4.6.4 to determine compliance with 3.5.4.

4.6.2.5 Vibration.- This test shall be conducted in accordance with Method 201 of MIL-STD-202 except that the motion shall be applied for a period of 10 minutes in each of the three mutually perpendicular

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

directions (total of 30 minutes) in compliance with the requirements of 3.5.5. During vibration, the regulator shall be enerized to determine compliance with 3.3.1. Subsequent to the vibration test, the regulator shall be subjected to a visual examination and shall show no evidence of physical damage and shall then be subjected to the tests specified in 4.6.3 and 4.6.4 to determine compliance with 3.5.5.

4.6.3 Performance - electrical.- The regulator performance tests shall be conducted utilizing commercial test equipment. The voltage applied to the battery terminal shall be 2.65 ± .3 Vdc, and the input voltage applied to the input terminal shall be 18-30 volt D.C. The output load shall be a variable resistor with a value of 58 ± 6 ohms connected to the output terminal of the regulator.

4.6.3.1 Polarization of input terminal.- When the voltages are applied as specified in 4.6.3, the input terminal shall be positive with respect to case ground in compliance with 3.6.1.

4.6.3.2 Polarization of output terminal.- When the voltages are applied as specified in 4.6.3 the output terminal shall be positive with respect to case ground in compliance with 3.6.2.

4.6.3.3 Polarization of battery terminal.- When the voltages are applied as specified in 4.6.3 the battery terminal shall be positive with respect to case ground in compliance with 3.6.3.

4.6.3.4 Input Potential.- The regulator shall be operable within the input voltage range of 18 Vdc to 30 Vdc in compliance with 3.6.4.

4.6.3.5 Reverse polarity.- The regulator shall not be damaged when the input terminal is negative to the voltages specified in the input potential test of 4.6.3.4 with respect to case ground to determine compliance with 3.6.5.

4.6.4 Performance - operational.- These tests shall be performed with the inputs and loads connected as specified in 4.6.3.

4.6.4.1 Electrical shock.- The regulator shall be operated as specified in 4.6.3. The input shall be adjusted for 24 Vdc and the output load varied between 50-60 ohns until 45 mini-amps is obtained The 24 Vdc Power supply shall be turned on and off as specified in 3.7.1. When the 24 vdc power supply is "on", the output terminal shall be 2.63 ± .3 Vdc. When the 24 Vdc power supply is "off, "the output terminal shall be the same potential as the battery terminal within .001 Vdc. The above procedure shall be repeated for input potential of 18 Vdc and 30 Vdc.

.4.6.4.2 Input voltage surge.- The regulator shall be connected as, specified in 4.6.3.utilizing.a pulse generator connected to the input terminal. Superimpose a voltage spike on the input D.C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

potential as defined in 3.7.2. Each spike shall be applied for a two minute period with an interval of ten seconds for a total of 12 spikes. Subsequently the regulator shall meet the other requirements of 3.7.

4.6.4.3 Output current.- The regulator shall be connected as specified in 4.6.3, and shall be capable of delivering 45 ma as the output load is varied for full load in compliance with 3.7.3.

4.6.4.4 Output voltage.- The regulator shall be connected as specified in 4.6.3. The output voltage shall meet the requirement of 3.7.4 as the input voltage is varied from 18 Vdc to 30 Vdc.

4.6.4.5 Emergency power source.- This test shall be performed in conjunction with 4.6.4.1 to meet the requirements of 3.7.5.

4.6.4.6 Rise time.- The regulator shall be connected as specified in 4.6.3 and the test shall be performed in conjunction with 4.6.4.1. At all times the D.C. power supply is switched from "off" to "on" the output shall be at least 95% of the final value specified in 3.7.4 in less than 3.0 mini seconds as measured on a dual trace, storage oscilloscope or equivalent to meet the requirements of 3.7.6.

4.6.5 Reliability.- A reliability demonstration test shall be conducted as part of first article test (FAT) to assure compliance with 3.8. A minimum of two hours on each of the ten first article samples shall be accumulated after/during exposure to each non-operating /operating environments of paragraph 3.5. Additional operation may be required at 75° ± 15°F in order to accumulate a minimum of 120 hours on each of the ten first article samples. The regulators shall be tested until the total accumulated hours meet the accept/reject criteria of Table IV.

TABLE IV

ACCUMULATED HOURS	ACCEPT NO.	REJECT NO.
1204	0	4
2439	1	4
3615	2	4
4762	3	4

4.6.5.1 Data collection.- Data collected will consist of all equipment malfunctions, number of hours and lasings completed when malfunction occurred, nature and cause of malfunction, time required to correct malfunction, required corrective action, item serial number and environmental exposure.

4.6.5.2 Failure definition.- A failure is defined as any malfunction which renders the regulator inoperative or operative outside the limits of this specification. In determination of chareable reliability failures the following clarification shall apply:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

a. If upon failure analysis (to determine the cause of the malfunction) an assignable cause (related to manufacturing process, procedure, basic design weakness, etc.) is determined as the basis of the malfunction, the malfunction will not be chargeable as a reliability failure. However, the correction to the manufacturing process or procedure (et al) shall be accomplished.

b. If upon failure analysis no assignable cause is evident and the malfunction is considered random in nature, the malfunction shall be a "chareable" reliability failure and as such must be considered in the above demonstration test criteria. The decisions as to chareable reliability failure must be coordinated with the procuring activity, Frankford Arsenl Reliability and Maintainability Engineering Branch, SARFA-QAR.

4.6.5.3 System interruption.- A system interruption is any system malfunction for which the regulator is operable within the limits set forth in this specification, -but requires maintenance to correct the malfunction. Subsequent to the reliability test, the sample systems shall be refurbished and readied for delivery and shipment.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing amd marking.- Packaging, packing and marking shall be in accordance with Packaging Data Sheet (see 2.1). The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use.- The regulator is a functional assembly of the Passive Elbow Assembly, M35E1. The major function of this assembly is to provide regulated voltage.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Applicable packaging data sheet number (see 2.1).
(c) Selection of applicable levels of preservation, packaging and packing.
(d) Applicable stock number.
(e) Requirement for First Article submission.

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project Number 1240-A580

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers' vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-R-48442(MU) Regulator: 11733468

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
FRANKFORD ARSENAL
ATTN: SARFA-MDM
PHILADELPHIA, PENNA. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:26Z
Check the source to verify that this is the current version before use.