INCH-POUND
A-A-60013
February 25, 2020

COMMERCIAL ITEM DESCRIPTION

SPILL KIT, HAZARDOUS MATERIAL AND OIL

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This Commercial Item Description (CID) covers the Hazardous Material (HM) spill response kit. The HM spill kit houses the materials used to contain and sorb HM and oil spills onboard Navy ships, excluding submarines.

2. SALIENT CHARACTERISTICS.

2.1 Materials. The contractor shall select the materials not identified herein, but the materials shall be capable of meeting all of the operational and environmental requirements specified herein. The materials shall not present any safety hazards to operating and maintenance personnel when used for their intended purpose.

2.1.1 Deterioration prevention and control. The kit shall be fabricated from compatible materials that are inherently corrosion- or deterioration-resistant or are treated to provide protection against the various forms of corrosion and deterioration to which the materials are susceptible.

2.1.2 Type. The sorbent materials shall conform to the following types:

2.1.2.1 Type I. Type I sorbent materials are loose, unconsolidated particles of sorbent material, also referred to as granular.

(NOTE: Type I sorbents are not required in HM spill response kits. However, some commercial spill kits procured through the government supply chain contain type I sorbents. Type I sorbents shall not be used and the ship shall not replenish type I sorbents if the ship supply is exhausted. Unused type I sorbents can be offloaded as ordinary trash while in port. Type I sorbents should not be processed in solid waste equipment nor should they be disposed of overboard. No further requirements are provided for type I sorbents within this document.)

2.1.2.2 Type II. Type II sorbent materials are pads or sheets where length and width dimensions greatly exceed the thickness.

2.1.2.3 Type III. Type III sorbent materials are pillows that are encased in outer fabric or netting where length and width dimensions exceed the thickness.

2.1.2.4 Type IV. Type IV sorbent materials are socks that are encased in outer fabric or netting where length dimensions greatly exceed all other dimensions.

2.1.3 Kit components. The HM spill response kit shall contain, at minimum, the quantities of items 1 through 6 specified in table I at all times. While type I sorbents are not required, they can be present in the kit.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: Commander, Naval Sea Systems Command, ATTN: SEA 05S, 1333 Isaac Hull Avenue, SE, Stop 5160, Washington Navy Yard DC 20376-5160 or emailed to CommandStandards@navy.mil, with the subject line "Document Comment". Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

FSC 4235

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

TABLE I. HM spill response kit components.

Item	Description	Minimum Quantity Required
1	Type I sorbent, HM (particulate, bag)	N/A
2	Type II sorbent, HM (pad)	25
3	Type III sorbent, HM (pillow)	2
4	Type IV sorbent, HM (sock)	3
5	Bags, disposal, hazardous material	2
6	Plastic drum, shipping and storage, 30-gallon	1

2.1.4 Performance characteristics. Sorbents and other spill response kit components shall be composed of materials that fulfill the requirements contained herein. Sorbent material shall not be soluble or react chemically with sorbed HM when used for its intended purpose. Manufacturers shall clearly state which chemicals or type of chemicals, if any, should not be used in combination with the sorbent.

2.2 Size and shape.

2.2.1 Type I. N/A.

2.2.2 Type II. Type II sorbents shall be supplied in pads in accordance with A-A-59759 with a minimum dimension of 12 inches by 12 inches and a maximum dimension of 24 inches by 24 inches.

2.2.3 Type III. Type III sorbents shall be supplied as individual pillows in accordance with A-A-59759. Type III sorbents shall have a minimum area of 80 square inches, where neither side is more than 2.5 times larger than the other, and a maximum area of 576 square inches with maximum dimensions of 24 inches by 24 inches. Type III sorbents shall have a maximum thickness of 3 inches.

2.2.4 Type IV. Type IV sorbents shall be individually supplied socks in accordance with A-A-59759 with a minimum length of 24 inches, a maximum length of 48 inches, and a maximum diameter of 3 inches.

2.2.5 Hazardous material disposal bag. The hazardous material disposal bag shall have a minimum volume capacity of 10 gallons and shall remain leak-proof upon agitation (i.e., when being transported) or when left stationary. The bag shall be visible at a distance of 25 feet to an individual with normal vision.

2.2.6 Plastic drum. The plastic drum shall have a capacity of 30±5 gallons with a removable lid that securely fastens when closed. The drum shall be in accordance with Code of Federal Regulations (CFR) Title 49, Section 178.509. The plastic drum shall be designed such that moisture does not accumulate within the drum.

3. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR). Used, rebuilt, or remanufactured components shall not be incorporated into the kit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

4. PRODUCT CONFORMANCE PROVISIONS.

4.1 Product conformance. The products provided shall meet the salient characteristics of this Commercial Item Description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The government reserves the right to require proof of such conformance.

4.2 Sampling requirements. Bid samples shall be as specified in the contract or order (see 6.2).

4.3 Examination. The bid sample HM spill kit shall be physically examined for compliance with the requirements in table II. Non-compliance with any specified requirement or the presence of one or more defects lessening required efficiency shall constitute cause for rejection.

TABLE II. Examinations for expected product conformance.

Number	Defect	Reference Paragraph	Method of Examination
101	Materials not as specified.	2.1	Visual/Doc. 1/
102	Kit component not as specified.	2.1.3	Visual/Doc.
103	Enclosed sorbent (pad type) not as specified.	2.2.2	Visual/Doc./SIE 2/
104	Enclosed sorbent (sock type) not as specified.	2.2.4	Visual/Doc./SIE
105	Enclosed sorbent (pillow type) not as specified.	2.2.3	Visual/Doc./SIE
106	Hazardous material disposal bag not as specified.	2.2.5	Visual/Doc./SIE
107	Plastic drum not as specified.	2.2.6	Visual/SIE

FOOTNOTES:

1/ Doc. = Documentation

2/ SIE = Standard Inspection Equipment

4.4 Tests. Bid sample testing shall be performed as listed below.

4.4.1 Sorbent bid sample test. Bid sample testing for type II, III, and IV sorbents shall be conducted in accordance with the procedures described in A-A-59759.

4.4.2 Disposal bag bid sample test. The disposal bag shall be filled with approximately 5 gallons of water (approximately 40 pounds) and closed at the open end of the bag. The disposal bag shall then be agitated for 3 minutes. Upon termination of agitation, the disposal bag shall then be left stationary for an additional 3 minutes. If at any point during the agitation or stationary periods the disposal bag shows any signs of leakage, the bag has failed the sample test.

4.5 Ambient test conditions. Test conditions (testing location temperature, humidity, and air pressure) for bid samples shall be conducted in accordance with the procedures defined in the conditioning section of ASTM F726. All contaminated material resulting from the test shall be disposed of properly.

4.6 Market acceptability. The manufacturers of the item must have been producing a product meeting the requirements contained herein for at least 2 years.

5. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

6. NOTES.

6.1 Source of documents.

6.1.1 ASTM International. ASTM standards are available from ASTM International, 100 Barr Harbor Dr., P.O. Box C700, West Conshohocken, PA 19428-2959 or online at www.astm.org.

6.1.2 Code of Federal Regulations (CFR). The CFR may be obtained from the Superintendent of Documents, U.S. Government Publishing Office, Washington, DC 20401 or online at www.ecfr.gov.

6.1.3 Commercial Item Descriptions. Commercial Item Descriptions are available online at https://quicksearch.dla.mil.

6.1.4 Federal Acquisition Regulation (FAR). The FAR may be obtained from the Superintendent of Documents, U.S. Government Publishing Office, Washington, DC 20402 or online at https://www.acquisition.gov/far.

6.2 Ordering data. Acquisition documents should specify the following:

a. CID document number and revision.
b. Product conformance provisions (see 4.2, 4.3, and 4.4).
c. Packaging requirements (see 5).
d. If required, the specific issue of individual documents referenced (see 6.1).
e. Instructions regarding bid samples (see 6.3).
f. If replacement parts and instructions are required (see 6.6).

6.3 Bid samples. When a bid sample inspection is required, the bid sample(s) must be identical to the production model. The contracting officer should include specific instructions in acquisition documents (see 6.2) regarding arrangements for examinations, approval of the bid sample results, and disposition of the bid sample.

6.4 Definition of recovered materials. Recovered materials are those materials that have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials.

6.6 Provisioning. The contracting officer should include provisioning requirements (see 6.2 for replacement parts and instructions on shipment of the HM spill control kit).

6.7 Key words.

Cleanup
Disposal
Pad
Pillow
Sheet
Sock
Sorbent

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

MILITARY INTERESTS:

Custodians:
Navy – SH

Review Activities:
DLA – GS

CIVIL AGENCY COORDINATING ACTIVITY:
GSA – FAS

Preparing Activity:
Navy – SH
(Project 4235-2019-001)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.