INCH-POUND
A-A-60016
July 28, 2020

COMMERCIAL ITEM DESCRIPTION

RECYCLING EQUIPMENT FOR NON-METALLIC ABRASIVE BLAST GRIT

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description (CID) establishes the functional requirements and design features of non-metallic abrasive blast grit recycling equipment that is capable of cleaning, removing fines and dust, and adding back appropriately sized new grit to match the working characteristics of the original grit working mix in a single process.

2. SALIENT CHARACTERISTICS.

2.1 Equipment. The recycling equipment covered by this CID shall have a hopper for input of the used load of grit to be recycled. Once input, the grit shall progress through the machine automatically for the entire cleaning and remixing process until it is output into useful containers that can be transported directly to the working jobsite. At minimum, the recycling equipment shall include the subassemblies and components listed below and discussed in the following paragraphs:

a. Input hopper
b. Grit movement device
c. Dust removal unit/mechanism
d. Grit sizing and fine removal unit
e Electrical junction box
f. New grit addition unit
g. Dust collection unit
h. Recycled grit hopper and dispensing unit
i. Operating instructions and repair manuals

2.1.1 Input hopper. The input hopper shall be capable of accommodating input from common barrels (55-gallon) or bulk bags (nominally 1-ton). Alternatively, spent grit may be input directly from collection at the blast process site.

2.1.2 Grit movement device. From the hopper, the equipment shall automatically move grit through the various components of the machine for processing.

2.1.3 Dust removal unit/mechanism. The input waste grit shall be cleaned to remove dry fines and debris. This removed portion shall be collected in a manner convenient for disposal.

2.1.4 Grit sizing and fine removal unit. The equipment shall automatically remove grit particles that do not meet user-set size characteristics. All non-dust grit particles that fall below the desired output size shall be collected in a manner suitable for convenient disposal or appropriate reuse.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: Commander, Naval Sea Systems Command, ATTN: SEA 05S, 1333 Isaac Hull Avenue, SE, Stop 5160, Washington Navy Yard DC 20376-5160 or emailed to CommandStandards@navy.mil, with the subject line "Document Comment". Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

FSC 4250

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

2.1.5 New grit addition unit. Following cleaning and sizing of input grit, the equipment shall facilitate input of a user-controlled portion of new, unused grit in order to meet sizing requirements for the working mix of the recycled load. A mixed proportion of used and cleaned additions and new, unused grit additions shall be adjustable by the user.

2.1.6 Dust collection unit. The equipment shall collect dust from the processed load of grit. Dust collection shall operate such that the equipment can be run indoors or outdoors without need for specialized area containment or use of a respirator by the operator during normal operation.

2.1.7 Recycled grit collection and dispensing unit. The load of recycled grit shall be collected at the end of the processing line in a manner convenient for dispensing into jobsite ready containers.

2.2 Design and construction. The recycling equipment shall be a complete and fully functional assembly capable of processing spent grit input by removing dust and fines and then sizing the output. The assembly shall run on 110V AC power and a compressed air feed. Equipment shall have a single-used grit input and single-recycled grit output as a minimum. Equipment shall be capable of running automatically with oversight from a single operator. The equipment shall be automatic in the sense that the operator is not required to pay constant attention to the unit while in operation. Dust, fines, and waste shall be collected in a contained, controlled manner facilitating easy disposal.

2.3 Electronic control box. The electronic control box shall allow the operator to switch power on and off, open and close filling valves for replenished grit, and shall include appropriate sensors and microprocessors to provide an automated diagnostic motor monitoring system. The control box shall include a red emergency stop palm button that will immediately disable all operation and motion of the recycling equipment moving parts.

2.4 Cleaning performance. The unit shall be capable of accepting a used load of non-metallic abrasive with working mix sizing between #16 and #80 mesh with associated dust, fines, and paint/corrosion debris typical of collected once through blasting waste. The input waste load can be up to 80 percent dust and fines that fall to a size below the smallest intended retained size. The equipment shall be capable of cleaning this debris to a condition that removes all fines and dust to a maximum of 1 percent of the output load. Recycled grit output from the machine shall satisfy the quality control test requirements for recycled working grit mix as specified in SSPC AB-1.

2.5 Mobile support frame or platform. The recycling equipment components including the input hopper, electronic control box, cleaning unit, sizing unit, and dust collector shall be securely mounted on a mobile frame or platform. The platform shall be designed and finished to resist corrosion in the marine atmosphere and be inherently suitable for exterior operation. The platform shall not be degraded by exposure to a typical industrial environment. The frame shall include suitable built-in lift points such that a small crane or forklift can easily move the unit and load onto a transport. The unit shall be capable of being transported without special permitting.

2.6 Operating instructions and repair manuals. The equipment shall be delivered with operating instructions and repair manuals that describe basic equipment operations, safety features, and repair processes. Manuals shall include descriptions of processes for ordering and installing repair parts. Hard copies of the manuals shall be supplied with each unit, and additional electronic copies shall be available in accordance with the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

3. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. PRODUCT CONFORMANCE PROVISIONS.

4.1 Product conformance. The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The government reserves the right to require proof of such conformance.

4.2 Market acceptability. In order to document the quality of the product to be provided under this CID, the manufacturer producing the item shall have a fully functional prototype that meets the requirements of this CID available for demonstration.

5. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

6. NOTES.

6.1 Source of documents.

6.1.1 Society for Protective Coatings (SSPC). SSPC standards are available from SSPC Publication Sales, 800 Trumbull Drive, Pittsburgh, PA 15205-4365 or online at www.sspc.org.

6.1.2 FAR. The Federal Acquisition Regulation may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402 or online at https://www.acquisition.gov/far.

6.2 Ordering data. The contract or order should specify the following:

a. CID document number.

b. Product conformance provisions.

c. Packaging requirements.

d. Quantity required.

6.3 Key words.

Recycled media

Hopper

Sieve sizes

Dust and fines

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

MILITARY INTERESTS:

Custodian:
Army – AV
Navy – SH

Review Activities:
Army – MI, MT

CIVIL AGENCY COORDINATING ACTIVITY:
GSA – FAS

Preparing Activity:
Navy – SH
(Project 4250-2020-001)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:32Z
Check the source to verify that this is the current version before use.