This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document

User activities: Army ME, AM, MC
Navy MC, OS
Air Force 99

Reviewer activities: Army MI, MU, AT
Navy AS, SH
Air Force 11

FED SUP CLASS
5935



INCHES	MM
.002	.06
.005	.13
.010	.25
.016	.41
020	.51
.075	1.91
.09	2.29
.130	3.30
.143	3.63
.150	3.81
.175	4.45
.195	4.95
.219	5.56
.250	6 35
.260	6.60
.365	9.27
.438	11.13
750	19.05
.900	22.86
1.250	31.75
1.562	39.67

DESIGN STANDARD FOR USE WITH MIL-C-28748/6.

NOTES
1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ± .015(.38 mm)
3. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm
4. Tolerance between any two adjacent contact centers shall be ± .004(10 mm). Tolerance between any two contact centers, other than adjacent contacts, shall be ± .006(.15 mm).
5. Contact identification may be located on either side of the contact hole but shall appear on the front and rear of each insert
6. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
7. Referenced documents shall be of the issue in effect on date of invitation for bid
8. Complete connectors covered by issues of MS 24013 dated prior to 20 May 1970 are replaced by M28748/6-100G1A.

Ⓕ denotes changes

APPROVED 12 Aug 1964 REVISED Ⓔ 20 May 1970 Ⓕ 23 June 1972

P A Navy - EC Other Cust AF-80 Army - EL	International interest	TITLE CONNECTOR, RECTANGULAR, ELECTRICAL, RACK AND PANEL,20, SIZE 20 SOLDER SOCKET CONTACTS	MILITARY STANDARD MS 24013
Procurement Specification MIL-C-28748		SUPERSEDES	Page 1 OF 1

DD FORM 1 Sep 63 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5935-1822-83

☆ U. S. GOVERNMENT PRINTING OFFICE 1972 714-535/28

Source: https://assist.dla.mil -- Downloaded: 20260410-23T14:46Z
Check the source to verify that this is the current version before use.