MIL-F-5508B
AMENDMENT 4
7 March 1983
Supersedes
AMENDMENT 3
7 September 1979

MILITARY SPECIFICATION

FUSES, AIRCRAFT AUTOMATIC QUANTITY-MEASURING, HYDRAULIC

This amendment forms a part of Military Specification MIL-F-5508B, dated 14 April 1964, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

*2.1: Under "SPECIFICATIONS, Federal", delete "QQ-P-416, QQ-Z-325" and "PPP-B-621", and their titles. Add the following:

"PPP-T-60 - Tape, Packaging, Waterproof
PPP-T-76 - Tape, Packaging, Paper (For Carton Sealing)"

*2.1: Under "SPECIFICATIONS, Military", delete "MIL-P-5514, MIL-P-5517" and "MIL-P-7936". Add the following:

"MIL-G-5514 - Gland Design, Packings, Hydraulic, General Requirements for
MIL-G-83488 - Coating, Aluminum, Ion Vapor Deposited"

*Add the following boxed paragraph to bottom of page:

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMEDO, Tinker APB OK 73145 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

*Under "STANDARDS", add "FEDERAL" and the following:

"FED-STD-123 - Marking for Shipment (Civil Agencies)"

*Under "STANDARDS, Military" add the following:

"MIL-STD-1188 - Commercial Packaging of Supplies and Equipment

MS 33649 - Boss, Fluid Connection-Internal Straight Thread"

Under 'DRAWINGS", delete "AND 10050".

*Add the following paragraph to section 2:

"2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

Source: https://assist.dla.mil - Downloaded: 2026-10-17T04:59Z
Check the source to verify that this is the current version before use.

NAS 1638 - Cleanliness Requirements of Parts Used in Hydraulic Systems

(Copies of this document may be obtained from Aerospace Industries Association of America, 1725 De Sales Street N.W., Washington D.C. 20036.)

ASTM B 633 - Electrodeposited Coatings of Zinc on Iron and Steel

(Copies of this document may be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia PA 19103)"

3.3.2: Delete paragraph and substitute the following:

"3.3.2 Steel parts. Steel parts, except those in constant contact with hydraulic fluid shall be coated with ion vapor deposited aluminum, where practicable, in accordance with MIL-C-83488, type I or II as applicable and of a class that is adequate to achieve the degree of protection required. Other protective coating, in lieu of MIL-C-83488 may be used if demonstrated to be satisfactory and approved by the cognizant engineering activity. Cadmium plating must be avoided when satisfactory alternative processes can be used. Steel parts may also be zinc plated in accordance with ASTM B 633 or chromium plated in accordance with QQ-C-320."

*3.3.3: Delete paragraph entirely.

*3.4.3: Delete "AND 10050" and substitute "MS 33649".

PAGE 3

4.3.1.1: Delete entire paragraph and substitute the following:

"4.3.1.1 "The test fluid shall be continuously filtered through a filter element or elements that will assure a contamination limit of Class 5 in accordance with NAS 1638. Procedure and records of testing results to assure conformance with this limit, shall be maintained and shall be made available to appropriate Government activities upon request. The filter and element used shall be satisfactory for the temperature range encountered and cleaned or replaced regularly to avoid clogging."

4.3.2, Delete the word "approximately" in the third and fifth lines.

PAGE 14

4.7: Delete paragraph and substitute the following:

"4.7 Internal treatment. Following inspection sampling and test procedures specified above, each fuse shall be internally flushed with hydraulic preservative oil conforming to MIL-H-6083 and contamination limits shall be as specified in paragraph 4.3. All parts shall be capped and plugged with closures conforming to MIL-C-5501 to prevent oil leakage.

*Delete Section 5 in its entirety and substitute the following:

5. Packaging

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:59Z
Check the source to verify that this is the current version before use.

5.1 Preservation- packaging: Preservation-packaging shall be Level A or C, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. Fuses shall be cleaned in accordance with MIL-P-116.

5.1.1.2 Drying. Fuses shall be dried in accordance with MIL-P-116.

5.1.1.3 Preservative application. Preservatives shall not be used.

5.1.1.4 Unit packaging. Unless otherwise specified (See 6.2), fuses shall be individually packaged in accordance with MIL-P-116, submethod IA8 insuring compliance with the applicable requirements of that specification.

5.1.2 Level C. Fuses shall be clean, dry and individually packaged in a manner that will afford adequate protection against corrosion, deterioration and physical damage during shipment from supply source to the first receiving activity, in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be Level A, B or C as specified, (See 6.2).

5.2.1 Level A . The packaged fuses shall be packed in snug-fitting, cleated-plywood containers conforming to overseas type of PPP-B-601.

5.2.2 Level B. The packaged fuses shall be packed in fiberboard containers-conforming to PPP-B-636, class weather resistant, style optional. In lieu of the closure and waterproofing requirements in the Appendix of PPP-B-636, closure and waterproofing shall be accomplished by sealing all seams, corners and manufacturer's joint with tape two inches minimum width, conforming to PPP-T-60, class 1 or PPP-T-76. Bending (reinforcement requirements) shall be applied in accordance with the Appendix to PPP-B-636 using nonmetallic or tape banding only.

5.2.3 Level C. The packaged fuses shall be packed in fiberboard containers conforming to PPP-B-636, class domestic, style optional. Closures shall be in accordance with the appendix thereto.

5.3 Marking. In addition to any special marking required by the contract (see 6.2), each unit package, intermediate and exterior container, and unitized load shall be marked in accordance with MIL-STD-129. When specified (See 6.2), the marking of domestic shipments for civil agencies shall be in accordance with FED-STD-123, except that shipments packaged and packed per Level C, may be marked in accordance with MIL-STD-1188."

NOTE : The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendments

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:59Z
Check the source to verify that this is the current version before use.