INCH-POUND

MIL-DTL-3943/106E
15 January 2008
SUPERSEDING
MIL-DTL-3943/106D
7 April 1999

DETAIL SPECIFICATION SHEET

DECORATION, COMMANDER'S AWARD FOR PUBLIC SERVICE, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass

FINISH: Oxidized, Buffed Relieved and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 4.

DIMENSIONS:

HEIGHT (including lug):
-1: 1-3/8 inch (REF)
-2: 3/4 inch (REF)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T00:47Z
Check the source to verify that this is the current version before use.

WIDTH (at widest point):
-1: 1-1/4 inch (REF)
-2: 5/8 inch (REF)
THICKNESS (at edge):
-1: 0.125 inch ± 0.010 inch
-2: 0.090 inch ± 0.010 inch

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Decoration set shall consist of a regular size medal, a miniature size medal, a service ribbon, and a lapel button all packaged in a presentation case conforming to MIL-C-14633, Type XVI with a Type XVI, Class 1 or 3 pad.

3. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/291.

4. The lapel button shall conform to MIL-DTL-11484/139.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH
(Project No. 8455-2008-098)

Review activities:
DLA - CT

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T00:47Z
Check the source to verify that this is the current version before use.