MIL-B-63299A(AR)
AMENDMENT 7
11 MARCH 1988
SUPERSEDING
AMENDMENT 6
22 December 1987

MILITARY SPECIFICATION

BODY ASSEMBLY
MINE, ANTI-PERSONNEL: HE, M74

This Amendment forms a part of Military Specification MIL-B-63299A(AR), dated 15 December 1983, and is approved for use within the US Army Armament, Munitions and Chemical Command is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.2, Drawings: Delete "(See 6.7)" and substitute "(See 6.8)".

PRODUCT AND PACKAGING DRAWING: Delete "... DRAWING" and substitute "...DRAWINGS".

3.3.1 Delete "...(see 3.7)." and substitute "...(see 3.7.1)."

PAGE 4

3.5.2: Delete "...a torque of 35 inch pounds (in-lbs) min. without ..." and substitute "...a torque of 18 ± 2 inch pounds (in-lbs) min. without ..."

3.6d: Delete "Presence of shorting eyelet." and substitute "Presence of detonator and micropiston actuator flex cable shunts."

PAGE 8

4.3: Delete "Insert (Dwg. 9292629)" and substitute "Insert, Bushing (Dwg. 9381375)".

PAGE 18

4.4.2.4: Delete present Page 18 and substitute included Page 18.



DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.4 | Insert, Bushing | 1 OF 1 | 9381375 |
| | | | NEXT HIGHER ASSEMBLY: 9292680 |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Critical | None defined | | | | |
| Major | None defined | | | | |
| Minor | | | | | |
| 201 | Length | | 0.65% | 3.2 | Gage |
| 202 | Outside diameter | | 0.65% | 3.2 | Gage |
| 203 | Diameter of hole | | 0.65% | 3.2 | Gage |
| 204 | Location of hole | | 0.65% | 3.2 | Gage |
| 205 | Evidence of poor workmanship | | 0.65% | 3.11 | Visual |

NOTES:







Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

PAGE 33

* 4.4.2.19, Major 115: Delete "True position of O-ring groove diameter" and substitute "O-ring runout incorrect".

PAGE 37

4.4.2.21, Major 101: Delete in its entirety.

Add "Major 104: Any sensors not covered by potting 0.40% 3.2 Visual".

PAGE 41

* 4.4.2.24, Major 120: Delete "True position of O-ring groove diameter" and substitute "O-ring runout incorrect".

PAGE 47

4.4.2.29, Major 101: Delete in its entirety.

Add "Major 104: Any sensors not covered by potting 0.40% 3.2 Visual".

PAGE 53

4.4.2.34:

Critical 1: Change inspection method from "Visual" to "Gage".

Critical 4: Delete "Shorting eyelet missing" and substitute "Flex cable shunts missing or improper".

PAGE 54

4.4.2.34: Delete Major 109 in its entirety.

PAGE 56

4.4.2.35 Cont'd: Add "Major 110, Shim missing or incorrect, 0.40%, 3.2, Visual".



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

PAGE 62

4.4.2.40: Delete in its entirety and substitute new PAGE 62, Paragraph 4.4.2.40 included.

PAGE 63

Add Page 63A, 4.4.2.41 included herein.

PAGE 65

4.5.1, line 30: Delete "DRSMC-QAT-I(D)" and substitute "AMSMC-QAT-I(D)".

PAGE 66

4.5.1 CONT., line 3: Delete "DRSMC-QAT-M(D)" and substitute "AMSMC-QAT-M(D)".

PAGE 73

6.3, line 3: Delete "DRSMC-QAT-I(D)" and substitute "AMSMC-QAT-I(D)".

6.4, line 3: Delete "DRSMC-QAT-M(D)" and substitute "AMSMC-QAT-M(D)".

6.6, line 4: Delete "DRSMC-QAT-M(D)" and substitute "AMSMC-QAT-M(D)".



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

| PARAGRAPH | TITLE | | SHEET 1 OF 2 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.40 | Body Assembly | | | | 9292689 |
| | | | | | NEXT HIGHER ASSEMBLY --- |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| | LOT ACCEPTANCE TESTS | 1/ | | | |
| Critical | | | | | |
| 1 | Unsafe after transportation-vibration | | 0-1 | 3.3.1 | 4.5.5 |
| 2 | Premature arming | | | 3.4 | 4.5.6.4, 2/ |
| 3 | Premature detonation | | | 3.4 | 4.5.6.4 |
| 4 | Hazardous dud | | | 3.4 | 4.5.6.4 |
| Major | | | | | |
| | PERFORMANCE TEST: LAUNCH/FUNCTION | | | 3.4 | 4.5.6 |
| 105 | Tripline (TL)/Breakwire (BW) mode | | | | |
| 106 | Self Destruct (SD): normal/extended | | | | |
| 107 | Antidisturbance (AD) mode | | | | |
| 108 | Dud | | | | |
| 109 | Early SD | | | | |

NOTES: 1/ See sheet 2. 2/ Acoustic sensor shall be used for monitoring.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS

| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.41 | Shim, Shorting Bar | 1 OF 1 | 9381374 |
| | | | NEXT HIGHER ASSEMBLY 9292680 |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Critical | None defined | | | | |
| Major | None defined | | | | |
| Minor | | | | | |
| 201 | Length | | 0.65% | 3.2 | Gage |
| 202 | Length of legs, 2 places | | 0.65% | 3.2 | Gage |
| 203 | Width | | 0.65% | 3.2 | Gage |
| 204 | Diameter of hole | | 0.65% | 3.2 | Gage |
| 205 | Evidence of poor workmanship | | 0.65% | 3.11 | Visual |

NOTES:



Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A498 )



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.