INCH-POUND

MIL-C-50790A (AR)
AMENDMENT 1
04 January 1993

MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLIES, TEST SET, AN/MWM-3

GENERAL SPECIFICATION FOR

This amendment forms a part of General Specification for MIL-C-50790A (AR), dated 31 May 1991, and is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1: Add the following military specification:

"MIL-STD-28800 - Test Equipment for use with Electrical and Electronic Equipment, General Specification for"

Delete the following military standard:

"MIL-STD-2000 - Standard Requirements for Soldering Electrical and Electronic Assemblies"

2.1.2: Add the following paragraph:

"Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:38Z
Check the source to verify that this is the current version before use.

DRAWINGS (See 6.4)

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

12950877 - Requirements for Soldering Electrical and Electronic Assemblies

(Copies of drawings required by the suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)"

PAGE 3

3.3.1: Delete in entirety and substitute the following:

"3.3.1 Vibration. The assembly shall not suffer damage and shall meet the requirements of 3.4 and 3.5 after exposure to sinosidal vibration, in each of three mutually perpendicular axes, as specified in MIL-T-28800 for Type 1, Class 2, Style A test equipment."

3.3.3, 3.3.3.1 and 3.3.3.2: Delete paragraph in their entirety and replace with the following:

"3.3.3 Altitude Operating. The assembly shall meet the requirements of 3.4 and 3.5 during and after exposure to barometric pressure encountered at 10,000 feet above sea level (20.6 inches of Hg)."

PAGE 4

3.7: Delete in entirety and substitute the following:

"3.7 Soldering. All soldering shall be in accordance with the requirements of Note 2 of Drawing 12950877."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:38Z
Check the source to verify that this is the current version before use.

PAGE 8

4.7.1.1: Delete in entirety and substitute the following:

"4.7.1.1 Vibration. This test shall be performed as specified in MIL-T-28800 for Type 1, Class 2, Style A test equipment with the exception that Step 4.c Resonance Dwell does not apply. The assembly shall be attached to the vibration generator directly or with a fixture, and securely held by its normal means of attachment. After vibration, the assembly shall be tested as specified in 4.7.2 and 4.7.3 herein to determine compliance with 3.3.1."

4.7.1.3: Delete in entirety and substitute the following:

"4.7.1.3 Altitude Operating. This test shall be performed as specified in Procedure II, Method 500, of MIL-STD-810. The operational checkout shall be as specified in 4.7.2 and 4.7.3 for compliance with 3.3.3."

PAGE 9

4.8: Delete in entirety and substitute the following:

"4.8 Soldering. Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of Note 2 of Drawing 12950877 as specified in paragraph 3.7."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 4931-A318)

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:38Z
Check the source to verify that this is the currentversion before use.