# MILITARY SPECIFICATION

# CIRCUIT CARD ASSEMBLY, NOISE SUPPRESSION

## 1. SCOPE

1.1 This specification covers the detail requirements for one type of circuit card assembly. The requirements of this specification together with the general requirements of MIL-C-60898 comprise the complete requirements for the Noise Suppression Circuit Card Assembly.

## 2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on the date of invitation for bids or request for proposal form a part of this specification to the extent specified herein,

SPECIFICATIONS

Military

| | |
|---|---|
| MIL-C-60898 | Circuit Card Assemblies, General Specifications for |

DRAWINGS

U. S. Army, Frankford Arsenal

| | |
|---|---|
| FI05542013 | Electronic Component Assembly, Noise Suppression |

PACKAGING DATA SHEET

| | |
|---|---|
| 10554208 | Packaging of Circuit Card Assembly, Noise Suppression |

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 4931

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.

## 3. REQUIREMENTS

3.1 Fabrication. The assembly shall be manufactured in accordance with Drawing F10554208 and drawings pertaining thereto.

3.2 General specifications. The assembly shall meet the requirements of MIL-C-60898.

3.3 Environmental service conditions. See MIL-C-60898.

3.3.1 Performance at temperature extremes. For the conditions of 3.3.2 of MIL-C-60898 the capacitance specified in 3.4.1 shall be 0.047 uf (±15 percent)

3.4 Electrical performance.

3.4.1 Capacitance. The capacitance shall be 0.047 uf (± 10 percent) between pin 28 and each of the following pins: 12, 15, 16, 17, 18, 20, 21, 22, 23, 26, and 27.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 General. The quality assurance provisions of MIL-C-60898 shall apply to the assembly covered by this detail specification.

4.2 First article inspection. As specified in MIL-C-60898.

4.3 Control test sample. As specified in MIL-C-60898.

4.4 Functional tests. The following characteristics shall be 100 percent tested in accordance with the applicable test method.

| | Characteristic | Requirement | Procedure |
|---|---|---|---|
| 100 | Capacitance | 3.4.1 | 4.5.2.1 |

4.4.1 Inspection equipment. As specified in MIL-C-60898 and 4.4.1.1.

4.4.1.1 Test equipment. In conjunction with 4.4.1, the following test equipment shall be utilized in the performance of the applicable tests as specified in 4.5.

| Item | Description |
|---|---|
| 1. CAPACITANCE BRIDGE | Capacitance read out from 0.005 uf to 100 uf with 1 percent accuracy and resolution or better, d-c and a-c operation. |

4.5 Test methods and procedures

4.5.1 Environmental. As specified in MIL-C-60898 except the requirements of 3.3.1 herein shall be verified during temperature extremes.

4.5.2 Electrical tests

4.5.2.1 Capacitance. Connect the CAPACITANCE BRIDGE, item 1 of 4.4.1.1, between pin 28 and each of the following pins: 12, 15, 16, 17, 18, 20, 21, 22, 23, 26, and 27. Verify a capacitance of 0.047 uf (± 10 percent) in each case.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.

## 5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with Packaging Data Sheet 10554208.

## 6. NOTES

6.1 The notes specified in MIL-C-60898 are applicable to this specification.

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 4931-A047



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.

# SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
Department of the Army

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-N1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:04Z
Check the source to verify that this is the current version before use.