INCH-POUND

MIL-DTL-52471/1C
4 December 2008
SUPERSEDING
MIL-DTL-52471/1B
27 April 1998

DETAIL SPECIFICATION SHEET

HOSE ASSEMBLIES, RUBBER, HYDRAULIC PRESSURE-TYPE, TYPE 100R1, SINGLE- WIRE BRAIDED REINFORCEMENT HOSE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-52471.




FIGURE 1. Hose assembly, fitting identification.

Operating pressure. Hose assembly shall operate at pressures shown in table I.

TABLE I. Hose assembly operating pressure. 1/ 2/

Dash number	Hose ID			Operating pressure max psi (MPa)
	Inch fraction	Inch decimal	mm	
-4	1/4	.250	6.35	2750 (19.0)
-6	3/8	.375	9.53	2250 (15.5)
-8	1/2	.500	12.70	2000 (13.8)
-12	3/4	.750	19.05	1250 (8.6)
-16	1	1.000	25.40	1000 (6.9)
-20	1-1/4	1.125	28.58	625 (4.3)

1/ Dimensions are in inches.
2/ Metric equivalents are given for information only.

Hose assembly code number. The purpose of this slash sheet is to provide hose assembly code numbers for determining the hose diameter, fitting X, fitting Y, and bend angles (when applicable) as shown in tables II through VII. The bend angles are called “style codes” and consist of hose assembly styles as explained in MIL-DTL-52471.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:19Z
Check the source to verify that this is the current version before use.

TABLE II. 1/4-inch hose assemblies.

Hose ID Inch fraction Inch decimal (mm)	Hose PIN 1/	Fitting X (see figure 1)		Fitting Y (see figure 1)		Assembly code number 3/
		PIN	Bend angle 2/	PIN	Bend angle 2/	
1/4 .250 (6.35)	M52471/4-4	M52525/5-4-4	0°	M52525/5-4-4 M52525/5-4-5	0°	A001 A002
				M52525/6-4-4 M52525/6-4-5	45°	A004 A005
				M52525/7-4-4 M52525/7-4-5	90° 4/	A006 A007
				M52525/8-4-4 M52525/8-4-5	90° 5/	A008 A009
		M52525/5-4-5	0°	M52525/5-4-5	0°	A010
				M52525/6-4-4 M52525/6-4-5	45°	A012 A013
				M52525/7-4-4 M52525/7-4-5	90° 4/	A014 A015
				M52525/8-4-4 M52525/8-4-5	90° 5/	A016 A017
		M52525/6-4-4	45°	M52525/6-4-4 M52525/6-4-5	45°	A025 A026
				M52525/7-4-4 M52525/7-4-5	90° 4/	A027 A028
				M52525/8-4-4 M52525/8-4-5	90° 5/	A029 A030
		M52525/6-4-5	45°	M52525/6-4-5	45°	A031
				M52525/7-4-4 M52525/7-4-5	90° 4/	A032 A033
				M52525/8-4-4 M52525/8-4-5	90° 5/	A034 A035
		M52525/7-4-4	90° 4/	M52525/7-4-6 M52525/7-4-5	90° 4/	A036 A037
				M52525/8-4-4 M52525/8-4-5	90° 5/	A038 A039
		M52525/7-4-5	90° 4/	M52525/7-4-5	90° 4/	A040
				M52525/8-4-4 M52525/8-4-5	90° 5/	A041 A042
		M52525/8-4-4	90° 5/	M52525/8-4-4 M52525/8-4-5	90° 5/	A043 A044
		M52525/8-4-5	90° 5/	M52525/8-4-5	90° 5/	A045

1/ Part or Identifying Number (PIN).
2/ Reference MIL-DTL-52471 for hose assembly bend angles and displacement angles used in the PIN.
3/ A suffix indicating plating finish shall be specified with the assembly code number, see table VIII.
4/ 90° short drop fitting.
5/ 90° long drop fitting.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:19Z
Check the source to verify that this is the current version before use.

TABLE III. 3/8-inch hose assemblies.

Hose ID Inch fraction Inch decimal (mm)	Hose PIN	Fitting X (see figure 1)		Fitting Y (see figure 1)		Assembly code number 2/
		PIN	Bend angle 1/	PIN	Bend angle 1/	
3/8 .375 (9.53)	M52471/4-6	M52525/5-6-6	0°	M52525/5-6-6 M52525/6-6-6 M52525/7-6-6 M52525/8-6-6 M52525/6-6-6	0° 45° 90° 3/ 90° 4/ 45°	A201 A203 A205 A207 A216
		M52525/6-6-6	45°	M52525/7-6-6 M52525/8-6-6	90° 3/ 90° 4/	A218 A220
		M52525/7-6-6	90° 3/	M52525/7-6-6 M52525/8-6-6	90° 3/ 90° 4/	A227 A229
		M52525/8-6-6	90° 4/	M52525/8-6-6	90° 4/	A234

1/ Reference MIL-DTL-52471 for hose assembly bend angles and displacement angles used in the PIN.
2/ A suffix indicating plating finish shall be specified with the assembly code number, see table VIII.
3/ 90° short drop fitting.
4/ 90° long drop fitting.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:19Z
Check the source to verify that this is the current version before use.

TABLE IV. 1/2-inch hose assemblies.

Hose ID Inch fraction Inch decimal (mm)	Hose PIN	Fitting X (see figure 1)		Fitting Y (see figure 1)		Assembly code number 2/
		PIN	Bend angle	PIN	Bend Angle 1/	
1/2 .500 (12.70)	M52471/4-8	M52525/5-8-8	0°	M52525/5-8-8 M52525/5-8-10	0°	A301 A302
				M52525/6-8-8 M52525/6-8-10	45°	A303 A304
				M52525/7-8-8 M52525/7-8-10	90° 3/	A305 A306
				M52525/8-8-8 M52525/8-8-10	90° 4/	A307 A308
		M52525/5-8-10	0°	M52525/5-8-10	0°	A309
				M52525/6-8-8 M52525/6-8-10	45°	A310 A311
				M52525/7-8-8 M52525/7-8-10	90° 3/	A312 A313
				M52525/8-8-8 M52525/8-8-10	90° 4/	A314 A315
		M52525/6-8-8	45°	M52525/6-8-8 M52525/6-8-10	45°	A316 A317
				M52525/7-8-8 M52525/7-8-10	90° 3/	A318 A319
				M52525/8-8-8 M52525/8-8-10	90° 4/	A320 A321
		M52525/6-8-10	45°	M52525/6-8-10	45°	A322
				M52525/7-8-8 M52525/7-8-10	90° 3/	A323 A324
				M52525/8-8-8 M52525/8-8-10	90° 4/	A325 A326
		M52525/7-8-8	90° 3/	M52525/7-8-8 M52525/7-8-10	90° 3/	A327 A328
				M52525/8-8-8 M52525/8-8-10	90° 4/	A329 A330
		M52525/7-8-10	90° 3/	M52525/7-8-10	90° 3/	A331
				M52525/8-8-8 M52525/8-8-10	90° 4/	A332 A333
		M52525/8-8-8	90° 4/	M52525/8-8-8 M52525/8-8-10	90° 4/	A334 A335
		M52525/8-8-10	90° 4/	M52525/8-8-10	90° 4/	A336

1/ Reference MIL-DTL-52471 for hose assembly bend angles and displacement angles used in the PIN.
2/ A suffix indicating plating finish shall be specified with the assembly code number, see table VIII.
3/ 90° short drop fitting.
4/ 90° long drop fitting.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:19Z
Check the source to verify that this is the current version before use.

TABLE V. 3/4-inch hose assemblies.

Hose ID Inch fraction Inch decimal (mm)	Hose PIN	Fitting X (see figure 1)		Fitting Y (see figure 1)		Assembly code number 2/
		PIN	Bend angle 1/	PIN	Bend angle 1/	
3/4 .750 (19.05)	M52471/4-12	M52525/5-12-12	0°	M52525/5-12-12	0°	A501
				M52525/6-12-12	45°	A503
				M52525/7-12-12	90° 3/	A505
				M52525/8-12-12	90° 4/	A507
		M52525/6-12-12	45°	M52525/6-12-12	45°	A516
				M52525/7-12-12	90° 3/	A518
				M52525/8-12-12	90° 4/	A520
				M52525/7-12-12	90° 3/	A527
		M52525/7-12-12	90° 3/	M52525/8-12-12	90° 4/	A529
		M52525/8-12-12	90° 4/	M52525/8-12-12	90° 4/	A534

1/ Reference MIL-DTL-52471 for hose assembly bend angles and displacement angles used in the PIN.
2/ A suffix indicating plating finish shall be specified with the assembly code number, see table VIII.
3/ 90° short drop fitting.
4/ 90° long drop fitting.

TABLE VI. 1-inch hose assemblies.

Hose ID Inch fraction Inch decimal (mm)	Hose PIN	Fitting X (see figure 1)		Fitting Y (see figure 1)		Assembly code number 2/
		PIN	Bend angle 1/	PIN	Bend angle 1/	
1 1.000 (25.40)	M52471/4-16	M52525/5-16-16	0°	M52525/5-16-16	0°	A601
				M52525/6-16-16	45°	A602
				M52525/7-16-16	90° 3/	A603
				M52525/8-16-16	90° 4/	A604
		M52525/6-16-16	45°	M52525/6-16-16	45°	A609
				M52525/7-16-16	90° 3/	A610
				M52525/8-16-16	90° 4/	A611
				M52525/7-16-16	90° 3/	A616
		M52525/7-16-16	90° 3/	M52525/8-16-16	90° 4/	A617
		M52525/8-16-16	90° 4/	M52525/8-16-16	9°0 3/	A622

1/ Reference MIL-DTL-52471 for hose assembly bend angles and displacement angles used in the PIN.
2/ A suffix indicating plating finish shall be specified with the assembly code number, see table VIII.
3/ 90° short drop fitting.
4/ 90° long drop fitting.

TABLE VII. 1-1/4 inch hose assemblies.

Hose ID Inch fraction Inch decimal (mm)	Hose PIN	Fitting X (see figure 1)		Fitting Y (see figure 1)		Assembly code number 2/
		PIN	Bend angle 1/	PIN	Bend angle 1/	
1-1/4 1.125 (28.58)	M52471/4-20	M52525/5-20-20	0°	M52525/5-20-20	0°	A701

1/ Reference MIL-DTL-52471 for hose assembly bend angles and displacement angles used in the PIN.
2/ A suffix indicating plating finish shall be specified with the assembly code number , see table VIII.

Fittings materials and finishes shall be in accordance with MIL-DTL-52525, material and plating designators are specified in table VIII.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:19Z
Check the source to verify that this is the current version before use.

TABLE VIII. Material and finish identification codes. 1/ 2/

PIN code material/plating finish	Material	Plating finish
A	Aluminum alloy 6061 or 7075	Anodize in accordance with MIL-A-8625, type II.
AN		Anodize in accordance with MIL-A-8625, type II and NAVAIR trivalent chromium pretreatment (TCP) in accordance with MIL-DTL-81706, type 2, class A.
BN		Bare aluminum with NAVAIR TCP in accordance with MIL-DTL-81706, type 2, class A.
C	Steel	Cadmium plating in accordance with SAE-AMS-C-81562, type II, class 3 or SAE-AMS-QQ-P-416, type II, class 2.
CN		Cadmium plating in accordance with SAE-AMS-C-81562, type II, class 3 or SAE-AMS-QQ-P-416, type II, class 2 and NAVAIR TCP in accordance with MIL-DTL-81706, type 2, class A.
YC	Chrome-molybdenum steel alloy 4130	Cadmium plating in accordance with SAE-AMS-C-81562, type II, class 3 or SAE-AMS-QQ-P-416, type II, class 2.
YN		Cadmium plating in accordance with SAE-AMS-C-81562, type II, class 3 or SAE-AMS-QQ-P-416, type II, class 2 and NAVAIR TCP in accordance with MIL-DTL-81706, type 2, class A.
F	Steel	NAVAIR TCP in accordance with MIL-DTL-81706, type 2, class A.
FN	Chrome-molybdenum steel alloy 4130	
G	Steel	Zinc plating with colorless passivate in accordance with ASTM B633, type V, Fe/Zn 25.
YG	Chrome-molybdenum steel alloy 4130	
H	Steel	Zinc phosphate finish in accordance MIL-DTL-16232, type Z, class1. 3/
YH	Chrome-molybdenum steel alloy 4130	
J	Steel	Zinc plating with chromate conversion in accordance with ASTM B633; type II or III, Fe/Zn 5, or ASTM B695, type II, class 5.
YJ	Chrome-molybdenum steel alloy 4130	
K	Nickel-copper alloy UNS N04400	No additional finish.
M	High-chromium nickel alloy UNS N06690	No additional finish.
N	Steel	Zinc aluminum in accordance with ASTM F1136, grade 3, NC.
YN	Chrome-molybdenum steel alloy 4130	
P	Steel	Zinc plating with colorless passivate in accordance with ASTM B633, type VI, Fe/Zn 5.
YP	Chrome-molybdenum steel alloy 4130	
S	Corrosion resistant steel	No additional finish. Passivation in accordance with SAE-AMS2700, type 6 or 7.
SN		Passivation above and NAVAIR TCP in accordance with MIL-DTL-81706, type 2, class A.
T	Titanium	Anodize in accordance with SAE-AMS2488, type 2.
V	Steel	Zinc-nickel in accordance with SAE-AMS2417, type 1.
W	Steel	Any zinc plating above.
YW	Chrome-molybdenum steel alloy 4130	
Z	Steel	Any zinc plating above with NAVAIR TCP in accordance with MIL-DTL-81706, type 2, class A.
YZ	Chrome-molybdenum steel alloy 4130	

1/ All materials and finishes shall be in accordance with MIL-DTL-52525.
2/ Embitterment test need not be run.
3/ Zinc phosphate finish is hexavalent chromium free.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:19Z
Check the source to verify that this is the current version before use.


REQUIREMENTS:

The hose assemblies shall be as specified on figure 1 and in tables I through VIII.

Hose shall be in accordance with MIL-DTL-52471/4.

Connector fittings for hose assemblies shall be in accordance with MIL-DTL-52525.

PIN: The PIN consists of the letter “M” the specification sheet number, an assigned code number for the hose assembly, material/plating, hose assembly length, and angular relationship of fittings, when applicable.



1/ Not applicable for assemblies with straight fittings.

PIN example: M52471/1-A216C-098-4-135, describes a hose assembly consisting of M52471/4-6 hose, fitting X M52525/5-6-6, bend angle 0°, fitting Y M52525/6-6-6, bend angle 45°, steel with cadmium plating, 98 ½ inches long, and a displacement angle of 135°.

This specification provides for a number of alternative plating materials via the PIN. Users should select the PIN with the least hazardous material that meets the form, fit and function requirements of their application.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-52471, this document references the following:

MIL-A-8625	ASTM B633	SAE-AMS2417
MIL-DTL-16232	ASTM B695	SAE-AMS2488
MIL-DTL-52471/4	ASTM F1136	SAE-AMS2700
MIL-DTL-52525	SAE-AMS-C-81562	
MIL-DTL-81706	SAE-AMS-QQ-P-416	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:19Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - AT
Navy - SH
Air Force - 99
DLA - CC

Preparing activity:
DLA - CC

(Project 4720-2007-017)

Review activities:
Army - AR, AV, GL
Navy - AS, MC, SA

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:19Z
Check the source to verify that this is the current version before use.