INCH-POUND

MIL-F-63518A (AR)
AMENDMENT 4
01 Sept 1989
SUPERSEDING
AMENDMENT 3
30 June 1989

MILITARY SPECIFICATION

FUZE, POINT DETONATING, M739A1
LESS BOOSTER PELLET

This Amendment forms a part of Military Specification MIL-F-63518A (AR), dated 6 October 1986, and is approved for use within the U.S. Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 35

4.4.2.25: change "9256645" to "9258646".

PAGE 36

4.4.2.25: change "9256645" to "9258646".

PAGE 37

4.4.2.25: change "9256646" to "9258646".

PAGE 49

4.4.2.34: change "9256638" to "9258638".

PAGE 64

4.4.2.45: change "9253634" to "9258634".

PAGE 73

4.4.2.52: for Critical 1, change "GAGE/VISUAL" TO "GAGE"

* 4.4.2.52: change "Gage" to "Gage, 4.5.32".

PAGE 94

4.4.2.72: Delete Major 105 in its entirety.

4.4.2.72: Add the following Major defect:

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

"108. Depth of detent retainer counterbore, min.; (a)., 3.1., Gage".

PAGE 102

4.5.13.2, last line: Delete "700" and substitute "750".

PAGE 106

4.5.27.1: For the 105MM M102, Zone 1, Delay Setting, change "8-in. Plywood" to "4-in. Plywood".

PAGE 108

4.5.27.2: For the 105MM M102, Zone 1, Delay Setting, change "8-in. Plywood" to "4-in. Plywood".

PAGE 110

* Add new paragraph 4.5.32 as follows:

"4.5.32 Gage for S&A module not in unarmed position.

The gage must be capable of detecting the following conditions:

a. The rotor is in the safe position.

b. The setback pin and spring are present.

c. The setback pin is engaged in and locking the rotor.

d. Both spinlocks are present and engaged in the rotor.

Of primary importance is that the gage, whether semi-automatic or fully automatic, must make the decision as to the safe position of the rotor in the S&A. The decision for safety of the rotor is not to be at the discretion of the operator/inspector.

The use of or operation of the gage should be such that the rejected S&A is controlled so that it cannot be inadvertently added to the accepted product. A rigid procedure for materiel handling of critical defects must be part of the operation/use of any gage inspecting for such a defect.

The inspection must be the last operation prior to assembling the S&A/retainer assembly into the body of the fuze. This means there is a smooth, continuous flow of accepted product between the gaging station and the assembly operation. It is desireable that accepted units be automatically marked for identification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.

The gage must pass a qualification test to demonstrate its reliability prior to its introduction into the production process. 1000 S&A/retainer assemblies shall be used for this purpose and they shall be of the following description:

300 properly assembled, fully safe

175 with both spinlocks missing (independent detection of each)

175 with setback pin missing

175 with setback pin and both spinlocks missing

175 with rotor, setback pin, and both spinlocks missing

When tested with all 1000 of the above masters, the gage must pass the test with no incorrect decisions.

PAGE 111

6.8: Add the following:

"Fuzes set delay which fail to function as intended behind the target, but which do function on subsequent impact (FSI), shall not be classed as duds and shall be reported "for information only"."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing Activity:
Army - AR

(Project 1390-A672)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:02Z
Check the source to verify that this is the current version before use.