MILITARY SPECIFICATION

INSTALLATION KIT, GAS-PARTICULATE FILTER UNIT, ARMORED VEHICLE, AMBULANCE, M37

1. SCOPE

1.1 Scope. This specification covers a filter unit installation kit.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-591 - Boxes, Fiberboard, Wood-Cleated.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Box, Fiberboard.
PPP-T-76 - Tape, Pressure-Sensitive Adhesive Paper, (For Carton Sealing.

MILITARY

MIL-P-116 - Preservation, Methods of,
MIL-B-121 - Barrier Material, Greaseproofed, Waterproofed, Flexible.

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:51Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129 - Marking for Shipment and Storage.

DRAWINGS

EDGEWOOD ARSENAL

DL5-19-1819 - Installation Kit, Gas-Particulate Filter Unit, Armored Vehicle, Ambulance, M37.

(All drawings referenced in this specification are listed on Crawing DL5-19-1819.)

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification Ratings, Rules and Regulations.

(Application for copies of these freight classification rules should readdressed to the Uniform Classification Committee, 202 Union Station, Chicago 6, Illinois.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL5-19-1819 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:51Z
Check the source to verify that this is the current version before use.

3.1,2 Components. All components of the installation kit shall conform to the specifications and drawings listed on Drawing DM-19-1819 and subsidiary drawings.

3.2 Manufacture and assembly. All components of the installation kit shall be manufactured and assembled in accordance with their respective assembly drawings listed on Drawing DL5-19-1819. Electrical components shall function properly and have electrical continuity, as applicable, when tested as specified in 4,6.1.

3.3 Workmanship. All metal parts of the installation kit shall be free of burrs and sharp edges and defects such as bent, broken, or cracked members, All rubber parts shall be smooth, of uniform thickness, and free of cuts, breaks, abrasions, and molding defects. Wiring shall be free of kinks and cuts, breaks, and abrasions of the insulating surface. All parts shall be free from foreign matter such as dirt or grease.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Supplier's responsibility will be as specified in the contract or order.

4.2 Special provisions.

4.2.1 Alternative inspection. The supplier may utilize any alternative inspection procedure which will provide equal or better assurance of quality by submitting a written proposal with justification and obtaining written approval from the Government prior to instituting the procedure. In case of dispute, the procedures of this specification will govern.

4.2.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.3 Lotting. A lot shall consist of the installation kits produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions.

4.4 Sampling for examination and nondestructive tests. Sampling shall be . conducted in accordance with Standard MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:51Z
Check the source to verify that this is the current version before use.

4.5 Inspection provisions.

4.5.1 For examination and nondestructive test. Sample kits shall be examined and tested in accordance with the classification of defects and Standard MIL-STD-105.

4.5.2 Classification of defects.

4.5.2.1 Metal support assemblies. (Dwgs: B5-19-1063, bracket; D5-19-1753, body, mounting bracket; D5-l9-1754, frame; B5-19-1823, bracket; and D5-l9-1769, mount, shock.)

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Component missing or incorrectly located or assembled
102	Hardware component inoperative
103	Weld missing or incomplete
104	Hole missing or location incorrect
105	Thread incorrect
106	Workmanship (3.3)
Minor:	AQL 2.5 percent defective
201	Protective finish missing

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:51Z
Check the source to verify that this is the current version before use.

4.5.2.2 Electrical system assemblies. (Dwgs: B5-19-1663, wire, ground; B5-19-1767, cable assembly; B5-19-1768, cable assembly; C5-19-1757, circuit breaker and switch.)

Categories		Defects	Acceptance standards
Critical:		None defined	
Major:	AQL	1.0 percent defective	
	101	Component missing, incorrectly located or assembled	
	102	Hole missing or location incorrect	
	103	Marking incorrect	
	104	Workmanship (3.3)	
Major A:	AQL	0.65 percent defective	
	151	Electrical continuity	4.6.1
	152	Switch or circuit breaker nonfunctioning	4.6.1
Minor:	AQL	2.5 percent defective	
	201	Protective finish missing	
	202	Marking illegible	

4.6 Tests.

4.6.1 Electrical continuity and circuit breaker/switch functioning. The electrical continuity of the cables and functioning of the circuit breaker and switch shall be determined using Edgewood Arsenal Test Lamp (Dwg B136-52-60).

5. PREPARATION FOR DELIVERY (For repair parts packaging, see 6.3)

5.1 Cleaning and drying. The components of the installation kit shall be cleaned and dried in conformance with Specification MIL-P-116. Cleaning process C-1 and any of the drying processes listed therein shall be used.

5.2 Preservation and packaging. Levels shall be as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:51Z
Check the source to verify that this is the current version before use.

5.2.1 Level A.

5.2.1.1 Unit packaging.

5.2.1.1.1 Frame assembly. The spring catch of the frame assembly shall be oiled with type P-7 preservative oil conforming to Specification MIL-P-116. The catch shall be actuated during application to assure penetration of the preservative oil. Excess oil shall be wiped off.

5.2.1.1.2 Shock mount assembly. The unpainted surfaces of the shock mount assembly shall be coated with type P-1 preservative compound conforming to Specification MIL-P-116.

5.2.1.1.3 Bracket assembly. The bracket assembly shall be packaged in accordance with method III of Specification MIL-P-116.

5.2.1.1.4 Wire and cable assemblies. The ground wire assembly (Dwg B5-19-1663) and cable assembly (Dwg B5-19-1768) shall be packaged together in accordance with method IA-15 of Specification MIL-P-116.

5.2.1.1.5 Cable assembly. The cable assembly (Dwg B5-19-1767) shall be coiled to the minimum safe diameter. The coiled cable assembly shall be secured in at least three places by tying with flat cotton tape and then packaging in accordance with method IA-15 of Specification MIL-P-116.

5.2.1.1.6 Circuit breaker and switch assembly. This assembly shall be packaged in accordance with method IA-15 of Specification MIL-P-116.

5.2.1.1.7 Miscellaneous metal items. No preservative shall be applied to nonferrous items, except for aluminum. Ferrous items and aluminum items shall be coated with type P-7 preservative oil conforming to Specification MIL-P-116. Like items shall be placed together in non-heat sealable envelopes fabricated from grade A greaseproof barrier-material conforming to Specification MIL-B-121. The envelopes containing the miscellaneous metal items shall then be packaged together in accordance with method IC-2 of Specification MIL-P-116.

5.2.1.1.8 Miscellaneous non-metallic items. Like items shall be packaged together in accordance with method III of Specification MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:51Z
Check the source to verify that this is the current version before use.

5.2.1.2 Intermediate packaging. The components of the kit, preserved and unit packaged as specified in 5.2.1.1, shall be intermediately packaged in a W5c, style RSC fiberboard box conforming to Specification PPP-B-636. Internal cushioning and blocking shall be used as required to make a tight package. In addition to the closure and reinforcement requirements specified for interior boxes, the box corners, seams, and manufacturer's joint shall be taped, except that pressure sensitive tape conforming to Specification PPP-T-76 shall be used.

5.2.2 Level C. The components of the installation kit shall be cleaned and dried as specified in 5.1 and preserved and packaged to afford adequate protection from the supply source to the first receiving activity for immediate use.

5.3 Packing. Levels shall be as specified (see 6.2).

5.3.1 Level A. The installation kits, packaged as specified in 5.2, shall be packed, not to exceed the weight limitations of the container, in an overseas type or class, style optional container conforming to Specification PPP-B-591, PPP-B-601, or PPP-B-621; or in a V3c, style RSC fiberboard box conforming to Specification PPP-B-636. Closure, strapping, or reinforcement of the container shall be in accordance with the requirements of the applicable container specification and the appendix thereto. In addition to the closure requirements specified in the appendix to Specification PPP-B-636, the seams, corners, and manufacturer's joint shall be taped. Either the tape specified in Specification PPP-B-636 or tape conforming to Specification PPP-T-76 shall be used. All strapping or metal banding used shall be galvanized.

5.3.2 Level B. The installation kits, packaged as specified in 5.2, shall be packed as specified in 5.3.1, except that domestic type or class containers shall be used. In addition, all strapping or metal banding shall be coated-finished.

5.3.3 Level C. The installation kits, packaged as specified in 5.2, shall be packed to insure carrier acceptance and safe delivery at first destination for immediate use. Containers shall be in accordance with Uniform Freight Classification rules or regulations of other carriers applicable to the mode of transportation.

5.4 Marking. In addition to any special marking required by the contract or order, unit and intermediate packaging and shipping containers shall be marked in accordance with Standard MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:51Z
Check the source to verify that this is the current version before use.

6, NOTES

6.1 Intended use. This installation kit is used for installation of the M14 Filter Unit in Armored (APC) Ambulances.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Level of packaging and packing required.

6.3 Repair parts packaging. When repair parts packaging is required for items authorized for stocking as repair parts, the repair parts packaging data sheets covering the applicable components of the M32 installation kit should be used, (Copies of repair parts packaging data sheets may be obtained from the Director of Engineering and Industrial Services, ATTN: Chief, Design Branch, US Army Edgewood Arsenal, Edgewood Arsenal, Maryland - 21010.)

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 4240-A191

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:51Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)* | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE C-8279

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:51Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:51Z
Check the source to verify that this is the current version before use.