Metric
MIL-PRF-49434A(CR)
27 August 1997
SUPERSEDING
MIL-L-49434(ER)
27 April 1997

PERFORMANCE SPECIFICATION
AIMING LIGHT, INFRARED, AN/PAQ-4C

This performance specification is approved for use by USA CECOM, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This performance specification pertains to the Aiming Light, Infrared, AN/PAQ-4C.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents will be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS), and supplements thereto, cited in the solicitation (see 6.2.n).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: HQ, USA Communications-Electronics Command, ATTN: AMSEL-LC-LEO-E-EP, Fort Monmouth, NJ 07703 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5855
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-461	-	Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference
MIL-STD-462	-	Electromagnetic Interference Characteristics,
MIL-STD-810C	-	Environmental Test Methods (Ref)
MIL-STD-1425	-	Safety Design Requirements for Military Lasers and Associated Support Equipment

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building #4, Section D, Philadelphia, PA 19111-5094.)

2.2.2 Other Government documents, drawings, and publications. The following government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues will be those in effect on the date of the solicitation (see 6.2.n).

DRAWINGS

A3186949	-	Bag, Textile
A3186950	-	M-16 Mounting Bracket Assembly (M16A1/A2, M16/M203)
AXXXXXXX	-	M-16 Mounting Bracket Assembly (M16A2 only)
A3186951	-	Case Assembly, Electronic Communication Equipment
A3186954	-	Battery Cap Assembly
A3259273	-	Strapless Remote Switch Assembly
A3187000	-	System, AN/PAQ-4C
A3187001	-	Infrared Aiming Light Assembly

PUBLICATIONS

TB MED 524	-	Department of Army: Controls of Hazards to Health from Laser Radiation

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2.3 Handbooks.

The following handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2). Handbooks are for guidance only and therefore are not mandatory.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

HANDBOOKS

DEPARTMENT OF DEFENSE

MIL-HDBK-454	- Standard General Requirements for Electronic Equipment
MIL-HDBK-781	- Reliability Testing for Engineering Development, Qualification and Production

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The AN/PAQ-4C Infrared Aiming Light (IAL) system consists of an operator's manual, an aiming light assembly, a remote switch assembly with cable hangers, M16 mounting equipment (see 6.2.o), a mounting adapter for M2 and M60, cleanup materials, a textile carrying bag, and a shipping/storage case. The IAL is a self-contained infrared (IR) source used by soldiers wearing Night Vision Goggles (NVG) to deliver accurate weapon fire at night. The output beam shall not be detectable by the naked eye under any environmental conditions.

3.2 Performance characteristics. The IAL shall easily mount on and zero with the M16 rifle (see 6.2.o) using the M16 mounting equipment provided with the IAL. The IAL shall be capable of being mounted on, zeroed, dismounted from, and mounted on the M16 rifle without changing beam location by greater than 0.5 milliradian (mrad) from the initial zero setting. Operation of the IAL on the M16 rifle shall not require any modification to the weapon. The IAL, when mounted on the M16, shall not interfere with normal sighting devices on the weapon or restrict movement of the soldier. The IAL, when used in conjunction with AN/PVS-7( ) NVG, shall enable the soldier to deliver accurate fire at a minimum range of 600 meters. The textile carrying bag shall be capable of carrying the IAL, an operator's manual, the M2/M60 adapter, and all equipment necessary to mount, operate, and zero the IAL to the M16 rifle.

3.3 Construction. The system shall be constructed in accordance with drawing A3187000 and all provisions of this specification. In the event of any inconsistency between this specification and the drawings, this specification shall govern.

3.4 Initial production inspection. When specified in the contract or purchase order, the contractor shall furnish initial production inspection (IPI) samples and inspect them in accordance with 4.2 (see 6.2.l).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

3.5 Parts and materials. The contractor shall select the materials, but the materials and parts used shall be fully capable of meeting all of the operational and environmental requirements specified herein. The materials specified in the applicable drawings are recommended, but are not mandatory. Selection criteria of the class, grade or type part shall be that the material will be able to perform its intended function when it is assembled. Verification of the supplier meeting the overall performance requirements shall be the governing acceptance standard. Recovered materials shall be used to the maximum extent possible.

3.6 Major components. All major components, down to the spare part component level, shall be interchangeable with respect to form, fit, and function.

3.6.1 Battery. The IAL shall be powered by equal or similar battery type BA-3058/U ("AA" alkaline).

3.6.2 Battery Cap Assembly. The battery cap assembly shall be constructed in accordance with drawing A3186954.

3.6.3 IAL assembly. The IAL assembly shall be in accordance with A3187001.

3.6.4 M16 mounting bracket assembly. The M16 mounting bracket assembly shall be in accordance with drawing AXXXXXXXXX.

3.6.5 Strapless remote switch assembly. The cable switch assembly shall be in accordance with drawing A3259273.

3.6.6 Textile Carrying Bag. The textile carrying bag shall be in accordance with drawing A3186949.

3.6.7 Shipping/storage case. The shipping/storage case shall be in accordance with drawing A3186951.

3.7 Performance characteristics.

3.7.1 Output beam width. The IAL shall project a well defined beam with a beam width of 0.25 mrad to 0.50 mrad along every axis in a plane perpendicular to the beam's longitudinal axis. In the same plane, the ratio of the largest beam width measurement to the smallest beam width measurement shall not exceed a value of 1.8.

3.7.2 Output power. When measured at the output aperture, with the optical baffle assembly removed and with an input voltage of 3.0 volts direct current (Vdc), the IAL's peak power shall not be less than 0.50 mW nor be greater than 0.70 mW. The IAL shall be designed in accordance with MIL-STD-1425 and TB MED 524 to be Class 1 (eye-safe) at the assembly output, both with and without the optical baffle assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

3.7.3 Modulation. The IAL shall project a continuous, unmodulated beam.

3.7.4 Output peak wavelength. The IAL shall have an output peak wavelength of 840 nanometers, +10 / -20, at room temperature (see 3.15.2).

3.7.5 Spectral bandwidth. The IAL, at room temperture (see 3.15.2) and with an input voltage of 3.0 Vdc, shall have a spectral bandwidth of no greater than 8 nanometers (nm).

3.7.6 Boresight retention (BR).

3.7.6.1 Boresight retention-shock. The IAL, mounted on the M16 rifle with the M16 bracket, shall retain a postfiring zero position within 0.5 mrad of its prefiring zero position after discharging 300 rounds of ammunition.

3.7.6.2 Boresight retention-vibration. The IAL, mounted on a simulated M16 rifle with the M16 bracket, shall retain a postvibration neutral position within 0.5 mrad of its previbration neutral position after each of the three axes is subjected to vibrations in a frequency range of 5 to 55 hertz (Hz) with an amplitude of 0.100 inch total excursion for 30 minutes in each direction.

3.7.7 Input current. The maximum dc input current of the IAL, at room temperature (see 3.15.2), shall be 50.0 milliamperes (mA) for an input voltage of 3.0 Vdc.

3.7.8 Controls and adjustments. All controls and adjustments shall operate smoothly without loss of the intended settings or the presence of backlash. Both the azimuth (AZ) and elevation (EL) adjuster knobs shall turn 6.0 rotations, +2.0 / -0.5, stop to stop, with audible and tactile detents. A white circumferential dot shall appear on each adjuster knob. A sighthole, for locating the white circumferential dot, shall be present at the front of each adjuster knob cover. Adjuster flanges shall be marked to display the bullet's "point-of-impact" movement during the zeroing procedure. The relationship between adjuster knob rotation and point-of-impact movement shall be regulated by the "left hand rule" (i.e., when moving the fingertips of a cupped left hand in the direction of adjuster knob rotation, the left thumb of the same hand points in the direction of the bullet's point-of-impact movement).

3.7.8.1 Neutral Position. The white circumferential dot on each adjuster knob, when set at the clockwise end-of-travel stop, shall be centerd in the adjuster cover sighthole to within ±2 clicks. The "neutral position" of each adjuster knob shall be three counterclockwise rotations from the clockwise end-of-travel stop with the white dot centered in the adjuster cover sighthole to within ± ½ click. When the AZ and EL adjuster knobs are both set to the neutral position, the IAL beam shall be within 1.0 mrad of the optical axis of the IAL.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

3.7.8.2 ON/OFF switch. The IAL shall have an ON/OFF switch with five positions: OFF, Momentary ON, ON, Momentary ON, and OFF. Only the Momentary ON position shall be used when the IAL is mounted on the M16A2 rifle by applying pressure to activate the switch and by removing pressure to deactivate the switch. The design of the ON/OFF switch shall prevent unintentional activation of the IAL when carrying (with either hand, or with a shoulder strap on either shoulder) or laying down the M16A2 rifle. ON/OFF switch operation shall be indicated on the IAL.

3.7.8.3 Beam movement. Each adjuster shall move the beam at a nominal rate of 0.4 mrad/click and each adjuster shall have sufficient accuracy to meet the following requirements at each of the eight test points.

	Zone boundries	**Actual beam position on target**
Zone 1	Within a circle of 8.0 mrad diameter centered on the target origin	Within a square of side 1.2 mrad centered on the true position
Zone 2	Within an annulus of 8.0 mrad inner diameter and 20.0 mrad outer diameter centered on the target origin	Within a square of side 1.6 mrad centered on the true position

target origin – defined as the location of the beam center point on the target when the IAL is set to the neutral position (both AZ and EL).
Zone 1 – the region defined by the described circle centered on the target origin.
Zone 2 – the region defined by the described annulus centered on the target origin and concentric with Zone 1.
true position – the theoretically exact location of the beam center point established solely by the number of adjuster clicks.

	Test Points							
	1	**2**	**3**	**4**	**5**	**6**	**7**	**8**
AZ Adjuster Clicks	5 c	5 c	5 cc	5 cc	15 c	15 c	15 cc	15 cc
EL Adjuster Clicks	5 c	5 cc	5 c	5 cc	15 c	15 cc	15 c	15 cc

c – clockwise from the neutral position.
cc – counterclockwise from the neutral position.

3.7.9 Weight. The weight of the IAL assembly with batteries shall not exceed 164 grams. The total weight of the IAL assembly to include batteries, and the M16 mounting bracket shall not exceed 279 grams.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

3.7.10 Visual security. The IAL shall incorporate a removable optical baffle assembly which prevents the IAL beam from being detected at off-axis angles of greater than 6 degrees when viewed with NVG. During IAL operation, there shall be no IAL beam reflections from the mounting bracket or the weapon when viewed with NVG.

3.7.11 Size. The external volume of the IAL with the optical baffle assembly, battery cap assembly, and thumbscrew assembly installed shall not exceed 7.2 in^3 +0.5 / -0.0.

3.7.12 Boresight alignment. When set to the neutral position and mounted on the M16 rifle with the M16 bracket, the IAL shall project a beam on a target at 25 meters which is within 4 inches vertically and 4 inches horizontally of the longitudinal axis of the M16 barrel.

3.7.13 Boresight repeatability. When set to the neutral position and mounted to a secured M16 bracket, and then fully detached from the secured M16 bracket, and then reattached to the secured M16 bracket, the IAL's final beam position shall be within 0.5 mrad of the initial beam position.

3.8 Environmental.

3.8.1 High temperature. The IAL shall not be damaged (see 3.15.1) by storage at temperatures to +71°C and operation at temperatures to +51°C when tested (IAW) MIL-STD-810C, Method 501.1, Procedure I.

3.8.2 Low temperature. The IAL shall not be damaged (see 3.15.1) by storage at temperatures to -57°C and operation at temperatures to -54°C when tested IAW MIL-STD-810C, Method 502.1, Procedure I.

3.8.3 Altitude (operational). The IAL assembly shall not be damaged (see 3.15.1) when operating at an altitude of 10,000 feet (3,048 meters) and a temperature of -54°C, and shall not be damaged after storage at an altitude of 50,000 feet (15,240 meters) and a temperature of -57°C when tested IAW MIL-STD-810C, Method 500.1, Procedure I.

3.8.4 Temperature shock (non-operational). The IAL assembly shall not be damaged (see 3.15.1) after being exposed to a temperature change from +65°C to -57°C in a five (5) minute period when tested IAW MIL-STD-810C, Method 503.1, Procedure I.

3.8.5 Humidity. The IAL assembly shall not be damaged (see 3.15.1) when exposed to a relative humidity of 94 percent $\pm$ 4 over a temperature range of +23°C to +65°C for up to 10 days when tested IAW MIL-STD-810C, Method 507.1, Procedure II.

3.8.6 Immersion (non-operational). The IAL assembly shall not be damaged (see 3.15.1) after being temperature soaked to 45°C and immersed in a minimum of 30 inches of fresh water for a minimum of 120 minutes when tested IAW MIL-STD-810C, Method 512.1, Procedure I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

3.8.6.1 Extended depth immersion (non-operational). The IAL assembly shall not be damaged (see 3.15.1) after being immersed in a minimum of 100 feet of fresh water for a minimum of 120 minutes.

3.8.7 High intensity shock (non-operational). The IAL assembly shall not be damaged (see 3.15.1) when subjected to three half-sine pulses with a peak amplitude of 400 g ± 15 percent (see 3.15.7) for a duration of 1 millisecond ± 5 percent along the horizontal, vertical, and optical axes when tested IAW MIL-STD-810C, Method 516.2, Procedure IV as modified by this paragraph.

3.8.8 Vibration (non-operational). The IAL assembly shall not be damaged (see 3.15.1) when subjected to random vibration having a power spectral density of up to 0.015 g^2/Hz over a frequency range of 10 to 500 Hz when tested IAW MIL-STD-810C, Method 514, as modified by paragraph 4.5.8 of this specification.

3.8.9 Transit drop. The IAL assembly and ancillary equipment contained in the shipping/storage case shall not be damaged (see 3.15.1) when subjected to drops from a minimum of 48 inches on each corner, edge, and face of the shipping/storage case when tested IAW MIL-STD-810C, Method 516.2, Procedure II.

3.8.10 Sand and dust. The IAL shall not be damaged (see 3.15.1) by sand and dust when tested IAW MIL-STD-810C, Method 510.1, Procedure I.

3.8.11 Salt fog. The IAL shall not be damaged (see 3.15.1) by salt fog when tested IAW MIL-STD-810C, Method 509.1, Procedure I.

3.8.12 Fungus. The IAL, in a non-operating condition, shall not be damaged (see 3.15.1) by fungus or support fungal growth when tested IAW MIL-STD-810C, Method 508.2.

3.8.13 Explosive atmosphere. The IAL, immersed in an explosive gaseous mixture, shall not cause ignition of the mixture during IAL turn-on, operation, or turn-off when tested IAW MIL-STD-810C, Method 511.1,Procedure I.

3.9 Reliability. The IAL assembly shall have a minimum Mean Cycles Between Failures (MCBF) of 30,000. MIL-HDBK-781 may be used for guidance.

3.10 Electromagnetic interference (EMI). The IAL assembly shall be tested in accordance with the following emission and susceptibility requirements of MIL-STD-461 Notice 4: RE02, RS02, and RS03. The upper frequency limit requirements of RE02 and RE02.1 shall be 400 MHz. For RS03, the IAL assembly shall be immersed in electric fields of the intensities shown in Table I using the specified modulation characteristics. The IAL assembly shall meet MIL-STD-461 requirements during RE testing and shall not be affected or damaged (see 3.15.1) during or after RS testing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

Table I. EMI test conditions.

Frequency Range	Field Intensity	Modulation Characteristics
0.01 to 1.90 MHz	1.0 volt/meter	400 Hz square wave – 50 percent
2.0 to 75.9 MHz	10.0 volts/meter	FM ± 8kHz deviation – 1000 Hz
76.0 to 400.0 MHz	10.0 volts/meter	AM 1000 Hz tone – 50 percent

3.11 Treatment and painting. Unless otherwise specified, the aiming light shall have an external surface of a composition or surface treatment which will prevent rust, corrosion, and fungus growth in the full range of environmental requirements. External color and surface shine shall reduce light reflection and reduce recognition. Adherence of surface treatments or coatings must be assured through the full range of environmental and use factors.

3.12 Marking. The IAL shall have markings to indicate battery orientation.

3.13 Workmanship. All electronic parts and components of the aiming light shall be free of smudges, excess solder, metal chips or the existence of any foreign material on any surface. Bearing assemblies shall be free from rust and tool marks. Wires and integrated circuitry shall be protected from contact with rough or irregular surfaces and be shielded from shorting. MIL-HDBK-454 may be used as guidance.

3.14 Environmental Stress Screening (ESS). The IAL and its subassemblies shall not be damaged (see 3.15.1) when subjected to the ESS exposures deemed necessary to reveal or display infant mortality type failures (see 3.15.4) or ESS failures (see 3.15.5).

3.15 Technical Interpretation. The following technical interpretations are, when referenced in section 3, 4, or 5, mandatory for this specification.

3.15.1 Damage. Damage is defined as any breakage, loosening, distortion, or shifting; failure of any finish, hardware, connection, or component; condensation on any internal surface; and failure to operate in accordance with the requirements of this specification.

3.15.2 Room temperature. Room temperature is defined as +23°C ± 10 C°.

3.15.3 Spectral bandwidth. Spectral bandwidth is defined as the difference between the upper and lower wavelength values measured at 50 percent of peak spectral intensity.

3.15.4 Infant mortality. Those failures which occur due to workmanship, weak parts, and/or inadequate design.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

3.15.5 Environmental Stress Screening (ESS). An ESS failure is any shortcoming, imperfection, or operational nonconformance, including a one-time nonrepeatable anomaly, either sudden or gradual in nature, which causes the unit under test to deviate from specified limits. ESS failures include poor workmanship, defective manufacturing processes, and defective components. Non-ESS failures are those directly attributed to failures of test monitoring equipment, failures due to operator errors, failures occurring during repair, or failures due to test equipment generating overstress conditions.

3.15.6 Zero/Zeroed/Zeroing. With the IAL attached to a weapon, this procedure adjusts the IAL's laser beam so that it is coincident with the bullet's point-of-impact on a target at a particular range.

3.15.7 g. Uniform (i.e., constant) acceleration of magnitude 32.17 ft s^{-2}.

4. Verification.

4.1 Classification of inspections. Inspections shall be classified as follows:

a. Initial production inspection (4.2)
b. Quality conformance inspection (4.5)

4.2 Initial production inspection. Unless otherwise specified in the contract or purchase order, the initial production inspection (IPI) shall be performed by the contractor (see 6.2.l).

4.2.1 IPI samples. Unless otherwise specified in the contract or purchase order, thirty samples shall be selected from the first IAL production lot for IPI. Disposition of IPI samples shall be in accordance with the contract or purchase order (see 6.2.j).

4.2.2 Inspection. Each IAL shall be inspected in accordance with Table II, both in process and when assembled, as required. ESS, if performed on IALs, shall be performed last. Presence of one or more defects shall be cause for rejection of that IAL and may be cause for rejection of IPI.

Table II. Inspection.

Inspection	Requirement paragraph	Test paragraph
Parts and Materials	3.5	Review
Treatment and Painting	3.11	4.8
Marking	3.12	4.9
Workmanship	3.13	4.10
ESS	3.14	4.11

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

4.2.3 IPI testing. Test samples shall be selected from IALs which have passed the requirements of Table II and shall meet the requirements of Table III. Sample size shall be 6 IALs for subgroup 1, 6 IALs for subgroup 2, and 3 IALs for subgroup 3. The first 12 tests may be performed in any order and must be performed first. In subgroup 3 one unit shall be tested for EMI and sand and dust; one unit for explosive atmosphere and salt fog; and one unit for fungus. Failure of any test shall constitute an initial production inspection (IPI) failure. Each sample shall be identified as to its applicable subgroup prior to the start of testing. Unless otherwise specified, the IALs shall be operated at a temperature of 23°C ± 10 C° (see 3.15.2).

4.3 Quality conformance inspection.

4.3.1 Inspection. All production IALs shall be subjected to the requirements of Table II. Unless otherwise specified, the IALs shall be operated at a temperature of 23°C ± 10 C° (see 3.15.2).

4.3.2 Group inspection.

4.3.2.1 Group A inspection. IALs that have passed the examination specified in 4.3.1 shall be tested in accordance with Table IV. Failure of any test shall be cause for rejection of that unit. IALs which pass Group A inspection shall be formed into lots. Lot size shall be determined by the contractor. Group A tests may be performed in any order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

Table III. Initial production inspection.

Inspection	Requirement paragraph	Test paragraph	Subgroup 1	2	3
Output beam width	3.7.1	4.4.1	X	X	X
Output power	3.7.2	4.4.2	X	X	X
Modulation	3.7.3	4.4.3	X	X	X
Output peak wavelength	3.7.4	4.4.4	X	X	X
Spectral bandwidth	3.7.5	4.4.5	X	X	X
BR-shock	3.7.6.1	4.4.6.1			X
BR-vibration	3.7.6.2	4.4.6.2			X
Input current	3.7.7	4.4.7	X	X	X
Controls and adjustments	3.7.8	4.4.8	X	X	X
Neutral position	3.7.8.1	4.4.8.1	X	X	X
ON/OFF switch	3.7.8.2	4.4.8.2	X	X	X
Beam movement	3.7.8.3	4.4.8.3	X	X	X
Weight	3.7.9	4.4.9	X	X	X
Visual security	3.7.10	4.4.10	X		
Size	3.7.11	4.4.11	X		
Boresight alignment	3.7.12	4.4.12	X	X	X
Boresight repeatability	3.7.13	4.4.13	X	X	X
High temperature	3.8.1	4.5.1	X		
Low temperature	3.8.2	4.5.2	X		
Altitude	3.8.3	4.5.3	X		
Temperature shock	3.8.4	4.5.4	X		
Humidity	3.8.5	4.5.5	X		
Immersion	3.8.6	4.5.6	X		
Extended depth immersion	3.8.6.1	4.5.6.1	X		
High intensity shock	3.8.7	4.5.7	X		
Vibration	3.8.8	4.5.8	X		
Transit drop	3.8.9	4.5.9	X		
Sand and dust	3.8.10	4.5.10			X
Salt fog	3.8.11	4.5.11			X
Fungus	3.8.12	4.5.12			X
Explosive atmosphere	3.8.13	4.5.13			X
Reliability	3.9	4.6		X	
EMI	3.10	4.7			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

Table IV. Group A inspection.

Inspection	Requirement paragraph	Test paragraph
Output beam width	3.7.1	4.4.1
Output power	3.7.2	4.4.2
Modulation	3.7.3	4.4.3
Controls and adjustments	3.7.8	4.4.8
Neutral position	3.7.8.1	4.4.8.1
Visual security	3.7.10	4.4.10

4.3.2.2 Group B inspection. Group B inspection shall be conducted on IALs selected from units which have passed the tests in 4.3.2.1. Sampling of lots shall be in accordance with the contract or purchase order (see 6.2.k).

Table V. Group B inspection.

Inspection	Requirement paragraph	Test paragraph
Output peak wavelength	3.7.4	4.4.4
Spectral bandwidth	3.7.5	4.4.5
Input current	3.7.7	4.4.7
Beam movement	3.7.8.3	4.4.8.3
Weight	3.7.9	4.4.9
Boresight alignment	3.7.12	4.4.12
Boresight repeatability	3.7.13	4.4.13

4.3.2.3 Group C inspection. Group C inspections shall be conducted on IALs selected from units which have passed the tests in 4.3.2.1. The IALs shall be tested in accordance with the inspections listed in Table VI, unless otherwise specified. Except for subgroup 3, samples shall be selected in accordance with the contract or purchase order (see 6.2.k). Group C tests shall be performed in the order stated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

Table VI. Group C inspection.

Inspection	Requirement paragraph	Test paragraph	Subgroup 1	Subgroup 2	Subgroup 3
BR-shock	3.7.6.1	4.4.6.1			X
BR-vibration	3.7.6.2	4.4.6.2			X
ON/OFF switch	3.7.8.2	4.4.8.2			X
Size	3.7.11	4.4.11			X
High temperature	3.8.1	4.5.1	X		
Low temperature	3.8.2	4.5.2		X	
Altitude	3.8.3	4.5.3		X	
Temperature shock	3.8.4	4.5.4			X
Humidity	3.8.5	4.5.5	X		
Immersion	3.8.6	4.5.6		X	
High intensity shock	3.8.7	4.5.7	X		
Vibration	3.8.8	4.5.8		X	
Transit drop	3.8.9	4.5.9			X

4.3.2.3.1 Subgroup testing.

4.3.2.3.1.1 Subgroup 1. For this subgroup, humidity shall be tested last.

4.3.2.3.1.2 Subgroup 2. For this subgroup, immersion shall be tested last.

4.3.2.3.1.3 Subgroup 3. For this subgroup, two IAL's shall be selected from each third lot.

4.3.2.3.2 Group C failures. Actions required relative to Group C failures shall be as specified in the contract or purchase order (see 6.2.f).

4.3.2.3.3 Reinspection of conforming Group C sample units. Unless otherwise specified, sample units which have been subjected to and passed Group C inspection may be accepted on the contract or purchase order, provided all visible and known damage is repaired and the sample units are resubjected to and pass the Group A inspections of Table IV.

4.3.2.4 Group D inspection. Reliability testing shall be conducted on IALs selected from the units which have passed the tests in 4.3.2.1. Tests shall be conducted IAW accordance with Table VII.

Table VII. Group D inspection.

Inspection	Requirement paragraph	Test paragraph
Reliability	3.9	4.6

4.3.2.4.1 Sampling for reliability testing. The production reliability acceptance test shall be performed on IALs from each production lot submitted. The sample size shall be a minimum of 3 IALs from each production lot and reliability test shall be performed every third production lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

4.3.2.4.2 Reliability failures. Actions required relative to reliability failures shall be as specified in the contract or purchase order (see 6.2.f).

4.3.2.4.3 Reinspection of reliability sample units. Unless otherwise specified, sample units which have been subjected to and passed reliability tests may be accepted on the contract or purchase order, provided all damage is repaired and the units are resubjected to and pass the Group A inspections of Table IV.

4.4 Test methods.

4.4.1 Output beam width. The IAL shall be mounted securely at one end of a 25 meter range. A detector shall be placed on an optical bench with the detector plane perpendicular to the beam's longitudinal axis at a distance of 25 meters from the front of the IAL. The detector shall be masked to a vertical slit of 1 mm maximum slit width. The output signal of the detector assembly shall be displayed on an oscilloscope or digital meter. The optical bench shall have graduation markings in millimeters. Using the above equipment, the peak intensity of the IAL output beam shall be determined and the horizontal extremes noted. The beam width is equal to the spatial dimension occuring between collinear 10 percent (of peak) intensity points. After completion of the measurements in the first orientation, the IAL shall be rotated $90^{\circ} \pm 5$ about its optical axis and the test repeated for the second orientation. An optical bench simulating the 25 meter range and testing requirements may be used. Failure to meet the requirement of 3.7.1 shall constitute failure of this test.

4.4.2 Output power. The output power of the IAL, with the optical baffle assembly removed, shall be measured using a calibrated thermopile (or equivalent meter) and a collecting lens and iris with an effective clear aperture equivalent to the diameter of the IAL refractive lens plus 4 cm. The thermopile shall be located at the focal plane of the collecting lens so as to collect only the energy within the specified beam width. The output power of the IAL shall be measured. Failure to meet the requirements of 3.7.2 shall constitute failure of this test.

4.4.3 Modulation. The output of the IAL shall be sensed by a photodiode or other suitable detector. The detector output will be displayed on an oscilloscope or processed by other acceptable means. This test shall be performed at both 2.4 Vdc and 3.0 Vdc. Failure to meet the requirements of 3.7.3 shall constitute failure of this test.

4.4.4 Output peak wavelength. The peak output wavelength of the IAL shall be measured using a spectrometer with a spectral resolution of at least 2 nanometers. Failure to meet the requirements of 3.7.4 shall constitute failure of this test.

4.4.5 Spectral bandwidth. The equipment described in 4.4.4 shall be used to measure the spectral bandwidth of the IAL, powered by a 3.0 Vdc power source, at the 50 percent peak intensity points. Failure to meet the requirements of 3.7.5 shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

4.4.6 Boresight retention (BR).

4.4.6.1 Boresight retention-shock. The IAL shall be mounted on an M16 rifle utilizing the M16 bracket and zeroed to 25 meters distance by locating the beam in accordance with paragraph 4.4.1 above; no further adjustments to the IAL shall be made. After completion of 300 firings, the rifle/bracket/IAL assembly postfiring beam position shall be compared, without making any adjustments, to the prefiring beam position by locating the beam in accordance with paragraph 4.4.1 and measuring the displacement of the 10 percent (of peak) intensity points. Failure to meet the requirements of 3.7.6.1 shall constitute failure of this test.

4.4.6.2 Boresight retention-vibration. The IAL shall be set to the neutral position and mounted on an M16 bracket which is attached to a simulated M16 rifle; no further adjustments to the IAL shall be made. The simulated rifle shall be placed in an appropriate mount, the IAL shall be turned on, and the beam location on a target at 25 meters noted. The simulated rifle/bracket/IAL assembly shall then be subjected to harmonic motion along each of three orthogonal axes, one being the longitudinal axis of the simulated rifle and the other two being orthogonal to the longitudinal axis and each other. The frequency of the harmonic motion shall be varied uniformly from 5 to 55 Hz ($\pm$2 Hz tolerance) and returned to 5 Hz in one minute. The vibration amplitude shall be 0.050 inch (0.100 inch $\pm$ 0.005 total excursion). Repeat the 5Hz-55Hz-5Hz frequency sweep 30 times in each of the three axis directions. Return the simulated rifle/bracket/IAL assembly to the mount and, without making any adjustments, note the beam location on the target at 25 meters. Failure to meet the requirements of 3.7.6.2 shall constitute failure of this test.

4.4.7 Input current. The IAL shall be powered by a 3.0 Vdc power source. An ammeter shall be connected in the power supply line to measure the average current. Failure to meet the requirement of 3.7.7 shall constitute failure of this test.

4.4.8 Controls and adjustments. All controls and adjustments shall be exercised throughout their entire range and examined for the required markings. Failure to meet the requirements of 3.7.8 shall constitute failure of this test.

4.4.8.1 Neutral position. Verify that each adjuster knob is marked with a white circumferential dot and that each adjuster cover has a sighthole at the front. Rotate each adjuster knob clockwise to the end-of-travel stop and verify that the white dot is centered in the sighthole to within $\pm$2 clicks. Rotate each adjuster knob three counterclockwise rotations from the clockwise end-of-travel stop and center each white dot in the applicable sighthole -- this is the "neutral position." Verify that the white dot is centered in the sighthole to within ± ½ click for each adjuster knob when set in the neutral position. Also verify that the IAL beam is within 1.0 mrad of the IAL optical axis when the AZ and EL adjuster knobs are both set in the neutral position. Failure to meet the requirements of 3.7.8.1 shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

4.4.8.2 ON/OFF switch. The ON/OFF switch shall be examined for the required markings and placed in each of the five switch positions. Verify that the IAL performs as intended in each of the five switch positions. The IAL shall then be mounted to an M16 rifle with the M16 mounting bracket. Alternately place the rifle on its left and right sides 10 times (5 times on each side) on a horizontal surface, examining each time with NVG for IAL turn-on. Next, a person wearing a ski-jacket shall alternately sling the rifle, using a shoulder strap, on his left and right shoulders 10 times (5 times on each shoulder) while a second person examines the procedure with NVG for IAL turn-on. Failure to meet the requirements of 3.7.8.2 shall constitute failure of this test.

4.4.8.3 Beam movement. The IAL shall be set to the neutral position and mounted on an M16 bracket which is attached to a simulated M16 barrel. The IAL beam shall be turned on and directed toward a target at a distance of 25 meters $\pm$ 0.1, and the beam center point and target origin shall be made coincident. The target markings shall include: an origin; a rectangular coordinate system using centimeter units; the two zones; the true position of each of the eight test points; and, the tolerance zone for each of the eight test points in true position. The adjuster knobs shall be rotated the required number of clicks for each test point and the actual beam location shall then be compared to the true position mark with its tolerance zone. Failure to meet the requirements of 3.7.8.3 shall constitute failure of this test.

4.4.9 Weight. The IAL including the two batteries ("AA" alkaline) shall be weighed on a scale with an accuracy of $\pm$3.0 grams or better. The M16 mounting bracket shall then be placed on the same scale with the IAL and the two AA batteries and the combination shall be weighed. Failure to meet the requirements of 3.7.9 shall constitute failure of this test.

4.4.10 Visual security. Place a photodiode detector assembly (or equivalent device) capable of measuring near infrared energy in front of the IAL such that it can be rotated in a horizontal arc about the IAL. A protractor, or other suitable device, capable of angular measurement to at least one tenth of a degree shall be used for this test. The center of the arc of rotation shall be the point at the front and center of the IAL where the output beam exits the optical baffle assembly; the 0 degree line shall be coincident with the laser beam axis. Starting at 0 degrees, rotate the detector to the angle at which the IAL output beam can no longer be detected and record the value. Rotate the detector back to 0 degrees and repeat the measurement on the other side of the IAL. Failure to meet the requirements of 3.7.10 shall constitute failure of this test.

4.4.11 Size. The IAL shall be placed in a device capable of measuring the IAL's true external volume to within $\pm$0.5 cubic inch. Failure to meet the requirement of 3.7.11 shall constitute failure of this test.

4.4.12 Boresight alignment. The IAL shall be set to the neutral position and mounted on an M16 bracket which is attached to a real or simulated M16 barrel. The IAL shall be turned on and the beam location on a target at 25 meters noted. Failure to meet the requirements of 3.7.12 shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

4.4.13 Boresight repeatability. The IAL shall be set to the neutral position and mounted on an M16 bracket which is attached to a real or simulated M16 barrel. The IAL shall be turned on and the beam location on a target at 25 meters noted. The IAL shall then be fully detached from the bracket, via the thumbscrew, and reattached. The IAL shall again be turned on and the beam location on the target at 25 meteres noted. Failure to meet the requirements of 3.7.13 shall constitute failure of this test.

4.5 Environmental tests. Unless otherwise specified, the environmental tests shall be performed in accordance with MIL-STD-810C as modified by this specification. The post operating tests required during these environmental conditions shall be as specified.

4.5.1 High temperature. The IAL shall be subjected to MIL-STD-810C, Method 501.1, Procedure I. Failure to meet the requirements of 3.7.1, 3.7.2, 3.7.3, 3.7.8, or 3.8.1 shall constitute failure of this test.

4.5.2 Low temperature. The IAL shall be subjected to MIL-STD-810C, Method 502.1, Procedure I. Failure to meet the requirements of 3.7.1, 3.7.2, 3.7.3, 3.7.8, or 3.8.2 shall constitute failure of this test.

4.5.3 Altitude. The IAL shall be subjected to MIL-STD-810C, Method 500.1, Procedure I. Failure to meet the requirements of 3.7.1, 3.7.2, 3.7.3, 3.7.8, or 3.8.3 shall constitute failure of this test.

4.5.4 Temperature shock. The IAL shall be subjected to MIL-STD-810C, Method 503.1, Procedure I. The temperature in steps 1 and 4 shall be +65°C (+149°F). Failure to meet the requirements of 3.7.1, 3.7.2, 3.7.3, 3.7.8, or 3.8.4 shall constitute failure of this test.

4.5.5 Humidity. The IAL shall be subjected to MIL-STD-810C, Method 507.1, Procedure II. Failure to meet the requirements of 3.7.2, 3.7.8, or 3.8.5 shall constitute failure of this test.

4.5.6 Immersion. The IAL shall be subjected to MIL-STD-810C, Method 512.1, Procedure I. Failure to meet the requirements of 3.7.2, 3.7.8, or 3.8.6 shall constitute failure of this test.

4.5.6.1 Extended depth immersion. The IAL shall be subjected to MIL-STD-810C, Method 512.1, Procedure I. Failure to meet the requirements of 3.7.2, 3.7.8, or 3.8.6.1 shall constitute failure of this test.

4.5.7 High intensity shock. The IAL shall be subjected to MIL-STD-810C, Method 516.2, Procedure IV except the shock pulse shall be 400 g, half sine, 1 millisecond duration. Failure to meet the requirements of 3.7.1, 3.7.2, 3.7.3, 3.7.8, or 3.8.7 shall constitute failure of this test.

4.5.8 Vibration. The IAL shall be subjected to MIL-STD-810C, Method 514.3, using the profiles of Figures 514.3-1, 514.3-2 and 514.3-3. Test duration shall be 30 minutes per axis. Failure to meet the requirements of 3.7.1, 3.7.3, 3.7.8, or 3.8.8 shall constitute failure of this test.

4.5.9 Transit drop. The IAL shall be subject to MIL-STD-810C, Method 516.2, Procedure II. The test shall be performed with the IAL and its components (i.e., mounting bracket(s), shroud, filter, etc.) installed in the shipping/storage case. Failure to meet the requirements of 3.7.2, 3.7.3, 3.7.8, or 3.8.9 shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

4.5.10 Sand and dust. The IAL shall be subjected to MIL-STD-810C, Method 510.1, Procedure I. Lens elements may be covered for this test. Failure to meet the requirement of 3.7.2, 3.7.8, or 3.8.10 shall constitute failure of this test.

4.5.11 Salt fog. The IAL shall be subjected to MIL-STD-810C, Method 509.3, Procedure I. Failure to meet the requirements of 3.7.2, 3.7.8, or 3.8.11 shall constitute failure of this test.

4.5.12 Fungus. The IAL shall be subjected to the MIL-STD-810C, Method 508.2. Failure to meet the requirements of 3.7.2, 3.7.8, or 3.8.12 shall constitute failure of this test.

4.5.13 Explosive atmosphere. The IAL shall be subjected to the MIL-STD-810C, Method 511.1, Procedure I. Failure to meet the requirements of 3.7.2, or 3.8.13 shall constitute failure of this test.

4.6 Reliability tests. The reliability testing shall be conducted using MIL-HDBK-781 for guidance.

4.6.1 Reliability sampling and testing. A sample of up to ten (10) randomly selected IALs, with no fewer than 3 IALs selected from each lot, shall be tested for a total of 555 hours (approximately 182,000 cycles) with no equipment operating less than 555/n hours, where n is the number of IALs on test. The equipment shall be monitored continuously. Inspections shall be performed every 12 hours and at the conclusion of reliability testing to ensure that the equipment conforms to the characteristics specified in Table IV of this specification. Only the time period between acceptable Group A Tests shall be accumulated as test time. Successful completion of the test occurs when the test units accumulate a total of 555 hours of operation with two or less failures. An external power source shall be used in place of batteries during the test.

Table VIII. Reliability test profile.

Environment	**Test Profile**
Temperature cycling	Two hour hold after stabilization at each temperature extreme of 0°C and +55°C.
Vibration	Random vibration per figure 514.3-1 of MIL-STD-810. Duration is 10 minutes minimum for each 60 minute cycle.
On-off cycling	Cycle on for eight seconds, off for three seconds, and repeat.
Input voltage cycling	The input voltage shall be varied as follows: 200 on/off cycles at 3.0 Vdc, then 200 on/off cycles at 2.7 Vdc, then 200 on/off cycles at 2.4 Vdc, and repeat.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

4.6.2 Failure definition. A failure is defined as any malfunction which causes an inability to commence operation, a cessation of operation, degradation of performance, any operation such that personnel safety is endangered, or damage (see 3.15.1). Failure to meet the requirements of 3.9 shall also constitute failure of this test.

4.7 Electromagnetic interference (EMI). The IAL shall be tested for compliance with the requirements of 3.10 using the approved measurement techniques of MIL-STD-462, as implemented by a government approved test plan. Failure to meet the requirements of 3.10 shall constitute failure of this test.

4.8 Treatment and painting. The IAL shall be examined for conformance to the requirements of paragraph 3.11.

4.9 Marking. The IAL and all components shall be examined for conformance to the requirements of paragraph 3.12.

4.10 Workmanship. The IAL shall be examined for conformance to the requirements of paragraph 3.13.

4.11 Environmental Stress Screening (ESS). ESS shall be conducted in accordance with an ESS test plan submitted by the contractor and approved by the government.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or purchase order (see 6.2.b). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department of Defense Agency or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory).

6.1 Intended use. The IAL is used in conjunction with AN/PVS-5 and AN/PVS-7 Night Vision Goggles to provide an aiming point that will allow the individual soldier to deliver accurate weapon fire on selected targets at night.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification and any amendment thereto.

b. Preservation, packaging, and packing requirements.

c. Date of delivery of Government furnished property, if any.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

d. A statement that IALs should not contain thorium, other radioactive material, or any combination of nuclear materials in excess of 0.05 percent by weight as defined in Title 10, Code of Federal Regulation, Part 40.

e. If available, Thermal and Vibration survey data will be provided to facilitate enhancement of the ESS temperature profile.

f. Actions required relative to Group C and D failures.

g. Whether batteries will be delivered or not, and, if delivered, instructions about how they are to be packed for shipment.

h. A prohibition against delivery of IALs with batteries installed.

i. That the contractor will supply batteries for tests.

j. Disposition of the Initial Production Inspection (IPI) samples.

k. Sampling for Group B and Group C testing. As guidance, unless otherwise specified sampling should be conducted per the requirements of MIL-STD-105.

l. Quantities and schedule for the Initial Production Inspection (IPI) Test.

m. Unless otherwise specified, MIL-STD-810C will be used for all environmental testing.

n. The issue of the applicable DODISS will be cited in the solicitation and, if required, the specific issues of individual documents required. (see 2.2.1 and 2.2.2).

o. The M16 rifle versions the AN/PAQ-4C being procured must interface with (e.g., M16A1, M16A2, M16/M203). Any additional weapons which the AN/PAQ-4C being procured must interface with.

6.3 Eye safety. The total output of the IAL will be measured with an Epply Thermopile (or equivalent) power meter. The IAL output will be Class 1 (eye safe) as established by MIL-STD-1425 and TB MED 524 for output power, wavelength, and any other pertinent parameters of the IAL's output. Such calculations will be provided to the government as an addendum to any IPI test report.

6.4 Qualification. The activity responsible for monitoring and approving/disapproving an AN/PAQ-4C qualification is the U.S. Army Communications-Electronics Command, Attn: AMSEL-LC-IEW-N-LS, Fort Monmouth, NJ 07703.

6.5 Definitions. See 3.15.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

6.6 Subject, term, and keyword list.

Azimuth
Class 1
Elevation
Eye-safe
Neutral position
Zero/zeroed/zeroing

CUSTODIAN:

Army – CR

PREPARING ACTIVITY:

Army – CR

(Project 5855-0100)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** MIL-PRF-49434A	**2. DOCUMENT DATE (YYMMDD)** 27 August 1997
3. DOCUMENT TITLE AIMING LIGHT, INFRARED, AN/PAQ-4C		
4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)		
5. REASON FOR RECOMMENDATION		
6. SUBMITTER		
a. NAME (Last, First, Middle initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON(If applicable)	7. DATE SUBMITTED (YYMMDD)
8. PREPARING ACTIVITY		
a. NAME US Army Communications-Electronics Command	b. TELEPHONE (Include Area Code) (1) Commercial (732) 532-9913 (2) AUTOVON 992-9913	
c. ADDRESS (Include Zip Code) ATTN:AMSEL-LC-LEO-E-EP Fort Monmouth, NJ 07703-5023	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 Previous editions are obsolete 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.