MILITARY SPECIFICATION
BATTERY, RECHARGEABLE, NICKEL-CADMIUM, VENTED, AIRCRAFT, BB-716/A

This amendment forms a part of MIL-B-49450(ER), dated 16 January 1987, and is approved for use within the Laboratory Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Insert after title:

"This specification is approved for use within Laboratory Comand, Department of the Army, and is available for use by all Department and Agencies of the Department of Defense."

PAGE 6

3.4.2.5, delete last sentence and substitute:

"The vent plug shall withstand 7 in-lb. of torque with no damage."

PAGE 7

3.4.3.1, delete second and third sentences and substitute:

"The thermistor used shall conform to MIL-T-23648. The thermistor shall be wired per applicable specification sheet."

PAGE 11

3.5.2.8, Instruction 4, line 3, delete "plate" and substitute "plates", 2 places.

PAGE 17

4.6.1.2.1, line 4, delete "distilded" and substitute "distilled".

FSC 6140

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:07Z
Check the source to verify that this is the current version before use.

PAGE 19

4.7.4.2, delete first sentence and substitute:

"The vent plug of each cell being tested shall be closed to a torque of 7 in-lb and then opened."

4.7.4.2, add the following sentence:

"The vent plugs may be screwed into a threaded metal adapter, rather than a cell, to conduct this test."

PAGE 21

4.7.14, delete first sentence and substitute:

"The battery shall be charged per 4.6.1.2.1 and subjected to the thermal shock test per procedure 1, Method 503.2 of MIL-STD-810 using a low temperature of -70°F (-57°C) and a high temperature of 160°F (71°C)."

4.7.14, insert the following after the first sentence:

"Diurnal cycling per procedure 1, Method 503.2 of MIL-STD-810 is not required."

PAGE 22

4.7.16, delete in its entirety and substitute:

"4.7.16 Humidity and charge retention. The battery shall be charged per 4.6.1.2.1 and then subjected to the humidity test per Procedure II, Method 507.1 of MIL-STD-810. The battery case air vents shall be positioned where the axis of the vents are parallel to the chamber air flow. Upon completion, accumulated water may be removed from the battery. The battery shall be discharged at the rate specified by the applicable specification sheet to the specified cut-off voltage and shall meet the requirements of 3.6.1 and 3.6.2.

Preparing Activity:
Army - ER

(Project 6140-A656)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:07Z
Check the source to verify that this is the current version before use.