
INCH-POUND
MIL-PRF-55514/12C
21 February 2002
SUPERSEDING
MIL-PRF-55514/12B
9 October 1997

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, FIXED, METALLIZED PLASTIC DIELECTRIC, DC, IN NONMETAL CASES, ESTABLISHED RELIABILITY, STYLE CFR29

The specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-55514.



Inches	mm
.002	0.05
.015	0.38
.032	0.81
.040	1.02
.062	1.57
.300	7.62
1.500	38.10

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information.

FIGURE 1. Configuration and dimensions.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:29Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figure 1.

Case: Non-hermetic.

* Dielectric: Polyphenylene sulfide (characteristic U); or
Metallized polycarbonate (characteristic R).

* Characteristics: R or U.

Capacitance value: See table I.

Capacitance tolerance: See table I.

* Operating temperature range: -55°C to +85°C, when properly voltage derated (see figure 2), characteristics R and U capacitors will operate to +125°C.

Voltage rating: See table I.

Preconditioning: Not applicable.

Burn-in: In accordance with MIL-PRF-55514 except for the following conditions:

a. DC burn-in voltage shall be 140 percent of the dc rated voltage applied for 48 hours minimum at 125°C, +4°C, -0°C.

b. AC burn-in: Not applicable.

Insulation resistance: Insulation resistance shall be measured at rated voltage at the applicable temperature. Charge time 2 minutes maximum; however, for capacitance values greater than 1.0 µF, an additional 1 minute per µF is permitted. The following limits shall apply:

Temperature	Insulation resistance
25°C	50,000
85°C	5,000
125°C	500

Marking: In accordance with MIL-PRF-55514.

Qualification submittal:

	Type designation	Sample size
*	CFR29RUA106FM	61
*	CFR29RUA506FM	61
*	CFR29RUG305FM	61
*	CFR29RUG506FM	61
*	CFR29RUB305FM	61
*	CFR29RUB506FM	61

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:29Z
Check the source to verify that this is the current version before use.

* TABLE I. Capacitor characteristics and dimensions.

Type designation 1/	Capacitance µF	Capacitance tolerance	Rated voltage at 85°C volts, dc	ESR milliohms at 100 kHz	Ripple current max at 25°C	Resonant frequency kHz	Dimensions		
							T 2/ 4/	W 2/ 4/	H 3/ 4/
CFR29R-A106--	10.0	J, K, M	50	11	12.6	318	.562	.862	.750
CFR29R-A206--	20.0	J, K, M	50	10	14.8	214	.718	.968	.875
CFR29R-A506--	50.0	J, K, M	50	6	23.5	130	1.000	1.375	1.000
CFR29R-G305--	3.0	J, K, M	75	15	10.3	672	.468	.718	.750
CFR29R-G505--	5.0	J, K, M	75	13	11.6	427	.500	.750	.875
CFR29R-G106--	10.0	J, K, M	75	12	13.5	301	.718	1.031	.875
CFR29R-G206--	20.0	J, K, M	75	11	16.5	205	.937	1.312	1.000
CFR29R-G506--	50.0	J, K, M	75	6	24.2	120	1.312	1.687	1.250
CFR29R-B305--	3.0	J, K, M	100	15	10.6	684	.437	.750	.875
CFR29R-B505--	5.0	J, K, M	100	13	12.4	427	.593	.906	.875
CFR29R-B106--	10.0	J, K, M	100	12	14.6	290	.781	1.093	1.000
CFR29R-B206--	20.0	J, K, M	100	11	17.1	192	.906	1.281	1.250
CFR29R-B506--	50.0	J, K, M	100	6	23.6	115	1.437	1.812	1.375

* 1/ The complete type designation will include additional symbols to indicate, characteristic (U or R), capacitance tolerance and product level (C, M, P, R, or S).
2/ Tolerances: Thickness and width +.062 inch, -.156 inch (+1.57 mm, -3.96 mm) on .437 inch through .500 inch (11.10 mm through 12.7 mm) and +.093 inch, -.187 inch (+2.36 mm, -4.75 mm) on .562 inch (14.27 mm) and greater.
3/ Tolerances: Length +.093 inch, -.062 inch (+2.36 mm, -1.57 mm).
4/ See dimension table below:

Inches	mm	Inches	mm	Inches	mm
.437	11.10	.862	21.89	1.250	31.76
.468	11.89	.875	22.23	1.281	32.54
.500	12.70	.906	23.01	1.312	33.32
.562	14.27	.937	23.80	1.375	34.93
.593	15.06	.968	24.59	1.437	36.50
.718	18.24	1.000	25.40	1.687	42.85
.750	19.05	1.031	26.19	1.812	46.02
.781	19.84	1.093	27.76		

Substitutability for capacitance tolerance shall be as follows:

Capacitance tolerance	Will replace capacitance tolerance
F	G, J, K
G	J, K
J	K
K	

Substitutability for voltage shall be as follows:

Volts dc	Will replace voltages
100	75, 50
75	50

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:29Z
Check the source to verify that this is the current version before use.




FIGURE 2. Voltage derating with temperature.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review Activities:
Navy - AS, MC, OS
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5910-2165-03)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:29Z
Check the source to verify that this is the current version before use.