MIL-P-50578D (AR)
AMENDMENT 2
14 July 1986
SUPERSEDING
AMENDMENT 1
30 July 1985

MILITARY SPECIFICATION

PROJECTILE, 155MM, HE, RA, M549 AND M549A1
(WITH WARHEAD AND MOTOR BODY)
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-P-50578D (AR), dated 1 May 1985, and is approved for use within the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

* 3.6.1.1 Add the following:

"The rocket motor shall ignite not earlier than four seconds after firing. Lots with early motor ignitions, which pass all other proving ground test requirements, shall be referred to the technical agency for disposition."

PAGE 6

* 3.6.1.2.2: Add the following: "unless the rocket motor fails to ignite".

* 3.6.2: Delete in its entirety and substitute the following:

"3.6.2 Safety. There shall be no premature burst or indication of metal parts sepration in the gun bore, or in flight, when fired at any of the conditions specified in 4.5.3. In addition, no projectile fired in the safety phase shall have a horizontal range less than 97.5 percent of the mean unless the rocket motor fails to ignite."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

PAGE 29

* 4.4.3.4: Delete in its entirety and substitute the following:

"4.4.3.4 Proving ground. These tests shall be performed as specified in 4.5.3. Defects shall be classified as follows:

Critical:
1. Premature burst or metal parts separation

Special:
a. Range less than 97.5 percent of mean horizontal range unless rocket motor fails to ingite (see 6.16)

Major:
101 Range probable error exceeds allowable limit (see 3.6.1.2.1).
102 Rocket motor fails to ignite.

Minor: None defined"

PAGE 30

4.4.3.4.2.2: Change "15" in the first sentence to "14".

PAGE 35

4.5.3.2: Delete in its entirety and substitute the following:

"4.5.3.2 Safety. The projectiles for this test shall be divided into three groups. Group 1, consisting of five projectiles, shall be conditioned and fired at -65°F with Charge 8, M203 series propelling charges conditioned at -65°F. Group 2, consisting of four projectiles, shall be conditioned and fired at 145°F. Group 3, consisting of five projectiles, shall be conditioned at 145°F and fired with PXR-6297 proof propelling charges conditioned at 145°F. The cold phase (Group 1) shall be fired at a quadrant elevation of 51 degrees, and the hot phases (Group 2 and 3) shall be fired at a quadrant elevation of 24 degrees."

PAGE 37

6.7: Under safety phase, change "15" to "14".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.

* Add the following paragraph:

"6.16 Short range. Projectiles failing to achieve required range with proper motor function shall be considered critical defects. Projectiles failing to achieve required range due to improper motor ignition delay or motor burn shall be considered as major defects."

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1320-A848)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:30Z
Check the source to verify that this is the current version before use.