MIL-P-60503B(MU)
AMENDMENT 3
3 August 1973
SUPERSEDING
AMENDMENT 2
30 October 1972

MILITARY SPECIFICATION

PULSE FORMING NETWORK POWER SUPPLY: 10540707

This amendment forms a part of Military Specification MIL-P-60503B(MU), dated 18 June 1970.

Paragraph 2.1: Add Military Specification "MIL-P-46843 - Printed Circuit Assemblies, Design and Production of".

Paragraph 3.3: Add "and MIL-P-46843".

Paragraph 3.3.1: Add after MIL-F-13926 "and MIL-P-46843".

Paragraph 3.8.5, Line 2: Change "1 ± .5 milliseconds" to read ".2 milliseconds minimum".

Paragraph 4.3.4: Delete and substitute:

Paragraph 4.3.4 Certification.- Certification shall include test data and results for the characteristics specified below. Certification shall be provided prior to performing final acceptance inspection, and remain in effect throughout the performance of the contract. This does not relieve the contractor from inspection throughout the contract production, including recording data and results therefrom. Recorded data and results shall be made available to the Government upon request. A new certification shall be required whenever any change(s) occur in materials, manufacturing processes and techniques previously certified. Exception to the above may be provided by certificate of compliance (COC) for those items for which the contractor cannot obtain recorded data, i.e., off the shelf items. This exception shall not apply without prior approval by Frankford Arsenal. Request for approval shall include item name, part number, identification of supplier, and justification for exception; and shall be forwarded to COMMANDER, FRANKFORD ARSENAL, ATTN: SARFA-Q4000."

Paragraph 4.4.1, TABLE III, NO. 303: Add "MIL-P-46843".

* Paragraph 4.6.1.3, second sentence: Delete "Procedure II" and substitute "Procedure I".

* Paragraph 4.6.1.4: Delete third sentence and substitute "The vibration equipment shall be capable of providing the conditions of amplitude, frequency and duration specified in 3.4." Add the following sentence: "The vibration test shall be performed in accordance with Figure 514-1 Curve C of

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.

MIL-STD-810 except double amplitude shall not exceed .036 inch."

* The outside margins have been marked to indicate where additions to the previous amendments have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous issue.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A531

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.