MILITARY SPECIFICATION

MEASURING AND CUTTING MACHINES, PAPER AND POLYETHYLENE FILM

1. SCOPE AND CLASSIFICATION

1.1 Scope.- This specification covers two types of measuring and cutting machines.

1.2 Classification.- Measuring and cutting machines shall be of the following types as specified (see 6.2).

Type I - For paper.
Type II - For polyethylene film.

* 2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

L-P-378	-	Plastic Sheet and Strip (Polyolefin).
CC-M-636	-	Motors, Fractional Horsepower (Alternating Current).
PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-C-650	-	Crates, Wood, Open and Covered.
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, For Sealing and Securing.

MILITARY

MIL-P-116	-	Preservation, Methods of.
MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:12Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-595 - Colors.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-461 - Electromagnetic Interference Characteristics, Requirement For.
MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement Of.
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking and Waterproofing with Appropriate Test Methods.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNDERWRITERS' LABORATORIES, INC. (UL)

Electrical Construction Materials List.

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 1285 Walt Whitman Road, Melville, L.I., N.Y. 11749; 207 East Ohio Street, Chicago, Ill. 60611; or 1655 Scott Blvd. Santa Clara, Calif. 95050.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

Standard No. 70 - The National Electric Code.

(Application for copies should be addressed to the National Fire Protection Association, 60 Batterymarch Street, Boston, Mass. 02110.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC.

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, ATTN: Tariff Order Section, 1616 P Street, N.W., Washington, D.C. 20036.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:12Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 202 Union Station, 516 W. Jackson Blvd., Chicago, Ill. 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

* 3.1 First article.- This specification contains provision for first article test and approval (see 4.2, 6.2 and 6.3).

* 3.2 Standard product.- The measuring and cutting machines covered by this specification shall be new and the manufacturer's regular commercial product, except for any changes necessary to comply with this specification.

* 3.3 Codes and standards.- Each type of measuring and cutting machine shall comply with the following: (1) the electrical materials and components shall conform to applicable UL standards, and (2) the installation of the electrical components shall conform to applicable requirements of NFPA Standard No. 70.

* 3.3.1 UL compliance.- Prior to approval of the preproduction sample, or if none is submitted, prior to approval of the first shipment, the supplier shall submit satisfactory evidence to the contracting officer or his authorized representative that the electrical materials or components he proposes to furnish under this specification meet the requirements of UL standards, as applicable. Acceptable evidence of meeting the requirements of the applicable UL standards shall be the UL label, UL listing mark, or a certified test report from a recognized independent testing laboratory acceptable to the Government, indicating that the electrical materials and components offered have been tested and conform to the applicable UL standards.

* 3.3.2 NFPA compliance.- Prior to the approval of the preproduction sample, or if none is submitted, prior to the approval of the first shipment, the supplier shall submit satisfactory evidence to the contracting officer or his authorized representative that each measuring and cutting machine he proposes to furnish under this specification meets the applicable requriements of NFPA Standard No. 70. Acceptable evidence of meeting requirements of NFPA Standard No. 70 shall be the manufacturer's certified statement that the machines conform to the applicable requirements.

3.4 Materials.- Material not definitely specified shall be of the quality normally used for the purpose in commercial practice.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:12Z
Check the source to verify that this is the current version before use.

3.5 Design and construction.- Each machine shall have a steel frame with removable panels for permitting interior inspection, adjustment, and maintenance of the machine; a corrosion-resisting steel top for use as a wrapping surface for packages, and adjustable legs for leveling and adjusting machine height. In addition, the machine shall have a motor-driven system for feeding, measuring, and cutting overwraps for packages and a visual measuring guage for assisting the machine operator in determining the length of overwrap required. Gear or chain drives shall be inclosed in a metal housing with means provided for maintenance and lubrication of the drive.

* 3.5.1 Feeding, measuring, and cutting system.- The feeding, measuring, and cutting system of each machine shall feed, measure, and cut overwraps in not less than 4 lengths as specified hereinafter. Lengths shall be within a tolerance of plus or minus 1/4 inch. The systems essentially shall consist of: (1) a mounting means for accommodating a roll of wrapping material with frictional means to prevent overturning of the roll; (2) a pair of motor-driven feed rollers with adjustable means for providing positive feeding and measuring of the wrapping material; (3) a knife or hot wire, as applicable (see 3.5.1.1 and 3.5.1.2) for automatically cutting off the overwrap as the rollers stop feeding and for independent operation by a machine operator with an electrical push-button switch; and (4) a set of 4 push-button electrical switches for feeding and cutting any one of 15, 25, 40 or 60 inch lengths of overwrap corresponding to each switch and as preset on the feed rollers.

* 3.5.1.1 Type I.- Type I machine shall have a feeding, measuring, and cutting system in accordance with 3.5.1 for handling paper normally used for laundry packages and accommodating paper rolls up to 36 inch maximum width and 15 inch maximum diameter. The machine shall have a knife for cutting off the overwrap. The knife shall have a guard for protection of the machine operator.

* 3.5.1.2 Type II.- Type II machine shall have a feeding, measuring and cutting system in accordance with 3.5.1 for handling polyethylene film of 1 mil minimum thickness, conforming to type I of L-P-378 and accommodating film rolls up to 34 inch maximum width and 9 inch maximum diameter. The machine shall have a hot wire for cutting off the polyethylene overwrap. The hot wire shall have a cover with safety switch for protection of the machine operator. The safety switch shall shut off the current to the hot wire when the cover is removed. In addition, the machine shall have a motor driven belt for conveying the polyethylene film from the feed roller to the machine top where the belt shall become the wrapping surface.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:12Z
Check the source to verify that this is the current version before use.

* 3.5.2 Visual measuring gauge.- The visual measuring gauge shall indicate the length of overwrap required, based on the height of the pack to be packaged. The gauge shall have an indicator marked to correspond to each of the electrical switches for feeding, measuring, and cutting the overwrap. The gauge shall be mounted on a pack conveyor or the machine top in a convenient location for the machine operator.

3.5.3 Adjustable legs.- The adjustable legs shall be made from steel and be adjustable to provide a minimum variation in machine height of 5 inches.

* 3.5.4 Electric motors.- Motors shall have inclosures in accordance with the manufacturer's commercial practice. The motors shall conform to CC-M-636 and the following requirements.

(a) Motors shall be equipped with ball bearings except that motors of less than 1/2 horsepower for horizontal application with sleeve bearings, shall be acceptable.

(b) Motor bearings of the permanently lubricated type shall be acceptable.

(c) The motor shall have a manually operated thermal overload reset switch.

* 3.5.5 Electrical characteristics.- Unless otherwise specified (see 6.2), all machines shall operate from a 120 volt, 60 Hertz, single phase, alternating current (ac) source.

* 3.5.6 Electrical wiring and diagram.- Electrical wiring shall be color coded and terminals marked to correspond with the coding used. A wiring diagram showing the complete circuit shall be affixed to the machine in a protective location. In addition, a copy of the wiring diagram shall be furnished with each machine.

* 3.5.7 Lubrication.- Each machine shall have lubricating fittings for lubrication of bearings and moving parts. Where lubricant reservoirs are required for chain or gear drives, the reservoirs shall have a threaded cap at the top and a drain plug at the bottom. Fittings shall have seals for preventing leakage of the lubricant. The machines shall be lubricated with the manufacturer's standard lubricant.

* 3.6 Performance.- Each machine with no wrapping material in the machine when tested as specified in 4.4.1 shall operate smoothly with no loose fitting or interference of parts or malfunctioning of the following operational controls:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:12Z
Check the source to verify that this is the current version before use.

(a) The four electric switches for feeding and cutting the overwrap.

(b) The switch for independent opearation of the cutoff knife or hot wire, as applicable.

(c) Safety switch on hot wire cutoff cover of type II machine.

(d) Feed roller adjustment for accomplishing the positive feeding and measuring function.

In addition, the machines shall feed, measure and cut overwraps smoothly with no snarling of the material and within the length tolerance specified (see 3.5.1), when tested as specified in 4.4.2.

* 3.7 Finish.- All machines shall be finished in accordacne with the manufacturer's commercial practice, except that the color of the machine panels shall correspond to No. 24172 of FED-STD-595.

* 3.8 Lubrication chart.- A corrosion-resistant and legible lubricating chart (metal or decal) shall be affixed to each machine, showing points requiring lubrication and when lubrication shall be accomplished.

* 3.9 Electromagnetic compatibility.- When specified (see 6.2), each machine shall be designed and equipped for electromagnetic compatibility in accordance with class IIB of MIL-STD-461 (see 4.4.8).

* 3.10 Marking for identification.- Each machine shall be marked in accordance with the manufacturer's commercial practice.

* 3.11 Workmanship.- All machines shall exhibit in particular, soundness of fabrication, electrical wiring and when applicable, soundness of welding, brazing, and soldering as specified hereinafter.

* 3.11.1 Fabrication.- Machine parts or components shall have no fractures, punctures or dents; shall not be bowed, malformed, or loose; shall be in alignment; and free of sharp burrs and slivers.

* 3.11.2 Electrical wiring.- Electrical wiring shall not be cut, abraided, improperly joined, loose at the terminals or with inadequate slack and shall be color coded and attached to terminals corresponding to code used.

* 3.11.3 Welding and brazing.- Welding and brazing shall be sound, adherent, and free from burn holes, scale, and flux deposits.

* 3.11.4 Soldering.- Soldering shall be continuous adherent and free from flux deposits and pinholes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:12Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as sepcified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 First article inspection.- When a preproduction sample is required, it shall be examined for defects in table I and dimensions specified, and tested as specified in 4.4.1, 4.4.2, and 4.4.3, if applicable. The presence of any visual or dimensional defects or failure to pass the tests shall be cause for rejection of the preproduction sample.

4.3 Inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 Inspection of components and materials.- In accordance with 4.1, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.3.2 End item inspection.- A lot shall consisit of all measuring and cutting machines of the same type offered for inspection at one time. The sample unit shall be one completely fabricated measuring and cutting machine.

* 4.3.2.1 Visual examination.- Visual examination shall be made of the completely assembled end item for defects in table I. The inspection level shall be level II with an accpetable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:12Z
Check the source to verify that this is the current version before use.

TABLE I.- Classification of defects

Examine	Defect	Classification Major	Classification Minor
Finish	Not as specified.		X
Design and construction (general)	Characteristic not as specified.	X	
	Part missing or not as specified.	X	
Workmanship (applicable to all components and assemblies)			
Fabrication	Part fractured, punctured, dented, bowed or malformed.	X	
	Loose.		X
	Not in alignment.	X	
	Any sharp burrs or slivers.		X
Electrical wiring	Wiring cut, abraded or improperly joined.	X	
	Loose at the terminals or slack inadequate.		X
	Not color coded or attached to terminals corresponding to code used.		X
Welding and brazing (when applicable)	Not sound or adherent.	X	
	Not free of burn holes, scale or flux deposits.		X
Soldering (when applicable)	Not continuous or adherent.	X	
	Not free of flux deposits or pin holes.		X
Lubrication	Not as specified.		X
	Fitting missing or defective.	X	
	Fitting inaccessible.		X
	Chart incomplete or not legible.	X	
	Chart missing.		X
Marking	Not as specified, incomplete or not legible.	X	
	Missing.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:12Z
Check the source to verify that this is the current version before use.

4.3.2.2 Dimensional examination.- Examination shall be made of the end item for compliance with dimensional requirements. Any nonconforming dimension shall be classified a defect. The inspection level shall be S-2 with an AQL of 2.5 expressed in terms of defects per hundred units.

4.3.2.3 Testing of the end item.- When a first article is not required, the initial production unit shall be tested as specified in 4.4.2 and 4.4.3, if applicable. Failure to pass any test shall be cause for rejection of the lot. Each machine shall be tested as sepcified in 4.4.1. Any nonconformance shall be cause for the rejection of the unit.

4.3.3 Code and standard compliance.- Proof of compliance with requirements of 3.3 shall be available to the Government representative.

4.3.4 Examination of preparation for delivery.- An examination shall be made of preservation, packaging, packing, and marking for compliance with section 5 of this specification. Defects shall be scored as specified in table II. The lot shall be all the containers offered for inspection. The sample unit shall be one container prepared for delivery except that it shall not be sealed. The inspection level shall be S-4 and the AQL shall be 6.5 defects expressed in terms of defects per hundred units.

TABLE II.- Examination of preparation for delivery

Examination	Defect
Marking (exterior and interior container)	Missing; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Component missing, damaged, or otherwise defective.
Workmanship	Inadequate application of barrier materials. Adjustable legs not turned up to shortest dimension and not immobilized.
Contents	More than specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:12Z
Check the source to verify that this is the current version before use.

4.4 Tests.-

* 4.4.1 Operation test.- The machine shall be operated with no wrapping material. The operation and controls shall then be checked to determine compliance with the smooth operation and no control malfunction requirements of 3.6. Any nonconformance shall constitute failure to pass this test.

* 4.4.2 Performance test.- The machine shall be loaded with a roll of applicable wrapping material. The machine shall be operated to feed, measure, and cut 10 lengths of overwraps each of 15, 25, 40, and 60 inch lengths. The machine operation and lengths of overwraps shall then be checked to determine compliance with the smooth operation, no material snarling, and overwrap length tolerance requirements of 3.6.

* 4.4.3 Electromagnetic compatibility test.- The preproduction unit or initial production unit shall be tested by the supplier in accordance with Test Method CE02 of MIL-STD-462. The Government reserves the right to witness tests performed by the supplier or his private testing organization. The supplier shall furnish the contracting officer for his approval, the Interference Control Plan, the EMI/EMC (Electromagnetic Interference/Electromagnet Compatibility) Test Plan and the Electromagnetic Compatibility Test Report required in MIL-STD-461 (see 6.4). Upon approval of the test report by the contracting officer and provided that all other requirements of the specification are met, the preproduction sample or initial unit of production as applicable, shall be used as a model for all production units.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.- Preservation and packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.-

5.1.1.1 Preservation.- All exposed, uncoated, ferrous metal surfaces, except corrosion-resisting steel, of each machine shall be cleaned process C-1 of MIL-P-116 and thoroughly dried. Surfaces cleaned as specified shall be coated with a preservative. Contacting surfaces (surfaces that contact other surfaces during operation) shall be coated with type P-6 preservative, and noncontacting surfaces (surfaces that do not contact other surfaces during operation) shall be coated with type P-1 preservative of MIL-P-116. Surfaces coated with type P-6 preservative, from which preservative might be removed by contact with packaging and packing materials, shall be covered, wrapped, or bagged with greaseproof barrier material conforming to type I or II, grade A of MIL-B-121. Barrier material shall be secured with twine made of jute, sisal, manila, or cotton; or with tape conforming to type III, grade A of PPP-T-45; or heat sealed when heat sealable barrier material is used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:12Z
Check the source to verify that this is the current version before use.

5.1.1.2 Packaging.- The adjustable legs shall be adjusted to the shortest dimensions. Parts that are free to move shall be secured by tying or blocking with cushioning material as required.

* 5.1.2 Level C.- Each machine shall be preserved and packaged to afford adequate protection against corrosion, deterioration, and damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets these requirements.

5.2 Packing.- Packing shall be level A, B, or C as specified (see 6.2).

* 5.2.1 Level A.- Each machine preserved and packaged as specifieid in 5.1 shall be packed in a shipping container constructed closed and strapped in accordance with overseas type style A, B or J of PPP-B-601. Each shipping container shall be provided with skids and the contents blocked, braced, cushioned and protected with a shroud in accordance with MIL-STD-1186.

* 5.2.2 Level B.- Each machine, preserved and packaged as specified in 5.1, shall be packed in a crate conforming to style A type IV of PPP-C-650. The contents shall be anchored and waterproofed, and the crate closed and strapped in accordance with the appendix of PPP-C-650. Alternatively, each machine shall be packed as specified in 5.2.1 except that a domestic type shipping container may be used.

* 5.2.3 Level C.- Each machine, preserved and packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules and National Motor Freight Classification Rules, as applicable.

5.3 Marking.- In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

* 6.1 Intended use.- The machine covered by this specification is intended for use in feeding, measuring, and cutting paper and polyethylene film for wrapping bundles in laundries.

* 6.2 Ordering data.- Procurement documents shall specify the following:

(a) Title, number, and date of this specification.
(b) Type required (see 1.2).
(c) First article (see 3.1, 4.2, and 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:12Z
Check the source to verify that this is the current version before use.

(d) Electrical characteristics if other than specified (see 3.5.5).
(e) When electromagnetic compatibility is required (see 3.9).
(f) Selection of applicable levels of preservation, packaging and packing (see 5.1 and 5.2).

* 6.3 First article.- The item covered by this specification required first article test and approval under the appropriate provisions of paragraph 7-104.55 of the Armed Services Procurement Regulations (ASPR). The first article should be a preproduction sample. The first article should consist of one measuring and cutting machine. The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for examination, test and approval of the first article.

* 6.4 Electromagnetic compatibility tests.- The contracting officer should submit a copy of the report(s) required (see 4.4.3) to the Commanding General, U.S. Army Electronics Command, ATTN: AMSEL-GG-EI, Fort Monmouth, New Jersey 07703 for approval.

6.5 The margins of this specification are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - GL

Preparing activity:

Army - GL

Project No. 3540-A077

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:12Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-M-40065C(GL)
Measuring and Cutting Machines, Paper and Polyethylene Film

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
   ☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:12Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. Army Natick Laboratories
Natick, Massachusetts 01760

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding General
U. S. Army Natick Laboratories
ATTN: AMXRES-BCS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:12Z
Check the source to verify that this is the current version before use.