MILITARY SPECIFICATION SHEET

ELECTRON TUBE, NEGATIVE GRID (MICROWAVE)

TYPE 2C40A

This amendment forms a part of Military Specification Sheet MIL-E-1/868E, dated 17 March 1977, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

GENERAL: Delete "See note 1."

PAGE 2

METHOD 1236, Power oscillation (pulsed): In LIMITS column, under MAX, add "1200."
In UNIT column, add "V."

PAGE 3

METHOD 1031, High frequency vibration: In CONDITIONS column, delete reference to note 4.

Under METHOD column, delete "1101."
Under TEST column, delete "Secureness of base, cap, or insert" and substitute "Torque."
Under CONDITIONS column of Torque test, delete reference to note 4.

Torque-test end point: Under UNIT column, delete "Adc" and substitute "μAdc."
Under CONDITIONS column, delete reference to note 4.

Frequency Drift: Under CONDITIONS column, delete reference to note 4.
Under SYMBOL column, delete "F" and substitute "ΔF."

PAGE 4

Delete note 1 and note 4 entirely.

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Air Force - 99
DLA - ES

User activities:
Army - MU
Navy - AS, OS, MC, CG
Air Force - 11

Preparing activity:
Air Force - 85

(Project No. 5960-0663)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:46Z
Check the source to verify that this is the current version before use.